



Dates of Tests: September 16 ~ October 04, 2013

Test Report S/N: LR500111310H

Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID

**SS4EP3XX**

APPLICANT

**BLUEBIRD INC.**

<b>Equipment Class</b>	<b>: Part 15 Spread Spectrum Transmitter (DSS)</b>
<b>Manufacturing Description</b>	<b>: Mobile Payment Terminal</b>
<b>Manufacturer</b>	<b>: BLUEBIRD INC.</b>
<b>Model name</b>	<b>: EP3XX</b>
<b>Test Device Serial No.:</b>	<b>: Identical prototype</b>
<b>Rule Part(s)</b>	<b>: FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	<b>: 2402 ~ 2480MHz</b>
<b>RF power</b>	<b>: Max 6.45 dBm – Conducted</b>
<b>Data of issue</b>	<b>: October 07, 2013</b>

This test report is issued under the authority of:

Jae-Ho Lee, Manager

The test was supervised by:

Young-Jin Lee, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION -----	3
2. INFORMATION ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 FREQUENCY HOPPING SYSTEM REQUIREMENTS-----	6
3.3 TECHNICAL CHARACTERISTICS TEST -----	8
3.3.1 CARRIER FREQUENCY SEPARATION -----	8
3.3.2 NUMBER OF HOPPING FREQUENCIES -----	10
3.3.3 20 dB BANDWIDTH -----	12
3.3.4 TIME OF OCCUPANCY (Dwell Time) -----	19
3.3.5 TRANSMITTER OUTPUT POWER -----	24
3.3.6 BAND EDGE -----	28
3.3.7 CONDUCTED SPURIOUS EMISSIONS -----	31
3.3.8 RADIATED SPURIOUS EMISSIONS -----	34
3.3.9 AC CONDUCTED EMISSIONS -----	43
APPENDIX -----	
APPENDIX TEST EQUIPMENT USED FOR TESTS -----	46

## 1. General information

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	UPDATING	ECT accredited Lab.
RRL	KOREA	KR0049	2015-03-06	EMC accredited Lab.
FCC	U.S.A	610755	2014-04-27	FCC filing
FCC	U.S.A	649054	UPDATING	FCC CAB
VCCI	JAPAN	R2133(10m), C2307	2014-06-21	VCCI registration
VCCI	JAPAN	T-2009	2013-12-23	VCCI registration
VCCI	JAPAN	G-563	2015-05-28	VCCI registration
IC	CANADA	5799A-1	2015-06-21	IC filing

## 2. Information about test item

### 2-1 Client & Manufacturer

Company name : BLUEBIRD INC.  
 Address : (Dogok-dong, SEI Tower 13~14), 39, Eonju-ro30-gil, Gangnam-gu  
 Seoul, Korea  
 Telephone / Facsimile : Tel : +82-70-7730-8210 / Fax :+82-2-548-0870

### 2-2 Equipment Under Test (EUT)

Trade name : 

Model name : EP3XX  
 Serial number : Identical prototype  
 Date of receipt : September 13, 2013  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip antenna (M/N:ALA621C4) Max Gain 3.5 dBi  
 Frequency Range : 2402 ~ 2480MHz  
 RF output power : Max. 6.45 dBm - Conducted  
 Number of channels : 79  
 Duty cycle : 80.69 %  
 Channel spacing : 1MHz  
 Channel Access Protocol : Frequency Hopping Spread Spectrum (FHSS)  
 Type of Modulation : Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)  
 Power Source : DC 3.7V by battery  
 Power for Adaptor : Input: 100-240VAC, 0.4A      Output: 5.0VDC, 3A  
 Firmware Version : V1.0.0

### 2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247(a)	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies    NC=Not Complies    NT=Not Tested    NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### Note 1: Antenna Requirement

→ The **BLUEBIRD INC.**, FCC ID: **SS4EP3XX** unit complies with the requirement of §15.203.  
The antenna type is chip antenna.

#### Note 2: The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003  
RSS-210 and ISSUE No.:8 Date:2010

#### Note3: TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.10-2009) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled “**Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems**” were used in the measurement of the **BLUEBIRD INC.**, FCC ID: **SS4EP3XX**

## 3.2 Frequency Hopping System Requirements

### 3.2.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 3.2.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 3.2.3 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

### 3.3 Transmitter requirements

#### 3.3.1 Carrier Frequency Separation

##### Procedure:

The test follows DA00-705. The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

##### The spectrum analyzer is set to:

Span = 2~ 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

##### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
0.9986	Complies

- See next pages for actual measured spectrum plots.

##### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

##### Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation

## Carrier Frequency Separation

### Basic Mode



### EDR Mode



### 3.3.2 Number of Hopping Frequencies

#### Procedure:

The test follows DA00-705. The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to (Bluetooth):

Frequency range      Start = 2400.0MHz,   Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more)      Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Span > 40MHz

**Measurement Data : Complies**

<b>Total number of Hopping Channels</b>	79
---	----


- See next pages for actual measured spectrum plots.

**Minimum Standard:**

At least 15 hopes

**Measurement Setup**

Same as the Chapter 3.3.1 (Figure 1)

Number of Hopping Frequencies

### 3.3.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to (Bluetooth):

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold

#### Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.821	0.881
2441	39	0.821	0.873
2480	78	0.821	0.873

#### Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.303	1.255
2441	39	1.311	1.259
2480	78	1.311	1.259



- See next pages for actual measured spectrum plots.



#### Minimum Standard:



N/A



#### Measurement Setup



Same as the Chapter 3.3.1 (Figure 1)



Channel 1 of basic mode20 dB Bandwidth99% Bandwidth

Channel 2 of basic mode20 dB Bandwidth99% Bandwidth

Channel 3 of basic mode20 dB Bandwidth99% Bandwidth

Channel 1 at EDR mode20 dB Bandwidth99% Bandwidth

Channel 2 at EDR mode20 dB Bandwidth99% Bandwidth

Channel 3 at EDR mode20 dB BandwidthBandwidth

### 3.3.4 Time of Occupancy (Dwell Time)

#### Procedure:

The test follows DA00-705. The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data (Bluetooth):

Mode	Number of transmission in a 31.6s ( 79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	30(Times / 3sec) *10.533 = 315.99	0.442	139.67	400
DH3	15(Times / 3sec) *10.533 = 158.00	1.710	270.18	400
DH5	10(Times / 3sec) *10.533 = 105.33	2.957	311.46	400
EDR 3Mbps DH5	10(Times / 3sec) *10.533 = 105.33	2.971	312.94	400



- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms



#### Minimum Standard:



0.4 seconds within a 30 second period per any frequency



#### Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

**DH1 at basic mode**

**DH3 at basic mode**

**DH5 at basic mode**

**DH5 at EDR mode with 3Mbps**

### 3.3.5 Transmitter Output Power

#### Procedure:

The test follows DA00-705. The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to :

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Sweep = auto

#### Measurement Data : Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>5.37</b>	<b>3.44</b>	Complies
2441	39	<b>5.51</b>	<b>3.36</b>	Complies
2480	78	<b>3.93</b>	<b>2.47</b>	Complies

#### Measurement Data : EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>6.19</b>	<b>4.16</b>	Complies
2441	39	<b>6.45</b>	<b>4.42</b>	Complies
2480	78	<b>4.90</b>	<b>3.09</b>	Complies

- See next pages for actual measured spectrum plots.


<b>Minimum Standard:</b>	< 250 mW
--------------------------	----------

#### Measurement Setup


Same as the Chapter 3.3.1 (Figure 1)

## Channel 1

### Basic mode




### EDR mode




## Channel 2

### Basic mode




## EDR mode




### Channel 3

#### Basic mode



#### EDR mode



### 3.3.6 Band Edge

## Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10~30 MHz      Detector function = peak

### Measurement Data: Complies


- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
  - See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------


## Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

Band Edge  
Lower edge



Upper edge



**Radiated Band edges in the restricted band 2310-2390 MHz measurement**

Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
			Antenna	Amp. Gain+CableLoss	AV / Peak	74	21.2	35.8	32.8	38.2
2383.8	22.8   37.4	V	28.8	30.4	54	74	21.2	35.8	32.8	38.2

**Radiated Band edges in the restricted band 2483.5-2500 MHz measurement**

Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
			Antenna	Amp. Gain+CableLoss	AV / Peak	74	22.6	36.7	31.4	37.3
2483.6	24.2   38.3	V	28.8	30.4	54	74	22.6	36.7	31.4	37.3

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**

### 3.3.7 Conducted Spurious Emissions

### **Procedure:**

The test follows DA00-705. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz      Detector function = peak

Trace = max hold

### Measurement Data: **Complies**



- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
  - See next pages for actual measured spectrum plots.

---


<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

## Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

Unwanted Emission – Low channelFrequency Range = 30 MHz ~ 26.5 GHzUnwanted Emission – Middle channelFrequency Range = 30 MHz ~ 26.5 GHz

### Unwanted Emission – High channel



### 3.3.8 Radiated Spurious Emissions

#### Procedure:

Radiated emissions from the EUT were measured according to the dictates of DA00-705. The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

- (a) In the frequency range of 9kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 3m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10<sup>th</sup> harmonic.

RBW = 120 kHz ( 30MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )


Span = 100 MHz



Detector function = peak

Trace = max hold

Sweep = auto

**below 30MHz**



**below 1GHz (30MHz to 1GHz)****above 1GHz****Measurement Data: Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20dB below limit include from 9KHz to 30MHz.

**Minimum Standard: FCC Part 15.209(a)**

Frequency (MHz)	Limit (uV/m) @ 3m
0.009 ~ 0.490	2400/F(kHz) (@ 300m)
0.490 ~ 1.705	24000/F(kHz) (@ 30m)
1.705 ~ 30	30(@ 30m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data :**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		D.C.F	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain+Cable		AV/Peak	AV/Peak	AV/Peak	AV/Peak	AV / Peak	AV / Peak
4804	32.5	47.8	H	33.1	27.6	-30.21	54.0	74.0	38.0	53.3	16.0	20.7
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		D.C.F	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain+Cable		AV/Peak	AV/Peak	AV/Peak	AV/Peak	AV / Peak	AV / Peak
4882	30.6	44.2	H	33.1	27.6	-30.21	54.0	74.0	36.1	49.7	17.9	24.3
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		D.C.F	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain+Cable		AV/Peak	AV/Peak	AV/Peak	AV/Peak	AV / Peak	AV / Peak
4960	33.6	49.5	H	33.1	27.6	-30.21	54.0	74.0	39.1	55.0	14.9	19.0
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-

- No other emissions were detected at a level greater than 20dB below limit.


- D.C.F ( Duty Cycle Correction Factor) =  $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(3.04\text{ms}/100\text{ms}) = -30.21$$

Radiated Emissions – Bluetooth mode

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

BUT/Model No.: EP3XX TEST MODE: Bluetooth mode  
Temp Humi : 23 / 57 Tested by: Ha J M



Freq MHz	Reading dBuV/m	C.F dB/m	Result dBuV/m	Limit QP		Margin dB	Height cm	Angle deg	Polarity
				dBuV/m	dB				
1 46.70	34.80	-15.88	18.92	29.50	10.58	100	142	VERTICAL	
2 124.25	34.20	-15.77	18.43	33.00	14.57	100	311	VERTICAL	
3 142.36	35.20	-14.54	20.66	33.00	12.34	400	128	VERTICAL	
4 804.60	30.40	-2.31	28.09	35.60	7.51	400	298	HORIZONTAL	
5 901.59	24.60	-0.65	23.95	35.60	11.65	400	147	HORIZONTAL	
6 945.23	21.60	-0.01	21.59	35.60	14.01	400	258	HORIZONTAL	

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.3.9 AC Conducted Emissions

#### Procedure:

AC power line conducted emissions from the EUT were measured according to the dictates of ANSI C63.4:2003. The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: **Complies**

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit
- It gave the worse case emissions

#### Minimum Standard: FCC Part 15.207(a)/EN 55022


Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Conducted Emissions – Bluetooth mode – LINE

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : EP30X Phase : LINE  
 Test Mode : Bluetooth mode Test Power : 120 / 60  
 Temp./Humi. : 23 / 52 Test Engineer : HA J M




Freq MHz	RD QP	RD AV	C. F dB	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.155	46.24	33.84	0.18	46.42	34.02	65.73	55.73	19.31	21.71
0.185	43.25	32.85	0.17	43.42	33.02	64.26	54.26	20.84	21.24
0.218	40.25	30.15	0.17	40.42	30.32	62.89	52.89	22.47	22.57
0.407	41.95	30.45	0.18	42.13	30.63	57.71	47.71	15.58	17.08
0.437	46.35	34.05	0.18	46.53	34.23	57.12	47.12	10.59	12.89
0.467	43.35	30.55	0.18	43.53	30.73	56.57	46.57	13.04	15.84

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

Conducted Emissions Bluetooth mode – NEUTRAL

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : EP30X Phase : NEUTRAL  
 Test Mode : Bluetooth mode Test Power : 120 / 60  
 Temp./Humid. : 23 / 52 Test Engineer : HA J M



Freq MHz	RD QP		RD AV		C. F dB	Result QP		Result AV		Limit QP		Limit AV		Margin dB	Margin dB
	dBuV	dBuV	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
0.156	45.54	31.84	0.21	45.76	32.06	65.67	55.67	19.92	23.62						
0.184	42.05	29.85	0.19	42.23	30.03	64.30	54.30	22.07	24.27						
0.216	39.95	27.25	0.17	40.12	27.42	62.97	52.97	22.85	25.55						
0.404	37.25	28.45	0.20	37.45	28.65	57.77	47.77	20.32	19.12						
0.435	38.25	30.85	0.22	38.47	31.07	57.16	47.16	18.69	16.09						
0.464	39.85	30.25	0.23	40.08	30.48	56.62	46.62	16.54	16.14						

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	<b>Description</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Manufacturer</b>	<b>Interval</b>	<b>Last Cal. Date</b>
1	Signal Analyzer (9kHz~30GHz)	FSV-30	100757	R&S	1 year	2013-01-15
2	Spectrum Analyzer (9kHz~2.9GHz)	8594E	3649A03649	HP	2 year	2012-03-26
3	Signal Generator (~3.2GHz)	8648C	3623A02597	HP	1 year	2013-03-25
4	SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2013-03-25
5	Attenuator (3dB)	8491A	37822	HP	2 year	2012-09-22
6	Attenuator (10dB)	8491A	63196	HP	2 year	2012-09-22
7	Test Receiver (~30MHz)	ESHS10	828404/009	R&S	1 year	2013-03-25
8	EMI Test Receiver (~7GHz)	ESCI7	100722	R&S	1 year	2013-09-16
9	RF Amplifier (~1.3GHz)	8447D OPT 010	2944A07684	HP	1 year	2013-09-16
10	RF Amplifier (1~26.5GHz)	8449B	3008A02126	HP	1 year	2013-03-25
11	Horn Antenna (1~18GHz)	3115	00114105	ETS	2 year	2013-05-13
12	DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2012-03-15
13	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2012-03-15
14	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2013-05-03
15	Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2013-03-14
16	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
17	Power Divider	11636A	06243	HP	2 year	2012-09-22
18	DC Power Supply	6674A	3637A01657	Agilent	-	-
19	Frequency Counter	5342A	2826A12411	HP	1 year	2013-03-25
20	Power Meter	EPM-441A	GB32481702	HP	1 year	2013-03-25
21	Power Sensor	8481A	US41030291	HP	1 year	2013-09-16
22	Audio Analyzer	8903B	3729A18901	HP	1 year	2013-09-16
23	Modulation Analyzer	8901B	3749A05878	HP	1 year	2013-09-16
24	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2013-09-16
25	Stop Watch	HS-3	601Q09R	CASIO	1 year	2013-03-15
26	LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2013-09-16
27	Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2013-04-25
28	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2013-07-25
29	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	-	-
30	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	-	-
31	Active Loop Antenna	FMZB 1519	1519-031	SCHWARZBECK	1 year	2012-12-14