



No.:
FCCSZ2025-0036-RF3

TEST REPORT

FCC ID : SS4S20W1



NAME OF SAMPLE : Enterprise Full Touch Handheld Computer

APPLICANT : BLUEBIRD INC.

CLASSIFICATION OF TEST : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant	Name: BLUEBIRD INC. Address: 3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea		
Manufacturer	Name: BLUEBIRD INC. Address: 3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea		
Equipment Under Test	Product Name: Enterprise Full Touch Handheld Computer Model Name: S20 Additional Model Name: N/A Brand Name: BLUEBIRD Serial NO.: N/A Sample NO.: FCCSZ2025-0036_4-1		
Date of Receipt.	Apr. 21, 2025	Date of Testing	Apr. 21, 2025 ~ Jun. 04, 2025
Test Specification		Test Result	
FCC Part 15, Subpart E (15.407)		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: Jun. 04, 2025		
Compiled by:  Zhu Yulin Name Signature	Reviewed by:  Mo Xianbiao Name Signature	Approved by:  Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST LOCATION	7
2 GENERAL INFORMATION	8
2.1 GENERAL PRODUCT INFORMATION	8
2.2 DESCRIPTION OF ACCESSORIES	9
2.3 CARRIER FREQUENCY AND CHANNEL	10
2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	13
2.5 DESCRIPTION OF SUPPORT UNITS	15
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3 TEST TYPES AND RESULTS	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	19
3.3 OCCUPIED BANDWIDTH MEASUREMENT	46
3.4 26DB EMISSION BANDWIDTH	47
3.5 6DB EMISSION BANDWIDTH	48
3.6 TRANSMIT POWER MEASUREMENT	49
3.7 POWER SPECTRAL DENSITY MEASUREMENT	50
3.8 FREQUENCY STABILITY	51
3.9 ANTENNA REQUIREMENT	52
4 PHOTOGRAPHS OF TEST SETUP	54
5 PHOTOGRAPHS OF THE EUT	55



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2025-0036-RF3	Original release	Jun. 04, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPARTE (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
FCC 15.207	AC Power Conducted Emission	PASS	See section 3.1
FCC 15.403(a)(e)	6dB&26dB Emission Bandwidth	PASS	Appendix A1&A3 of FCCSZ2025-0036-RF3-A1
---	Occupied Bandwidth Measurement	N/A	Appendix A2 of FCCSZ2025-0036-RF3-A1 (For reference)
FCC 15.407(b)	Radiated Emission and Bandedge	PASS	See section 3.2
FCC 15.407(a)	Transmit Power	PASS	Appendix C of FCCSZ2025-0036-RF3-A1
FCC 15.407(a)	Power Spectral Density	PASS	Appendix D of FCCSZ2025-0036-RF3-A1
FCC 15.407(g)	Frequency Stability	PASS	Appendix E of FCCSZ2025-0036-RF3-A1
FCC 15.203 FCC 15.407(a)	Antenna Requirement	PASS	See section 3.9



1.1 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial Number	Cal. interval	Cal. Due
Antenna Port Conducted Test					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 30	104408	1 year	2026/4/22
#3Shielding room	MORI	443	N/A	3 year	2026/5/16
Wideband radio communication tester	Rohde&Schwarz	CMW 500	168587	1 year	2025/7/2
Analog signal Generator (100kHz ~ 40GHz)	Rohde&Schwarz	SMB 100A	181934	1 year	2026/4/22
Vector signal Generator (9kHz ~ 6GHz)	Rohde&Schwarz	SGT 100A	111724	1 year	2026/4/22
RF control unit(BT/WiFi)	Tonscend	JS0806-2-8CH	CS0300023	1 year	2026/4/22
10db attenuator	JUNKE	SMA-10-18-N	250312743	1 year	2026/6/6
Power splitter	Anritsu	K240CPOWERDIVIDER	012334	1 year	2026/6/6
Temperature and humidity meter	/	C193561457	C193561457	1 year	2026/4/28
Radiation Spurious Test - 3M Chamber #2					
Signal&Spectrum Analyzer	Rohde&Schwarz	FSV 40	101898	1 year	2026/4/22
EMI Test Receiver	Rohde&Schwarz	ESR3	102694	1 year	2026/5/21
Antenna(30MHz~1001MHz)	SCHWARZBECK	VULB 9168	01133	1 year	2026/1/22
Horn antenna(1GHz-18GHz)	ETS	3117	227611	1 year	2026/3/28
Horn antenna(18GHz-40GHz)	QMS	QMS-00880	22051	1 year	2026/3/21
3m anechoic chamber	MORI	966	CS0300011	3 year	2026/5/18
Filter group(RSE-BT/WiFi)	Rohde&Schwarz	WiFi /BT Variant 1	100820	1 year	2026/4/22
Filter group(RSE-Cellular)	Rohde&Schwarz	Cellular Variant 1	100768	1 year	2026/4/22
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100299	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100801	1 year	2026/4/22
Preamplifier(18GHz-40GHz)	Rohde&Schwarz	SCU-40A	101209	1 year	2026/4/22
Temperature and humidity meter	/	C193561517	C193561517	1 year	2026/4/28
Radiation Spurious Test - 3M Chamber #1					
EMI Test Receiver	Rohde&Schwarz	ESR 26	101718	1 year	2026/5/21
Loop antenna(8.3k~30MHz)	Rohde&Schwarz	HFH2-Z2E	100951	1 year	2026/6/5
Antenna(30MHz~1000MHz)	SCHWARZBECK	VULB 9168	01132	1 year	2026/2/27
Horn antenna(1GHz-18GHz)	SCHWARZBECK	BBHA9120D	02793	1 year	2026/1/20
3m anechoic chamber	MORI	966	N/A	1 year	2026/5/18
Preamplifier(10kHz-1GHz)	Rohde&Schwarz	SCU-01F	100298	1 year	2026/4/22
Preamplifier(1GHz-18GHz)	Rohde&Schwarz	SCU-18F	100799	1 year	2026/4/22
Attenuator	/	SJ-5dB	607684	1 year	2026/2/27
#1 control room	MORI	433	/	1 year	2026/5/16
Temperature and humidity meter	/	C193561473	C193561473	1 year	2026/4/28
Conducted emission					
EMI Test Receiver	Rohde&Schwarz	ESR3	102693	1 year	2026/5/21
limiter(10 dB)	Rohde&Schwarz	VTSD 9561	01216	1 year	2026/4/22
Voltage probe	Rohde&Schwarz	CVP9222C	00028	1 year	2026/4/28
Current probe	Rohde&Schwarz	EZ-17	101442	1 year	2026/4/22
ISN network	Rohde&Schwarz	ENV 81	100401	1 year	2026/4/22
ISN network	Rohde&Schwarz	ENV 81 Cat6	101896	1 year	2026/4/22
#1Shielding room	MORI	854	N/A	3 year	2026/5/16
LISN	SCHWARZBECK	NSLK 8129	5021	1 year	2026/4/22
Temperature and humidity meter	/	C193561430	C193561430	1 year	2026/4/28



1.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

No.	Item	Measurement Uncertainty
1	Occupied Channel Bandwidth	± 1.86 %
2	RF output power, conducted	± 0.9 dB
3	Power Spectral Density, conducted	± 0.8 dB
4	Conducted emission test	± 2.7 dB
5	Radiated emission 9kHz-30MHz	± 5.6 dB
	Radiated emission 30MHz-1GHz	± 4.6 dB
	Radiated emission 1GHz-18GHz	± 4.4 dB
	Radiated emission 18GHz-40GHz	± 5.1 dB
6	Temperature	± 0.73 °C
7	Humidity	± 3.90 %
8	Supply voltages	± 0.37 %
9	Time	± 0.27 %
Remark: 95% Confidence Levels, k=2.		

1.3 TEST LOCATION

The tests and measurements refer to this report were performed by EMC testing Lab. of CVC Testing Technology (Shenzhen) Co., Ltd.

CABID:CN0137

Lab Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province 518110 P.R.China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

FCC(Test firm designation number: CN1363)

IC(Test firm CAB identifier number: CN0137)

CNAS(Test firm designation number: L16091)



2 GENERAL INFORMATION

2.1 GENERAL PRODUCT INFORMATION

PRODUCT NAME	Enterprise Full Touch Handheld Computer		
BRAND NAME	BLUEBIRD		
MODEL NAME	S20		
ADDITIONAL MODEL NAME	N/A		
POWER SUPPLY	1. DC 3.85V (1*3.85V Rechargeable Li-ion Polymer battery) 2. DC 5V From Adapter		
MODULATION TECHNOLOGY	OFDM, OFDMA		
MODULATION TYPE	256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA		
TRANSFER RATE	802.11a: up to 54Mbps, 802.11n: up to 300Mbps, 802.11ac: up to 866.6Mbps, 802.11ax: up to 1200.5Mbps		
OPERATING FREQUENCY AND MAXIMUM POWER	Frequency	MAX Output Power(dBm)	MAX.EIPR(dBm)
	5180 ~ 5240MHz	16.28	17.16
	5260 ~ 5320MHz	16.17	17.05
	5500 ~ 5700MHz	13.79	15.71
	5745 ~ 5825MHz	15.76	14.86
NUMBER OF CHANNEL	See section 2.2		
ANTENNA TYPE (Remark 4/5)	ANT1: PIFA Antenna, ANT2: PIFA Antenna		
	5180 ~ 5240MHz: ANT1: 0.88dBi, ANT2: 0.34dBi		
	5260 ~ 5320MHz: ANT1: 0.88dBi, ANT2: 0.34dBi		
	5500 ~ 5720MHz: ANT1: 1.92dBi, ANT2: -0.36dBi		
	5745 ~ 5825MHz: ANT1: -1.61dBi, ANT2: -0.90dBi		
HARDWARE VERSION:	V1.01		
SOFTWARE VERSION:	R1.00		
FIX FREQUENCY SOFTWARE	Qualcomm Radio Control Tool		
I/O PORTS	Refer to user' s manual		
CABLE SUPPLIED	USB Cabel, 100cm, unshielded		



Remark:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. EUT photo refer to report (Report NO.: FCCSZ2025-0036-EUT).
4. Please refer to the antenna report.
5. Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
6. The EUT have MIMO function, provides 2 completed transmitter and 2 receiver.

2.2 DESCRIPTION OF ACCESSORIES

	Adapter
Brand	ULLPOWER
Model No.:	ICP20-050-3000B
Input:	100-240V~50/60Hz 0.6A
Output:	5.0V $\equiv$ 3.0A, 15.0W
SN	82-2-2686-3235
AC Cable:	Unshielded without ferrite
DC Cable:	Unshielded without ferrite



2.3 CARRIER FREQUENCY AND CHANNEL

FOR 5180 ~ 5320MHz

8 channels are provided for 802.11a, 802.11n(HT20), 802.11ac(VHT20), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180MHz	40	5200MHz
44	5220 MHz	48	5240MHz
52	5260MHz	56	5280MHz
60	5300MHz	64	5320MHz

4 channels are provided for 802.11n(HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190MHz	46	5230 MHz
54	5270MHz	62	5310MHz

2 channels are provided for 802.11ac(VHT80), 802.11ax(HE80):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
42	5210MHz	58	5290 MHz

1 channels are provided for 802.11ac(VHT160), 802.11ax(HE160):

CHANNEL	FREQUENCY
50	5250MHz

FOR 5500 ~ 5700MHz

11 channels are provided for 802.11a, 802.11n(HT20) 802.11ac(VHT40), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500MHz	124	5620MHz
104	5520MHz	128	5640MHz
108	5540MHz	132	5660MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600MHz		

5 channels are provided for 802.11n(HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		

2 channels are provided for 802.11ac(VHT80), 802.11ax(HE80):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
106	5530MHz	122	5610 MHz



1 channels are provided for 802.11ac(VHT160), 802.11ax(HE160):

CHANNEL	FREQUENCY
114	5570MHz

FOR 5745 ~ 5825MHz

5 channels are provided for 802.11a, 802.11n(HT20), 802.11ac(VHT80), 802.11ax(HE20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	153	5765MHz
157	5785MHz	161	5805MHz
165	5825MHz	--	--

2 channels are provided for 802.11n(HT40), 802.11ac(VHT40), 802.11ax(HE40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac(VHT80), 802.11ax(HE80):

CHANNEL	FREQUENCY
155	5775MHz

1. The channels which were indicated in bold type of the above channel list were selected as representative test channel. Therefore only the data of the test channels were recorded in this report.



2. By means of test software which provided by manufacture, the power levels during the tests were set according to the following codes:

Operated in 5180 ~ 5240MHz band							
802.11a		802.11ac(VHT20)/ax(HE20)		802.11ac(VHT40)/ax(HE40)		802.11ac(VHT80)/ax(HE80)	
FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING
5180	15	5180	15/12	5190	15/12	5210	15/12
5200	15	5200	15/12	5230	15/12	---	---
5240	15	5240	15/12	---	---	---	---
Operated in 5260 ~ 5320MHz band							
802.11a		802.11n(HT20)/ax(HE20)		802.11n(HT40)/ax(HE40)		802.11ac(VHT80)/ax(HE80)	
FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING
5260	15	5260	15/12	5270	15/12	5290	15/12
5300	15	5300	15/12	5310	15/12	---	---
5320	15	5320	15/12	---	---	---	---
Operated in 5500 ~ 5700MHz band							
802.11a		802.11n(HT20)/ax(HE20)		802.11n(HT40)/ax(HE40)		802.11ac(VHT80)/ax(HE80)	
FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING
5500	15	5500	15/12	5510	15/12	5530	15/12
5580	15	5550	15/12	5550	15/12	5610	15/12
5700	15	5700	15/12	5670	15/12	---	---
Operated in 5745 ~ 5825MHz band							
802.11a		802.11n(HT20)/ax(HE20)		802.11n(HT40)/ax(HE40)		802.11ac(VHT80)/ax(HE80)	
FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING	FREQUENCY (MHZ)	POWER SETTING
5745	15	5745	15/12	5755	15/12	5755	15/12
5785	15	5785	15/12	5795	15/12	---	---
5825	15	5825	15/12	---	---	---	---



2.4 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	DC 5V with wifi(5G) link

Where **RE≥1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

NOTE: "-" means no effect.

TEST CASES	ANTENNA 1	ANTENNA 2	MIMO/CDD	PARTIAL RU
AC Power Conducted Emission	/	/	O	/
6dB&26dB Emission Bandwidth	O	O	/	/
Occupied Bandwidth Measurement	O	O	/	/
Radiated Emission and Band edge	/	/	O	O
Transmit Power	O	O	O	/
Power Spectral Density	O	O	O	O
Frequency Stability	O	O	/	/
RU Configure (OFDMA)	802.11ax(HE20)	802.11ax(HE40)	802.11ax(HE80)	802.11ax(HE160)
26 Tone RU Index 0	O	/	/	/
26 Tone RU Index 8	O	/	/	/
52 Tone RU Index 37	O	/	/	/
52 Tone RU Index 40	O	/	/	/
106 Tone RU Index 53	O	/	/	/
106 Tone RU Index 54	O	/	/	/
242 Tone RU Index 61	/	O	/	/
242 Tone RU Index 62	/	O	/	/
484 Tone RU Index 65	/	/	O	/
484 Tone RU Index 66	/	/	O	/
996 Tone RU Index 67	/	/	/	O
996 Tone RU Index 68	/	/	/	O
Full RU	O	O	O	O

Note1: "O" mean test

Note2: Partial RU PSD < Full RU PSD, perform additional testing on Partial RU modes for band edge and spurious emissions

Note3: All the RU mode have been tested, only worst case are recorded



MODULATION	DATA RATE
802.11a	6Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ac VHT160	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0
802.11ax HE160	MCS0

Remark: Due to the same modulation between 802.11n and 802.11ac, meanwhile, power level for 802.11n-HT20/HT40/HT80/HT160 will not be greater than 802.11ac-VHT20/VHT40/VHT80/VHT160.

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	25.2deg. C, 57%RH	DC 5V from USB host unit	Liu Yuan
RE≥1G	25.2deg. C, 57%RH	DC 5V from USB host unit	Liu Yuan
PLC	25.2deg. C, 57%RH	DC 5V from USB host unit	Zhou Ye
APCM	25.2deg. C, 57%RH	DC 5V from USB host unit	Zhu Yulin



2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support Equipment							
NO	Description	Brand		Model No.	Serial Number	Supplied by	
1	Mobile phone	MIYU		MIYU R17-X25	N/A	Lab	
Support Cable							
NO	Description	Quantity (Number)	Length (cm)	Detachable (Yes/ No)	Shielded (Yes/ No)	Cores (Number)	Supplied by
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

ANSI C63.10-2020

All test items have been performed and recorded as per the above standards

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE:1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST PROCEDURES


a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 μ H of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit - 20 dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.


3.1.3 TEST SETUP




NOTE: For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.1.4 TEST RESULTS







3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.



3.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO	LIMIT	
KDB 789033 D02 General UNII Test Procedures New Rules v02r01	FIELD STRENGTH AT 3m	
	PK:74 (dBμV/m)	AV:54 (dBμV/m)
APPLICABLE TO	EIRP LIMIT	EQUIVALENT FIELD STRENGTH AT 3m
15.407(b)(1)	PK:-27 (dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)	Note	Note

NOTE:

For transmitters operating in the 5.725-5.85 GHz band:Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the alternative limit.

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below theband edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above orbelow the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$



3.1.3 TEST PROCEDURES


- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz)and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 TEST SETUP


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:




Note: For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Setup)



3.1.5 TEST RESULTS - BELOW 1GHz


BELOW 1GHz WORST-CASE DATA





Worst Test Mode	802.11a	Channel	CH 36
Frequency Range	9KHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Vertical



NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]
1	33.589	11.70	19.79	31.49	40.00	8.51	100	129
2	53.088	6.30	19.92	26.22	40.00	13.78	100	201
3	80.154	9.65	16.06	25.71	40.00	14.29	100	57
4	130.405	10.46	19.44	29.90	43.50	13.60	100	338
5	160.478	11.84	21.19	33.03	43.50	10.47	100	299
6	229.355	22.69	18.62	41.31	46.00	4.69	100	325

Remark: 1. 9KHz~30MHz have been test and test data more than 20dB margin.
2. The emission levels of other frequencies were greater than 20dB margin.
3. Level (dBμV/m) = Reading (dBμV/m) + Factor (dB).
4. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
5. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



3.1.6 TEST RESULTS - Band 1 (5180-5240MHz):

ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH36	Frequency	5180 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5132.00	34.61	8.18	42.79	54.00	11.21	AV
2	5137.76	46.56	8.00	54.56	74.00	19.44	PK
3	5150.00	35.34	8.03	43.37	54.00	10.63	AV
4	5150.00	46.35	8.03	54.38	74.00	19.62	PK
5	5181.46	90.82	7.75	98.57			AV
6	5186.74	98.92	7.58	106.50			PK
7	10356.80	27.53	15.59	43.12	68.20	25.08	PK
8	10360.00	18.46	15.59	34.05	54.00	19.95	AV
9	15540.00	23.74	21.44	45.18	74.00	28.82	PK
10	15540.00	15.28	21.44	36.72	54.00	17.28	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH36	Frequency	5180 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5131.52	46.05	8.20	54.25	74.00	19.75	PK
2	5147.36	35.16	8.00	43.16	54.00	10.84	AV
3	5150.00	35.55	8.03	43.58	54.00	10.42	AV
4	5150.00	46.30	8.03	54.33	74.00	19.67	PK
5	5177.14	89.70	7.79	97.49			AV
6	5178.10	98.15	7.79	105.94			PK
7	10356.80	27.83	15.59	43.42	68.20	24.78	PK
8	10360.00	18.52	15.59	34.11	54.00	19.89	AV
9	15540.00	24.24	21.44	45.68	74.00	28.32	PK
10	15540.00	14.67	21.44	36.11	54.00	17.89	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel		802.11a CH 40		Frequency		5200MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10400.00	27.07	15.80	42.87	68.20	25.33	PK
2	10400.00	18.51	15.80	34.31	54.00	19.69	AV
3	15600.00	22.92	21.58	44.50	74.00	29.50	PK
4	15600.00	13.91	21.58	35.49	54.00	18.51	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10400.00	28.01	15.80	43.81	68.20	24.39	PK
2	10400.00	18.17	15.80	33.97	54.00	20.03	AV
3	15600.00	22.81	21.58	44.39	74.00	29.61	PK
4	15600.00	14.54	21.58	36.12	54.00	17.88	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel	802.11a CH48	Frequency	5240 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
N O.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5241.49	90.37	8.02	98.39			AV
2	5241.97	98.72	8.02	106.74			PK
3	5350.00	34.11	9.66	43.77	54.00	10.23	AV
4	5350.00	45.23	9.66	54.89	74.00	19.11	PK
5	5360.11	46.62	9.75	56.37	74.00	17.63	PK
6	5409.57	34.58	10.01	44.59	54.00	9.41	AV
7	10480.00	27.49	15.87	43.36	68.20	24.84	PK
8	10480.00	18.48	15.87	34.35	54.00	19.65	AV
9	15720.00	23.42	22.33	45.75	74.00	28.25	PK
10	15720.00	13.67	22.33	36.00	54.00	18.00	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH48	Frequency	5240 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5241.49	88.35	8.02	96.37			AV
2	5241.97	97.18	8.02	105.20			PK
3	5350.00	44.41	9.66	54.07	74.00	19.93	PK
4	5350.00	34.17	9.66	43.83	54.00	10.17	AV
5	5412.46	46.47	9.88	56.35	74.00	17.65	PK
6	5415.34	34.95	9.74	44.69	54.00	9.31	AV
7	10480.00	27.68	15.87	43.55	68.20	24.65	PK
8	10480.00	18.15	15.87	34.02	54.00	19.98	AV
9	15720.00	22.99	22.33	45.32	74.00	28.68	PK
10	15720.00	14.09	22.33	36.42	54.00	17.58	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



3.1.7 TEST RESULTS - Band 2 (5260-5320MHz):


ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH52	Frequency	5260 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5109.91	34.55	8.08	42.63	54.00	11.37	AV
2	5133.44	46.64	8.15	54.79	74.00	19.21	PK
3	5150.00	34.12	8.03	42.15	54.00	11.85	AV
4	5150.00	44.20	8.03	52.23	74.00	21.77	PK
5	5259.74	98.42	9.10	107.52			PK
6	5261.66	90.61	9.01	99.62			AV
7	10520.00	28.18	15.70	43.88	68.20	24.32	PK
8	10520.00	18.86	15.70	34.56	54.00	19.44	AV
9	15780.00	22.90	22.35	45.25	74.00	28.75	PK
10	15780.00	13.05	22.35	35.40	54.00	18.60	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH52	Frequency	5260 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5119.99	34.75	7.76	42.51	54.00	11.49	AV
2	5125.27	46.19	8.02	54.21	74.00	19.79	PK
3	5150.00	44.78	8.03	52.81	74.00	21.19	PK
4	5150.00	34.14	8.03	42.17	54.00	11.83	AV
5	5255.90	88.43	8.69	97.12			AV
6	5261.66	96.30	9.01	105.31			PK
7	10520.00	26.96	15.70	42.66	68.20	25.54	PK
8	10520.00	18.59	15.70	34.29	54.00	19.71	AV
9	15780.00	22.18	22.35	44.53	74.00	29.47	PK
10	15780.00	13.13	22.35	35.48	54.00	18.52	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]




Channel		802.11a CH60		Frequency		5300MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10600.00	27.63	15.48	43.11	74.00	30.89	PK
2	10600.00	18.44	15.48	33.92	54.00	20.08	AV
3	15900.00	22.59	22.49	45.08	74.00	28.92	PK
4	15900.00	13.51	22.49	36.00	54.00	18.00	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	10600.00	27.26	15.48	42.74	74.00	31.26	PK
2	10600.00	18.80	15.48	34.28	54.00	19.72	AV
3	15900.00	22.07	22.49	44.56	74.00	29.44	PK
4	15900.00	14.44	22.49	36.93	54.00	17.07	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel	802.11a CH64	Frequency	5320 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5321.21	89.99	8.74	98.73			AV
2	5321.69	98.46	8.76	107.22			PK
3	5350.00	36.03	9.66	45.69	54.00	8.31	AV
4	5350.00	47.42	9.66	57.08	74.00	16.92	PK
5	5359.15	47.95	9.75	57.70	74.00	16.30	PK
6	5360.11	35.13	9.75	44.88	54.00	9.12	AV
7	10640.00	28.43	15.47	43.90	74.00	30.10	PK
8	10640.00	18.18	15.47	33.65	54.00	20.35	AV
9	15960.00	23.92	22.57	46.49	74.00	27.51	PK
10	15960.00	14.30	22.57	36.87	54.00	17.13	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH64			Frequency	5320 MHz		
Frequency Range	Above 1G			Detector Function	PK/AV		
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5315.93	95.73	8.77	104.50			PK
2	5316.41	87.58	8.76	96.34			AV
3	5350.00	35.23	9.66	44.89	54.00	9.11	AV
4	5350.00	46.92	9.66	56.58	74.00	17.42	PK
5	5361.55	35.04	9.73	44.77	54.00	9.23	AV
6	5380.76	46.90	9.82	56.72	74.00	17.28	PK
7	10640.00	26.73	15.47	42.20	74.00	31.80	PK
8	10640.00	18.77	15.47	34.24	54.00	19.76	AV
9	15960.00	23.12	22.57	45.69	74.00	28.31	PK
10	15960.00	13.77	22.57	36.34	54.00	17.66	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



3.1.8 TEST RESULTS - Band 3 (5500-5700MHz):

ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH100	Frequency	5500 MHz				
Frequency Range	Above 1G	Detector Function	PK/AV				
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5411.16	46.55	9.96	56.51	74.00	17.49	PK
2	5462.81	48.16	9.78	57.94	68.20	10.26	PK
3	5470.00	48.21	9.75	57.96	68.20	10.24	PK
4	5476.06	39.13	9.22	48.35	54.00	5.65	AV
5	5499.20	99.05	8.98	108.03			PK
6	5502.70	90.01	9.16	99.17			AV
7	11000.00	26.24	16.33	42.57	74.00	31.43	PK
8	11000.00	17.77	16.33	34.10	54.00	19.90	AV
9	16500.00	22.08	24.06	46.14	68.20	22.06	PK
10	16500.00	12.13	24.06	36.19	54.00	17.81	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.

2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).

3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).


4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH100	Frequency	5500 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5451.93	46.96	9.57	56.53	74.00	17.47	PK
2	5465.31	47.62	9.77	57.39	68.20	10.81	PK
3	5470.00	47.07	9.75	56.82	68.20	11.38	PK
4	5470.31	35.32	9.73	45.05	54.00	8.95	AV
5	5504.08	95.14	9.24	104.38			PK
6	5504.20	86.85	9.24	96.09			AV
7	11000.00	27.35	16.33	43.68	74.00	30.32	PK
8	11000.00	17.50	16.33	33.83	54.00	20.17	AV
9	16500.00	21.28	24.06	45.34	68.20	22.86	PK
10	16500.00	12.24	24.06	36.30	54.00	17.70	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel		802.11a CH 116		Frequency		5580MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11160.00	26.90	16.69	43.59	74.00	30.41	PK
2	11160.00	17.59	16.69	34.28	54.00	19.72	AV
3	16740.00	21.91	25.38	47.29	68.20	20.91	PK
4	16740.00	12.17	25.38	37.55	54.00	16.45	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11160.00	27.08	16.69	43.77	74.00	30.23	PK
2	11160.00	18.35	16.69	35.04	54.00	18.96	AV
3	16740.00	20.79	25.38	46.17	68.20	22.03	PK
4	16740.00	12.32	25.38	37.70	54.00	16.30	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBuV/m] - Level [dBuV/m]							



Channel		802.11a CH140		Frequency		5700 MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5702.78	98.93	8.87	107.80			PK
2	5725.00	48.07	8.89	56.96	68.20	11.24	PK
3	5729.79	48.63	8.69	57.32	68.20	10.88	PK
4	11400.00	28.04	16.60	44.64	74.00	29.36	PK
5	11400.00	17.57	16.60	34.17	54.00	19.83	AV
6	17100.00	21.05	27.23	48.28	68.20	19.92	PK
7	17100.00	10.95	27.23	38.18	54.00	15.82	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel		802.11a CH140		Frequency		5700 MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5696.77	97.26	8.66	105.92			PK
2	5725.00	46.71	8.89	55.60	68.20	12.60	PK
3	5738.99	48.35	8.91	57.26	68.20	10.94	PK
4	11400.00	25.95	16.60	42.55	74.00	31.45	PK
5	11400.00	17.34	16.60	33.94	54.00	20.06	AV
6	17100.00	19.62	27.23	46.85	68.20	21.35	PK
7	17100.00	11.03	27.23	38.26	54.00	15.74	AV

Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel		802.11a CH144		Frequency		5720 MHz	
Frequency Range		Above 1G		Detector Function		PK/AV	
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11440.00	26.15	16.50	42.65	74.00	31.35	PK
2	11440.00	16.88	16.50	33.38	54.00	20.62	AV
3	17160.00	19.92	27.22	47.14	68.20	21.06	PK
4	17160.00	10.65	27.22	37.87	54.00	16.13	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11440.00	25.56	16.50	42.06	74.00	31.94	PK
2	11440.00	16.36	16.50	32.86	54.00	21.14	AV
3	17160.00	19.26	27.22	46.48	68.20	21.72	PK
4	17160.00	11.35	27.22	38.57	54.00	15.43	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]							



3.1.9 TEST RESULTS - Band 4 (5745-5825MHz):


ABOVE 1GHz DATA

All test modes have been conducted, and the report only presents the worst case.

Channel	802.11a CH149	Frequency	5745 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5611.44	47.68	9.03	56.71	68.20	11.49	PK
2	5743.88	98.87	8.94	107.81			PK
3	5925.10	47.40	10.40	57.80	68.20	10.40	PK
4	11490.00	25.99	16.45	42.44	74.00	31.56	PK
5	11490.00	18.04	16.45	34.49	54.00	19.51	AV
6	17235.00	19.73	27.05	46.78	68.20	21.42	PK
7	17235.00	12.69	27.05	39.74	54.00	14.26	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin (dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH149	Frequency	5745 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5627.20	47.46	9.03	56.49	68.20	11.71	PK
2	5746.32	95.35	8.93	104.28			PK
3	5939.54	47.30	10.80	58.10	68.20	10.10	PK
4	11490.00	25.19	16.45	41.64	74.00	32.36	PK
5	11490.00	18.90	16.45	35.35	54.00	18.65	AV
6	17235.00	21.55	27.05	48.60	68.20	19.60	PK
7	17235.00	13.94	27.05	40.99	54.00	13.01	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin (dB) = Limit [dBμV/m] - Level [dBμV/m]




Channel	802.11a CH157			Frequency	5785 MHz		
Frequency Range	Above 1G			Detector Function	PK/AV		
Horizontal							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11570.00	26.18	16.81	42.99	74.00	31.01	PK
2	11570.00	18.77	16.81	35.58	54.00	18.42	AV
3	17355.00	20.21	28.18	48.39	68.20	19.81	PK
4	17355.00	12.78	28.18	40.96	54.00	13.04	AV
Vertical							
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	11570.00	26.23	16.81	43.04	74.00	30.96	PK
2	11570.00	19.48	16.81	36.29	54.00	17.71	AV
3	17355.00	21.10	28.18	49.28	68.20	18.92	PK
4	17355.00	13.15	28.18	41.33	54.00	12.67	AV
Remark: 1. The emission levels of other frequencies were greater than 20dB margin. 2. Level (dBuV/m) = Reading (dBuV) + Factor (dB/m). 3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB). 4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]							



Channel	802.11a CH165	Frequency	5825 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Horizontal

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5642.02	47.59	8.52	56.11	68.20	12.09	PK
2	5824.17	98.58	8.81	107.39			PK
3	5968.81	48.71	9.99	58.70	68.20	9.50	PK
4	11650.00	27.34	16.70	44.04	74.00	29.96	PK
5	11650.00	19.53	16.70	36.23	54.00	17.77	AV
6	17475.00	19.68	28.12	47.80	68.20	20.40	PK
7	17475.00	12.66	28.12	40.78	54.00	13.22	AV




Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



Channel	802.11a CH165	Frequency	5825 MHz
Frequency Range	Above 1G	Detector Function	PK/AV

Vertical

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector
1	5648.96	48.48	8.80	57.28	68.20	10.92	PK
2	5825.49	94.43	8.79	103.22			PK
3	5931.29	47.69	10.54	58.23	68.20	9.97	PK
4	11650.00	26.89	16.70	43.59	74.00	30.41	PK
5	11650.00	19.57	16.70	36.27	54.00	17.73	AV
6	17475.00	20.09	28.12	48.21	68.20	19.99	PK
7	17475.00	12.25	28.12	40.37	54.00	13.63	AV



Remark: 1. The emission levels of other frequencies were greater than 20dB margin.
2. Level (dBμV/m) = Reading (dBμV) + Factor (dB/m).
3. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
4. Margin(dB) = Limit[dBμV/m] - Level [dBμV/m]



3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 Measurement procedure

The transmitter antenna output was connected to the spectrum analyzer through an attenuator. The resolution bandwidth shall be set to the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP





3.4 26DB EMISSION BANDWIDTH

3.4.1 LIMITS OF 26DB EMISSION BANDWIDTH

This section is for reporting purpose only, there is on restriction limit of bandwidth


3.4.2 TEST PROCEDURES

FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

3.4.3 TEST SETUP

FOR 26dB BANDWIDTH





3.5 6DB EMISSION BANDWIDTH

3.5.1 LIMITS OF 6DB EMISSION BANDWIDTH

The minimum of 6dB Bandwidth Measurement is 0.5MHz.


3.5.2 TEST PROCEDURES

FOR 6dB BANDWIDTH

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW) ≥ 3 RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 TEST SETUP

FOR 6dB BANDWIDTH





3.6 TRANSMIT POWER MEASUREMENT

3.6.1 LIMITS OF TRANSMIT POWER MEASUREMENT(FCC)

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
		Indoor Access Point	1 Watt (30 dBm)
	√	Mobile and Portable client device	250mW (24 dBm)
U-NII-2A	√		250mW(24dBm) or 11 dBm+10LogB*
U-NII-2C	√		250mW(24dBm) or 11 dBm+10LogB*
U-NII-3	√		1 Watt (30 dBm)


NOTE: 1. Where B is the 26dB emission bandwidth in MHz.

3.6.2 TEST PROCEDURES

FOR AVERAGE POWER MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is added to measured value.

3.6.3 TEST SETUP





3.7 POWER SPECTRAL DENSITY MEASUREMENT

3.7.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT(FCC)

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
		Indoor Access Point	
	√	Mobile and Portable client device	11dBm/ MHz
U-NII-2A	√		11dBm/ MHz
U-NII-2C	√		11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

3.7.2 TEST PROCEDURE

For U-NII-1, U-NII-2A, U-NII-2Cband:

Using method SA-2


- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1MHz, Set VBW =3 MHz, Detector = AV
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to“free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 300 kHz, Set VBW =1 MHz, Detector = AV
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to“free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

3.7.3 TEST SETUP



3.8 FREQUENCY STABILITY


3.8.1 LIMITS OFFREQUENCY STABILITY

The frequency of the carrier signal shall be maintained within band of operation.

3.8.2 TEST PROCEDURES

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

3.8.3 TEST SETUP





3.9 ANTENNA REQUIREMENT

3.9.1 LIMITS OFFREQUENCY STABILITY

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. According to FCC 47 CFR Section 15.407(a)(1)(2) , if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.9.2 ANTENNA ANTI-REPLACEMENT CONSTRUCTION

The antenna used for this product is PIFA antenna and that no antenna other than that furnished by the responsible party shall be used with the device



3.9.3 ANTENNA GAIN

Refer to KDB662911 D01 Multiple Transmitter Output v02r01.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements on all devices,

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain “DG” is calculated as following table.

Operation Band	Chain 1 Antenna Gain(dBi)	Chain 2 Antenna Gain(dBi)	DG For PSD (dBi)	DG For Power (dBi)	PSD Limit Reduction	Power Limit Reduction
WiFi 5G Band1	0.88	0.34	3.62	0.88	0	0
WiFi 5G Band2	0.88	0.34	3.62	0.88	0	0
WiFi 5G Band3	1.92	-0.36	3.86	1.92	0	0
WiFi 5G Band4	-1.61	-0.90	1.76	-0.90	0	0

Calculation example:

$G_{ANT1} = 0.88\text{dBi}$; $G_{ANT2} = 0.34\text{dBi}$

Directional gain of power measurement = $\max(0.88, 0.34) = 0.88\text{dBi}$

Directional gain of PSD derived from formula which is:

$10 \log \{ [10^{(0.88 \text{ dBi}/20)} + 10^{(0.34 \text{ dBi}/20)}]^2 / 2 \} = 3.62\text{dBi}$

Power and PSD limit reduction = Composite gain -6dBi



4 PHOTOGRAPHS OF TEST SETUP

Please refer to the attached file (Test Setup Photo).



5 PHOTOGRAPHS OF THE EUT

Please refer to the attached file (External Photos report and Internal Photos).

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street,
Longhua District, Shenzhen, Guangdong, 518110, P. R. China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>