

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2002-0024

2. Customer

• Name : BLUEBIRD INC.

• Address : (Dogok-dong, SEI Tower 13,14) 39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea

3. Use of Report : FCC & IC Original Grant

4. Product Name / Model Name : Smart Rugged Tablet Computer / ST102

FCC ID : SS4ST102 / IC : 22515-ST102

5. Test Method Used : KDB971168 D01v03, ANSI/TIA-603-E-2016, ANSI C63.26-2015

Test Specification : §2, §24, §27

RSS-130 Issue 2, 133 Issue 6, 139 Issue 3

6. Date of Test : 2019.09.09 ~ 2019.11.12

7. Testing Environment : Refer to appended test report.

8. Test Result : Refer to the attached test result.

Affirmation	Tested by	 (Signature)	Reviewed by	 (Signature)
	Name : Inhee Bae		Name : JaeJin Lee	

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2020 . 02 . 03 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Tested by	Reviewed by
DRTFCC2002-0024	Feb. 03, 2020	Initial issue	InHee Bae	JaeJin Lee

Table of Contents

1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1 EUT DESCRIPTION	6
2.2. EUT CAPABILITIES	6
2.3. TESTING ENVIRONMENT.....	6
2.4 MEASURING INSTRUMENT CALIBRATION.....	6
2.5. MEASUREMENT UNCERTAINTY	6
2.6. TEST FACILITY.....	6
3. DESCRIPTION OF TESTS.....	7
3.1 ERP & EIRP (Effective Radiated Power & Equivalent Isotropic Radiated Power)	7
3.2 PEAK TO AVERAGE RATIO	9
3.3 OCCUPIED BANDWIDTH.....	10
3.4 BAND EDGE EMISSIONS AT ANTENNA TERMINAL	11
3.5 EMISSION MASK.....	12
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	13
3.7 UNDESIRABLE EMISSIONS.....	14
3.8 FREQUENCY STABILITY	15
4. LIST OF TEST EQUIPMENT.....	16
5. SUMMARY OF TEST RESULTS.....	17
6. SAMPLE CALCULATION	18
7. TEST DATA	20
7.1 OCCUPIED BANDWIDTH.....	20
7.2 PEAK TO AVERAGE RATIO	20
7.3 BAND EDEG EMISSIONS (Conducted)	20
7.4 SPURIOUS AND HARMONICS EMISSIONS (Conducted)	20
7.5 EMISSION MASK (Conducted)	20
7.6 ERP & EIRP	21
7.6.1 LTE Band 12.....	21
7.6.2 LTE Band 4.....	22
7.6.3 LTE Band 2.....	23
7.7 UNDESIRABLE EMISSIONS (Radiated)	24
7.7.1 LTE Band 12.....	24
7.7.2 LTE Band 4.....	25
7.7.3 LTE Band 2.....	26
7.8 FREQUENCY STABILITY	27
7.8.1 LTE Band 12.....	27
7.8.2 LTE Band 4.....	28
7.8.3 LTE Band 2.....	29
8. TEST PLOTS.....	30
8.1 OCCUPIED BANDWIDTH.....	30
8.1.1 LTE Band 12.....	30
8.1.2 LTE Band 4.....	34

8.1.3 LTE Band 2.....	40
8.2 PEAK TO AVERAGE RATIO	46
8.2.1 LTE Band 12.....	46
8.2.2 LTE Band 4.....	50
8.2.3 LTE Band 2.....	56
8.3 BAND EDGE EMISSIONS(Conducted)	62
8.3.1 LTE Band 12.....	62
8.3.2 LTE Band 4.....	70
8.3.3 LTE Band 2.....	82
8.4 SPURIOUS AND HARMONICS EMISSIONS(Conducted).....	94
8.4.1 LTE Band 12.....	94
8.4.2 LTE Band 4.....	101
8.4.3 LTE Band 2.....	119

1. GENERAL INFORMATION

Applicant Name : BLUEBIRD INC.
Address : (Dogok-dong, SEI Tower 13,14) 39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea
FCC ID : SS4ST102
IC : 22515-ST102
FCC Classification : PCS Licensed Transmitter (PCB)
EUT Type : Smart Rugged Tablet Computer
Model Name : ST102
Add Model Name : NA
Supplying power : DC 3.80 V
Antenna Information : PIFA Antenna

Mode	TX Frequency (MHz)	Emission Designator	Modulation	ERP		EIRP	
				Max power (dBm)	Max power (W)	Max power (dBm)	Max power (W)
LTE Band 12	704 ~ 711	8M93G7D	QPSK	16.69	0.047	-	-
LTE Band 12	704 ~ 711	8M94W7D	16QAM	15.31	0.034	-	-
LTE Band 12	701.5 ~ 713.5	4M48G7D	QPSK	16.61	0.046	-	-
LTE Band 12	701.5 ~ 713.5	4M48W7D	16QAM	15.26	0.034	-	-
LTE Band 12	700.5 ~ 714.5	2M69G7D	QPSK	16.51	0.045	-	-
LTE Band 12	700.5 ~ 714.5	2M69W7D	16QAM	15.10	0.032	-	-
LTE Band 12	699.7 ~ 715.3	1M09G7D	QPSK	16.48	0.044	-	-
LTE Band 12	699.7 ~ 715.3	1M09W7D	16QAM	15.09	0.032	-	-
LTE Band 4	1720 ~ 1745	17M9G7D	QPSK	-	-	17.60	0.058
LTE Band 4	1720 ~ 1745	17M9W7D	16QAM	-	-	16.11	0.041
LTE Band 4	1717.5 ~ 1747.5	13M4G7D	QPSK	-	-	17.39	0.055
LTE Band 4	1717.5 ~ 1747.5	13M4W7D	16QAM	-	-	15.81	0.038
LTE Band 4	1715 ~ 1750	8M96G7D	QPSK	-	-	17.06	0.051
LTE Band 4	1715 ~ 1750	8M94W7D	16QAM	-	-	15.67	0.037
LTE Band 4	1712.5 ~ 1752.5	4M48G7D	QPSK	-	-	17.34	0.054
LTE Band 4	1712.5 ~ 1752.5	4M49W7D	16QAM	-	-	15.83	0.038
LTE Band 4	1711.5 ~ 1753.5	2M69G7D	QPSK	-	-	17.37	0.055
LTE Band 4	1711.5 ~ 1753.5	2M69W7D	16QAM	-	-	15.73	0.037
LTE Band 4	1710.7 ~ 1754.3	1M09G7D	QPSK	-	-	17.23	0.053
LTE Band 4	1710.7 ~ 1754.3	1M09W7D	16QAM	-	-	15.59	0.036
LTE Band 2	1860 ~ 1900	17M9G7D	QPSK	-	-	16.89	0.049
LTE Band 2	1860 ~ 1900	17M8W7D	16QAM	-	-	15.76	0.038
LTE Band 2	1857.5 ~ 1902.5	13M4G7D	QPSK	-	-	17.14	0.052
LTE Band 2	1857.5 ~ 1902.5	13M4W7D	16QAM	-	-	16.06	0.040
LTE Band 2	1855 ~ 1905	8M95G7D	QPSK	-	-	17.57	0.057
LTE Band 2	1855 ~ 1905	8M95W7D	16QAM	-	-	16.26	0.042
LTE Band 2	1852.5 ~ 1907.5	4M49G7D	QPSK	-	-	17.51	0.056
LTE Band 2	1852.5 ~ 1907.5	4M49W7D	16QAM	-	-	16.21	0.042
LTE Band 2	1851.5 ~ 1908.5	2M69G7D	QPSK	-	-	17.42	0.055
LTE Band 2	1851.5 ~ 1908.5	2M69W7D	16QAM	-	-	16.06	0.040
LTE Band 2	1850.7 ~ 1909.3	1M09G7D	QPSK	-	-	17.31	0.054
LTE Band 2	1850.7 ~ 1909.3	1M09W7D	16QAM	-	-	16.03	0.040

2. INTRODUCTION

2.1 EUT DESCRIPTION

The Equipment Under Test (EUT) supports WCDMA/LTE Tablet with Bluetooth, WLAN.

2.2. EUT CAPABILITIES

This EUT contains the following capabilities:

850/1700/1900 WCDMA/HSUPA, Multi-band LTE, 802.11b/g/n WLAN(2.4GHz),
802.11a/n WLAN(5GHz), Bluetooth(BDR, EDR, LE).

2.3. TESTING ENVIRONMENT

Ambient Condition	
▪ Temperature	+23 °C ~ +25 °C
▪ Relative Humidity	39 % ~ 45 %

2.4 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Radiated Disturbance (Below 1 GHz)	5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated Disturbance (Above 18 GHz)	5.3 dB (The confidence level is about 95 %, $k = 2$)


2.6. TEST FACILITY

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI 63.4-2014.		
- FCC MRA Accredited Test Firm No. : KR0034		
- IC Test site No. : 5740A		
www.dtnet.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

3. DESCRIPTION OF TESTS

3.1 ERP & EIRP (Effective Radiated Power & Equivalent Isotropic Radiated Power)

Test Set-up



These measurements were performed at 3 m test site. The equipment under test is placed on a non-conductive table 0.8 meters or 1.5 meters above a turntable which is flush with the ground plane and 3 meters from the receive antenna. For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.

Test Procedure

- ANSI/TIA-603-E-2016 - Section 2.2.17
- KDB971168 D01v03 - Section 5.2.2
- ANSI C63.26-2015 – Section 5.2.4.4.1

Test setting

1. Set span to 2 x to 3 x the OBW.
2. Set RBW = 1% to 5% of the OBW.
3. Set VBW $\geq$ 3 x RBW.
4. Set number of points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
 - 1) Set = auto-couple, or
 - 2) Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. Transmission period is the on and off time of the transmitter.
6. Detector = power averaging (rms).
7. If the EUT can be configured to transmit continuously, then set the trigger to free run.
8. If the EUT cannot be configured to transmit continuously, then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Verify that the sweep time is less than or equal to the transmission burst duration. Time gating can also be used under similar constraints (i.e., configured such that measurement data is collected only during active full-power transmissions).
9. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over multiple symbols, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.

10. Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function, with the band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

The receiver antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer.

A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminal of the substitute antenna is measured.


The ERP/EIRP is calculated using the following formula:

ERP/EIRP = The conducted power at the substitute antenna's terminal [dBm] + Substitute Antenna gain [dBd for ERP , dBi for EIRP]

For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn antenna and an isotropic antenna are taken into consideration.

3.2 PEAK TO AVERAGE RATIO

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 5.7.2
- ANSI C63.26-2015 – Section 5.2.3.4

A peak to average ratio measurement is performed at the conducted port of the EUT.

The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The present of time the signal spends at or above the level defines the probability for that particular power level.


Test setting

The spectrum Analyzer's CCDF measurement function is enabled.

1. Set resolution/measurement bandwidth $\geq$ OBW or specified reference bandwidth.
2. Set the number of counts to a value that stabilizes the measured CCDF curve.
3. Set the measurement interval as follows:
 - 1) For continuous transmissions, set to the greater of $[10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$ or 1 ms.
 - 2) For burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize. Set the measurement interval to a time that is less than or equal to the burst duration.
 - 3) If there are several carriers in a single antenna port, the peak power shall be determined for each individual carrier (by disabling the other carriers while measuring the required carrier) and the total peak power calculated from the sum of the individual carrier peak powers.
4. Record the maximum PAPR level associated with a probability of 0.1%.
5. The peak power level is calculated from the sum of the PAPR value from step d) to the measured average power.

3.3 OCCUPIED BANDWIDTH.

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 4.3
- ANSI C63.26-2015 – Section 5.4.4


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power of a given emission.

Test setting

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 \sim 5 \%$ of the expected OBW & $VBW \geq 3 \times RBW$
3. Detector = Peak
4. Trance mode = Max hold
5. Sweep = Auto couple
6. The trace was allowed to stabilize
7. If necessary, step 2 ~ 6 were repeated after changing the RBW such that it would be within 1 ~ 5 % of the 99 % occupied bandwidth observed in step 6.

3.4 BAND EDGE EMISSIONS AT ANTENNA TERMINAL

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 6
- ANSI C63.26-2015 – Section 5.7

All out of band emissions are measured by means of a calibrated spectrum analyzer. The EUT was setup to maximum output power at its lowest and highest channel with all bandwidths, modulations and RB configurations.

The power of any spurious emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.

Test setting

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW ≥ 1 % of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS & Trace mode = Max hold
6. Sweep time = Auto couple or 1 s for band edge
7. Number of sweep point $\geq 2 \times$ span / RBW
8. The trace was allowed to stabilize


Note 1: Per Part 24.238(b) / 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Note 2: Per Part 27(g) for operations in the 600 MHz band and the 698-746 MHz band, compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

3.5 EMISSION MASK

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 6
- ANSI C63.26-2015 – Section 5.7

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The EUT was setup to maximum output power at its low, middle, high channel with all bandwidths, modulations and RB configurations.

Transmitters used in the radio services by Part 90 must comply with the emission masks.


Test setting

1. RBW = 100 kHz(Below 1 GHz) or 1 MHz(Above 1 GHz) & VBW $\geq 3 \times$ RBW (Refer to Note 1)
2. Detector = RMS & Trace mode = Max hold
3. Sweep time = Auto couple
4. Number of sweep point $\geq 2 \times$ span / RBW
5. The trace was allowed to stabilize

Note 1: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1GHz and 1MHz or greater for frequencies greater than 1GHz.

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 6
- ANSI C63.26-2015 – Section 5.7

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The EUT was setup to maximum output power at its low, middle, high channel with all bandwidths, modulations and RB configurations. The spectrum is scanned from 9 kHz up to a frequency including its 10th harmonic.

The power of any spurious emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.


Test setting

6. RBW = 100 kHz(Below 1 GHz) or 1 MHz(Above 1 GHz) & VBW $\geq 3 \times$ RBW (Refer to Note 1)
7. Detector = RMS & Trace mode = Max hold
8. Sweep time = Auto couple
9. Number of sweep point $\geq 2 \times$ span / RBW
10. The trace was allowed to stabilize

Note 1: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for frequencies less than 1GHz and 1MHz or greater for frequencies greater than 1GHz.

3.7 UNDESIRABLE EMISSIONS

Test Set-up



These measurements were performed at 3 test site. The equipment under test is placed on a non-conductive table 0.8 meters or 1.5 meters above a turntable which is flush with the ground plane and 3 meters from the receive antenna. For measurements above 1 GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.

Test Procedure

- ANSI/TIA-603-E-2016 - Section 2.2.12
- KDB971168 D01v03 - Section 5.8
- ANSI C63.26-2015 – Section 5.5

Test setting

1. RBW = 100 kHz for below 1 GHz and 1 MHz for above 1 GHz / VBW $\geq 3 \times$ RBW
2. Detector = RMS & Trace mode = Max hold
3. Sweep time = Auto couple
4. Number of sweep point $\geq 2 \times$ span / RBW
5. The trace was allowed to stabilize

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer.


For radiated power measurements below 1 GHz, a half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading.

For radiated power measurements above 1 GHz, a Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. The difference between the gain of the horn and an isotropic antenna are taken into consideration.

This measurement was performed with the EUT oriented in 3 orthogonal axis.

3.8 FREQUENCY STABILITY

Test Set-up



Test Procedure

- ANSI/TIA-603-E-2016
- KDB971168 D01v03 - Section 9

The frequency stability of the transmitter is measured by:

a.) **Temperature:**

The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.

b.) **Primary Supply Voltage:**

The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification:

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block for Part 24, 27. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency for Part 22.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature.
(20 °C to provide a reference)
2. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C.
A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

4. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal. Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/06/26	20/06/26	MY46471251
Spectrum Analyzer	Agilent Technologies	N9030A	19/03/15	20/03/15	MY53310140
DC power supply	Agilent Technologies	66332A	19/06/25	20/06/25	MY43000394
Multimeter	FLUKE	17B	18/12/18	19/12/18	26030065WS
Power Splitter	Anritsu	K241B	18/12/19	19/12/19	016681
Power Divider	Weinschel	WA1575	19/06/25	20/06/25	WA1575-1
Temp & Humi	MG Indus	THP31R1	19/07/04	20/07/04	20131002-1
Radio Communication Analyzer	ANRITSU	MT8820C	18/12/20	19/12/20	6201274516
Thermohygrometer	BODYCOM	BJ5478	18/12/27	19/12/27	120612-2
Thermohygrometer	BODYCOM	BJ5478	18/12/27	19/12/27	120612-1
Signal Generator	Rohde Schwarz	SMBV100A	18/12/19	19/12/19	255571
Signal Generator	ANRITSU	MG3695C	18/12/20	19/12/20	173501
Loop Antenna	ETS-Lindgren	6502	19/09/18	21/09/18	00226186
BILOG ANTENNA	Schwarzbeck	VULB9160	19/04/23	21/04/23	9160-3362
Dipole Antenna	Schwarzbeck	VHA9103	19/02/28	21/02/28	2116
Dipole Antenna	Schwarzbeck	VHA9103	18/04/13	20/04/13	2117
Dipole Antenna	Schwarzbeck	FCC-4	19/03/26	21/03/26	710A
Dipole Antenna	Schwarzbeck	UHA9105	18/04/13	20/04/13	2262
HORN ANT	ETS	3117	18/05/10	20/05/10	00140394
HORN ANT	ETS	3117	18/03/26	20/03/26	00152145
HORN ANT	A.H.Systems	SAS-574	19/04/23	21/04/23	154
HORN ANT	A.H.Systems	SAS-574	19/07/03	21/07/03	155
Amplifier	RFBAY.Inc.	MPA-40-40	18/12/10	19/12/10	21151801
Amplifier	EMPOWER	BBS3Q7ELU	19/06/24	20/06/24	1020
PreAmplifier	H.P	8447D	18/12/18	19/12/18	2944A07774
PreAmplifier	Agilent	8449B	19/06/27	20/06/27	3008A02108
High-pass filter	Wainwright	WHKX12-935-1000-15000-40SS	19/06/24	20/06/24	7
High-pass filter	Wainwright	WHKX12-2580-3000-18000-80SS	19/06/24	20/06/24	3
High-pass filter	Wainwright	WHNX8.5/26.5G-6SS	19/06/24	20/06/24	1
Cable	Radiall	TESTPRO3	19/01/16	20/01/16	M-01
Cable	DTNC	Cable	19/01/16	20/01/16	M-04
Cable	Junkosha	MWX315	19/01/16	20/01/16	M-05
Cable	Junkosha	MWX221	19/01/16	20/01/16	M-06
Cable	DTNC	Cable	19/01/16	20/01/16	RF-73

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Status Note 1
2.1046	-	Conducted Output Power	N/A	Conducted	C Note2
2.1049	RSS-GEN[6.7]	Occupied Bandwidth	N/A		C
24.232(d) 27.50(d.5)	RSS-130 [4.6.1] RSS-133 [6.4] RSS-139 [6.5]	Peak to Average Ratio	< 13 dB		C
2.1051 24.238(a) 27.53(g) 27.53(h)	RSS-130 [4.7.1] RSS-133 [6.5] RSS-139 [6.6]	Band Edge / Conducted Spurious Emissions	> 43 + 10log ₁₀ (P) dB at Band edge and for all out-of-band emissions		C
2.1055 24.235 27.54	RSS-130 [4.5] RSS-133 [6.3] RSS-139 [6.4]	Frequency Stability	Fundamental emissions must stay within Authorized frequency block (Part 24, 27)		C
27.50(c.10)	RSS-130 [4.6.3]	Radiated Output Power (B12)	< 3 Watts max. ERP (FCC & IC)	Radiated	C
27.50(d.4)	RSS-139 [6.5]	Radiated Output Power (B4)	< 1 Watts max. EIRP (FCC & IC)		C
24.232(c)	RSS-133 [6.4]	Radiated Output Power (B2)	< 2 Watts max. EIRP (FCC & IC)		C
2.1053 24.238(a) 27.53(g) 27.53(h)	RSS-130 [4.7.1] RSS-133 [6.5] RSS-139 [6.6]	Undesirable Emissions	> 43 + 10log ₁₀ (P) dB for all out-of-band emissions		C
Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable Note 2: Refer to RF Exposure Report (Test Report SAR)					

6. SAMPLE CALCULATION

A. Emission Designator

LTE Band 12 (QPSK)

Emission Designator = **8M93G7D**
LTE OBW = 8.930 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data Transmission

LTE Band 4(QPSK)

Emission Designator = **17M9G7D**
LTE OBW = 17.873 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data Transmission

LTE Band 2(QPSK)

Emission Designator = **17M9G7D**
LTE OBW = 17.879 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data Transmission

LTE Band 12 (16QAM)

Emission Designator = **8M94W7D**
LTE OBW = 8.940 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data Transmission

LTE Band 4(16QAM)

Emission Designator = **17M9W7D**
LTE OBW = 17.860 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data Transmission

LTE Band 2(16QAM)

Emission Designator = **17M8W7D**
LTE OBW = 17.844 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data Transmission

B. For substitution method

EIRP for Band 4

Channel Bandwidth (MHz)	Test Frequency (MHz)	Test Mode	RB Size/ Offset	Spectrum Reading Value(dBm)	EUT Axis	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain (dBi)	EIRP (dBm)	EIRP (W)
20	1720	QPSK	1/50	-28.34	Z	H	11.65	5.95	17.60	0.058

ERP or EIRP = Level @ Ant Terminal LEVEL(dBm) + Tx Ant. Gain

- 1) The EUT mounted on a non-conductive turntable is 0.8 meters or 1.5 meters above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with substituted antenna gain is the rating of ERP, EIRP or Radiated spurious emission.

7. TEST DATA

7.1 OCCUPIED BANDWIDTH

- Plots of the EUT's Occupied Bandwidth are shown in Clause 8.1

7.2 PEAK TO AVERAGE RATIO

- Plots of the EUT's Peak- to- Average Ratio are shown in Clause 8.2

7.3 BAND EDGE EMISSIONS (Conducted)

- Plots of the EUT's Band Edge Emissions are shown in Clause 8.3

7.4 SPURIOUS AND HARMONICS EMISSIONS (Conducted)

- Plots of the EUT's Spurious Emissions are shown in Clause 8.4

7.5 EMISSION MASK (Conducted)

- Plots of the EUT's Spurious Emissions are shown in Clause 8.4
-

7.6 ERP & EIRP

7.6.1 LTE Band 12

Channel Bandwidth (MHz)	Test Frequency (MHz)	Test Mode	RB Size/ Offset	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain (dBd)	ERP (dBm)	ERP (W)
10	704	QPSK	1/25	H	17.10	-0.65	16.45	0.044
		16QAM	1/25	H	15.76	-0.65	15.11	0.032
	711	QPSK	1/25	H	17.32	-0.63	16.69	0.047
		16QAM	1/25	H	15.94	-0.63	15.31	0.034
5	701.5	QPSK	1/12	H	16.86	-0.66	16.20	0.042
		16QAM	1/12	H	15.52	-0.66	14.86	0.031
	707.5	QPSK	1/12	H	17.25	-0.64	16.61	0.046
		16QAM	1/12	H	15.90	-0.64	15.26	0.034
	713.5	QPSK	1/12	H	16.89	-0.62	16.27	0.042
		16QAM	1/12	H	15.43	-0.62	14.81	0.030
3	700.5	QPSK	1/7	H	16.71	-0.66	16.05	0.040
		16QAM	1/7	H	15.28	-0.66	14.62	0.029
	707.5	QPSK	1/7	H	17.15	-0.64	16.51	0.045
		16QAM	1/7	H	15.74	-0.64	15.10	0.032
	714.5	QPSK	1/7	H	16.61	-0.62	15.99	0.040
		16QAM	1/7	H	15.16	-0.62	14.54	0.028
1.4	699.7	QPSK	1/2	H	16.60	-0.66	15.94	0.039
		16QAM	1/2	H	15.25	-0.66	14.59	0.029
	707.5	QPSK	1/2	H	17.12	-0.64	16.48	0.044
		16QAM	1/2	H	15.73	-0.64	15.09	0.032
	715.3	QPSK	1/2	H	16.46	-0.62	15.84	0.038
		16QAM	1/2	H	15.11	-0.62	14.49	0.028

Note: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

7.6.2 LTE Band 4

Channel Bandwidth (MHz)	Test Frequency (MHz)	Test Mode	RB Size/ Offset	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain (dBi)	EIRP (dBm)	EIRP (W)
20	1720	QPSK	1/50	H	11.65	5.95	17.60	0.058
		16QAM	1/50	H	10.16	5.95	16.11	0.041
	1732.5	QPSK	1/50	H	11.57	5.84	17.41	0.055
		16QAM	1/50	H	9.98	5.84	15.82	0.038
	1745	QPSK	1/50	H	9.31	5.73	15.04	0.032
		16QAM	1/50	H	7.99	5.73	13.72	0.024
15	1717.5	QPSK	1/36	H	11.33	5.97	17.30	0.054
		16QAM	1/36	H	9.81	5.97	15.78	0.038
	1732.5	QPSK	1/36	H	11.55	5.84	17.39	0.055
		16QAM	1/36	H	9.97	5.84	15.81	0.038
	1747.5	QPSK	1/36	H	9.26	5.70	14.96	0.031
		16QAM	1/36	H	7.96	5.70	13.66	0.023
10	1715	QPSK	1/25	H	10.94	6.00	16.94	0.049
		16QAM	1/25	H	9.41	6.00	15.41	0.035
	1732.5	QPSK	1/25	H	11.22	5.84	17.06	0.051
		16QAM	1/25	H	9.83	5.84	15.67	0.037
	1750	QPSK	1/25	H	9.37	5.68	15.05	0.032
		16QAM	1/25	H	7.98	5.68	13.66	0.023
5	1712.5	QPSK	1/12	H	10.79	6.02	16.81	0.048
		16QAM	1/12	H	9.31	6.02	15.33	0.034
	1732.5	QPSK	1/12	H	11.50	5.84	17.34	0.054
		16QAM	1/12	H	9.99	5.84	15.83	0.038
	1752.5	QPSK	1/12	H	9.41	5.65	15.06	0.032
		16QAM	1/12	H	8.17	5.65	13.82	0.024
3	1711.5	QPSK	1/7	H	10.79	6.03	16.82	0.048
		16QAM	1/7	H	9.27	6.03	15.30	0.034
	1732.5	QPSK	1/7	H	11.53	5.84	17.37	0.055
		16QAM	1/7	H	9.89	5.84	15.73	0.037
	1753.5	QPSK	1/7	H	9.42	5.63	15.05	0.032
		16QAM	1/7	H	8.10	5.63	13.73	0.024
1.4	1710.7	QPSK	1/2	H	10.63	6.03	16.66	0.046
		16QAM	1/2	H	9.07	6.03	15.10	0.032
	1732.5	QPSK	1/2	H	11.39	5.84	17.23	0.053
		16QAM	1/2	H	9.75	5.84	15.59	0.036
	1754.3	QPSK	1/2	H	9.54	5.62	15.16	0.033
		16QAM	1/2	H	8.06	5.62	13.68	0.023

Note: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

7.6.3 LTE Band 2

Channel Bandwidth (MHz)	Test Frequency (MHz)	Test Mode	RB Size/ Offset	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain (dBi)	EIRP (dBm)	EIRP (W)
20	1860	QPSK	1/50	H	10.70	4.91	15.61	0.036
		16QAM	1/50	H	9.57	4.91	14.48	0.028
	1880	QPSK	1/50	H	12.09	4.80	16.89	0.049
		16QAM	1/50	H	10.96	4.80	15.76	0.038
	1900	QPSK	1/50	H	10.83	4.69	15.52	0.036
		16QAM	1/50	H	9.58	4.69	14.27	0.027
15	1857.5	QPSK	1/36	H	10.76	4.92	15.68	0.037
		16QAM	1/36	H	9.74	4.92	14.66	0.029
	1880	QPSK	1/36	H	12.34	4.80	17.14	0.052
		16QAM	1/36	H	11.26	4.80	16.06	0.040
	1902.5	QPSK	1/36	H	11.21	4.68	15.89	0.039
		16QAM	1/36	H	10.02	4.68	14.70	0.030
10	1855	QPSK	1/25	H	10.98	4.94	15.92	0.039
		16QAM	1/25	H	9.87	4.94	14.81	0.030
	1880	QPSK	1/25	H	12.77	4.80	17.57	0.057
		16QAM	1/25	H	11.46	4.80	16.26	0.042
	1905	QPSK	1/25	H	11.39	4.67	16.06	0.040
		16QAM	1/25	H	10.18	4.67	14.85	0.031
5	1852.5	QPSK	1/12	H	10.89	4.95	15.84	0.038
		16QAM	1/12	H	9.78	4.95	14.73	0.030
	1880	QPSK	1/12	H	12.71	4.80	17.51	0.056
		16QAM	1/12	H	11.41	4.80	16.21	0.042
	1907.5	QPSK	1/12	H	11.24	4.65	15.89	0.039
		16QAM	1/12	H	10.06	4.65	14.71	0.030
3	1851.5	QPSK	1/7	H	10.78	4.95	15.73	0.037
		16QAM	1/7	H	9.73	4.95	14.68	0.029
	1880	QPSK	1/7	H	12.62	4.80	17.42	0.055
		16QAM	1/7	H	11.26	4.80	16.06	0.040
	1908.5	QPSK	1/7	H	11.23	4.65	15.88	0.039
		16QAM	1/7	H	9.99	4.65	14.64	0.029
1.4	1850.7	QPSK	1/2	H	10.81	4.96	15.77	0.038
		16QAM	1/2	H	9.69	4.96	14.65	0.029
	1880	QPSK	1/2	H	12.51	4.80	17.31	0.054
		16QAM	1/2	H	11.23	4.80	16.03	0.040
	1909.3	QPSK	1/2	H	10.99	4.64	15.63	0.037
		16QAM	1/2	H	9.74	4.64	14.38	0.027

Note: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

7.7 UNDESIRABLE EMISSIONS (Radiated)

7.7.1 LTE Band 12

B.W (MHz)	Test Freq. (MHz)	RB Size/ Offset	Test Mode	Freq.(MHz)	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain(dBd)	Result		Limit (dBc)
								(dBm)	(dBc)	
10	704	1/25	QPSK	1409.27	H	-53.71	2.78	-50.93	67.38	29.45
				2111.96	H	-51.95	3.06	-48.89	65.34	
			16QAM	1407.47	H	-53.52	2.77	-50.75	65.86	28.11
				2111.98	H	-51.77	3.06	-48.71	63.82	
	711	1/25	QPSK	1422.42	H	-53.83	2.92	-50.91	67.60	29.69
				2134.48	H	-52.25	3.15	-49.10	65.79	
			16QAM	1421.62	H	-53.97	2.91	-51.06	66.37	28.31
				2132.93	H	-51.65	3.15	-48.50	63.81	

Note 1: Limit Calculation = $43 + 10\log_{10}(P[\text{Watts}])$

Note 2: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

Note 3: The frequency spectrum is examined from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter. No other spurious and harmonic emissions were reported greater than listed emissions above table.

7.7.2 LTE Band 4

B.W (MHz)	Test Freq. (MHz)	RB Size/ Offset	Test Mode	Freq.(MHz)	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain(dBi)	Result		Limit (dBc)
								(dBm)	(dBc)	
20	1720	1/50	QPSK	3439.70	H	-55.23	8.05	-47.18	64.78	30.60
				5158.74	V	-42.60	10.27	-32.33	49.93	
			16QAM	3440.81	H	-55.38	8.06	-47.32	63.43	29.11
				5159.27	V	-42.62	10.27	-32.35	48.46	
	1732.5	1/50	QPSK	3465.82	H	-55.26	8.12	-47.14	64.55	30.41
				5197.81	V	-42.30	10.34	-31.96	49.37	
			16QAM	3466.50	H	-55.09	8.12	-46.97	62.79	28.82
				5196.84	V	-42.72	10.33	-32.39	48.21	
	1745	1/50	QPSK	3464.51	H	-54.99	8.11	-46.88	61.92	28.04
				5197.45	V	-42.57	10.34	-32.23	47.27	
			16QAM	3464.93	H	-55.05	8.12	-46.93	60.65	26.72
				5196.04	V	-42.36	10.33	-32.03	45.75	

Note 1: Limit Calculation = $43 + 10\log_{10}(P[\text{Watts}])$

Note 2: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

Note 3: The frequency spectrum is examined from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter. No other spurious and harmonic emissions were reported greater than listed emissions above table.

7.7.3 LTE Band 2

B.W (MHz)	Test Freq. (MHz)	RB Size/ Offset	Test Mode	Freq.(MHz)	Ant Pol (H/V)	Level(dBm) @ Ant Terminal	TX Ant Gain(dBi)	Result		Limit (dBc)
								(dBm)	(dBc)	
20	1860	1/50	QPSK	3721.42	V	-53.82	8.39	-45.43	61.04	28.61
				5579.97	V	-50.15	10.51	-39.64	55.25	
			16QAM	3720.88	V	-54.14	8.39	-45.75	60.23	27.48
				5578.51	V	-49.97	10.51	-39.46	53.94	
	1880	1/50	QPSK	3758.78	V	-53.88	8.37	-45.51	62.40	29.89
				5640.32	V	-49.84	10.64	-39.20	56.09	
			16QAM	3759.01	V	-53.67	8.37	-45.30	61.06	28.76
				5639.77	V	-50.01	10.64	-39.37	55.13	
	1900	1/50	QPSK	3800.85	V	-53.95	8.22	-45.73	61.25	28.52
				5698.95	V	-50.19	10.74	-39.45	54.97	
			16QAM	3800.82	V	-53.59	8.22	-45.37	59.64	27.27
				5699.68	V	-49.70	10.74	-38.96	53.23	
10	1855	1/25	QPSK	3709.22	V	-53.98	8.38	-45.60	61.52	28.92
				5563.97	V	-50.08	10.46	-39.62	55.54	
			16QAM	3710.35	V	-54.14	8.38	-45.76	60.57	27.81
				5564.54	V	-50.29	10.46	-39.83	54.64	
	1880	1/25	QPSK	3760.95	V	-53.66	8.36	-45.30	62.87	30.57
				5638.81	V	-50.17	10.64	-39.53	57.10	
			16QAM	3758.67	V	-53.62	8.37	-45.25	61.51	29.26
				5640.55	V	-50.27	10.64	-39.63	55.89	
	1905	1/25	QPSK	3809.11	V	-53.68	8.22	-45.46	61.52	29.06
				5715.74	V	-49.67	10.73	-38.94	55.00	
			16QAM	3808.86	V	-53.86	8.22	-45.64	60.49	27.85
				5713.56	V	-50.24	10.73	-39.51	54.36	

Note 1: Limit Calculation = $43 + 10\log_{10}(P[\text{Watts}])$

Note 2: This device was tested under all bandwidths, modulations and RB configurations and the worst case data are reported in the table above.

Note 3: The frequency spectrum is examined from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter. No other spurious and harmonic emissions were reported greater than listed emissions above table.

7.8 FREQUENCY STABILITY

7.8.1 LTE Band 12

OPERATING FREQUENCY : 707.5 MHz
 REFERENCE VOLTAGE : 3.80 VDC
 LIMIT(FCC&IC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQUENCY (Hz)	FREQ.Dev (Hz)	Deviation	
					(ppm)	(%)
100%	3.80	+20(Ref)	707,500,007	7	0.0099	0.000000989
100%		-30	707,500,012	12	0.0170	0.000001696
100%		-20	707,499,994	-6	-0.0085	-0.000000848
100%		-10	707,499,990	-10	-0.0141	-0.000001413
100%		0	707,500,011	11	0.0155	0.000001555
100%		+10	707,500,008	8	0.0113	0.000001131
100%		+20	707,500,007	7	0.0099	0.000000989
100%		+30	707,500,008	8	0.0113	0.000001131
100%		+40	707,500,007	7	0.0099	0.000000989
100%		+50	707,500,005	5	0.0071	0.000000707
115%	4.37	+20	707,499,990	-10	-0.0141	-0.000001413
BATT.ENDPOINT	3.00	+20	707,499,991	-9	-0.0127	-0.000001272

Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

7.8.2 LTE Band 4

OPERATING FREQUENCY : 1732.5 MHz
 REFERENCE VOLTAGE : 3.80 VDC
 LIMIT(FCC&IC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQUENCY (Hz)	FREQ.Dev (Hz)	Deviation	
					(ppm)	(%)
100%	3.80	+20(Ref)	1,732,499,987	-13	-0.0075	-0.000000750
100%		-30	1,732,499,992	-8	-0.0046	-0.000000462
100%		-20	1,732,500,009	9	0.0052	0.000000519
100%		-10	1,732,500,006	6	0.0035	0.000000346
100%		0	1,732,500,007	7	0.0040	0.000000404
100%		+10	1,732,499,990	-10	-0.0058	-0.000000577
100%		+20	1,732,499,987	-13	-0.0075	-0.000000750
100%		+30	1,732,500,007	7	0.0040	0.000000404
100%		+40	1,732,499,992	-8	-0.0046	-0.000000462
100%		+50	1,732,499,991	-9	-0.0052	-0.000000519
115%	4.37	+20	1,732,500,012	12	0.0069	0.000000693
BATT.ENDPOINT	3.00	+20	1,732,499,994	-6	-0.0035	-0.000000346

Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

7.8.3 LTE Band 2

OPERATING FREQUENCY : 1880.0 MHz
 REFERENCE VOLTAGE : 3.80 VDC
 LIMIT(FCC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
 LIMIT(IC) : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQUENCY (Hz)	FREQ.Dev (Hz)	Deviation	
					(ppm)	(%)
100%	3.80	+20(Ref)	1,880,000,009	9	0.0048	0.000000479
100%		-30	1,879,999,990	-10	-0.0053	-0.000000532
100%		-20	1,879,999,989	-11	-0.0059	-0.000000585
100%		-10	1,880,000,008	8	0.0043	0.000000426
100%		0	1,880,000,007	7	0.0037	0.000000372
100%		+10	1,879,999,992	-8	-0.0043	-0.000000426
100%		+20	1,880,000,009	9	0.0048	0.000000479
100%		+30	1,879,999,991	-9	-0.0048	-0.000000479
100%		+40	1,879,999,990	-10	-0.0053	-0.000000532
100%		+50	1,880,000,005	5	0.0027	0.000000266
115%	4.37	+20	1,880,000,007	7	0.0037	0.000000372
BATT.ENDPOINT	3.00	+20	1,880,000,006	6	0.0032	0.000000319


Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

8. TEST PLOTS


Note: All bandwidths, RB configurations, and modulations were investigated.
The worst case test results are reported.

8.1 OCCUPIED BANDWIDTH


8.1.1 LTE Band 12




LTE Band 12 / 10 MHz / QPSK - RB Size 50




LTE Band 12 / 10 MHz / 16QAM - RB Size 50




LTE Band 12 / 5 MHz / QPSK - RB Size 25



LTE Band 12 / 5 MHz / 16QAM - RB Size 25




LTE Band 12 / 3 MHz / QPSK - RB Size 15



LTE Band 12 / 3 MHz / 16QAM - RB Size 15




LTE Band 12 / 1.4 MHz / QPSK - RB Size 6




LTE Band 12 / 1.4 MHz / 16QAM - RB Size 6


8.1.2 LTE Band 4




LTE Band 4 / 20 MHz / QPSK - RB Size 100




LTE Band 4 / 20 MHz / 16QAM - RB Size 100




LTE Band 4 / 15 MHz / QPSK - RB Size 75




LTE Band 4 / 15 MHz / 16QAM - RB Size 75




LTE Band 4 / 10 MHz / QPSK - RB Size 50




LTE Band 4 / 10 MHz / 16QAM - RB Size 50




LTE Band 4 / 5 MHz / QPSK - RB Size 25




LTE Band 4 / 5 MHz / 16QAM - RB Size 25




LTE Band 4 / 3 MHz / QPSK - RB Size 15



LTE Band 4 / 3 MHz / 16QAM - RB Size 15




LTE Band 4 / 1.4 MHz / QPSK - RB Size 6




LTE Band 4 / 1.4 MHz / 16QAM - RB Size 6


8.1.3 LTE Band 2




LTE Band 2 / 20 MHz / QPSK - RB Size 100




LTE Band 2 / 20 MHz / 16QAM - RB Size 100




LTE Band 2 / 15 MHz / QPSK - RB Size 75



LTE Band 2 / 15 MHz / 16QAM - RB Size 75



LTE Band 2 / 10 MHz / QPSK - RB Size 50



LTE Band 2 / 10 MHz / 16QAM - RB Size 50