

FCC SAR TEST REPORT

Product Name: Smart Tablet Computer

Trade Mark:



Model No.: T10

Report Number: 24122015364SAR-1

Test Standards: FCC 47 CFR Part 2 §2.1093
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013

FCC ID: SS4T10F1

Test Result: PASS

Date of Issue: January 23, 2025

Prepared for:

Bluebird Inc.

3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

**16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

Curry Xue
Test Engineer

Reviewed by:

Henry Lu
Team Leader

Approved by:

Robben Chen
Assistant Manager

Date:

January 23, 2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Version

Version No.	Date	Description
V1.0	January 23, 2025	Original Report



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

CONTENTS

1. GENERAL INFORMATION	5
1.1. STATEMENT OF COMPLIANCE	5
1.2. CLIENT INFORMATION	6
1.3. EUT INFORMATION	6
1.3.1. GENERAL DESCRIPTION OF EUT	6
1.3.2. DESCRIPTION OF ACCESSORIES	6
1.3.3. EUT Tx FREQUENCY BANDS	7
1.3.4. WIRELESS TECHNOLOGIES	8
1.4. MAXIMUM CONDUCTED POWER	9
1.5. OTHER INFORMATION	11
1.6. TEST LOCATION	11
1.7. TEST FACILITY	11
1.8. GUIDANCE STANDARD	11
2. SPECIFIC ABSORPTION RATE (SAR)	12
2.1. INTRODUCTION	12
2.2. SAR DEFINITION	12
2.3. SAR LIMITS	12
3. SAR MEASUREMENT SYSTEM	13
3.1. SPEAG DASY SYSTEM	13
3.1.1. ROBOT	13
3.1.2. PROBE	14
3.1.3. DATA ACQUISITION ELECTRONICS (DAE)	14
3.1.4. PHANTOM	15
3.1.5. DEVICE HOLDER	16
3.1.6. SYSTEM VALIDATION DIPOLES	16
3.2. SAR SCAN PROCEDURE	17
3.2.1. SAR REFERENCE MEASUREMENT (DRIFT)	17
3.2.2. AREA SCAN	17
3.2.3. ZOOM SCAN	18
3.2.4. SAR DRIFT MEASUREMENT	18
3.3. EQUIPMENT LIST	19
3.4. MEASUREMENT UNCERTAINTY	20
3.5. TISSUE DIELECTRIC PARAMETER MEASUREMENT & SYSTEM VERIFICATION	22
3.5.1. TISSUE SIMULATING LIQUIDS	22
3.5.2. SYSTEM CHECK DESCRIPTION	24
3.5.3. TISSUE VERIFICATION	25
3.5.4. SYSTEM VERIFICATION	25
4. SAR MEASUREMENT EVALUATION	26
4.1. EUT CONFIGURATION AND SETTING	26
4.1.1. GSM CONFIGURATION AND TESTING	26
4.1.2. WCDMA CONFIGURATION AND TESTING	26
4.1.3. LTE CONFIGURATION AND TESTING	28
4.1.4. WLAN CONFIGURATION AND TESTING	29
4.2. EUT TESTING POSITION	31
4.3. PROXIMITY SENSORS TRIGGERING DISTANCES	32
4.3.1. TRIGGERING DISTANCE FOR PERPENDICULAR DUT ORIENTATION	32
4.3.2. TRIGGERING DISTANCE FOR TILTED DUT ORIENTATION	33
4.3.3. PROCEDURE FOR DETERMINING PROXIMITY SENSOR COVERAGE AREA	33
4.4. MEASURED CONDUCTED POWER RESULT	34
4.4.1. CONDUCTED POWER OF GSM BANDS	34
4.4.2. CONDUCTED POWER OF WCDMA BANDS	35
4.4.3. CONDUCTED POWER OF LTE BANDS	36

4.4.4. CONDUCTED POWER OF WLAN	52
4.4.5. CONDUCTED POWER OF BT	54
4.5. SAR TEST EXCLUSION EVALUATIONS	55
4.5.1. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	55
4.5.2. ESTIMATED SAR CALCULATION	58
4.6. SAR TESTING RESULTS	60
4.6.1. SAR TEST REDUCTION CONSIDERATIONS	60
4.6.2. SAR RESULTS FOR BODY EXPOSURE CONDITION	62
4.7. SAR MEASUREMENT VARIABILITY	67
4.7.1. REPEATED MEASUREMENT	67
4.8. SIMULTANEOUS MULTI-BAND TRANSMISSION EVALUATION	68
4.8.1. SIMULTANEOUS TRANSMISSION SAR TEST EXCLUSION CONSIDERATIONS	68
4.8.2. SIMULTANEOUS TRANSMISSION POSSIBILITIES	69
4.8.3. MAX. STANDALONE SAR	70
4.8.4. SUM OF SAR	71

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup

1. GENERAL INFORMATION

1.1. STATEMENT OF COMPLIANCE

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Equipment Class	Mode	Highest Reported Body SAR _{1g} (0 cm Gap) (W/kg)
PCB	GSM 850	0.437
	PCS 1900	0.478
	WCDMA Band II	0.684
	WCDMA Band IV	0.513
	WCDMA Band V	0.425
	LTE Band 2	0.741
	LTE Band 5	0.522
	LTE Band 7	1.034
	LTE Band 12 (17)	0.471
	LTE Band 13	0.367
	LTE Band 14	0.464
	LTE Band 38	0.669
	LTE Band 66 (4)	0.421
DTS	2.4G WLAN	0.766
NII	5G WLAN	0.896
DSS	Bluetooth	0.311
DXX	NFC	N/A
Highest Simultaneous Transmission SAR		Body (0 cm Gap) (W/kg)
PCB + DSS		1.345
PCB + DTS		1.345
PCB + NII		1.475

1.2. CLIENT INFORMATION

Applicant:	Bluebird Inc.
Address of Applicant:	3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea
Manufacturer:	Bluebird Inc.
Address of Manufacturer:	3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea

1.3. EUT INFORMATION

1.3.1. General Description of EUT

Product Name:	Smart Tablet Computer
Trade Mark:	 BLUEBIRD A TSC Company
Model No.:	T10
FCC ID:	SS4T10F1
DUT Stage:	Identical Prototype
Sample Number:	S202411294756-ZJA03, S202411294756-ZJA02
Software Version:	R1.00 (Provided by the customer)
Hardware Version:	REV_C (Provided by the customer)
Sample Received Date:	November 29, 2024
Sample Tested Date:	January 9, 2025 to January 21, 2025

1.3.2. Description of Accessories

Adapter	
Model No.:	ICP20-050-3000B
Input:	100-240V~50/60Hz 0.6A
Output:	5.0V $\overline{\text{---}}$ 3.0A

Battery	
Model No.:	BAT-800001
Battery Type:	Lithium-ion Polymer Battery
Rated Voltage:	3.8Vdc
Limited Charge Voltage:	4.35Vdc
Rated Capacity:	8000mAh

Cable	
Description:	USB Type-C to USB 3.0 Type A Cable
Connector:	USB Type-C / USB 3.0 Type A
Cable Type:	Shielded without ferrite
Length:	1 Meter

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

1.3.3. EUT Tx Frequency Bands

RF Type	Band(s)	Tx Frequency Range (Unit: MHz)
GSM	GSM 850:	824.2 - 848.8
	PCS 1900:	1850.2 - 1909.8
WCDMA	WCDMA Band II:	1852.4 - 1907.6
	WCDMA Band IV:	1712.4 - 1752.6
	WCDMA Band V:	826.4 - 846.6
LTE	LTE Band 2:	1850.7 - 1909.3 (1.4M), 1851.5 - 1908.5 (3M), 1852.5 - 1907.5 (5M), 1855 - 1905 (10M), 1857.5 - 1902.5 (15M), 1860 - 1900 (20M)
	LTE Band 4:	1710.7 - 1754.3 (1.4M), 1711.5 - 1753.5 (3M), 1712.5 - 1752.5 (5M), 1715 - 1750 (10M), 1717.5 - 1747.5 (15M), 1720 - 1745 (20M)
	LTE Band 5:	824.7 - 848.3 (1.4M), 825.5 - 847.5 (3M), 826.5 - 846.5 (5M), 829 - 844 (10M)
	LTE Band 7:	2502.5 - 2567.5 (5M), 2505 - 2565 (10M), 2507.5 - 2562.5 (15M), 2510 - 2560 (20M)
	LTE Band 12:	699.7 - 715.3 (1.4M), 700.5 - 714.5 (3M), 701.5 - 713.5 (5M), 704 - 711 (10M)
	LTE Band 13:	779.5 - 784.5 (5M), 782 (10M)
	LTE Band 14:	790.5 - 795.5 (5M), 793 (10M)
	LTE Band 17:	706.5 - 713.5 (5M), 709 - 711 (10M)
	LTE Band 38:	2572.5 - 2617.5 (5M), 2575 - 2615 (10M), 2577.5 - 2612.5 (15M), 2580 - 2610 (20M)
	LTE Band 66:	1710.7 - 1779.3 (1.4M), 1711.5 - 1778.5 (3M), 1712.5 - 1777.5 (5M), 1715 - 1775 (10M), 1717.5 - 1772.5 (15M), 1720 - 1770 (20M)
WLAN	2.4 GHz:	2412 - 2472
	U-NII-1:	5180 - 5240
	U-NII-2A:	5260 - 5320
	U-NII-2C:	5500 - 5720
	U-NII-3:	5745 - 5825
Bluetooth	2.4 GHz:	2402 - 2480
NFC	13.553-13.567 MHz	13.56
Note 1: According to 201504 FCC TCB workshop RF exposure slides, for overlapping bands, only larger band was tested.		
1. The maximum output power, including tolerance, for the smaller band is = the larger band to qualify for the SAR test exclusion.		
2. The channel bandwidth and other operating parameters for the smaller band is fully supported by the larger band.		
➢ Band 66 (1710 - 1780 MHz) SAR can support band 4 (1710 - 1755 MHz).		
➢ Band 12 (699 - 716 MHz) SAR can support band 17 (704 - 716 MHz).		

1.3.4. Wireless Technologies

GSM	Voice GPRS (Multi-Slot Class: 33-4UP) EDGE (Multi-Slot Class: 33-4UP)
WCDMA	RMC HSDPA HSUPA
LTE	QPSK 16QAM
2.4G WLAN	802.11b 802.11g 802.11n (HT20/HT40)
5G WLAN	802.11a 802.11n (HT20/HT40) 802.11ac (VHT20/VHT40/VHT80)
Bluetooth	BR+EDR LE
Others	NFC
Device Class (GSM)	B
Antenna Type	PIFA Antenna
Power Reduction	P-Sensor
Dynamic Antenna	Not Support
Wireless Router (Hotspot)	2.4G WLAN: Support 5.2G WLAN: Support 5.3G WLAN: Not Support 5.6G WLAN: Not Support 5.8G WLAN: Support
VOIP	Support Note: Since this device supports VOIP capability through 3rd party apps software, we have evaluated data mode for body SAR.

1.4. MAXIMUM CONDUCTED POWER

The maximum conducted average power including tune-up tolerance is shown as below.

➤ GSM

Mode	Maximum conducted average power (dBm)			
	Without Power Reduction		With Power Reduction	
	GSM 850	PCS 1900	GSM 850	PCS 1900
GSM (GMSK, 1Tx-slot)	33.0	29.5	17.0	15.5
GPRS (GMSK, 1Tx-slot)	33.0	29.5	17.0	15.5
GPRS (GMSK, 2Tx-slot)	31.0	27.5	17.0	15.5
GPRS (GMSK, 3Tx-slot)	29.5	26.0	17.0	15.5
GPRS (GMSK, 4Tx-slot)	27.5	24.0	17.0	15.5
EDGE (8PSK, 1Tx-slot)	25.0	28.0	14.5	15.5
EDGE (8PSK, 2Tx-slot)	25.0	25.5	14.5	15.5
EDGE (8PSK, 3Tx-slot)	23.5	23.5	14.0	15.5
EDGE (8PSK, 4Tx-slot)	22.0	22.0	14.0	15.5

Mode	Source-Based Time-Averaged Power (dBm)			
	Without Power Reduction		With Power Reduction	
	GSM 850	PCS 1900	GSM 850	PCS 1900
GSM (GMSK, 1Tx-slot)	24.0	20.5	8.0	6.5
GPRS (GMSK, 1Tx-slot)	24.0	20.5	8.0	6.5
GPRS (GMSK, 2Tx-slot)	25.0	21.5	11.0	9.5
GPRS (GMSK, 3Tx-slot)	25.0	21.5	12.5	11.0
GPRS (GMSK, 4Tx-slot)	24.5	21.0	14.0	12.5
EDGE (8PSK, 1Tx-slot)	16.0	19.0	5.5	6.5
EDGE (8PSK, 2Tx-slot)	19.0	19.5	8.5	9.5
EDGE (8PSK, 3Tx-slot)	19.0	19.0	10.0	11.0
EDGE (8PSK, 4Tx-slot)	19.0	19.0	11.0	12.5

➤ WCDMA

Mode	Maximum conducted average power (dBm)					
	Without Power Reduction			With Power Reduction		
	WCDMA Band II	WCDMA Band V	WCDMA Band IV	WCDMA Band II	WCDMA Band V	WCDMA Band IV
RMC 12.2K	23.0	24.0	25.0	15.5	14.5	15.5
HSDPA Subtest-1	22.5	23.5	24.0	14.0	13.5	14.5
HSDPA Subtest-2	22.5	22.5	23.5	13.5	13.0	14.0
HSDPA Subtest-3	21.0	21.5	23.5	13.5	13.0	14.0
HSDPA Subtest-4	21.0	21.5	23.5	13.5	13.0	14.0
HSUPA Subtest-1	19.0	20.5	24.0	14.0	13.5	14.5
HSUPA Subtest-2	19.5	20.5	21.5	12.0	11.5	12.5
HSUPA Subtest-3	20.0	20.5	23.0	13.0	12.5	13.5
HSUPA Subtest-4	20.0	20.5	22.0	12.0	11.5	12.5
HSUPA Subtest-5	21.5	23.5	24.0	14.0	13.5	14.5

➤ LTE

Band	Mode	Maximum Conducted Power (dBm)	
		Without Power Reduction	With Power Reduction
LTE Band 2	QPSK/16QAM	24.5	15.0
LTE Band 5	QPSK/16QAM	24.5	15.0
LTE Band 4	QPSK/16QAM	24.0	14.5
LTE Band 7	QPSK/16QAM	24.0	15.0
LTE Band 12	QPSK/16QAM	24.0	14.5
LTE Band 13	QPSK/16QAM	23.5	14.0
LTE Band 14	QPSK/16QAM	24.0	15.0
LTE Band 17	QPSK/16QAM	24.0	14.5
LTE Band 38	QPSK/16QAM	24.0	15.5
LTE Band 66	QPSK/16QAM	25.0	17.0

➤ 2.4GHz WLAN

Mode	Maximum Conducted Power (dBm)		
	Channel 1~11	Channel 12	Channel 13
802.11b	12.5	8.5	6.5
802.11g	11.5	8.5	6.0
802.11n-HT20	11.0	8.0	6.0
Mode	Maximum Conducted Power (dBm)		
	Channel 3~9	Channel 10	Channel 11
802.11n-HT40	11.0	8.5	9.0

➤ 5GHz WLAN

Mode	Maximum Conducted Power (dBm)			
	Band 1	Band 2	Band 3	Band 4
802.11a	11.5	11.5	11.0	10.0
802.11n-HT20	10.5	9.5	10.0	9.0
802.11n-HT40	11.0	10.5	10.5	9.5
802.11ac-VHT20	10.5	10.5	10.0	9.0
802.11ac-VHT40	11.0	10.5	10.5	9.5
802.11ac-VHT80	11.0	10.0	10.5	9.5

➤ Bluetooth

Mode	Modulation	Maximum Conducted Power (dBm)
BR + EDR	GFSK	5.0
	$\pi/4$ -DQPSK	3.0
	8-DPSK	3.0
LE	GFSK	4.0

1.5. OTHER INFORMATION

None.

1.6. TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7. TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8. GUIDANCE STANDARD

The tests documented in this report were performed in accordance with FCC 47 CFR Part 2 §2.1093, IEEE Std 1528-2013, ANSI/IEEE C95.1-1992, the following FCC Published RF exposure KDB procedures:

KDB 865664 D01 v01r04

KDB 865664 D02 v01r02

KDB 248227 D01 v02r02

KDB 447498 D04 v01

KDB 616217 D04 v01r02

KDB 941225 D01 v03r01

KDB 941225 D05 v02r05

KDB 941225 D05A v01r02

KDB 941225 D06 v02r01

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

2. SPECIFIC ABSORPTION RATE (SAR)

2.1. INTRODUCTION

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling, by appropriate techniques, to produce specific absorption rates (SARs) as averaged over the whole-body, any 1 g or any 10 g of tissue (defined as a tissue volume in the shape of a cube). All SAR values are to be averaged over any six-minute period. When portable device was used within 20 cm of the user's body, SAR evaluation of the device will be required. The SAR limit in chapter 2.3.

2.2. SAR DEFINITION

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

2.3. SAR LIMITS

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0


Note:

- 1) Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.
- 2) At frequencies above 6.0 GHz, SAR limits are not applicable and MPE limits for power density should be applied at 5 cm or more from the transmitting device.
- 3) The SAR limit is specified in FCC 47 CFR Part 2 §2.1093, ANSI/IEEE C95.1-1992.

3. SAR MEASUREMENT SYSTEM

3.1. SPEAG DASY SYSTEM

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.



3.1.1. Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

3.1.2. Probe

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.1.3. Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detectors for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16-bit resolution and two range settings: 4mV, 400mV)	
Input Voltage Offset	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

3.1.4. Phantom

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.1.5. Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.1.6. System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

3.2. SAR SCAN PROCEDURE

3.2.1. SAR Reference Measurement (drift)

Prior to the SAR test, local SAR shall be measured at a stationary reference point where the SAR exceeds the lower detection limit of the measurement system.

3.2.2. Area Scan

Measurement procedures for evaluating the SAR of wireless device start with a coarse measurement grid to determine the approximate location of the local peak SAR values. This is known as the area-scan procedure. All antennas and radiating structures that may contribute to the measured SAR or influence the SAR distribution must be included in the area scan. The area scan measurement resolution must enable the extrapolation algorithms of the SAR system to correctly identify the peak SAR location(s) for subsequent zoom scan measurements to correctly determine the 1-g SAR. Area scans are performed at a constant distance from the phantom surface, determined by the measurement frequencies. When a measured peak is closer than ½ the zoom scan volume dimension (x, y) from the edge of the area scan region, unless the entire peak and gram-averaging volume are both captured within the zoom scan volume, the area scan must be repeated by shifting and expanding the area scan region to ensure all peaks are away from the area scan boundary. The area scan resolutions specified in the table below must be applied to the SAR measurements.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scans spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

3.2.3. Zoom Scan

To evaluate the peak spatial-average SAR values with respect to 1 g or 10 g cubes, fine resolution volume scans, called zoom scans, are performed at the peak SAR locations identified during the area scan. If the cube volume within the zoom scan chosen to calculate the peak spatial-average SAR touches any boundary of the zoom-scan volume, the zoom scan shall be repeated with the center of the zoom-scan volume shifted to the new maximum SAR location. For any secondary peaks found in the area scan that are within 2 dB of the maximum peak and are not within this zoom scan, the zoom scan shall be performed for such peaks, unless the peak spatial-average SAR at the location of the maximum peak is more than 2 dB below the applicable SAR limit (i.e., 1 W/kg for a 1.6 W/kg 1 g limit, or 1.26 W/kg for a 2 W/kg 10 g limit). The zoom scan resolutions specified in the table below must be applied to the SAR measurements.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom Scan spatial resolution, normal to phantom surface	uniform grid: $\Delta Z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta Z_{Zoom}(1)$: between 1 ST two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta Z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta Z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

3.2.4. SAR Drift Measurement

The local SAR (or conducted power) shall be measured at exactly the same location as in 3.2.1 section. The absolute value of the measurement drift (the difference between the SAR measured in 3.2.1 and 3.2.4 section) shall be recorded. The SAR drift shall be kept within ± 5%.

3.3. EQUIPMENT LIST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1066	Jan. 02, 2024	3 Year
System Validation Dipole	SPEAG	D835V2	4d005	Mar. 15, 2024	3 Year
System Validation Dipole	SPEAG	D1750V2	1086	Mar. 14, 2024	3 Year
System Validation Dipole	SPEAG	D1900V2	509	Mar. 14, 2024	3 Year
System Validation Dipole	SPEAG	D2450V2	883	Jan.02, 2024	3 Year
System Validation Dipole	SPEAG	D2600V2	1082	Jan.02, 2024	3 Year
System Validation Dipole	SPEAG	D5GHzV2	1115	Jan. 02, 2024	3 Year
Data Acquisition Electronics	SPEAG	DAE4	662	Mar. 18,2024	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1557	Oct. 08, 2024	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7506	Nov. 12, 2024	1 Year
Dosimetric E-Field Probe	SPEAG	ES3DV3	3090	Mar. 26,2024	1 Year
Wideband Radio Communication Tester	R&S	CMW500	120932	Mar. 29, 2024	1 Year
ENA Series Network Analyzer	Agilent	8753ES	US39170317	Oct. 25, 2024	1 Year
Twin Phantom	SPEAG	SAM	TP-1376	N/A	N/A
Twin Phantom	SPEAG	SAM	TP-1378	N/A	N/A
Head tissue simulating liquid	SPEAG	HBBL600-10000V6	180604-1	N/A	N/A
Robot controller	STAUBLI	CS7MB	F05/511KA1/A/01	N/A	N/A
Robot	STAUBLI	RX90BL	F05/511KA1/A/01	N/A	N/A
Dielectric Assessment Kit	SPEAG	DAK-3.5	1070	N/A	N/A
USB/GPIB Interface	Agilent	82357B	N10149	N/A	N/A
Signal Generator	R&S	SMB100A	103718	Mar. 29, 2024	1 Year
POWER METER	R&S	NRP	101293	Oct. 25, 2024	1 Year
Thermometer	Shanghai Gao Zhi Precision Instrument Co., Ltd.	HB6801	18022507	Oct. 29, 2024	1 Year
Dual Directional Coupler	Agilent	778D	MY52180234	Oct. 25, 2024	1 Year
Amplifier	Mini-Circuit	ZHL42	QA1252001	Mar. 29, 2024	1 Year
DC Source	Agilent	66319B	MY43000795	Oct. 25, 2024	1 Year

3.4. MEASUREMENT UNCERTAINTY

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

TABLE 1 EXPOSURE ASSESSMENT UNCERTAINTY FOR HANDSET SAR

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g) (± %)	Standard Uncertainty (10g) (± %)	Vi Veff
Measurement System								
Probe Calibration (< 3 GHz)	7.5	N (k=2)	2	1	1	3.75	3.75	∞
Probe Calibration (> 3 GHz)	6.3	N (k=2)	2	1	1	3.15	3.15	∞
Axial Isotropy	1.2	N (k=2)	2	0.7	0.7	0.42	0.42	∞
Hemispherical Isotropy	3.2	N (k=2)	2	0.7	0.7	1.12	1.12	∞
Boundary Effects	2	Rectangular	√3	1	1	1.15	1.15	∞
Linearity	0.9	N (k=2)	2	1	1	0.45	0.45	∞
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Modulation Response	2.4	Rectangular	√3	1	1	1.39	1.39	∞
Readout Electronics	0.3	Normal	1	1	1	0.30	0.30	∞
Response Time	0	Rectangular	√3	1	1	0.00	0.00	∞
Integration Time	1.7	Rectangular	√3	1	1	0.98	0.98	∞
RF Ambient – Noise	3	Rectangular	√3	1	1	1.73	1.73	∞
RF Ambient – Reflections	3	Rectangular	√3	1	1	1.73	1.73	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	6.7	Rectangular	√3	1	1	3.87	3.87	∞
Max. SAR Evaluation	4	Rectangular	√3	1	1	2.31	2.31	∞
Test Sample Related								
Device Positioning	2.3 / 2.4	Normal	1	1	1	2.30	2.40	30
Device Holder	2.8 / 2.8	Normal	1	1	1	2.80	2.80	30
Power Drift	5	Rectangular	√3	1	1	2.89	2.89	∞
Power Scaling	0	Rectangular	√3	1	1	0.00	0.00	∞
Phantom and Setup								
Phantom Uncertainty	7.9	Rectangular	√3	1	1	4.56	4.56	∞
SAR correction	1.2 / 0.97	Rectangular	√3	1	0.84	0.69	0.47	∞
Liquid Conductivity (Meas.)	2.5	Rectangular	√3	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Meas.)	2.5	Rectangular	√3	0.26	0.26	0.38	0.38	∞
Temp. unc. - Conductivity	3.4	Rectangular	√3	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	Rectangular	√3	0.23	0.26	0.05	0.06	∞
Combined Standard Uncertainty (k = 1) (≤ 3 GHz)						9.64	9.62	
Combined Standard Uncertainty (k = 1) (> 3 GHz)						9.42	9.40	
Max. Expanded Uncertainty (k = 2)						19.27	19.23	

TABLE 2SYSTEM VALIDATION Measurement uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g) (± %)	Standard Uncertainty (10g) (± %)	Vi Veff
Measurement System								
Probe Calibration (< 3 GHz)	7.5	N (k=2)	2	1	1	3.75	3.75	∞
Probe Calibration (> 3 GHz)	6.3	N (k=2)	2	1	1	3.15	3.15	∞
Axial Isotropy	1.2	N (k=2)	2	0.7	0.7	0.42	0.42	∞
Hemispherical Isotropy	3.2	N (k=2)	2	0.7	0.7	1.12	1.12	∞
Boundary Effects	2	Rectangular	√3	1	1	1.15	1.15	∞
Linearity	0.9	N (k=2)	2	1	1	0.45	0.45	∞
Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Modulation Response	2.4	Rectangular	√3	1	1	1.39	1.39	∞
Readout Electronics	0.3	Normal	1	1	1	0.30	0.30	∞
Response Time	0	Rectangular	√3	1	1	0.00	0.00	∞
Integration Time	1.7	Rectangular	√3	1	1	0.98	0.98	∞
RF Ambient – Noise	3	Rectangular	√3	1	1	1.73	1.73	∞
RF Ambient – Reflections	3	Rectangular	√3	1	1	1.73	1.73	∞
Probe Positioner	0.4	Rectangular	√3	1	1	0.23	0.23	∞
Probe Positioning	6.7	Rectangular	√3	1	1	3.87	3.87	∞
Max. SAR Evaluation	4	Rectangular	√3	1	1	2.31	2.31	∞
Test Sample Related								
Device Positioning	2.3 / 2.4	Normal	1	1	1	2.30	2.40	30
Device Holder	2.8 / 2.8	Normal	1	1	1	2.80	2.80	30
Power Drift	5	Rectangular	√3	1	1	2.89	2.89	∞
Power Scaling	0	Rectangular	√3	1	1	0.00	0.00	∞
Phantom and Setup								
Phantom Uncertainty	7.9	Rectangular	√3	1	1	4.56	4.56	∞
SAR correction	1.2 / 0.97	Rectangular	√3	1	0.84	0.69	0.47	∞
Liquid Conductivity (Meas.)	2.5	Rectangular	√3	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Meas.)	2.5	Rectangular	√3	0.26	0.26	0.38	0.38	∞
Temp. unc. - Conductivity	3.4	Rectangular	√3	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	Rectangular	√3	0.23	0.26	0.05	0.06	∞
Combined Standard Uncertainty (k = 1) (≤ 3 GHz)						9.64	9.62	
Combined Standard Uncertainty (k = 1) (> 3 GHz)						9.42	9.40	
Max. Expanded Uncertainty (k = 2)						19.27	19.23	


3.5. TISSUE DIELECTRIC PARAMETER MEASUREMENT & SYSTEM VERIFICATION

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

3.5.1. Tissue Simulating Liquids

The temperature of the tissue-equivalent medium used during measurement must also be within 18 °C to 25 °C and within ± 2 °C of the temperature when the tissue parameters are characterized. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 - 4 days of use; or earlier if the dielectric parameters can become out of tolerance.

The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm with $\leq \pm 0.5$ cm variation for SAR measurements ≤ 3 GHz and ≥ 10.0 cm with $\leq \pm 0.5$ cm variation for measurements > 3 GHz. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.




Tissue Dielectric Parameters for Head and Body				
Target Frequency	Head		Body	
(MHz)	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
750	41.9	0.89	55.5	0.96
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
1450	40.5	1.20	54.0	1.30
1640	40.3	1.29	53.8	1.40
1750	40.1	1.37	53.4	1.49
1800	40.0	1.40	53.3	1.52
1900	40.0	1.40	53.3	1.52
2000	40.0	1.40	53.3	1.52
2300	39.5	1.67	52.9	1.81
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3500	37.9	2.91	51.3	3.31
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5800	35.3	5.27	48.2	6.00
(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000$ kg/m ³)				

The following table gives the recipes for tissue simulating liquids.

Recipes of Tissue Simulating Liquid								
Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.4	57.0	-	41.1	-
H835	0.1	-	1.0	1.4	57.0	-	40.5	-
H900	0.1	-	1.0	1.5	56.5	-	40.9	-
H1450	-	45.5	-	0.7	-	-	53.8	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	44.5	-	0.3	-	-	55.2	-
H1800	-	44.9	-	0.2	-	-	54.9	-
H1900	-	44.9	-	0.2	-	-	54.9	-
H2000	-	50	-	-	-	-	50	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.52	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	29.4	-	0.4	-	-	70.2	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.5.2. System Check Description

The system check procedure provides a simple, fast, and reliable test method that can be performed daily or before every SAR measurement. The objective here is to ascertain that the measurement system has acceptable accuracy and repeatability. This test requires a flat phantom and a radiating source. The system verification setup is shown as below.



3.5.3. Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)	Test Date
Head	750	20.6	0.883	41.23	0.90	42.00	-1.93	-1.83	Jan. 16, 2025
Head	750	20.1	0.873	41.75	0.90	42.00	-2.99	-0.60	Jan. 19, 2025
Head	835	20.3	0.911	41.13	0.90	41.50	1.26	-0.89	Jan. 15, 2025
Head	1750	20.0	1.381	39.45	1.37	40.10	0.80	-1.62	Jan. 19, 2025
Head	1900	20.1	1.455	40.12	1.40	40.00	3.93	0.30	Jan. 20, 2025
Head	2450	20.2	1.783	40.18	1.80	39.20	-0.94	2.50	Jan. 09, 2025
Head	2600	20.7	2.049	37.74	1.96	39.00	4.54	-3.23	Jan. 17, 2025
Head	5250	21.6	4.627	37.150	4.71	35.90	-1.76	3.48	Jan. 11, 2025
Head	5600	21.6	5.016	36.480	5.07	35.50	-1.07	2.76	Jan. 11, 2025
Head	5800	21.6	5.237	36.128	5.27	35.30	-0.63	2.35	Jan. 11, 2025

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. The variation of the liquid temperature must be within $\pm 2^\circ\text{C}$ during the test.

3.5.4. System Verification

The measuring result for system verification is tabulated as below.

Test Date	Freq. (MHz)	1W Target SAR-1g (W/kg)	1W Target SAR-10g (W/kg)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Normalized to 1W SAR-10g (W/kg)	Deviation (%)		Dipole S/N	Probe S/N	DAE S/N
								SAR-1g	SAR-10g			
Jan. 16, 2025	750	8.60	5.64	2.180	1.440	8.72	5.76	1.40	2.13	1066	3090	662
Jan. 19, 2025	750	8.60	5.64	2.240	1.480	8.96	5.92	4.19	4.96	1066	3090	662
Jan. 15, 2025	835	9.61	6.23	2.460	1.600	9.84	6.40	2.39	2.73	4d005	3090	662
Jan. 19, 2025	1750	36.80	19.50	9.230	5.100	36.92	20.40	0.33	4.62	1086	3090	662
Jan. 20, 2025	1900	40.00	20.90	10.500	5.550	42.00	22.20	5.00	6.22	509	3090	662
Jan. 09, 2025	2450	51.80	24.80	12.500	5.900	50.00	23.60	-3.47	-4.84	883	3090	662
Jan. 17, 2025	2600	56.10	24.80	13.300	6.090	53.20	24.36	-5.17	-1.77	1082	3090	662
Jan. 11, 2025	5250	78.60	22.30	8.15	2.36	81.50	23.60	3.69	5.83	1115	7506	1557
Jan. 11, 2025	5600	81.90	23.10	8.49	2.41	84.90	24.10	3.66	4.33	1115	7506	1557
Jan. 11, 2025	5800	78.60	22.00	7.97	2.26	79.70	22.60	1.40	2.73	1115	7506	1557

Note:

Comparing to the reference SAR value, the validation data should be within its specification of 10%. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4. SAR MEASUREMENT EVALUATION

4.1. EUT CONFIGURATION AND SETTING

Connections between EUT and System Simulator

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

4.1.1. GSM Configuration and Testing

GSM (GMSK: CS1) voice mode transmits with 1 time slot. GPRS (GMSK: CS1) and EDGE (GMSK: MCS1, 8PSK: MCS9) may transmit up to 4 time slots in the 8 time-slot frame according to the multislot class implemented in a device.

4.1.2. WCDMA Configuration and Testing

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices”, for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.

Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

HSPA+ SAR Guidance

The 3G SAR test reduction procedure is applied to HSPA+ (uplink) with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 6 HSPA, SAR is required for Rel. 7 HSPA+. Power is measured for HSPA+ that supports uplink 16QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

DC-HSDPA SAR Guidance

The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 5 HSDPA, SAR is required for Rel. 8 DC-HSDPA. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

4.1.3. LTE Configuration and Testing


UE power class is category 3. The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power please refer to the tune up procedure.

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

A properly configured base station simulator is used for the SAR and power measurements, so spectrum plots for each RB allocation and offset configuration are not included in the SAR report to demonstrate that the tested RB allocations have been correctly established at the maximum output power conditions.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe						
Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592·Ts	2192·Ts	2560·Ts	7680·Ts	2192·Ts	2560·Ts
1	19760·Ts			20480·Ts		
2	21952·Ts			23040·Ts		
3	24144·Ts			25600·Ts		
4	26336·Ts	4384·Ts	5120·Ts	7680·Ts	4384·Ts	5120·Ts
5	6592·Ts			20480·Ts		
6	19760·Ts			23040·Ts		
7	21952·Ts			12800·Ts		
8	24144·Ts			-	-	-
9	13168·Ts			-	-	-

Uplink-Downlink Configurations and duty cycle												
Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number										Duty-Cycle
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33%
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33%
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33%
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67%
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67%
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67%
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

4.1.4. WLAN Configuration and Testing

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset-based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.


- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

4.2. EUT TESTING POSITION

RF Exposure Conditions	Test Position	Separation Distance	SAR test exclusion
Body	Rear Face	0 cm	Note 4
	Left Side		
	Right Side		
	Top Side		
	Bottom Side		

Note:

- 1) Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary.
- 2) When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.
- 3) Next to the ear operation is generally not expected for tablets with overall diagonal dimension > 20 cm. However, when next to the ear voice mode is supported, regardless of the overall dimension, phablets must be tested according to the requirements described in KDB Publication 648474 D04.
- 4) For SAR test exclusion, please refer to section 4.4



4.3. PROXIMITY SENSORS TRIGGERING DISTANCES


Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed.

Proximity sensor triggering distance testing was performed according and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (2600MHz) and lowest (750MHz) frequency was used for proximity sensor triggering testing.

For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance -1mm was performed.

4.3.1. Triggering distance for perpendicular DUT orientation

The sensors can use to detect the proximity of the user's body or handheld states at the rear or left or top side of the device use a detection threshold distance. When rear/top sides of body or handheld condition is detected reduced power will be active.




The trigger distance shown in the sections below.

P-Sensor< Sensor for WWAN Main Antenna >

Proximity Sensor Triggering Distance (mm)								
Position	Front		Rear		Right Side		Top Side	
	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Triggering Distance	N/A	N/A	11	12	N/A	N/A	20	23

4.3.2. Triggering distance for tilted DUT orientation

- Position the DUT edge at the minimum triggering distance determined.
- Ensure that the proximity sensor is triggered when the DUT is in the perpendicular orientation specified.
- Rotate the DUT, The angle shall vary by $\pm 40^\circ$ from the perpendicular orientation in increments of 10° . At each of these angles, ensure that the proximity sensor is still triggered.
- Reduce the edge distance to the phantom by 1 mm and go back to step b) if sensor triggering is released or normal maximum output power is restored in step c).
- The smallest separation distance determined in steps a) and b) is the sensor triggering distance for non-perpendicular edge triggering conditions.
- The smallest triggering distance determined for the edge in perpendicular and rotated conditions shall be the minimum triggering distance for that edge.



The trigger distance shown in the sections below.

P-Sensor< Sensor for WWAN Main Antenna >

Proximity Sensor Triggering Distance (mm)				
Position	Right Side		Top Side	
	Moving towards	Moving away	Moving towards	Moving away
Minimum	N/A	N/A	19	23

4.3.3. Procedure for determining proximity sensor coverage area

Capacitive proximity sensor placed coincident with antenna elements at the top end of the Tablet are utilized to determine when the device comes in proximity of the user's body or finger or hand at the front or back or bottom or left or right or top side of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.

4.4. MEASURED CONDUCTED POWER RESULT

4.4.1. Conducted Power of GSM Bands

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	32.46	32.44	32.43	29.07	29.21	29.16
GPRS (GMSK, 1Tx-slot)	32.45	32.42	32.42	29.08	29.21	29.15
GPRS (GMSK, 2Tx-slot)	30.63	30.54	30.46	26.94	26.70	26.47
GPRS (GMSK, 3Tx-slot)	28.89	28.76	28.64	25.39	25.08	24.80
GPRS (GMSK, 4Tx-slot)	26.98	26.82	26.67	23.47	23.15	22.86
EDGE (8PSK, 1Tx-slot)	24.37	24.32	24.32	27.41	27.02	26.63
EDGE (8PSK, 2Tx-slot)	24.27	24.24	24.25	24.86	24.57	24.18
EDGE (8PSK, 3Tx-slot)	22.88	22.90	22.91	22.78	22.49	22.13
EDGE (8PSK, 4Tx-slot)	21.58	21.61	21.61	21.40	21.22	20.86
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	23.46	23.44	23.43	20.07	20.21	20.16
GPRS (GMSK, 1Tx-slot)	23.45	23.42	23.42	20.08	20.21	20.15
GPRS (GMSK, 2Tx-slot)	24.63	24.54	24.46	20.94	20.70	20.47
GPRS (GMSK, 3Tx-slot)	24.63	24.50	24.38	21.13	20.82	20.54
GPRS (GMSK, 4Tx-slot)	23.98	23.82	23.67	20.47	20.15	19.86
EDGE (8PSK, 1Tx-slot)	15.37	15.32	15.32	18.41	18.02	17.63
EDGE (8PSK, 2Tx-slot)	18.27	18.24	18.25	18.86	18.57	18.18
EDGE (8PSK, 3Tx-slot)	18.62	18.64	18.65	18.52	18.23	17.87
EDGE (8PSK, 4Tx-slot)	18.58	18.61	18.61	18.40	18.22	17.86

Power Reduction

Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	16.26	16.51	16.66	15.17	14.60	13.99
GPRS (GMSK, 1Tx-slot)	16.21	16.38	16.54	15.13	14.49	13.88
GPRS (GMSK, 2Tx-slot)	16.16	16.35	16.52	15.05	14.46	13.85
GPRS (GMSK, 3Tx-slot)	16.09	16.30	16.47	14.96	14.40	13.79
GPRS (GMSK, 4Tx-slot)	16.01	16.25	16.41	14.88	14.32	13.71
EDGE (8PSK, 1Tx-slot)	13.96	13.82	13.82	14.87	14.00	13.20
EDGE (8PSK, 2Tx-slot)	13.84	13.77	13.75	14.85	14.29	13.83
EDGE (8PSK, 3Tx-slot)	13.75	13.65	13.66	14.78	14.29	13.81
EDGE (8PSK, 4Tx-slot)	13.61	13.53	13.52	14.76	14.26	13.81
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	7.26	7.51	7.66	6.17	5.60	4.99
GPRS (GMSK, 1Tx-slot)	7.21	7.38	7.54	6.13	5.49	4.88
GPRS (GMSK, 2Tx-slot)	10.16	10.35	10.52	9.05	8.46	7.85
GPRS (GMSK, 3Tx-slot)	11.83	12.04	12.21	10.70	10.14	9.53
GPRS (GMSK, 4Tx-slot)	13.01	13.25	13.41	11.88	11.32	10.71
EDGE (8PSK, 1Tx-slot)	4.96	4.82	4.82	5.87	5.00	4.20
EDGE (8PSK, 2Tx-slot)	7.84	7.77	7.75	8.85	8.29	7.83
EDGE (8PSK, 3Tx-slot)	9.49	9.39	9.40	10.52	10.03	9.55
EDGE (8PSK, 4Tx-slot)	10.61	10.53	10.52	11.76	11.26	10.81

Note:

- 1) SAR testing was performed on the maximum frame-averaged power mode.
- 2) The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:
- 3) Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)

4.4.2. Conducted Power of WCDMA Bands

The measuring conducted average power (Unit: dBm) is shown as below.

Band	WCDMA Band II			WCDMA Band V			WCDMA Band IV		
Channel	9262	9400	9538	4132	4182	4233	1312	1413	1513
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	1712.4	1732.6	1752.6
RMC 12.2K	22.60	22.31	22.23	23.11	23.18	23.27	24.18	24.35	24.36
HSDPA Subtest-1	22.05	20.98	21.21	23.04	22.98	22.61	23.27	23.41	23.07
HSDPA Subtest-2	21.91	20.84	21.12	21.94	21.93	21.57	22.72	22.86	22.64
HSDPA Subtest-3	20.42	19.35	19.45	20.60	20.78	20.45	23.07	22.83	22.86
HSDPA Subtest-4	20.49	19.37	19.53	20.66	20.83	20.49	22.72	22.83	22.78
HSUPA Subtest-1	18.39	17.28	17.29	19.85	19.34	19.12	23.28	23.47	23.20
HSUPA Subtest-2	18.83	17.91	17.91	19.83	19.86	19.65	21.24	21.21	21.21
HSUPA Subtest-3	19.28	17.89	17.88	19.96	19.71	19.49	22.34	22.25	22.28
HSUPA Subtest-4	19.36	18.13	18.19	19.89	19.59	19.40	21.14	21.31	21.26
HSUPA Subtest-5	21.08	20.09	20.13	23.18	23.12	22.83	23.29	23.37	23.15

Power Reduction

Band	WCDMA Band II			WCDMA Band V			WCDMA Band IV		
Channel	9262	9400	9538	4132	4182	4233	1312	1413	1513
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	1712.4	1732.6	1752.6
RMC 12.2K	14.82	14.36	14.45	13.78	14.20	13.26	14.91	14.23	14.89
HSDPA Subtest-1	13.65	13.22	13.31	12.64	13.12	12.20	13.84	13.22	13.92
HSDPA Subtest-2	13.07	12.67	12.77	12.19	12.66	11.75	13.36	12.73	13.44
HSDPA Subtest-3	13.02	12.62	12.73	12.21	12.70	11.76	13.35	12.73	13.44
HSDPA Subtest-4	12.98	12.57	12.70	12.21	12.69	11.79	13.34	12.72	13.43
HSUPA Subtest-1	13.49	13.10	13.21	12.74	13.23	12.30	13.89	12.26	13.98
HSUPA Subtest-2	11.46	11.07	11.19	10.67	11.17	10.27	11.88	11.26	11.98
HSUPA Subtest-3	12.45	12.06	12.19	11.75	12.22	11.31	12.47	12.27	12.97
HSUPA Subtest-4	11.43	11.02	11.17	10.67	11.16	10.27	11.87	11.27	11.95
HSUPA Subtest-5	13.40	12.99	13.10	12.75	13.21	12.27	13.88	13.24	13.92

4.4.3. Conducted Power of LTE Bands

The measuring conducted average power (Unit: dBm) is shown as below.

➤ LTE Band 2

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth	RB	18607	18900	19193	18607	18900	19193
	(MHz)		1850.7 MHz	1880 MHz	1909.3 MHz	1850.7 MHz	1880 MHz	1909.3 MHz
2	1.4	1@0	23.80	23.64	23.57	22.59	22.88	22.54
		1@3	23.74	23.61	23.64	22.69	22.40	22.82
		1@5	23.65	23.85	23.61	22.81	22.68	22.25
		3@0	23.63	23.84	23.66	22.78	22.66	22.26
		3@1	22.55	22.65	22.59	21.44	21.65	21.61
		3@3	23.80	23.64	23.57	22.59	22.88	22.54
		6@0	23.74	23.61	23.64	22.69	22.40	22.82
Band	Bandwidth	RB	18615	18900	19185	18615	18900	19185
			1851.5 MHz	1880 MHz	1908.5 MHz	1851.5 MHz	1880 MHz	1908.5 MHz
2	3	1@0	23.40	23.66	23.78	22.40	22.32	22.52
		1@8	23.45	23.57	23.75	22.39	22.23	22.43
		1@14	22.58	22.57	22.62	21.71	21.55	21.56
		8@0	22.50	22.59	22.64	21.72	21.57	21.58
		8@4	22.56	22.52	22.51	21.51	21.61	21.56
		8@7	23.40	23.66	23.78	22.40	22.32	22.52
		15@0	23.45	23.57	23.75	22.39	22.23	22.43
Band	Bandwidth	RB	18625	18900	19175	18625	18900	19175
			1852.5 MHz	1880 MHz	1907.5 MHz	1852.5 MHz	1880 MHz	1907.5 MHz
2	5	1@0	23.66	23.55	23.51	22.50	22.36	22.43
		1@12	23.76	23.72	23.73	22.51	22.62	23.09
		1@24	23.78	23.65	23.57	22.22	22.27	22.62
		12@0	22.52	22.44	22.61	21.63	21.76	21.60
		12@7	22.53	22.47	22.50	21.55	21.69	21.62
		12@13	22.51	22.45	22.57	21.58	21.59	21.71
		25@0	22.51	22.53	22.63	21.54	21.59	21.68
Band	Bandwidth	RB	18650	18900	19150	18650	18900	19150
			1855 MHz	1880 MHz	1905 MHz	1855 MHz	1880 MHz	1905 MHz
2	10	1@0	23.54	23.53	23.49	22.52	22.90	23.24
		1@25	23.59	23.72	23.88	22.82	22.49	22.80
		1@49	23.73	23.70	23.77	22.54	22.28	22.95
		25@0	22.58	22.69	22.46	21.66	21.52	21.57
		25@12	22.60	22.63	22.49	21.66	21.45	21.58
		25@25	22.52	22.45	22.66	21.57	21.36	21.79
		50@0	22.57	22.45	22.58	21.63	21.47	21.86
Band	Bandwidth	RB	18675	18900	19125	18675	18900	19125
			1857.5 MHz	1880 MHz	1902.5 MHz	1857.5 MHz	1880 MHz	1902.5 MHz
2	15	1@0	23.52	23.61	23.49	22.45	22.62	23.20
		1@37	23.58	23.42	23.54	22.77	22.76	22.93
		1@74	23.50	23.35	23.55	22.41	22.60	22.97
		36@0	22.55	22.52	22.59	22.62	22.53	22.60
		36@20	22.53	22.54	22.60	22.61	22.54	22.60
		36@39	22.52	22.54	22.60	22.68	22.54	22.62
		75@0	22.60	22.54	22.62	21.57	21.72	21.53
Band	Bandwidth	RB	18700	18900	19100	18700	18900	19100
			1860 MHz	1880 MHz	1900 MHz	1860 MHz	1880 MHz	1900 MHz
2	20	1@0	23.45	23.62	23.26	22.65	23.21	22.26
		1@49	23.96	23.76	23.83	22.99	23.52	22.67
		1@99	23.63	23.31	23.46	22.70	22.59	22.35
		50@0	22.67	22.66	22.39	21.72	21.61	21.62
		50@24	22.49	22.62	22.43	21.72	21.63	21.62
		50@50	22.59	22.51	22.57	21.73	21.48	21.61
		100@0	22.60	22.48	22.48	21.65	21.46	21.55

➤ LTE Band 4

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	19957	20175	20393	19957	20175	20393
			1710.7 MHz	1732.5 MHz	1754.3 MHz	1710.7 MHz	1732.5 MHz	1754.3 MHz
4	1.4	1@0	23.71	23.44	23.81	22.40	23.27	22.61
		1@3	23.58	23.52	23.99	22.22	23.17	22.94
		1@5	23.88	23.82	23.85	22.79	22.22	22.35
		3@0	23.85	23.83	23.76	22.75	22.22	22.35
		3@1	22.82	22.60	22.77	21.72	21.92	21.90
		3@3	23.71	23.44	23.81	22.40	23.27	22.61
		6@0	23.58	23.52	23.99	22.22	23.17	22.94
Band	Bandwidth (MHz)	RB	19965	20175	20385	19965	20175	20385
			1711.5 MHz	1732.5 MHz	1753.5 MHz	1711.5 MHz	1732.5 MHz	1753.5 MHz
4	3	1@0	23.46	23.88	23.56	22.64	22.62	23.36
		1@8	23.18	23.50	23.75	22.44	22.30	23.14
		1@14	22.73	22.67	22.84	21.90	21.72	22.07
		8@0	22.72	22.69	22.85	21.48	21.47	22.08
		8@4	22.51	22.73	22.82	21.89	21.69	21.66
		8@7	23.46	23.88	23.56	22.64	22.62	23.36
		15@0	23.18	23.50	23.75	22.44	22.30	23.14
Band	Bandwidth (MHz)	RB	19975	20175	20375	19975	20175	20375
			1712.5 MHz	1732.5 MHz	1752.5 MHz	1712.5 MHz	1732.5 MHz	1752.5 MHz
4	5	1@0	23.54	23.71	23.99	22.64	22.82	22.71
		1@12	23.41	23.62	23.84	23.09	23.15	22.69
		1@24	23.50	23.48	23.66	22.20	22.70	22.79
		12@0	22.63	22.75	22.71	21.76	21.79	21.91
		12@7	22.72	22.67	22.72	21.35	21.71	21.92
		12@13	22.32	22.70	22.79	21.72	21.73	21.99
		25@0	22.51	22.62	22.81	21.56	21.84	21.93
Band	Bandwidth (MHz)	RB	20000	20175	20350	20000	20175	20350
			1715 MHz	1732.5 MHz	1750 MHz	1715 MHz	1732.5 MHz	1750 MHz
4	10	1@0	23.56	23.46	23.53	23.03	22.63	22.93
		1@25	23.94	23.69	23.98	22.89	22.32	23.38
		1@49	23.81	23.71	23.76	23.37	22.56	22.98
		25@0	22.57	22.67	22.75	21.74	21.59	21.91
		25@12	22.57	22.68	22.76	21.73	21.60	21.92
		25@25	22.72	22.62	22.76	22.07	21.74	21.94
		50@0	22.70	22.67	22.72	21.69	21.61	21.78
Band	Bandwidth (MHz)	RB	20025	20175	20325	20025	20175	20325
			1717.5 MHz	1732.5 MHz	1747.5 MHz	1717.5 MHz	1732.5 MHz	1747.5 MHz
4	15	1@0	23.63	23.65	23.97	22.64	22.71	22.56
		1@37	23.55	23.71	23.72	23.06	22.17	22.77
		1@74	23.65	23.61	23.66	22.55	22.50	22.99
		36@0	22.70	22.63	22.86	22.69	22.63	22.87
		36@20	22.69	22.63	22.87	22.68	22.64	22.86
		36@39	22.68	22.64	22.86	22.67	22.64	22.87
		75@0	22.67	22.64	22.87	21.68	21.65	21.93
Band	Bandwidth (MHz)	RB	20050	20175	20300	20050	20175	20300
			1720 MHz	1732.5 MHz	1745 MHz	1720 MHz	1732.5 MHz	1745 MHz
4	20	1@0	23.73	23.58	23.79	22.58	23.36	22.77
		1@49	24.01	24.07	23.73	23.20	23.43	22.53
		1@99	23.73	23.56	23.97	22.89	23.16	22.75
		50@0	22.68	22.73	22.83	21.88	21.70	21.97
		50@24	22.68	22.75	22.94	21.78	21.62	21.91
		50@50	22.72	22.63	22.74	21.89	21.60	21.93
		100@0	22.71	22.62	22.83	21.80	21.74	22.01

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ LTE Band 5

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	20407	20525	20643	20407	20525	20643
			824.7 MHz	836.5 MHz	848.3 MHz	824.7 MHz	836.5 MHz	848.3 MHz
5	1.4	1@0	23.64	23.41	23.50	22.52	22.27	23.12
		1@3	23.54	23.54	23.59	23.12	22.52	23.02
		1@5	23.46	23.45	23.46	22.18	22.49	22.07
		3@0	23.61	23.37	23.60	22.34	22.50	22.42
		3@1	22.65	22.56	22.58	21.52	21.28	21.25
		3@3	23.64	23.41	23.50	22.52	22.27	23.12
		6@0	23.54	23.54	23.59	23.12	22.52	23.02
Band	Bandwidth (MHz)	RB	20415	20525	20635	20415	20525	20635
			825.5 MHz	836.5 MHz	847.5 MHz	825.5 MHz	836.5 MHz	847.5 MHz
5	3	1@0	23.32	23.56	23.49	22.57	22.91	23.16
		1@8	23.31	23.39	23.60	22.48	22.69	23.07
		1@14	22.68	22.59	22.82	21.77	21.49	21.95
		8@0	22.69	22.60	22.77	21.78	21.54	22.06
		8@4	22.62	22.57	22.61	21.71	21.50	21.83
		8@7	22.64	22.55	22.76	21.52	21.53	21.66
		15@0	23.32	23.56	23.49	22.57	22.91	23.16
Band	Bandwidth (MHz)	RB	20425	20525	20625	20425	20525	20625
			826.5 MHz	836.5 MHz	846.5 MHz	826.5 MHz	836.5 MHz	846.5 MHz
5	5	1@0	23.52	23.31	23.47	22.60	22.05	22.58
		1@12	23.39	23.33	23.63	22.16	22.98	23.14
		1@24	23.54	23.37	23.35	22.07	22.14	22.55
		12@0	22.58	22.51	22.78	21.48	21.18	21.70
		12@7	22.57	22.52	22.73	21.48	21.19	21.72
		12@13	22.54	22.48	22.70	21.44	21.44	21.75
		25@0	22.64	22.52	22.73	21.37	21.71	21.66
Band	Bandwidth (MHz)	RB	20450	20525	20600	20450	20525	20600
			829 MHz	836.5 MHz	844 MHz	829 MHz	836.5 MHz	844 MHz
5	10	1@0	23.46	23.59	23.34	22.77	22.95	22.57
		1@25	23.39	23.68	23.42	22.22	23.04	22.71
		1@49	23.31	23.56	23.27	22.71	22.91	22.52
		25@0	22.65	22.52	22.67	21.91	21.71	21.61
		25@12	22.63	22.53	22.60	21.89	21.71	21.63
		25@25	22.59	22.68	22.68	21.77	21.76	21.65
		50@0	22.62	22.53	22.69	21.64	21.60	21.48

➤ LTE Band 7

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	20775	21100	21425	20775	21100	21425
			2502.5 MHz	2535 MHz	2567.5 MHz	2502.5 MHz	2535 MHz	2567.5 MHz
7	5	1@0	23.73	23.47	23.42	22.28	22.57	22.39
		1@12	23.64	23.63	23.49	23.11	22.91	22.57
		1@24	22.52	22.47	22.41	21.68	21.54	21.40
		12@0	22.59	22.48	22.35	21.67	21.46	21.33
		12@7	22.67	22.40	22.42	21.85	21.58	21.30
		12@13	23.73	23.47	23.42	22.28	22.57	22.39
		25@0	23.64	23.63	23.49	23.11	22.91	22.57
Band	Bandwidth (MHz)	RB	20800	21100	21400	20800	21100	21400
			2505 MHz	2535 MHz	2565 MHz	2505 MHz	2535 MHz	2565 MHz
7	10	1@0	23.51	23.28	23.50	22.52	22.57	22.26
		1@25	23.64	23.32	23.59	22.92	22.63	22.72
		1@49	22.76	22.49	22.47	21.85	21.66	21.77
		25@0	22.75	22.52	22.49	21.84	21.67	21.60
		25@12	22.67	22.43	22.45	21.59	21.57	21.42
		25@25	22.66	22.43	22.47	21.77	21.37	21.57
		50@0	23.51	23.28	23.50	22.52	22.57	22.26
Band	Bandwidth (MHz)	RB	20825	21100	21375	20825	21100	21375
			2507.5 MHz	2535 MHz	2562.5 MHz	2507.5 MHz	2535 MHz	2562.5 MHz
7	15	1@0	23.54	23.41	23.61	22.51	22.62	22.74
		1@37	23.67	23.39	23.36	23.03	22.60	22.75
		1@74	23.54	23.51	23.28	22.57	22.62	22.12
		36@0	22.60	22.43	22.55	22.59	22.44	22.56
		36@20	22.60	22.45	22.56	22.60	22.44	22.44
		36@39	22.60	22.45	22.45	22.61	22.45	22.46
		75@0	22.61	22.45	22.46	21.83	21.59	21.68
Band	Bandwidth (MHz)	RB	20850	21100	21350	20850	21100	21350
			2510 MHz	2535 MHz	2560 MHz	2510 MHz	2535 MHz	2560 MHz
7	20	1@0	23.52	23.57	23.51	22.58	22.48	23.20
		1@49	23.50	23.61	23.76	23.14	23.00	23.58
		1@99	23.57	23.50	23.32	22.27	22.65	23.08
		50@0	22.70	22.67	22.49	21.80	21.65	21.51
		50@24	22.69	22.60	22.54	21.86	21.66	21.61
		50@50	22.61	22.43	22.49	21.69	21.57	21.48
		100@0	22.56	22.57	22.51	21.69	21.71	21.56

➤ **LTE Band 12**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	23017	23095	23173	23017	23095	23173
			699.7 MHz	707.5 MHz	715.3 MHz	699.7 MHz	707.5 MHz	715.3 MHz
12	1.4	1@0	23.26	23.17	23.43	21.97	22.45	22.32
		1@3	23.35	23.48	23.43	22.06	22.62	22.38
		1@5	23.39	23.26	23.32	22.28	21.68	22.54
		3@0	23.37	23.16	23.31	22.27	21.67	22.54
		3@1	22.24	22.17	22.37	21.30	21.03	21.13
		3@3	23.26	23.17	23.43	21.97	22.45	22.32
		6@0	23.35	23.48	23.43	22.06	22.62	22.38
Band	Bandwidth (MHz)	RB	23025	23095	23165	23025	23095	23165
			700.5 MHz	707.5 MHz	714.5 MHz	700.5 MHz	707.5 MHz	714.5 MHz
12	3	1@0	23.06	23.12	23.13	21.98	22.01	22.57
		1@8	23.07	23.51	23.12	21.95	22.23	22.13
		1@14	23.10	23.13	23.18	21.84	21.98	22.11
		8@0	22.15	22.19	22.36	21.49	21.25	21.32
		8@4	22.25	22.20	22.37	21.31	21.24	21.32
		8@7	22.21	22.22	22.31	21.26	21.51	21.38
		15@0	22.17	22.21	22.31	21.16	21.04	21.22
Band	Bandwidth (MHz)	RB	23035	23095	23155	23035	23095	23155
			701.5 MHz	707.5 MHz	713.5 MHz	701.5 MHz	707.5 MHz	713.5 MHz
12	5	1@0	22.88	23.15	23.12	21.64	22.08	22.15
		1@12	23.21	23.39	23.45	22.22	22.15	22.21
		1@24	23.09	23.19	23.14	21.71	22.05	22.22
		12@0	22.08	22.22	22.25	21.13	21.23	21.15
		12@7	22.10	22.22	22.28	21.13	21.23	21.07
		12@13	22.14	22.16	22.36	21.10	21.18	21.11
		25@0	22.14	22.20	22.26	21.28	21.09	21.25
Band	Bandwidth (MHz)	RB	23060	23095	23130	23060	23095	23130
			704 MHz	707.5 MHz	711 MHz	704 MHz	707.5 MHz	711 MHz
12	10	1@0	22.90	22.79	23.20	21.93	22.03	22.93
		1@25	23.09	23.50	23.66	22.32	22.53	22.39
		1@49	22.84	22.98	23.13	22.01	22.03	22.62
		25@0	22.10	22.15	22.22	20.95	21.13	21.34
		25@12	22.11	22.16	22.23	20.86	21.14	21.34
		25@25	22.24	22.21	22.32	20.95	21.07	21.49
		50@0	22.22	22.18	22.16	21.35	21.13	21.21

➤ **LTE Band 13**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	23205	23230	23255	23205	23230	23255
			779.5 MHz	782 MHz	784.5 MHz	779.5 MHz	782 MHz	784.5 MHz
13	5	1@0	22.58	22.79	22.85	21.71	21.74	22.11
		1@12	23.09	23.18	23.00	21.98	21.88	22.33
		1@24	21.96	21.98	21.91	20.89	20.98	20.95
		12@0	21.87	22.05	21.92	20.97	21.05	20.95
		12@7	21.87	21.93	21.93	21.34	20.92	20.96
		12@13	21.86	21.86	21.89	20.78	21.03	21.13
		25@0	22.58	22.79	22.85	21.71	21.74	22.11
Band	Bandwidth (MHz)	RB	--	23230	--	--	23230	--
			--	782 MHz	--	--	782 MHz	--
13	10	1@0	--	22.44	--	--	21.74	--
		1@25	--	22.95	--	--	22.41	--
		1@49	--	23.24	--	--	22.08	--
		25@0	--	21.97	--	--	21.08	--
		25@12	--	21.95	--	--	21.08	--
		25@25	--	21.96	--	--	21.06	--
		50@0	--	21.90	--	--	20.94	--

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ **LTE Band 14**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth	RB	5305	5330	5355	5305	5330	5355
	(MHz)		790.5 MHz	793 MHz	795.5 MHz	790.5 MHz	793 MHz	795.5 MHz
17	5	1@0	23.00	23.12	23.19	22.06	21.85	21.42
		1@12	23.08	22.93	23.21	22.05	21.98	22.57
		1@24	23.03	23.14	23.11	22.04	22.05	21.79
		12@0	22.05	22.00	22.04	21.07	21.02	21.06
		12@7	22.05	22.00	22.05	21.06	21.02	21.07
		12@13	22.08	22.05	22.08	21.03	21.00	21.24
		25@0	22.01	22.07	22.01	21.18	21.10	20.93
Band	Bandwidth	RB	--	5330	--	--	5330	--
			--	793 MHz	--	--	793 MHz	--
17	10	1@0	--	23.23	--	--	21.92	--
		1@25	--	23.26	--	--	22.25	--
		1@49	--	23.36	--	--	22.07	--
		25@0	--	22.10	--	--	21.08	--
		25@12	--	22.04	--	--	20.91	--
		25@25	--	22.03	--	--	20.90	--
		50@0	--	22.08	--	--	21.06	--

➤ **LTE Band 17**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth	RB	23755	23790	23825	23755	23790	23825
	(MHz)		706.5 MHz	710 MHz	713.5 MHz	706.5 MHz	710 MHz	713.5 MHz
17	5	1@0	23.44	23.41	23.28	22.33	22.33	22.22
		1@12	23.54	23.46	23.20	22.81	22.24	22.75
		1@24	22.27	22.14	22.38	21.32	21.43	21.36
		12@0	22.27	22.15	22.40	21.31	21.43	21.27
		12@7	22.35	22.32	22.33	21.48	21.51	21.33
		12@13	22.25	22.21	22.46	21.39	21.32	21.32
		25@0	23.44	23.41	23.28	22.33	22.33	22.22
Band	Bandwidth	RB	23780	23790	23800	23780	23790	23800
			709 MHz	710 MHz	711 MHz	709 MHz	710 MHz	711 MHz
17	10	1@0	23.27	23.30	23.20	22.36	22.05	23.07
		1@25	23.16	23.33	23.63	22.42	22.30	22.47
		1@49	23.39	23.08	23.33	22.41	21.87	22.83
		25@0	22.39	22.37	22.27	21.25	21.49	21.34
		25@12	22.39	22.38	22.29	21.25	21.44	21.55
		25@25	22.37	22.44	22.43	21.11	21.52	21.51
		50@0	22.41	22.41	22.43	21.36	21.39	21.66

➤ **LTE Band 38**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth	RB	37775	38000	38225	37775	38000	38225
	(MHz)		2572.5 MHz	2595 MHz	2617.5 MHz	2572.5 MHz	2595 MHz	2617.5 MHz
38	5	1@0	22.69	22.79	22.91	22.09	22.17	22.73
		1@12	22.77	22.92	22.26	22.18	22.33	22.74
		1@24	21.90	21.73	22.05	20.96	20.72	21.09
		12@0	21.92	21.84	22.06	20.97	20.84	21.01
		12@7	21.86	21.78	22.01	20.93	20.70	21.14
		12@13	22.69	22.79	22.91	22.09	22.17	22.73
		25@0	22.77	22.92	22.26	22.18	22.33	22.74
Band	Bandwidth	RB	37800	38000	38200	37800	38000	38200
	(MHz)		2575 MHz	2595 MHz	2615 MHz	2575 MHz	2595 MHz	2615 MHz
38	10	1@0	22.96	22.92	22.86	22.43	22.00	22.36
		1@25	22.64	22.29	22.24	22.41	22.12	22.48
		1@49	22.80	22.98	22.88	22.29	22.27	21.76
		25@0	21.95	21.91	22.00	21.07	20.87	21.19
		25@12	21.96	21.91	22.01	21.07	20.87	21.19
		25@25	21.97	21.95	22.04	20.95	20.90	21.21
		50@0	22.02	21.93	22.06	21.13	21.10	21.00
Band	Bandwidth	RB	37825	38000	38175	37825	38000	38175
	(MHz)		2577.5 MHz	2595 MHz	2612.5 MHz	2577.5 MHz	2595 MHz	2612.5 MHz
38	15	1@0	23.00	22.97	23.02	21.91	22.08	22.37
		1@37	22.64	22.47	22.27	21.88	22.35	22.10
		1@74	22.75	22.99	22.92	21.78	22.09	22.20
		36@0	21.93	21.89	22.17	21.86	22.00	22.18
		36@20	21.94	22.00	22.17	21.94	22.00	22.18
		36@39	21.93	22.01	22.18	21.85	22.02	22.19
		75@0	21.85	22.02	22.27	21.01	21.10	21.38
Band	Bandwidth	RB	37850	38000	38150	37850	38000	38150
	(MHz)		2580 MHz	2595 MHz	2610 MHz	2580 MHz	2595 MHz	2610 MHz
38	20	1@0	23.00	23.03	22.94	22.65	22.24	21.93
		1@49	23.28	23.18	23.09	22.59	22.32	21.83
		1@99	22.98	23.17	22.87	22.43	22.27	21.80
		50@0	22.02	21.99	22.18	21.31	21.17	21.24
		50@24	22.03	22.01	22.11	21.17	21.17	21.24
		50@50	21.93	22.14	22.16	21.14	21.35	21.21
		100@0	22.01	22.26	22.17	21.07	21.09	21.25

➤ LTE Band 66

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	131979	132322	132665	131979	132322	132665
			1710.7 MHz	1745 MHz	1779.3 MHz	1710.7 MHz	1745 MHz	1779.3 MHz
66	1.4	1@0	23.74	23.84	23.93	22.63	22.86	23.34
		1@3	23.62	24.26	24.03	22.91	22.80	23.27
		1@5	23.70	23.96	23.79	22.28	23.08	22.69
		3@0	23.74	24.03	23.79	22.26	22.36	22.49
		3@1	22.86	22.72	22.79	21.55	21.72	21.95
		3@3	23.74	23.84	23.93	22.63	22.86	23.34
		6@0	23.62	24.26	24.03	22.91	22.80	23.27
Band	Bandwidth (MHz)	RB	131987	132322	132657	131987	132322	132657
			1711.5 MHz	1745 MHz	1778.5 MHz	1711.5 MHz	1745 MHz	1778.5 MHz
66	3	1@0	23.55	23.80	23.68	22.32	22.74	22.86
		1@8	23.41	23.77	23.84	22.62	22.49	22.89
		1@14	22.72	23.00	22.76	21.89	21.80	21.78
		8@0	22.79	22.96	22.78	21.89	22.07	21.79
		8@4	22.86	23.01	22.76	21.92	21.73	21.64
		8@7	23.55	23.80	23.68	22.32	22.74	22.86
		15@0	23.41	23.77	23.84	22.62	22.49	22.89
Band	Bandwidth (MHz)	RB	131997	132322	132647	131997	132322	132647
			1712.5 MHz	1745 MHz	1777.5 MHz	1712.5 MHz	1745 MHz	1777.5 MHz
66	5	1@0	23.57	23.90	23.76	22.63	22.79	22.87
		1@12	23.58	23.95	23.75	22.29	22.78	23.17
		1@24	23.65	23.91	23.89	22.65	22.78	22.72
		12@0	22.66	22.96	22.69	21.70	21.96	21.51
		12@7	22.67	22.97	22.71	21.70	21.97	21.52
		12@13	22.79	22.96	22.84	21.59	21.72	21.64
		25@0	22.50	22.94	22.77	21.55	21.93	21.80
Band	Bandwidth (MHz)	RB	132022	132322	132622	132022	132322	132622
			1715 MHz	1745 MHz	1775 MHz	1715 MHz	1745 MHz	1775 MHz
66	10	1@0	23.36	23.79	23.80	23.03	22.78	22.96
		1@25	23.49	24.12	23.95	23.25	23.12	23.36
		1@49	23.74	24.21	23.79	22.94	23.11	23.16
		25@0	22.76	22.99	22.71	21.76	22.16	21.76
		25@12	22.76	23.01	22.68	21.76	22.17	21.78
		25@25	22.80	22.99	22.83	21.74	22.07	21.82
		50@0	22.80	23.00	22.68	21.81	21.99	21.66
Band	Bandwidth (MHz)	RB	132047	132322	132597	132047	132322	132597
			1717.5 MHz	1745 MHz	1772.5 MHz	1717.5 MHz	1745 MHz	1772.5 MHz
66	15	1@0	23.67	23.98	23.84	22.73	22.66	23.14
		1@37	23.54	23.80	23.57	22.70	22.60	23.32
		1@74	23.81	23.80	23.73	22.74	22.86	22.76
		36@0	22.85	22.92	22.68	22.85	22.92	22.63
		36@20	22.85	22.93	22.81	22.85	22.93	22.65
		36@39	22.85	22.93	22.65	22.85	22.93	22.65
		75@0	22.85	22.93	22.65	21.68	21.94	21.74
Band	Bandwidth (MHz)	RB	132072	132322	132572	132072	132322	132572
			1720 MHz	1745 MHz	1770 MHz	1720 MHz	1745 MHz	1770 MHz
66	20	1@0	23.70	23.82	23.81	22.80	23.57	22.73
		1@49	23.76	23.98	23.86	23.31	23.59	22.88
		1@99	23.88	24.44	23.85	22.74	23.60	22.58
		50@0	22.64	22.96	22.79	21.88	22.06	21.96
		50@24	22.77	22.99	22.76	21.88	22.06	21.88
		50@50	22.83	22.92	22.74	21.88	21.87	21.88
		100@0	22.82	22.92	22.75	21.83	21.96	21.84

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ **LTE Band 2 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	18607	18900	19193	18607	18900	19193
			1850.7 MHz	1880 MHz	1909.3 MHz	1850.7 MHz	1880 MHz	1909.3 MHz
2	1.4	1@0	14.28	13.83	13.83	14.17	13.75	13.62
		1@3	14.23	13.83	13.78	14.14	13.78	13.62
		1@5	14.07	13.84	13.67	13.97	13.74	13.50
		3@0	14.21	13.84	13.76	14.00	13.64	13.59
		3@1	14.21	13.84	13.76	14.00	13.64	13.59
		3@3	14.11	13.75	13.67	13.91	13.57	13.50
		6@0	14.19	13.83	13.70	14.17	13.82	13.56
Band	Bandwidth (MHz)	RB	18615	18900	19185	18615	18900	19185
			1851.5 MHz	1880 MHz	1908.5 MHz	1851.5 MHz	1880 MHz	1908.5 MHz
2	3	1@0	14.16	13.79	13.97	14.13	13.57	13.71
		1@8	14.13	13.96	13.94	14.13	13.76	13.71
		1@14	13.87	13.87	13.58	13.84	13.63	13.36
		8@0	14.19	13.80	13.98	14.17	13.76	13.96
		8@4	14.20	13.81	13.98	14.17	13.76	13.96
		8@7	14.00	13.90	13.80	13.97	13.85	13.77
		15@0	14.09	13.85	13.87	14.07	13.77	13.78
Band	Bandwidth (MHz)	RB	18625	18900	19175	18625	18900	19175
			1852.5 MHz	1880 MHz	1907.5 MHz	1852.5 MHz	1880 MHz	1907.5 MHz
2	5	1@0	13.96	13.40	13.50	13.83	13.45	13.34
		1@12	14.21	13.95	14.14	14.10	14.00	14.04
		1@24	13.81	13.52	13.31	13.75	13.54	13.20
		12@0	14.05	13.74	13.85	13.99	13.76	13.86
		12@7	14.05	13.76	13.85	13.99	13.77	13.86
		12@13	14.03	13.85	13.76	13.99	13.86	13.77
		25@0	13.91	13.86	13.92	13.87	13.79	13.93
Band	Bandwidth (MHz)	RB	18650	18900	19150	18650	18900	19150
			1855 MHz	1880 MHz	1905 MHz	1855 MHz	1880 MHz	1905 MHz
2	10	1@0	13.57	13.00	12.98	13.52	12.84	12.69
		1@25	14.25	13.97	13.95	14.26	13.78	13.68
		1@49	13.55	13.33	13.01	13.57	13.11	12.75
		25@0	13.85	13.63	13.51	13.81	13.63	13.50
		25@12	13.85	13.64	13.52	13.81	13.63	13.50
		25@25	14.14	13.74	13.77	14.06	13.72	13.77
		50@0	13.98	13.74	13.64	13.95	13.72	13.61
Band	Bandwidth (MHz)	RB	18675	18900	19125	18675	18900	19125
			1857.5 MHz	1880 MHz	1902.5 MHz	1857.5 MHz	1880 MHz	1902.5 MHz
2	15	1@0	13.27	12.70	13.00	13.17	12.83	12.70
		1@37	14.31	13.80	13.78	14.31	13.93	13.51
		1@74	13.20	12.93	12.73	13.17	13.04	12.43
		36@0	13.86	13.60	13.50	13.85	13.60	13.49
		36@20	13.85	13.60	13.49	13.85	13.60	13.49
		36@39	13.84	13.60	13.49	13.84	13.60	13.49
		75@0	13.84	13.60	13.49	13.80	13.57	13.49
Band	Bandwidth (MHz)	RB	18700	18900	19100	18700	18900	19100
			1860 MHz	1880 MHz	1900 MHz	1860 MHz	1880 MHz	1900 MHz
2	20	1@0	13.06	12.61	12.78	12.85	12.71	12.56
		1@49	14.33	13.92	13.75	14.19	14.03	13.58
		1@99	13.03	13.25	12.80	12.87	13.38	12.58
		50@0	13.99	13.48	13.69	13.98	13.49	13.73
		50@24	13.98	13.49	13.69	13.97	13.49	13.73
		50@50	13.91	13.74	13.55	13.88	13.73	13.57
		100@0	13.87	13.57	13.62	13.81	13.53	13.62

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ **LTE Band 4 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	19957	20175	20393	19957	20175	20393
			1710.7 MHz	1732.5 MHz	1754.3 MHz	1710.7 MHz	1732.5 MHz	1754.3 MHz
4	1.4	1@0	13.99	13.33	14.41	13.77	13.09	14.27
		1@3	13.99	13.33	14.43	13.86	13.08	14.32
		1@5	13.93	13.28	14.34	13.79	13.02	14.20
		3@0	13.87	13.32	14.37	13.70	13.09	14.09
		3@1	13.86	13.33	14.37	13.69	13.09	14.09
		3@3	13.86	13.28	14.32	13.69	13.01	14.07
		6@0	13.87	13.29	14.36	13.75	13.26	14.29
Band	Bandwidth (MHz)	RB	19965	20175	20385	19965	20175	20385
			1711.5 MHz	1732.5 MHz	1753.5 MHz	1711.5 MHz	1732.5 MHz	1753.5 MHz
4	3	1@0	13.79	13.36	14.35	13.76	13.22	13.99
		1@8	14.14	13.36	14.51	14.15	13.18	14.18
		1@14	14.03	13.26	14.28	14.02	13.05	13.97
		8@0	13.88	13.31	14.39	13.92	13.28	14.29
		8@4	13.88	13.31	14.39	13.91	13.28	14.29
		8@7	14.01	13.27	14.36	14.05	13.25	14.27
		15@0	13.98	13.29	14.35	14.02	13.21	14.19
Band	Bandwidth (MHz)	RB	19975	20175	20375	19975	20175	20375
			1712.5 MHz	1732.5 MHz	1752.5 MHz	1712.5 MHz	1732.5 MHz	1752.5 MHz
4	5	1@0	13.51	13.06	13.89	13.37	13.00	13.98
		1@12	14.33	13.40	14.52	14.23	13.29	14.50
		1@24	13.83	13.00	13.93	13.75	12.95	13.90
		12@0	13.77	13.22	14.17	13.80	13.19	14.24
		12@7	13.76	13.22	14.17	13.80	13.19	14.24
		12@13	14.03	13.19	14.25	14.07	13.15	14.21
		25@0	13.91	13.21	14.26	13.96	13.20	14.15
Band	Bandwidth (MHz)	RB	20000	20175	20350	20000	20175	20350
			1715 MHz	1732.5 MHz	1750 MHz	1715 MHz	1732.5 MHz	1750 MHz
4	10	1@0	13.18	12.81	13.26	13.17	12.61	13.00
		1@25	14.36	13.35	14.45	14.36	13.17	14.22
		1@49	13.54	12.59	13.62	13.56	12.36	13.30
		25@0	13.82	13.23	13.98	13.82	13.27	14.00
		25@12	13.81	13.24	13.97	13.81	13.27	14.00
		25@25	14.13	13.06	14.07	14.13	13.07	14.13
		50@0	13.97	13.20	14.02	13.97	13.24	14.02
Band	Bandwidth (MHz)	RB	20025	20175	20325	20025	20175	20325
			1717.5 MHz	1732.5 MHz	1747.5 MHz	1717.5 MHz	1732.5 MHz	1747.5 MHz
4	15	1@0	12.75	12.72	12.59	12.72	12.78	12.30
		1@37	14.40	13.19	14.21	14.40	13.33	13.95
		1@74	13.04	12.31	13.29	12.98	12.40	12.94
		36@0	13.89	13.15	13.75	13.88	13.16	13.75
		36@20	13.88	13.16	13.75	13.88	13.16	13.75
		36@39	13.87	13.16	13.75	13.87	13.17	13.75
		75@0	13.87	13.17	13.75	13.86	13.10	13.76
Band	Bandwidth (MHz)	RB	20050	20175	20300	20050	20175	20300
			1720 MHz	1732.5 MHz	1745 MHz	1720 MHz	1732.5 MHz	1745 MHz
4	20	1@0	12.52	12.74	11.97	12.43	12.78	11.79
		1@49	14.54	13.30	14.03	14.32	13.42	13.84
		1@99	12.59	12.71	13.38	12.41	12.81	13.08
		50@0	13.91	13.39	13.32	13.91	13.37	13.36
		50@24	13.90	13.40	13.32	13.90	13.37	13.36
		50@50	13.76	13.14	14.01	13.73	13.13	14.04
		100@0	13.75	13.22	13.54	13.77	13.18	13.57

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ **LTE Band 5 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	20407	20525	20643	20407	20525	20643
			824.7 MHz	836.5 MHz	848.3 MHz	824.7 MHz	836.5 MHz	848.3 MHz
5	1.4	1@0	13.75	14.00	14.17	13.69	13.83	13.82
		1@3	13.70	14.05	13.90	13.68	13.95	13.53
		1@5	13.69	14.01	13.58	13.61	13.89	13.20
		3@0	13.70	13.97	14.11	13.51	13.85	13.76
		3@1	13.69	13.97	14.11	13.51	13.85	13.76
		3@3	13.70	13.98	13.70	13.52	13.85	13.30
		6@0	13.78	13.96	13.89	13.78	13.86	13.76
Band	Bandwidth (MHz)	RB	20415	20525	20635	20415	20525	20635
			825.5 MHz	836.5 MHz	847.5 MHz	825.5 MHz	836.5 MHz	847.5 MHz
5	3	1@0	13.55	13.78	13.78	13.57	13.64	13.56
		1@8	13.69	14.10	14.23	13.71	13.97	13.86
		1@14	13.37	13.92	13.43	13.36	13.75	13.07
		8@0	13.73	13.92	14.10	13.74	13.94	14.07
		8@4	13.73	13.92	14.11	13.74	13.95	14.07
		8@7	13.63	13.97	14.06	13.63	14.00	13.92
		15@0	13.61	13.95	14.02	13.62	13.90	13.82
Band	Bandwidth (MHz)	RB	20425	20525	20625	20425	20525	20625
			826.5 MHz	836.5 MHz	846.5 MHz	826.5 MHz	836.5 MHz	846.5 MHz
5	5	1@0	13.26	13.30	13.24	13.28	13.20	13.17
		1@12	13.73	14.13	14.19	13.76	14.07	14.14
		1@24	12.92	13.53	13.16	12.97	13.46	12.94
		12@0	13.50	13.75	13.68	13.53	13.79	13.70
		12@7	13.50	13.76	13.68	13.54	13.79	13.69
		12@13	13.43	13.87	14.04	13.48	13.93	13.89
		25@0	13.47	13.83	13.85	13.44	13.89	13.87
Band	Bandwidth (MHz)	RB	20450	20525	20600	20450	20525	20600
			829 MHz	836.5 MHz	844 MHz	829 MHz	836.5 MHz	844 MHz
5	10	1@0	13.02	12.99	13.30	13.01	12.84	13.06
		1@25	13.60	14.24	13.86	13.64	14.00	13.61
		1@49	13.03	13.25	13.23	13.04	13.08	12.84
		25@0	13.49	13.66	13.59	13.44	13.68	13.60
		25@12	13.48	13.66	13.60	13.44	13.68	13.60
		25@25	13.37	13.90	13.83	13.36	13.95	13.86
		50@0	13.43	13.77	13.72	13.42	13.81	13.73

➤ **LTE Band 7 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	20775	21100	21425	20775	21100	21425
			2502.5 MHz	2535 MHz	2567.5 MHz	2502.5 MHz	2535 MHz	2567.5 MHz
7	5	1@0	13.25	12.83	13.08	13.12	12.74	13.14
		1@12	14.21	13.45	13.47	14.10	13.35	13.52
		1@24	13.62	12.81	12.62	13.53	12.74	12.67
		12@0	13.61	13.20	13.29	13.59	13.17	13.32
		12@7	13.61	13.19	13.30	13.59	13.17	13.32
		12@13	13.89	13.14	13.11	13.86	13.11	13.15
		25@0	13.80	13.13	13.21	13.80	13.13	13.18
Band	Bandwidth (MHz)	RB	20800	21100	21400	20800	21100	21400
			2505 MHz	2535 MHz	2565 MHz	2505 MHz	2535 MHz	2565 MHz
7	10	1@0	12.92	12.52	13.67	12.93	12.53	13.49
		1@25	14.17	13.37	13.78	14.17	13.36	13.61
		1@49	13.94	12.88	12.51	13.91	12.89	12.33
		25@0	13.65	13.19	13.89	13.62	13.15	13.87
		25@12	13.65	13.19	13.89	13.62	13.15	13.87
		25@25	14.34	13.18	13.21	14.29	13.16	13.22
		50@0	13.99	13.11	13.56	13.97	13.09	13.57
Band	Bandwidth (MHz)	RB	20825	21100	21375	20825	21100	21375
			2507.5 MHz	2535 MHz	2562.5 MHz	2507.5 MHz	2535 MHz	2562.5 MHz
7	15	1@0	12.84	12.67	14.03	12.83	12.66	14.18
		1@37	14.53	13.33	14.07	14.52	13.33	14.19
		1@74	13.94	12.96	12.34	13.95	12.97	12.49
		36@0	14.32	13.18	13.85	14.31	13.18	13.85
		36@20	14.31	13.18	13.85	14.31	13.18	13.84
		36@39	14.31	13.18	13.85	14.31	13.18	13.84
		75@0	14.31	13.18	13.84	14.24	13.14	13.82
Band	Bandwidth (MHz)	RB	20850	21100	21350	20850	21100	21350
			2510 MHz	2535 MHz	2560 MHz	2510 MHz	2535 MHz	2560 MHz
7	20	1@0	10.88	11.01	12.09	10.77	10.90	12.16
		1@49	14.61	13.08	13.29	13.48	11.97	13.41
		1@99	12.55	12.05	11.12	12.44	11.89	11.26
		50@0	14.10	13.19	14.20	14.07	13.20	14.18
		50@24	14.09	13.20	14.18	14.07	13.20	14.17
		50@50	14.22	13.41	13.58	14.35	13.40	13.60
		100@0	14.39	13.35	14.10	14.36	13.35	14.13

➤ **LTE Band 12 (Power Reduction)**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	23017	23095	23173	23017	23095	23173
			699.7 MHz	707.5 MHz	715.3 MHz	699.7 MHz	707.5 MHz	715.3 MHz
12	1.4	1@0	13.69	13.91	14.08	13.67	13.86	13.86
		1@3	13.84	13.90	14.04	13.88	13.93	13.89
		1@5	13.78	13.84	13.99	13.78	13.81	13.83
		3@0	13.68	13.80	13.96	13.54	13.66	13.79
		3@1	13.68	13.81	13.96	13.54	13.66	13.78
		3@3	13.76	13.78	13.88	13.66	13.64	13.71
		6@0	13.80	13.78	13.97	13.87	13.82	13.80
Band	Bandwidth (MHz)	RB	23025	23095	23165	23025	23095	23165
			700.5 MHz	707.5 MHz	714.5 MHz	700.5 MHz	707.5 MHz	714.5 MHz
12	3	1@0	13.49	13.78	13.77	13.55	13.66	13.53
		1@8	13.95	14.01	14.22	14.05	13.91	13.92
		1@14	13.79	13.71	13.84	13.85	13.56	13.57
		8@0	13.76	13.86	13.98	13.85	13.87	14.03
		8@4	13.76	13.86	13.99	13.85	13.87	14.03
		8@7	13.90	13.77	14.06	13.96	13.81	14.02
		15@0	13.82	13.87	13.89	13.91	13.82	13.82
Band	Bandwidth (MHz)	RB	23035	23095	23155	23035	23095	23155
			701.5 MHz	707.5 MHz	713.5 MHz	701.5 MHz	707.5 MHz	713.5 MHz
12	5	1@0	13.17	13.40	13.19	13.13	13.43	13.09
		1@12	14.06	14.01	14.12	14.04	14.14	14.07
		1@24	13.48	13.25	13.45	13.41	13.34	13.33
		12@0	13.61	13.76	13.63	13.66	13.86	13.68
		12@7	13.61	13.75	13.63	13.65	13.85	13.69
		12@13	13.80	13.63	13.95	13.83	13.72	13.95
		25@0	13.71	13.75	13.75	13.77	13.77	13.81
Band	Bandwidth (MHz)	RB	23060	23095	23130	23060	23095	23130
			704 MHz	707.5 MHz	711 MHz	704 MHz	707.5 MHz	711 MHz
12	10	1@0	13.05	13.22	13.24	13.13	13.14	13.00
		1@25	14.24	13.97	13.79	14.17	13.88	13.56
		1@49	13.19	13.16	13.29	13.23	13.04	12.99
		25@0	13.72	13.76	13.63	13.73	13.81	13.67
		25@12	13.71	13.75	13.63	13.73	13.81	13.67
		25@25	13.81	13.61	13.71	13.82	13.65	13.76
		50@0	13.71	13.62	13.68	13.73	13.67	13.70

➤ **LTE Band 13 (Power Reduction)**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	23205	23230	23255	23205	23230	23255
			779.5 MHz	782 MHz	784.5 MHz	779.5 MHz	782 MHz	784.5 MHz
13	5	1@0	12.79	13.10	13.23	12.96	13.05	13.24
		1@12	13.29	13.11	13.25	13.16	13.46	13.10
		1@24	13.17	13.09	13.15	13.02	13.02	12.80
		12@0	13.13	13.18	13.13	13.41	13.10	13.13
		12@7	13.21	13.18	13.23	13.39	13.10	13.14
		12@13	13.16	13.13	13.12	13.36	13.09	13.13
		25@0	13.18	13.11	13.09	13.27	13.38	13.22
Band	Bandwidth (MHz)	RB	--	23230	--	--	23230	--
			--	782 MHz	--	--	782 MHz	--
13	10	1@0	--	12.94	--	--	13.07	--
		1@25	--	13.42	--	--	13.17	--
		1@49	--	13.50	--	--	13.13	--
		25@0	--	13.20	--	--	13.30	--
		25@12	--	13.20	--	--	13.30	--
		25@25	--	13.14	--	--	13.23	--
		50@0	--	13.12	--	--	13.04	--

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

➤ **LTE Band 14 (Power Reduction)**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	5305	5330	5355	5305	5330	5355
			790.5 MHz	793 MHz	795.5 MHz	790.5 MHz	793 MHz	795.5 MHz
17	5	1@0	13.76	13.36	13.20	13.67	13.31	12.97
		1@12	14.18	13.86	14.47	13.99	13.85	14.35
		1@24	13.19	13.61	13.27	13.01	13.60	13.09
		12@0	13.95	13.65	13.68	13.83	13.61	13.60
		12@7	13.94	13.65	13.68	13.82	13.61	13.61
		12@13	13.75	13.67	14.15	13.64	13.64	14.13
		25@0	13.79	13.75	13.89	13.69	13.64	13.85
Band	Bandwidth (MHz)	RB	--	5330	--	--	5330	--
			--	793 MHz	--	--	793 MHz	--
17	10	1@0	--	13.45	--	--	13.47	--
		1@25	--	14.52	--	--	13.76	--
		1@49	--	13.42	--	--	13.36	--
		25@0	--	13.75	--	--	13.62	--
		25@12	--	13.75	--	--	13.62	--
		25@25	--	13.88	--	--	13.78	--
		50@0	--	13.91	--	--	13.82	--

➤ **LTE Band 17 (Power Reduction)**

Conducted Power(dBm)								
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	23755	23790	23825	23755	23790	23825
			706.5 MHz	710 MHz	713.5 MHz	706.5 MHz	710 MHz	713.5 MHz
17	5	1@0	13.65	13.52	13.62	13.61	13.57	13.52
		1@12	14.17	13.91	14.16	14.04	13.98	14.16
		1@24	13.59	13.62	13.55	13.48	13.68	13.45
		12@0	13.82	13.65	13.83	13.87	13.68	13.84
		12@7	13.85	13.65	13.85	13.89	13.70	13.85
		12@13	13.89	13.71	13.86	13.76	13.81	13.86
		25@0	13.88	13.78	13.88	13.88	13.73	13.90
Band	Bandwidth (MHz)	RB	23780	23790	23800	23780	23790	23800
			709 MHz	710 MHz	711 MHz	709 MHz	710 MHz	711 MHz
17	10	1@0	13.90	14.06	14.01	13.92	13.92	13.70
		1@25	13.91	13.98	14.25	13.94	13.86	13.78
		1@49	13.96	14.14	13.87	13.97	13.96	13.58
		25@0	14.01	13.98	13.95	13.95	13.96	13.95
		25@12	14.02	13.99	13.94	13.96	13.97	13.94
		25@25	13.88	13.98	14.04	13.87	13.99	14.06
		50@0	14.01	13.98	13.99	14.00	14.00	13.98

➤ **LTE Band 38 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	37775	38000	38225	37775	38000	38225
			2572.5 MHz	2595 MHz	2617.5 MHz	2572.5 MHz	2595 MHz	2617.5 MHz
38	5	1@0	14.33	13.68	13.44	14.46	13.72	13.81
		1@12	14.88	14.33	14.11	15.03	14.36	14.48
		1@24	14.22	13.61	13.48	14.38	13.66	13.82
		12@0	14.78	14.12	13.94	14.82	14.07	13.94
		12@7	14.77	14.12	13.95	14.82	14.07	13.94
		12@13	14.72	14.08	13.99	14.75	14.03	13.94
		25@0	14.80	14.12	14.04	14.80	14.07	14.04
Band	Bandwidth (MHz)	RB	37800	38000	38200	37800	38000	38200
			2575 MHz	2595 MHz	2615 MHz	2575 MHz	2595 MHz	2615 MHz
38	10	1@0	14.26	13.69	13.37	14.44	13.87	13.02
		1@25	14.88	14.34	14.15	15.09	14.53	13.84
		1@49	13.99	13.49	13.38	14.22	13.67	13.04
		25@0	14.73	14.13	13.91	14.77	14.18	13.84
		25@12	14.73	14.13	13.92	14.77	14.17	13.84
		25@25	14.62	14.05	14.01	14.69	14.09	13.99
		50@0	14.74	14.10	13.98	14.72	14.08	13.99
Band	Bandwidth (MHz)	RB	37825	38000	38175	37825	38000	38175
			2577.5 MHz	2595 MHz	2612.5 MHz	2577.5 MHz	2595 MHz	2612.5 MHz
38	15	1@0	14.18	13.67	13.36	14.36	13.86	13.14
		1@37	14.85	14.30	14.20	15.06	14.49	13.95
		1@74	13.76	13.33	13.33	13.96	13.51	13.11
		36@0	14.59	14.08	13.93	14.58	14.08	13.93
		36@20	14.58	14.08	13.93	14.58	14.08	13.93
		36@39	14.58	14.07	13.93	14.57	14.08	13.93
		75@0	14.57	14.07	13.93	14.59	14.06	13.94
Band	Bandwidth (MHz)	RB	37850	38000	38150	37850	38000	38150
			2580 MHz	2595 MHz	2610 MHz	2580 MHz	2595 MHz	2610 MHz
38	20	1@0	14.83	13.74	13.28	11.75	11.48	11.32
		1@49	15.12	14.20	13.85	13.05	12.72	12.87
		1@99	14.23	13.96	13.93	11.87	11.64	11.95
		50@0	14.73	14.16	13.91	14.74	14.14	13.91
		50@24	14.71	14.15	13.91	14.73	14.13	13.90
		50@50	14.40	13.95	13.86	14.44	13.91	13.89
		100@0	14.53	14.06	13.92	14.54	14.06	13.87

➤ **LTE Band 66 (Power Reduction)**

			Conducted Power(dBm)					
Modulation			QPSK			16QAM		
Band	Bandwidth (MHz)	RB	131979	132322	132665	131979	132322	132665
			1710.7 MHz	1745 MHz	1779.3 MHz	1710.7 MHz	1745 MHz	1779.3 MHz
66	1.4	1@0	15.70	15.25	16.14	15.58	15.07	15.88
		1@3	15.74	15.26	16.18	15.67	15.14	15.92
		1@5	15.54	15.30	16.11	15.45	15.16	15.85
		3@0	15.64	15.22	16.09	15.43	15.10	15.87
		3@1	15.65	15.23	16.08	15.43	15.11	15.86
		3@3	15.57	15.31	16.09	15.37	15.18	15.84
		6@0	15.64	15.22	16.07	15.62	15.10	16.08
Band	Bandwidth (MHz)	RB	131987	132322	132657	131987	132322	132657
			1711.5 MHz	1745 MHz	1778.5 MHz	1711.5 MHz	1745 MHz	1778.5 MHz
66	3	1@0	15.53	15.13	16.03	15.51	14.96	15.73
		1@8	15.65	15.34	16.16	15.66	15.19	15.90
		1@14	15.50	15.17	15.95	15.49	14.98	15.70
		8@0	15.67	15.25	16.04	15.65	15.26	16.03
		8@4	15.67	15.25	16.03	15.65	15.26	16.02
		8@7	15.58	15.27	16.00	15.57	15.25	16.00
		15@0	15.67	15.20	15.97	15.66	15.14	15.90
Band	Bandwidth (MHz)	RB	131997	132322	132647	131997	132322	132647
			1712.5 MHz	1745 MHz	1777.5 MHz	1712.5 MHz	1745 MHz	1777.5 MHz
66	5	1@0	15.23	14.80	15.76	15.10	14.86	15.63
		1@12	15.72	15.31	16.28	15.62	15.39	16.18
		1@24	15.16	14.85	15.67	15.05	14.92	15.59
		12@0	15.48	15.17	15.94	15.44	15.25	15.97
		12@7	15.49	15.18	15.94	15.45	15.26	15.96
		12@13	15.36	15.14	15.97	15.32	15.20	16.00
		25@0	15.43	15.23	16.01	15.43	15.21	16.05
Band	Bandwidth (MHz)	RB	132022	132322	132622	132022	132322	132622
			1715 MHz	1745 MHz	1775 MHz	1715 MHz	1745 MHz	1775 MHz
66	10	1@0	14.93	14.52	15.51	14.90	14.39	15.21
		1@25	15.62	15.33	16.26	15.62	15.19	16.00
		1@49	14.69	14.66	15.32	14.72	14.49	15.07
		25@0	15.40	15.07	15.88	15.35	15.08	15.90
		25@12	15.39	15.07	15.87	15.34	15.07	15.90
		25@25	15.22	15.09	15.80	15.23	15.11	15.83
		50@0	15.27	15.01	15.84	15.23	15.05	15.86
Band	Bandwidth (MHz)	RB	132047	132322	132597	132047	132322	132597
			1717.5 MHz	1745 MHz	1772.5 MHz	1717.5 MHz	1745 MHz	1772.5 MHz
66	15	1@0	14.51	14.01	15.26	14.46	14.18	14.98
		1@37	15.37	15.17	16.27	15.42	15.35	16.01
		1@74	14.22	14.25	15.04	14.27	14.43	14.75
		36@0	15.13	14.96	16.21	15.13	14.97	16.20
		36@20	15.14	14.97	16.20	15.14	14.97	16.20
		36@39	15.14	14.98	16.19	15.14	14.98	16.19
		75@0	15.14	14.98	16.18	15.15	15.02	16.20
Band	Bandwidth (MHz)	RB	132072	132322	132572	132072	132322	132572
			1720 MHz	1745 MHz	1770 MHz	1720 MHz	1745 MHz	1770 MHz
66	20	1@0	14.38	15.86	14.74	14.22	13.98	14.55
		1@49	15.55	15.30	16.30	15.46	15.44	16.13
		1@99	14.35	14.65	15.00	14.27	14.77	14.81
		50@0	15.22	14.93	15.89	15.17	14.96	15.96
		50@24	15.20	14.94	15.88	15.16	14.96	15.96
		50@50	15.16	15.15	15.79	15.19	15.15	15.84
		100@0	15.25	14.97	15.96	15.23	15.00	15.99

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

4.4.4. Conducted Power of WLAN

The measuring conducted average power is shown as below.

Band	Mode	Channel	Frequency (MHz)	Average Power (dBm)
2.4GHz	802.11b	1	2412	12.02
		6	2437	11.67
		11	2462	12.25
		12	2467	8.19
		13	2472	6.03
	802.11g	1	2412	10.68
		6	2437	10.30
		11	2462	10.83
		12	2467	7.84
		13	2472	5.62
	802.11n-HT20	1	2412	10.51
		6	2437	10.16
		11	2462	10.64
		12	2467	7.75
		13	2472	5.56
	802.11n-HT40	3	2422	10.42
		6	2437	10.28
		9	2452	10.39
		10	2457	8.13
		11	2462	8.42

Mode	Band	Channel	Freq. (MHz)	Average Power (dBm)
IEEE 802.11a	U-NII-1	36	5180	10.86
		44	5220	10.72
		48	5240	10.33
	U-NII-2A	52	5260	10.11
		60	5300	9.74
		64	5320	9.85
	U-NII-2C	100	5500	9.41
		116	5580	10.21
		120	5600	10.32
		140	5700	10.38
		144	5720	10.28
	U-NII-3	149	5745	9.58
		157	5785	9.24
		165	5825	8.89
IEEE 802.11n-HT20	U-NII-1	36	5180	9.99
		44	5220	9.82
		48	5240	9.49
	U-NII-2A	52	5260	9.25
		60	5300	8.84
		64	5320	8.77
	U-NII-2C	100	5500	8.47
		116	5580	9.20
		120	5600	9.38
		140	5700	9.51
		144	5720	9.34
	U-NII-3	149	5745	8.74
		157	5785	8.26
		165	5825	7.76
	U-NII-1	38	5190	10.68

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Mode	Band	Channel	Freq. (MHz)	Average Power (dBm)
IEEE 802.11n-HT40	U-NII-2A	46	5230	10.50
		54	5270	9.94
		62	5310	9.54
	U-NII-2C	102	5510	9.34
		110	5550	9.74
		118	5590	10.03
		134	5670	10.45
		142	5710	10.28
	U-NII-3	151	5755	9.40
		159	5795	8.92
IEEE 802.11ac-VHT20	U-NII-1	36	5180	10.01
		44	5220	9.84
		48	5240	9.52
	U-NII-2A	52	5260	9.29
		60	5300	9.87
		64	5320	8.78
	U-NII-2C	100	5500	8.46
		116	5580	9.21
		120	5600	9.41
		140	5700	9.51
		144	5720	9.36
	U-NII-3	149	5745	8.73
		157	5785	8.25
		165	5825	7.73
IEEE 802.11ac-VHT40	U-NII-1	38	5190	10.69
		46	5230	10.48
	U-NII-2A	54	5270	9.94
		62	5310	9.53
	U-NII-2C	102	5510	9.31
		110	5550	9.71
		118	5590	10.01
		134	5670	10.42
		142	5710	10.26
	U-NII-3	151	5755	9.40
		159	5795	8.91
IEEE 802.11ac-VHT80	U-NII-1	42	5210	10.30
	U-NII-2A	58	5290	9.42
	U-NII-2C	106	5530	9.09
		122	5610	9.83
		138	5690	9.74
	U-NII-3	155	5775	8.91

4.4.5. Conducted Power of BT

Mode	Modulation	Channel	Frequency (MHz)	Average Power (dBm)
BR + EDR	GFSK	0	2402	4.31
		39	2441	4.33
		78	2480	4.34
	$\pi/4$ -DQPSK	0	2402	2.32
		39	2441	2.29
		78	2480	2.34
	8-DPSK	0	2402	2.29
		39	2441	2.32
		78	2480	2.40

Mode	Modulation	Channel	Frequency (MHz)	Average Power (dBm)
LE	GFSK	0	2402	3.05
		19	2440	3.68
		39	2480	3.07

4.5. SAR TEST EXCLUSION EVALUATIONS

4.5.1. Standalone SAR Test Exclusion Considerations

According to KDB 447498 D04, SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Max. Power

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?
GSM 850	25.0	316.23	0	0.00	Yes	2.988	115.38	Yes	15.55	1209.81	No	0	0.00	Yes	15.286	1180.66	No
PCS 1900	21.5	165.96	0	0.00	Yes	2.988	91.17	Yes	15.55	1921.89	No	0	0.00	Yes	15.286	1862.03	No
WCDMA Band II	23.0	234.42	0	0.00	Yes	2.988	91.22	Yes	15.55	1922.01	No	0	0.00	Yes	15.286	1862.15	No
WCDMA Band IV	25.0	363.08	0	0.00	Yes	2.988	94.46	Yes	15.55	1930.93	No	0	0.00	Yes	15.286	1871.38	No
WCDMA Band V	24.0	251.19	0	0.00	Yes	2.988	115.45	Yes	15.55	1207.19	No	0	0.00	Yes	15.286	1178.13	No
LTE Band 2	24.5	336.51	0	0.00	Yes	2.988	91.18	Yes	15.55	1921.92	No	0	0.00	Yes	15.286	1862.05	No
LTE Band 5	24.5	323.59	0	0.00	Yes	2.988	94.43	Yes	15.55	1930.83	No	0	0.00	Yes	15.286	1871.28	No
LTE Band 4	24.0	251.19	0	0.00	Yes	2.988	115.40	Yes	15.55	1209.22	No	0	0.00	Yes	15.286	1180.08	No
LTE Band 7	24.0	371.54	0	0.00	Yes	2.988	80.69	Yes	15.55	1891.06	No	0	0.00	Yes	15.286	1830.14	No
LTE Band 12	24.0	251.19	0	0.00	Yes	2.988	120.19	Yes	15.55	1048.54	No	0	0.00	Yes	15.286	1025.22	No
LTE Band 13	23.5	223.87	0	0.00	Yes	2.988	117.57	Yes	15.55	1132.70	No	0	0.00	Yes	15.286	1106.37	No
LTE Band 14	24.0	251.19	0	0.00	Yes	2.988	117.18	Yes	15.55	1145.96	No	0	0.00	Yes	15.286	1119.15	No
LTE Band 17	24.0	251.19	0	0.00	Yes	2.988	120.26	Yes	15.55	1046.33	No	0	0.00	Yes	15.286	1023.10	No
LTE Band 38	24.0	380.19	0	0.00	Yes	2.988	80.05	Yes	15.55	1889.07	No	0	0.00	Yes	15.286	1828.08	No
LTE Band 66	25.0	363.08	0	0.00	Yes	2.988	93.88	Yes	15.55	1929.34	No	0	0.00	Yes	15.286	1869.73	No
WLAN 2.4G	12.5	26.61	0	0.00	Yes	14.6	1680.64	No	8.968	664.45	No	0	0.00	Yes	14.945	1757.07	No
WLAN 5.2G&5.3G	11.5	18.41	0	0.00	Yes	14.6	1596.53	No	8.968	582.95	No	0	0.00	Yes	14.945	1675.50	No
WLAN 5.6G	11.0	16.41	0	0.00	Yes	14.6	1587.00	No	8.968	574.12	No	0	0.00	Yes	14.945	1666.24	No
WLAN 5.8G	11.0	16.41	0	0.00	Yes	14.6	1585.03	No	8.968	572.30	No	0	0.00	Yes	14.945	1664.32	No
Bluetooth	5.0	4.73	0	0.00	Yes	14.6	1680.27	No	8.968	664.07	No	0	0.00	Yes	14.945	1756.71	No

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Power Reduction

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?	Ant. to Surface (cm)	Calculated Result (mW)	Require SAR Testing?
GSM 850	14.0	25.12	0	0.00	Yes	2.988	115.38	No	15.55	1209.81	No	0	0.00	Yes	15.286	1180.66	No
PCS 1900	12.5	20.89	0	0.00	Yes	2.988	91.17	No	15.55	1921.89	No	0	0.00	Yes	15.286	1862.03	No
WCDMA Band II	15.5	41.69	0	0.00	Yes	2.988	91.22	No	15.55	1922.01	No	0	0.00	Yes	15.286	1862.15	No
WCDMA Band IV	15.5	40.74	0	0.00	Yes	2.988	94.46	No	15.55	1930.93	No	0	0.00	Yes	15.286	1871.38	No
WCDMA Band V	14.5	28.18	0	0.00	Yes	2.988	115.45	No	15.55	1207.19	No	0	0.00	Yes	15.286	1178.13	No
LTE Band 2	15.0	37.76	0	0.00	Yes	2.988	91.18	No	15.55	1921.92	No	0	0.00	Yes	15.286	1862.05	No
LTE Band 5	15.0	36.31	0	0.00	Yes	2.988	94.43	No	15.55	1930.83	No	0	0.00	Yes	15.286	1871.28	No
LTE Band 4	14.5	28.18	0	0.00	Yes	2.988	115.40	No	15.55	1209.22	No	0	0.00	Yes	15.286	1180.08	No
LTE Band 7	15.0	46.77	0	0.00	Yes	2.988	80.69	No	15.55	1891.06	No	0	0.00	Yes	15.286	1830.14	No
LTE Band 12	14.5	28.18	0	0.00	Yes	2.988	120.19	No	15.55	1048.54	No	0	0.00	Yes	15.286	1025.22	No
LTE Band 13	14.0	25.12	0	0.00	Yes	2.988	117.57	No	15.55	1132.70	No	0	0.00	Yes	15.286	1106.37	No
LTE Band 14	15.0	31.62	0	0.00	Yes	2.988	117.18	No	15.55	1145.96	No	0	0.00	Yes	15.286	1119.15	No
LTE Band 17	14.5	28.18	0	0.00	Yes	2.988	120.26	No	15.55	1046.33	No	0	0.00	Yes	15.286	1023.10	No
LTE Band 38	15.5	53.70	0	0.00	Yes	2.988	80.05	No	15.55	1889.07	No	0	0.00	Yes	15.286	1828.08	No
LTE Band 66	17.0	57.54	0	0.00	Yes	2.988	93.88	No	15.55	1929.34	No	0	0.00	Yes	15.286	1869.73	No

Note:

- 1) Based on the antenna location shown on appendix D of this report for SAR test exclusion.
- 2) The 1 mW Blanket Exemption applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

4.5.2. Estimated SAR Calculation

According to KDB 447498 D04, when an antenna qualifies for test exemption in single transmitter/antenna mode, its actual SAR value may not be available, because it was not required to be measured. In this case, the SAR contribution of that antenna to simultaneous transmission must be estimated relative to the SAR or MPE based exemption criteria for the applicable terms in the equation of § 1.1307(b)(3)(ii)(B) (see also Appendix C), by multiplying the corresponding ratio by the SAR limit of 1.6 W/kg for 1-g SAR. This is referred to as estimated SAR.

For instance, a given antenna may qualify for a SAR-based exemption according to Section B.4, with $P_{ant} < P_{th}$, where P_{ant} is maximum time-averaged power or effective radiated power (ERP), whichever is greater, and P_{th} is defined in Formula (B.2). Then, per the preceding paragraph, the estimated SAR is computed as $SAR_{est} = 1.6 * P_{ant} / P_{th}$ [W/kg].

If RF exposure testing requirements for a specific device are covered in a KDB publication, those requirements must be satisfied before applying any SAR test exemption provisions. For example, this is the case for handheld PTT two-way radios, handsets, laptops, and tablets, etc.

Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

Power Reduction Estimated SAR

Mode / Band	Frequency (GHz)	P_{ant} (mW)	Ant. to Surface (cm)	P_{th} (mW)	Test Position	Estimated 10g SAR (W/kg)
GSM 850	848.8	25.12	15.55	1209.81	Right Side	0.033
PCS 1900	1909.8	20.89	15.55	1921.89	Right Side	0.017
WCDMA Band II	1907.6	41.69	15.55	1922.01	Right Side	0.035
WCDMA Band IV	1752.6	40.74	15.55	1930.93	Right Side	0.034
WCDMA Band V	846.6	28.18	15.55	1207.19	Right Side	0.037
LTE Band 2	1909.3	37.76	15.55	1921.92	Right Side	0.031
LTE Band 5	1754.3	36.31	15.55	1930.83	Right Side	0.030
LTE Band 4	848.3	28.18	15.55	1209.22	Right Side	0.037
LTE Band 7	2567.5	46.77	15.55	1891.06	Right Side	0.040
LTE Band 12	715.3	28.18	15.55	1048.54	Right Side	0.043
LTE Band 13	784.5	25.12	15.55	1132.70	Right Side	0.035
LTE Band 14	795.5	31.62	15.55	1145.96	Right Side	0.044
LTE Band 17	713.5	28.18	15.55	1046.33	Right Side	0.043
LTE Band 38	2617.5	53.70	15.55	1889.07	Right Side	0.045
LTE Band 66	1779.3	57.54	15.55	1929.34	Right Side	0.048
SM 850	848.8	25.12	15.286	1180.66	Bottom Side	0.034
PCS 1900	1909.8	20.89	15.286	1862.03	Bottom Side	0.018
WCDMA Band II	1907.6	41.69	15.286	1862.15	Bottom Side	0.036
WCDMA Band IV	1752.6	40.74	15.286	1871.38	Bottom Side	0.035
WCDMA Band V	846.6	28.18	15.286	1178.13	Bottom Side	0.038
LTE Band 2	1909.3	37.76	15.286	1862.05	Bottom Side	0.032
LTE Band 5	1754.3	36.31	15.286	1871.28	Bottom Side	0.031
LTE Band 4	848.3	28.18	15.286	1180.08	Bottom Side	0.038
LTE Band 7	2567.5	46.77	15.286	1830.14	Bottom Side	0.041
LTE Band 12	715.3	28.18	15.286	1025.22	Bottom Side	0.044
LTE Band 13	784.5	25.12	15.286	1106.37	Bottom Side	0.036
LTE Band 14	795.5	31.62	15.286	1119.15	Bottom Side	0.045
LTE Band 17	713.5	28.18	15.286	1023.10	Bottom Side	0.044
LTE Band 38	2617.5	53.70	15.286	1828.08	Bottom Side	0.047
LTE Band 66	1779.3	57.54	15.286	1869.73	Bottom Side	0.049

Max. Power Estimated SAR

Mode / Band	Frequency (GHz)	P _{ant} (mW)	Ant. to Surface (cm)	P _{th} (mW)	Test Position	Estimated 10g SAR (W/kg)
GSM 850	848.8	316.23	15.55	1209.81	Right Side	0.418
PCS 1900	1909.8	165.96	15.55	1921.89	Right Side	0.138
WCDMA Band II	1907.6	234.42	15.55	1922.01	Right Side	0.195
WCDMA Band IV	1752.6	363.08	15.55	1930.93	Right Side	0.301
WCDMA Band V	846.6	251.19	15.55	1207.19	Right Side	0.333
LTE Band 2	1909.3	336.51	15.55	1921.92	Right Side	0.280
LTE Band 5	1754.3	323.59	15.55	1930.83	Right Side	0.268
LTE Band 4	848.3	251.19	15.55	1209.22	Right Side	0.332
LTE Band 7	2567.5	371.54	15.55	1891.06	Right Side	0.314
LTE Band 12	715.3	251.19	15.55	1048.54	Right Side	0.383
LTE Band 13	784.5	223.87	15.55	1132.70	Right Side	0.316
LTE Band 14	795.5	251.19	15.55	1145.96	Right Side	0.351
LTE Band 17	713.5	251.19	15.55	1046.33	Right Side	0.384
LTE Band 38	2617.5	380.19	15.55	1889.07	Right Side	0.322
LTE Band 66	1779.3	363.08	15.55	1929.34	Right Side	0.301
WLAN 2.4G	2472	26.61	8.968	664.45	Right Side	0.064
WLAN 5.2G&5.3G	5320	18.41	8.968	582.95	Right Side	0.051
WLAN 5.6G	5720	16.41	8.968	574.12	Right Side	0.046
WLAN 5.8G	5825	16.41	8.968	572.30	Right Side	0.046
Bluetooth	2480	4.73	8.968	664.07	Right Side	0.011
GSM 850	848.8	316.23	15.286	1180.66	Bottom Side	0.429
PCS 1900	1909.8	165.96	15.286	1862.03	Bottom Side	0.143
WCDMA Band II	1907.6	234.42	15.286	1862.15	Bottom Side	0.201
WCDMA Band IV	1752.6	363.08	15.286	1871.38	Bottom Side	0.310
WCDMA Band V	846.6	251.19	15.286	1178.13	Bottom Side	0.341
LTE Band 2	1909.3	336.51	15.286	1862.05	Bottom Side	0.289
LTE Band 5	1754.3	323.59	15.286	1871.28	Bottom Side	0.277
LTE Band 4	848.3	251.19	15.286	1180.08	Bottom Side	0.341
LTE Band 7	2567.5	371.54	15.286	1830.14	Bottom Side	0.325
LTE Band 12	715.3	251.19	15.286	1025.22	Bottom Side	0.392
LTE Band 13	784.5	223.87	15.286	1106.37	Bottom Side	0.324
LTE Band 14	795.5	251.19	15.286	1119.15	Bottom Side	0.359
LTE Band 17	713.5	251.19	15.286	1023.10	Bottom Side	0.393
LTE Band 38	2617.5	380.19	15.286	1828.08	Bottom Side	0.333
LTE Band 66	1779.3	363.08	15.286	1869.73	Bottom Side	0.311
WLAN 2.4G	2472	26.61	14.945	1757.07	Bottom Side	0.024
WLAN 5.2G&5.3G	5320	18.41	14.945	1675.50	Bottom Side	0.018
WLAN 5.6G	5720	16.41	14.945	1666.24	Bottom Side	0.016
WLAN 5.8G	5825	16.41	14.945	1664.32	Bottom Side	0.016
Bluetooth	2480	4.73	14.945	1756.71	Bottom Side	0.004
WLAN 2.4G	2472	26.61	14.6	1680.64	Left Side	0.025
WLAN 5.2G&5.3G	5320	18.41	14.6	1596.53	Left Side	0.018
WLAN 5.6G	5720	16.41	14.6	1587.00	Left Side	0.017
WLAN 5.8G	5825	16.41	14.6	1585.03	Left Side	0.017
Bluetooth	2480	4.73	14.6	1680.27	Left Side	0.005

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

4.6. SAR TESTING RESULTS

4.6.1. SAR Test Reduction Considerations

KDB 447498 D01 General RF Exposure Guidance

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- a) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- b) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- c) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 941225 D01 3G SAR Procedures

a) GSM SAR Test Reduction

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

b) 3G SAR Test Reduction Procedure

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

KDB 941225 D05 SAR for LTE Devices

a) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

b) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

c) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

d) Others channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

KDB 248227 D01 Wi-Fi SAR

- a) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- b) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- c) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- d) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

4.6.2. SAR Results for Body Exposure Condition

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	RB#	RB Offset	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
1	GSM 850	GPRS12	Rear Face	0	251	-	-	with	17.0	16.41	-0.04	0.0544	0.0189	1.15	0.062
	GSM 850	GPRS12	Top Side	0	251	-	-	with	17.0	16.41	-0.12	0.0769	0.0268	1.15	0.088
	GSM 850	GPRS10	Rear Face	1	128	-	-	without	31.0	30.63	0.02	0.401	0.243	1.09	0.437
	GSM 850	GPRS10	Left Side	0	128	-	-	without	31.0	30.63	0.02	0.276	0.167	1.09	0.301
	GSM 850	GPRS10	Top Side	1.5	128	-	-	without	31.0	30.63	0.08	0.236	0.149	1.09	0.257
2	PCS 1900	GPRS12	Rear Face	0	512	-	-	with	15.5	14.88	0.12	0.313	0.133	1.15	0.361
	PCS 1900	GPRS12	Top Side	0	512	-	-	with	15.5	14.88	0.04	0.293	0.127	1.15	0.338
	PCS 1900	GPRS11	Rear Face	1	512	-	-	without	26.0	25.39	0.06	0.415	0.233	1.15	0.478
	PCS 1900	GPRS11	Left Side	0	512	-	-	without	26.0	25.39	0.05	0.184	0.0937	1.15	0.212
	PCS 1900	GPRS11	Top Side	1.5	512	-	-	without	26.0	25.39	0.08	0.21	0.127	1.15	0.242
3	WCDMA BAND II	RMC12.2K	Rear Face	0	9262	-	-	with	15.5	14.82	0.13	0.299	0.138	1.17	0.350
	WCDMA BAND II	RMC12.2K	Top Side	0	9262	-	-	with	15.5	14.82	0.05	0.201	0.0846	1.17	0.235
	WCDMA BAND II	RMC12.2K	Rear Face	1	9262	-	-	without	23.0	22.60	0.10	0.624	0.35	1.10	0.684
	WCDMA BAND II	RMC12.2K	Left Side	0	9262	-	-	without	23.0	22.60	0.08	0.263	0.132	1.10	0.288
	WCDMA BAND II	RMC12.2K	Top Side	1.5	9262	-	-	without	23.0	22.60	0.04	0.302	0.183	1.10	0.331
4	WCDMA BAND IV	RMC12.2K	Rear Face	0	1312	-	-	with	15.5	14.91	0.15	0.388	0.18	1.15	0.444
	WCDMA BAND IV	RMC12.2K	Top Side	0	1312	-	-	with	15.5	14.91	0.18	0.172	0.089	1.15	0.197
	WCDMA BAND IV	RMC12.2K	Rear Face	1	1513	-	-	without	25.0	24.36	0.06	0.443	0.264	1.16	0.513
	WCDMA BAND IV	RMC12.2K	Left Side	0	1513	-	-	without	25.0	24.36	0.03	0.173	0.0911	1.16	0.200
	WCDMA BAND IV	RMC12.2K	Top Side	1.5	1513	-	-	without	25.0	24.36	0.04	0.293	0.175	1.16	0.340
5	WCDMA BAND V	RMC12.2K	Rear Face	0	4132	-	-	with	14.5	14.20	0.05	0.0909	0.0492	1.07	0.097
	WCDMA BAND V	RMC12.2K	Top Side	0	4132	-	-	with	14.5	14.20	0.03	0.117	0.0592	1.07	0.125
	WCDMA BAND V	RMC12.2K	Rear Face	1	4233	-	-	without	24.0	23.27	0.13	0.318	0.2	1.18	0.376
	WCDMA BAND V	RMC12.2K	Left Side	0	4233	-	-	without	24.0	23.27	0.04	0.219	0.115	1.18	0.259
	WCDMA BAND V	RMC12.2K	Top Side	1.5	4233	-	-	without	24.0	23.27	0.09	0.359	0.222	1.18	0.425
	LTE BAND 2	QPSK20M	Rear Face	0	18700	1	49	with	15.0	14.33	0.07	0.496	0.231	1.17	0.579
	LTE BAND 2	QPSK20M	Top Side	0	18700	1	49	with	15.0	14.33	0.09	0.374	0.158	1.17	0.436

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	RB#	RB Offset	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
6	LTE BAND 2	QPSK20M	Rear Face	0	18700	50	0	with	14.5	13.99	0.08	0.383	0.178	1.12	0.431
	LTE BAND 2	QPSK20M	Top Side	0	18700	50	0	with	14.5	13.99	0.17	0.228	0.0965	1.12	0.256
	LTE BAND 2	QPSK20M	Rear Face	1	18700	1	49	without	24.5	23.96	-0.02	0.654	0.362	1.13	0.741
	LTE BAND 2	QPSK20M	Left Side	0	18700	1	49	without	24.5	23.96	0.13	0.249	0.126	1.13	0.282
	LTE BAND 2	QPSK20M	Top Side	1.5	18700	1	49	without	24.5	23.96	-0.02	0.322	0.194	1.13	0.365
	LTE BAND 2	QPSK20M	Rear Face	1	18700	50	0	without	23.0	22.67	0.12	0.524	0.289	1.08	0.565
	LTE BAND 2	QPSK20M	Left Side	0	18700	50	0	without	23.0	22.67	-0.02	0.199	0.101	1.08	0.215
	LTE BAND 2	QPSK20M	Top Side	1.5	18700	50	0	without	23.0	22.67	0.04	0.26	0.132	1.08	0.281
7	LTE BAND 5	QPSK10M	Rear Face	0	20525	1	25	with	14.5	14.24	0.07	0.0765	0.0415	1.06	0.081
	LTE BAND 5	QPSK10M	Top Side	0	20525	1	25	with	14.5	14.24	0.02	0.097	0.049	1.06	0.103
	LTE BAND 5	QPSK10M	Rear Face	0	20525	25	25	with	14.5	13.90	0.14	0.065	0.0353	1.15	0.075
	LTE BAND 5	QPSK10M	Top Side	0	20525	25	25	with	14.5	13.90	0.02	0.0817	0.0416	1.15	0.094
	LTE BAND 5	QPSK10M	Rear Face	1	20525	1	25	without	24.0	23.68	-0.05	0.485	0.293	1.08	0.522
	LTE BAND 5	QPSK10M	Left Side	0	20525	1	25	without	24.0	23.68	0.03	0.272	0.138	1.08	0.293
	LTE BAND 5	QPSK10M	Top Side	1.5	20525	1	25	without	24.0	23.68	0.12	0.324	0.202	1.08	0.349
	LTE BAND 5	QPSK10M	Rear Face	1	20525	25	25	without	23.0	22.68	-0.05	0.39	0.236	1.08	0.420
	LTE BAND 5	QPSK10M	Left Side	0	20525	25	25	without	23.0	22.68	0.02	0.218	0.132	1.08	0.235
	LTE BAND 5	QPSK10M	Top Side	1.5	20525	25	25	without	23.0	22.68	0.03	0.261	0.158	1.08	0.281
8	LTE BAND 7	QPSK20M	Rear Face	0	20850	1	49	with	15.0	14.61	0.09	0.341	0.121	1.09	0.373
	LTE BAND 7	QPSK20M	Top Side	0	20850	1	49	with	15.0	14.61	0.09	0.451	0.16	1.09	0.493
	LTE BAND 7	QPSK20M	Rear Face	0	20850	50	50	with	14.5	14.22	0.02	0.528	0.226	1.07	0.563
	LTE BAND 7	QPSK20M	Top Side	0	20850	50	50	with	14.5	14.22	0.03	0.697	0.239	1.07	0.743
	LTE BAND 7	QPSK20M	Top Side	0	21100	50	50	with	14.5	13.41	0.13	0.522	0.178	1.29	0.671
	LTE BAND 7	QPSK20M	Top Side	0	21350	50	50	with	14.5	13.58	-0.05	0.544	0.186	1.24	0.672
	LTE BAND 7	QPSK20M	Rear Face	1	21350	1	49	without	24.0	23.76	-0.10	0.978	0.493	1.06	1.034
	LTE BAND 7	QPSK20M	Left Side	0	21350	1	49	without	24.0	23.76	-0.07	0.519	0.232	1.06	0.548
	LTE BAND 7	QPSK20M	Top Side	1.5	21350	1	49	without	24.0	23.76	0.03	0.519	0.282	1.06	0.548
	LTE BAND 7	QPSK20M	Rear Face	1	20850	1	49	without	24.5	23.50	0.16	0.624	0.321	1.26	0.786
	LTE BAND 7	QPSK20M	Rear Face	1	21100	1	49	without	24.5	23.61	-0.03	0.716	0.364	1.23	0.879
	LTE BAND 7	QPSK20M	Rear Face	1	20850	50	0	without	23.0	22.70	0.09	0.704	0.356	1.07	0.754
	LTE BAND 7	QPSK20M	Left Side	0	20850	50	0	without	23.0	22.70	-0.05	0.376	0.168	1.07	0.403

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	RB#	RB Offset	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE BAND 7	QPSK20M	Top Side	1.5	20850	50	0	without	23.0	22.70	0.07	0.372	0.202	1.07	0.399
	LTE BAND 12 (17)	QPSK10M	Rear Face	0	23060	1	25	with	14.5	14.24	-0.04	0.156	0.0702	1.06	0.166
	LTE BAND 12 (17)	QPSK10M	Top Side	0	23060	1	25	with	14.5	14.24	0.04	0.138	0.0526	1.06	0.147
	LTE BAND 12 (17)	QPSK10M	Rear Face	0	23060	25	25	with	14.5	13.81	0.02	0.177	0.0796	1.17	0.207
	LTE BAND 12 (17)	QPSK10M	Top Side	0	23060	25	25	with	14.5	13.81	0.02	0.156	0.0593	1.17	0.183
9	LTE BAND 12 (17)	QPSK10M	Rear Face	1	23130	1	25	without	24.0	23.52	0.02	0.422	0.261	1.12	0.471
	LTE BAND 12 (17)	QPSK10M	Left Side	0	23130	1	25	without	24.0	23.52	-0.05	0.196	0.103	1.12	0.219
	LTE BAND 12 (17)	QPSK10M	Top Side	1.5	23130	1	25	without	24.0	23.52	0.05	0.166	0.105	1.12	0.185
	LTE BAND 12 (17)	QPSK10M	Rear Face	1	23130	25	25	without	23.0	22.32	0.05	0.381	0.225	1.17	0.446
	LTE BAND 12 (17)	QPSK10M	Left Side	0	23130	25	25	without	23.0	22.32	-0.02	0.168	0.0882	1.17	0.196
	LTE BAND 12(17)	QPSK10M	Top Side	1.5	23130	25	25	without	23.0	22.32	0.04	0.144	0.0911	1.17	0.168
	LTE BAND 13	QPSK10M	Rear Face	0	23230	1	49	with	14.0	13.50	-0.16	0.17	0.0769	1.12	0.191
	LTE BAND 13	QPSK10M	Top Side	0	23230	1	49	with	14.0	13.50	0.04	0.182	0.0775	1.12	0.204
	LTE BAND 13	QPSK10M	Rear Face	0	23230	25	0	with	13.5	13.20	0.02	0.157	0.0758	1.07	0.168
	LTE BAND 13	QPSK10M	Top Side	0	23230	25	0	with	13.5	13.20	0.06	0.168	0.0715	1.07	0.180
10	LTE BAND 13	QPSK10M	Rear Face	1	23230	1	49	without	23.5	23.24	-0.02	0.346	0.213	1.06	0.367
	LTE BAND 13	QPSK10M	Left Side	0	23230	1	49	without	23.5	23.24	0.02	0.153	0.081	1.06	0.162
	LTE BAND 13	QPSK10M	Top Side	1.5	23230	1	49	without	23.5	23.24	-0.05	0.199	0.124	1.06	0.211
	LTE BAND 13	QPSK10M	Rear Face	1	23230	25	0	without	22.5	21.97	0.06	0.298	0.184	1.13	0.337
	LTE BAND 13	QPSK10M	Left Side	0	23230	25	0	without	22.5	21.97	0.05	0.132	0.0822	1.13	0.149
	LTE BAND 13	QPSK10M	Top Side	1.5	23230	25	0	without	22.5	21.97	-0.05	0.174	0.108	1.13	0.197
	LTE BAND 14	QPSK10M	Rear Face	0	23330	1	25	with	15.0	14.52	0.02	0.112	0.0556	1.12	0.125
	LTE BAND 14	QPSK10M	Top Side	0	23330	1	25	with	15.0	14.52	0.03	0.133	0.0522	1.12	0.149
	LTE BAND 14	QPSK10M	Rear Face	0	23330	25	25	with	14.5	13.88	0.03	0.102	0.0506	1.15	0.118
	LTE BAND 14	QPSK10M	Top Side	0	23330	25	25	with	14.5	13.88	0.02	0.12	0.0554	1.15	0.138
11	LTE BAND 14	QPSK10M	Rear Face	1	23330	1	49	without	24.0	23.36	0.07	0.4	0.244	1.16	0.464
	LTE BAND 14	QPSK10M	Left Side	0	23330	1	49	without	24.0	23.36	-0.06	0.138	0.0729	1.16	0.160
	LTE BAND 14	QPSK10M	Top Side	1.5	23330	1	49	without	24.0	23.36	0.03	0.174	0.11	1.16	0.202
	LTE BAND 14	QPSK10M	Rear Face	1	23330	25	0	without	22.5	22.10	-0.20	0.306	0.188	1.10	0.336
	LTE BAND 14	QPSK10M	Left Side	0	23330	25	0	without	22.5	22.10	0.12	0.105	0.0571	1.10	0.115

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	RB#	RB Offset	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE BAND 14	QPSK10M	Top Side	1.5	23330	25	0	without	22.5	22.10	0.04	0.133	0.0841	1.10	0.146
	LTE BAND 38	QPSK20M	Rear Face	0	37850	1	49	with	15.5	15.12	0.06	0.293	0.124	1.09	0.320
	LTE BAND 38	QPSK20M	Top Side	0	37850	1	49	with	15.5	15.12	0.17	0.286	0.122	1.09	0.312
	LTE BAND 38	QPSK20M	Rear Face	0	37850	50	0	with	15.0	14.73	-0.04	0.392	0.165	1.06	0.417
	LTE BAND 38	QPSK20M	Top Side	0	37850	50	0	with	15.0	14.73	0.03	0.391	0.136	1.06	0.416
12	LTE BAND 38	QPSK20M	Rear Face	1	37850	1	49	without	24.0	23.28	-0.11	0.567	0.288	1.18	0.669
	LTE BAND 38	QPSK20M	Left Side	0	37850	1	49	without	24.0	23.28	0.10	0.288	0.128	1.18	0.340
	LTE BAND 38	QPSK20M	Top Side	1.5	37850	1	49	without	24.0	23.28	0.06	0.255	0.139	1.18	0.301
	LTE BAND 38	QPSK20M	Rear Face	1	38150	50	0	without	22.5	22.18	0.03	0.341	0.175	1.08	0.367
	LTE BAND 38	QPSK20M	Left Side	0	38150	50	0	without	22.5	22.18	-0.04	0.173	0.0768	1.08	0.186
	LTE BAND 38	QPSK20M	Top Side	1.5	38150	50	0	without	22.5	22.18	0.04	0.152	0.0675	1.08	0.164
	LTE BAND 66(4)	QPSK20M	Rear Face	0	132572	1	49	with	17.0	16.30	-0.09	0.169	0.0779	1.17	0.199
	LTE BAND 66(4)	QPSK20M	Top Side	0	132572	1	49	with	17.0	16.30	0.05	0.0752	0.0384	1.17	0.088
	LTE BAND 66(4)	QPSK20M	Rear Face	0	132572	50	0	with	16.5	15.89	-0.08	0.281	0.129	1.15	0.323
	LTE BAND 66(4)	QPSK20M	Top Side	0	132072	50	0	with	16.5	15.89	0.02	0.125	0.0638	1.15	0.144
13	LTE BAND 66(4)	QPSK20M	Rear Face	1	132322	1	99	without	25.0	24.44	-0.04	0.37	0.234	1.14	0.421
	LTE BAND 66(4)	QPSK20M	Left Side	0	132322	1	99	without	25.0	24.44	0.05	0.171	0.0874	1.14	0.195
	LTE BAND 66(4)	QPSK20M	Top Side	1.5	132322	1	99	without	25.0	24.44	-0.03	0.262	0.153	1.14	0.298
	LTE BAND 66(4)	QPSK20M	Rear Face	1	132322	50	25	without	23.5	22.99	-0.09	0.285	0.18	1.12	0.321
	LTE BAND 66(4)	QPSK20M	Left Side	0	132322	50	25	without	23.5	22.99	-0.15	0.134	0.0685	1.12	0.151
	LTE BAND 66(4)	QPSK20M	Top Side	1.5	132322	50	25	without	23.5	22.99	0.04	0.203	0.105	1.12	0.228

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	Duty Cycle	Power Reduction	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Measured SAR-10g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
14	2.4G	BT DH5	Rear Face	0	78	76.80%	N/A	5.0	4.34	0.07	0.205	0.0862	1.16	0.311
	2.4G	BT DH5	Top Side	0	78	76.80%	N/A	5.0	4.34	0.04	0.0775	0.0288	1.16	0.117
15	2.4G	IEEE 802.11b	Rear Face	0	11	97.65%	N/A	12.5	12.25	-0.04	0.706	0.285	1.06	0.766
	2.4G	IEEE 802.11b	Top Side	0	11	97.65%	N/A	12.5	12.12	0.08	0.424	0.145	1.09	0.474
*	2.4G	IEEE 802.11b	Rear Face	1	11	97.65%	N/A	12.5	12.25	-0.03	0.272	0.107	1.06	0.295
16	5.2&5.3G	IEEE 802.11a	Rear Face	0	36	98.57%	N/A	11.5	10.86	-0.04	0.758	0.187	1.16	0.891
	5.2&5.3G	IEEE 802.11a	Rear Face	0	48	98.57%	N/A	11.5	10.33	-0.07	0.663	0.156	1.31	0.881
	5.2&5.3G	IEEE 802.11a	Rear Face	0	64	98.57%	N/A	11.5	9.85	0.02	0.541	0.134	1.46	0.803
	5.2&5.3G	IEEE 802.11a	Top Side	0	36	98.57%	N/A	11.5	10.86	-0.13	0.196	0.041	1.16	0.230
*	5.2&5.3G	IEEE 802.11a	Rear Face	1	36	98.57%	N/A	11.5	10.86	-0.08	0.292	0.107	1.16	0.343
17	5.6G	IEEE 802.11a	Rear Face	0	140	98.57%	N/A	11.0	10.38	-0.09	0.766	0.159	1.15	0.896
	5.6G	IEEE 802.11a	Rear Face	0	100	98.57%	N/A	11.0	9.41	-0.02	0.524	0.119	1.44	0.767
	5.6G	IEEE 802.11a	Rear Face	0	116	98.57%	N/A	11.0	10.21	-0.03	0.675	0.146	1.20	0.821
	5.6G	IEEE 802.11a	Top Side	0	140	98.57%	N/A	11.0	10.38	-0.08	0.354	0.072	1.15	0.414
*	5.6G	IEEE 802.11a	Rear Face	1	140	98.57%	N/A	11.0	10.38	-0.07	0.295	0.097	1.15	0.345
18	5.8G	IEEE 802.11a	Rear Face	0	149	98.57%	N/A	10.0	9.58	0.12	0.679	0.136	1.10	0.759
	5.8G	IEEE 802.11a	Top Side	0	149	98.57%	N/A	10.0	9.58	-0.09	0.312	0.055	1.10	0.349
*	5.8G	IEEE 802.11a	Rear Face	1	149	98.57%	N/A	10.0	9.58	0.04	0.279	0.086	1.10	0.312

Note:

1. Scaled SAR-10g (W/kg) = (Measured SAR-10g (W/kg) x Scaling Factor) / Duty Cycle.
2. The data marked with "*" is only used for simultaneous transmission computation.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

4.7. SAR MEASUREMENT VARIABILITY

4.7.1. Repeated Measurement

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

- 1) When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
- 2) When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
- 4) If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Separation Distance (cm)	Channel	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
Body Exposure Condition											
LTE Band 7	QPSK20M	Rear Face	1	21350	0.978	0.969	1.0093	N/A	N/A	N/A	N/A

4.8. SIMULTANEOUS MULTI-BAND TRANSMISSION EVALUATION

4.8.1. Simultaneous Transmission SAR Test Exclusion Considerations

a) Sum of SAR

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

b) SAR to Peak Location Separation Ratio

The simultaneous transmitting antennas in each operating mode and exposure condition combination are considered one pair at a time to determine the SPLSR.

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / R_i$$

The ratio is rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion. When 10-g SAR applies, the ratio must be ≤ 0.10 .

SAR_1 and SAR_2 are the highest reported or estimated SAR values for each antenna in the pair, and R_i is the separation distance in mm between the peak SAR locations for the antenna pair

$$\text{peak location separation distance} = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2}$$

Where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the area or zoom scans.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna. Due to curvatures on the SAM phantom, when SAR is estimated for one of the antennas in an antenna pair, the measured peak SAR location will be translated onto the test device to determine the peak location separation for the antenna pair.

When SAR is estimated for both antennas, the peak location separation should be determined by the closest physical separation of the antennas, according to the feed-point or geometric center of the antennas.

c) Volume Scan

When the SPLSR is ≤ 0.04 for 1-g SAR and ≤ 0.10 for 10-g SAR, the simultaneous transmission SAR is not required. Otherwise, the enlarged zoom scan and volume scan post-processing procedures will be performed.

4.8.2. Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous Transmission Configurations	Body Exposure Condition
GSM (Voice / Data) + WLAN (Data)	Yes
WCDMA (Voice / Data) + WLAN (Data)	Yes
LTE (Data) + WLAN (Data)	Yes
GSM (Voice / Data) + BT (Data)	Yes
WCDMA (Voice / Data) + BT (Data)	Yes
LTE (Data) + BT (Data)	Yes
GSM (Voice / Data) + WLAN (Data) + BT (Data)	No
WCDMA (Voice / Data) + WLAN (Data) + BT (Data)	No
LTE (Data) + WLAN (Data) + BT (Data)	No

Note:

- 1) The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
- 2) The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.
- 3) Both WCDMA and LTE can transmit through either WWAN MAIN Ant. However, only one technology (WCDMA or LTE) can transmit from an antenna at a time, and the other technology transmits through the other antenna

4.8.3. Max. Standalone SAR

Position		GSM Band		WCDMA Band			LTE Band								2.4G		5G
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)	BT	Wi-Fi	Wi-Fi
Body (0mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.062	0.361	0.350	0.444	0.097	0.579	0.081	0.563	0.207	0.191	0.125	0.417	0.323	0.311	0.766	0.896
	Left Side	--	--	--	--	--	--	--	--	--	--	--	--	--	0.005	0.025	0.019
	Right Side	0.033	0.017	0.035	0.034	0.037	0.031	0.03	0.04	0.043	0.035	0.044	0.045	0.048	0.011	0.064	0.051
	Top Side	0.088	0.338	0.235	0.197	0.125	0.436	0.103	0.743	0.183	0.204	0.149	0.416	0.144	0.117	0.474	0.414
	Bottom Side	0.034	0.018	0.036	0.035	0.038	0.032	0.031	0.041	0.044	0.036	0.045	0.047	0.049	0.004	0.024	0.018
Body (≥10mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.437	0.478	0.684	0.513	0.376	0.741	0.522	1.034	0.471	0.367	0.464	0.669	0.421	0.311	0.295	0.345
	Left Side	0.301	0.212	0.288	0.200	0.259	0.282	0.293	0.548	0.219	0.180	0.160	0.340	0.195	0.005	0.025	0.019
	Right Side	0.418	0.138	0.195	0.301	0.333	0.28	0.268	0.314	0.383	0.316	0.351	0.322	0.301	0.011	0.064	0.051
	Top Side	0.257	0.242	0.331	0.340	0.425	0.365	0.349	0.548	0.185	0.211	0.202	0.301	0.298	0.117	0.474	0.414
	Bottom Side	0.429	0.143	0.201	0.31	0.341	0.289	0.277	0.325	0.392	0.324	0.359	0.333	0.311	0.004	0.024	0.018

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

4.8.4. Sum of SAR

WWAN Power Reduction + BT (DSS)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (0mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.373	0.672	0.661	0.755	0.408	0.89	0.392	0.874	0.518	0.502	0.436	0.728	0.634
	Left Side	--	--	--	--	--	--	--	--	--	--	--	--	--
	Right Side	0.044	0.028	0.046	0.045	0.048	0.042	0.041	0.051	0.054	0.046	0.055	0.056	0.059
	Top Side	0.205	0.455	0.352	0.314	0.242	0.553	0.22	0.86	0.3	0.321	0.266	0.533	0.261
	Bottom Side	0.038	0.022	0.04	0.039	0.042	0.036	0.035	0.045	0.048	0.04	0.049	0.051	0.053
Highest Simultaneous Transmission SAR (W/kg)		0.890												

WWAN Max Power + BT (DSS)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (≥10mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.748	0.789	0.995	0.824	0.687	1.052	0.833	1.345	0.782	0.678	0.775	0.980	0.732
	Left Side	0.306	0.217	0.293	0.205	0.264	0.287	0.298	0.553	0.224	0.185	0.165	0.345	0.200
	Right Side	0.429	0.149	0.206	0.312	0.344	0.291	0.279	0.325	0.394	0.327	0.362	0.333	0.312
	Top Side	0.374	0.359	0.448	0.457	0.542	0.482	0.466	0.665	0.302	0.328	0.319	0.418	0.415
	Bottom Side	0.433	0.147	0.205	0.314	0.345	0.293	0.281	0.329	0.396	0.328	0.363	0.337	0.315
Highest Simultaneous Transmission SAR (W/kg)		1.345												

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

WWAN Power Reduction + WLAN (DTS)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (0mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.828	1.127	1.116	1.210	0.863	1.345	0.847	1.329	0.973	0.957	0.891	1.183	1.089
	Left Side	--	--	--	--	--	--	--	--	--	--	--	--	--
	Right Side	0.097	0.081	0.099	0.098	0.101	0.095	0.094	0.104	0.107	0.099	0.108	0.109	0.112
	Top Side	0.562	0.812	0.709	0.671	0.599	0.910	0.577	1.217	0.657	0.678	0.623	0.890	0.618
	Bottom Side	0.058	0.042	0.060	0.059	0.062	0.056	0.055	0.065	0.068	0.060	0.069	0.071	0.073
Highest Simultaneous Transmission SAR (W/kg)		1.345												

WWAN Max Power + WLAN (DTS)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (≥10mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.732	0.773	0.979	0.808	0.671	1.036	0.817	1.329	0.766	0.662	0.759	0.964	0.716
	Left Side	0.326	0.237	0.313	0.225	0.284	0.307	0.318	0.573	0.244	0.205	0.185	0.365	0.220
	Right Side	0.482	0.202	0.259	0.365	0.397	0.344	0.332	0.378	0.447	0.380	0.415	0.386	0.365
	Top Side	0.731	0.716	0.805	0.814	0.899	0.839	0.823	1.022	0.659	0.685	0.676	0.775	0.772
	Bottom Side	0.453	0.167	0.225	0.334	0.365	0.313	0.301	0.349	0.416	0.348	0.383	0.357	0.335
Highest Simultaneous Transmission SAR (W/kg)		1.329												

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

WWAN Power Reduction + WLAN (NII)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (0mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.958	1.257	1.246	1.340	0.993	1.475	0.977	1.459	1.103	1.087	1.021	1.313	1.219
	Left Side	--	--	--	--	--	--	--	--	--	--	--	--	--
	Right Side	0.084	0.068	0.086	0.085	0.088	0.082	0.081	0.091	0.094	0.086	0.095	0.096	0.099
	Top Side	0.502	0.752	0.649	0.611	0.539	0.850	0.517	1.157	0.597	0.618	0.563	0.830	0.558
	Bottom Side	0.052	0.036	0.054	0.053	0.056	0.050	0.049	0.059	0.062	0.054	0.063	0.065	0.067
Highest Simultaneous Transmission SAR (W/kg)		1.475												

WWAN Max Power + WLAN (NII)

Position		GSM Band		WCDMA Band			LTE Band							
		850	1900	II	IV	V	2	5	7	12 (17)	13	14	38	66 (4)
Body (≥10mm) (W/kg)	Front Face	--	--	--	--	--	--	--	--	--	--	--	--	--
	Rear Face	0.782	0.823	1.029	0.858	0.721	1.086	0.867	1.379	0.816	0.712	0.809	1.014	0.766
	Left Side	0.320	0.231	0.307	0.219	0.278	0.301	0.312	0.567	0.238	0.199	0.179	0.359	0.214
	Right Side	0.469	0.189	0.246	0.352	0.384	0.331	0.319	0.365	0.434	0.367	0.402	0.373	0.352
	Top Side	0.671	0.656	0.745	0.754	0.839	0.779	0.763	0.962	0.599	0.625	0.616	0.715	0.712
	Bottom Side	0.447	0.161	0.219	0.328	0.359	0.307	0.295	0.343	0.410	0.342	0.377	0.351	0.329
Highest Simultaneous Transmission SAR (W/kg)		1.379												

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-SAR-IEEE Std 1528-2013-V1.1

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

APPENDIX A. SAR PLOTS OF SYSTEM VERIFICATION

The plots for system verification with largest deviation for each SAR system combination are shown as follows.



APPENDIX B. SAR PLOTS OF SAR MEASUREMENT

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.



APPENDIX C. CALIBRATION CERTIFICATE FOR PROBE AND DIPOLE

The calibration certificates are shown as follows.



APPENDIX D. PHOTOGRAPHS OF EUT AND SETUP

The photographs of EUT and setup are shown as follows.

