

## **MPE CALCULATION**

For *HYUNDAI MOBIS CO., LTD* - ; Model: DP1W  
FCC ID:SSNDP1W0702

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65 / 47 CFR §2.1091
EUT Frequency Band:	2402 – 2480 MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 – 100,000 MHz
Power Density Limit:	1.0mW/ cm <sup>2</sup> ;

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

---

Low Channel (2437 MHz): Power = 19.35 dBm, Antenna Gain = 2.2625 dBi, Prediction distance 20cm

S = 0.02884 mW/cm<sup>2</sup>

### **Result**

The Above Result had shown that Device complied with 1.0 mW/cm<sup>2</sup> Power density requirement for distance of 20cm.

Completed By : Jong Suek Lee

Date : July 13, 2010