



HCT CO., LTD.

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8525

CERTIFICATE OF COMPLIANCE FCC PART 15.247 Certification

Applicant Name:

LG Electronics Inc.

50 Hyangjung-dong, Heungdeok-gu, Chongju-si,
Chungchong-bukdo, S.Korea

Date of Issue:

June 15, 2009

Test Site/Location:

HCT.CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,
Kyungki-do, Korea

Test Report No.: HCT-RF09-0616

HCT FRN: 0005866421

IC Recognition No.: IC 5944A-1

FCC ID: SSNMNC4U1186

APPLICANT: LG Electronics Inc.

Model(s): CM-400

EUT Type: Wireless Mouse

Max. RF Output Power: -12.37 dBm(5.79 mW)

Frequency Range: 2402 - 2480 MHz

Modulation type: GFSK

FCC Classification: FCC Part 15 Frequency Hopping Spread Spectrum Transceiver

FCC Rule Part(s): Part 15 subpart C 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT.CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.862

Report prepared by

: Hyo Sun Kwak

Test engineer of RF Team

Approved by

: Sang Jun Lee

Manager of RF Team

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:		FCC ID:	
HCT-RF09-0616	June 15, 2009	Wireless Mouse		SSNMNC4U1186	Page 1 of 39



Table of Contents

1. GENERAL INFORMATION	3
2. EUT DESCRIPTION.....	3
3. TEST METHODOLOGY	4
3.1 EUT CONFIGURATION	4
3.2 EUT EXERCISE.....	4
3.3 GENERAL TEST PROCEDURES.....	4
3.4 DESCRIPTION OF TEST MODES.....	4
4. INSTRUMENT CALIBRATION.....	5
5. FACILITIES AND ACCREDITATIONS	5
5.1 FACILITIES.....	5
5.2 EQUIPMENT.....	5
6. ANTENNA REQUIREMENTS	6
7. FCC PART 15.247 REQUIREMENTS.....	7
7.1 PEAK POWER	7
7.2 BAND EDGES MEASUREMENT	10
7.3 FREQUENCY SEPARATION.....	12
7.4 NUMBER OF HOPPING FREQUENCY	12
7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME).....	12
7.6 SPURIOUS EMISSIONS	12
7.6.1 Conducted Spurious Measurement	12
7.6.2 Radiated Spurious Emissions.....	12
7.6.3 Radiated Restricted Band Edge Measurements.....	12
7.7 POWERLINE CONDUCTED EMISSIONS.....	12
8. LIST OF TEST EQUIPMENT	12

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 2 of 39



1. GENERAL INFORMATION

Applicant: LG Electronics Inc.
Address: 50 Hyangjung-dong, Heungdeok-gu, Chongju-si,
Chungchong-bukdo, S.Korea
FCC ID: SSNMNC4U1186
EUT: Wireless Mouse
Model: CM-400
Date of Test: May 08, 2009 ~ June 01, 2009
Name: Kwang-soon(Brian) Jang
Contact person: Phone #: +82-43-279-3249
Fax #: +82-43-279-3118

2. EUT DESCRIPTION

Product	Wireless Mouse
Model Name	CM-400
Power Supply	Powered by 2 x AAA Batteries (DC 3V)
Frequency Range	2402 ~ 2480 MHz
Transmit Power	-12.37 dBm(5.79 mW)
Modulation Type	GFSK
Modulation Technique	FHSS
Number of Channels	16 Channels
Antenna Specification	Manufacturer: SHENZHEN WALTEK SERVICES CO., LTD. Antenna type: Microstrip meander antenna Peak Gain : -0.46501 dBi

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 3 of 39



3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz(ANSI C63.4-2003) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" were used in the measurement of the **LG Electronics Inc.**

Wireless Mouse FCC ID: SSNMNC4U1186

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID: SSNMNC4U1186		Page 4 of 39
HCT-RF09-0616	June 15, 2009	Wireless Mouse			



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009(Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 5 of 39



6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 6 of 39

7. FCC PART 15.247 REQUIREMENTS


7.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode.

1. Span = 5 MHz
2. RBW = 3 MHz
3. VBW = 3 MHz
4. Sweep = auto

TEST RESULTS

No non-compliance noted


Test Data

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (W)	Result
Low	2402	-12.51	5.61	1	PASS
Mid	2441	-12.59	5.51		PASS
High	2480	-12.37	5.79		PASS

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:			FCC ID: SSNMNC4U1186
HCT-RF09-0616	June 15, 2009	Wireless Mouse			Page 7 of 39


Test Plots

Peak Power (Low CH)



Date: 1.JUN.2009 10:06:01

Peak Power (Mid CH)




Date: 1.JUN.2009 10:05:14

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 8	of 39



Peak Power (High CH)



Date: 1.JUN.2009 10:04:09


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 9	of 39

7.2 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration



TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 8 MHz
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto
5. Detector Mode = Peak


TEST RESULTS

See attached.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 10 of 39


Test Data

Band Edges (Low-CH)



Date: 1.JUN.2009 10:07:13

Band Edges (High-CH)



Date: 1.JUN.2009 10:10:13


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type:			FCC ID:	
HCT-RF09-0616	June 15, 2009	Wireless Mouse			SSNMNC4U1186	Page 11 of 39

7.3 FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Configuration



TEST PROCEDURE

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 30 kHz
3. VBW = 100 kHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

TEST RESULTS

No non-compliance noted


Test Data

Channel Separation (MHz)	20dB Bandwidth (kHz)		Limit (kHz)	Result
3.00	Low CH	1026	>25 or >2/3 of the 20dB BW	Pass
	Middle CH	1020		
	High CH	1026		

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 1 2 of 39

Test Plot


Measurement of Channel Separation



Date: 1.JUN.2009 10:18:49


Test Plot

20 dB bandwidth (Low CH)




Date: 1.JUN.2009 09:59:43

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type:			FCC ID:	
HCT-RF09-0616	June 15, 2009	Wireless Mouse			SSNMNC4U1186	Page 13 of 39

(Mid CH)


Date: 1.JUN.2009 10:01:53

(High CH)


Date: 1.JUN.2009 10:03:11


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 14 of 39

7.4 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation (Start = 2400 MHz, Stop = 2483.5 MHz)
2. RBW = 300 kHz
3. VBW = 300 kHz
4. Sweep = auto

The trace was allowed to stabilize.

TEST RESULTS

No non-compliance noted

Test Data

Result (No. of CH)	Limit (No. of CH)	Result
16	>15	Pass


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186 www.hct.co.kr



Test Plot


Number of Channels

2.4 GHz – 2.441 GHz



Date: 1.JUN.2009 10:20:21

2.441 GHz – 2.4835 GHz



Date: 1.JUN.2009 10:23:07


FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 16 of 39

7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



TEST PROCEDURE

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the Pulse width.

$$\text{Pulse width} * \text{Number of Pulses in 640(ms)} * 10 = \text{Average Time}$$


TEST RESULTS

See the table.


Channel	Pulse Time (ms)	Number of Pulses in 640 (ms)	Average Time(ms)	Limit (ms)	Result
Low	0.103	10	10.3	400	PASS
Mid	0.103	10	10.3		PASS
High	0.103	10	10.3		PASS

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 17 of 39

(Low CH)




Date: 30.JUN.2009 16:24:37




Date: 30.JUN.2009 15:10:02

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 18	of 39

(Mid CH)




Date: 30.JUN.2009 16:27:08




Date: 30.JUN.2009 15:27:44

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 19	of 39

(CH High)


Date: 30.JUN.2009 16:28:17



Date: 30.JUN.2009 15:28:41

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 20	of 39


7.6 SPURIOUS EMISSIONS

7.6.1 Conducted Spurious Measurement

LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS

No non-compliance noted

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 21 of 39

Test Plots: 30 MHz ~ 1 GHz(RBW:100 kHz, VBW: 300 kHz)
(Low CH)



Date: 25.JUN.2009 15:03:42

(Mid CH)


Date: 25.JUN.2009 15:02:00


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:			
HCT-RF09-0616	June 15, 2009	Wireless Mouse	FCC ID: SSNMNC4U1186		Page 22 of 39

(High CH)




Date: 25.JUN.2009 15:04:36

Test Plots: 1 GHz ~ 26 GHz (RBW: 1 MHz, VBW: 1 MHz) (Low CH)




Date: 1.JUN.2009 11:47:43

FCC CERTIFICATION REPORT				
www.hct.co.kr				
HCT PT.15.247 TEST REPORT	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 23 of 39

(Mid CH)


Date: 1.JUN.2009 11:44:54

(High CH)


Date: 1.JUN.2009 11:41:48

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID: SSNMNC4U1186		Page 24 of 39
HCT-RF09-0616	June 15, 2009	Wireless Mouse			



7.6.2 Radiated Spurious Emissions

LIMIT


1. 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 25 of 39

Test Configuration

Below 30 MHz




30 MHz - 1 GHz



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 26	of 39

Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 27 of 39



TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Link

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 28 of 39



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Frequency MHz	Reading dB μ V	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dB μ V/m	Limit dB μ V/m	Margin dB
33.5	7.4	11.4	1.3	V	20.1	30.0	9.9
103.8	8.6	9.4	2.4	V	20.4	30.0	9.6
142.1	6.0	12.4	2.8	H	21.2	30.0	8.8
151.4	8.2	12.6	2.9	V	23.7	30.0	6.3
182.4	7.9	11.4	3.2	V	22.5	30.0	7.5
202.0	8.9	10.0	3.4	H	22.3	30.0	7.7
233.7	15.6	10.9	3.7	V	30.2	37.0	6.8
252.5	15.3	11.5	3.8	H	30.6	37.0	6.4
275.0	14.7	12.3	4.0	H	31.0	37.0	6.0
307.9	13.0	13.2	4.2	V	30.4	37.0	6.6
451.2	10.5	16.6	5.0	H	32.1	37.0	4.9
503.5	9.9	17.3	5.3	H	32.5	37.0	4.5

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 29 of 39



Above 1 GHz

Operation Mode: CH Low

Frequency [MHz]	Reading dBuV	AN.+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	57.24	-4.79	V	52.45	74	21.55	PK
4804	54.58	-4.79	V	49.79	54	4.21	AV
7206	50.57	1.21	V	51.78	74	22.22	PK
7206	37.65	1.21	V	38.86	54	15.14	AV
4804	53.58	-4.79	H	48.79	74	25.21	PK
4804	49.55	-4.79	H	44.76	54	9.24	AV
7206	50.16	1.21	H	51.37	74	22.63	PK
7206	38.01	1.21	H	39.22	54	14.78	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 30 of 39

**Operation Mode: CH Mid**

Frequency [MHz]	Reading dBuV	AN.+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4896	52.16	-4.61	V	47.55	74	26.45	PK
4896	46.26	-4.61	V	41.65	54	12.35	AV
7344	49.00	1.62	V	50.62	74	23.38	PK
7344	36.36	1.62	V	37.98	54	16.02	AV
4896	50.12	-4.61	H	45.51	74	28.49	PK
4896	40.82	-4.61	H	36.21	54	17.79	AV
7344	52.68	1.62	H	54.30	74	19.70	PK
7344	43.72	1.62	H	45.34	54	8.66	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 31 of 39

**Operation Mode: CH High**

Frequency [MHz]	Reading dBuV	AN.+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	54.22	-4.42	V	49.80	74	24.20	PK
4960	50.44	-4.42	V	46.02	54	7.98	AV
7440	50.20	2.04	V	52.24	74	21.76	PK
7440	41.26	2.04	V	43.30	54	10.70	AV
4960	49.31	-4.42	H	44.89	74	29.11	PK
4960	42.26	-4.42	H	37.84	54	16.16	AV
7440	52.11	2.04	H	54.15	74	19.85	PK
7440	42.57	2.04	H	44.61	54	9.39	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MH.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse	FCC ID: SSNMNC4U1186	Page 32 of 39



7.6.3 Radiated Restricted Band Edge Measurements

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode:	GFSK(Normal)						
Operating Frequency	2402, 2480 MHz						
Channel No.	0, 78 Ch						

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2340.24	48.53	-10.37	H	38.16	74	35.84	PK
2340.24	36.33	-10.37	H	25.96	54	28.04	AV
2360.24	48.68	-10.28	V	38.40	74	35.60	PK
2360.24	35.97	-10.28	V	25.69	54	28.31	AV
2498.48	47.46	-9.70	H	37.76	74	36.24	PK
2498.48	36.11	-9.70	H	26.41	54	27.59	AV
2499.14	47.76	-9.70	V	38.06	74	35.94	PK
2499.14	36.20	-9.70	V	26.50	54	27.50	AV

Notes:

1. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 33 of 39



7.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type:			FCC ID:	
HCT-RF09-0616	June 15, 2009	Wireless Mouse			SSNMNC4U1186	Page 34 of 39

Test Plot

Conducted emissions (Line 1 / Mid CH)


HCT

EMC TEST LAB

EUT: CM-400
 Manufacturer: LG ELECTRONICS INC.
 Operating Condition: NORMAL
 Test Site: SHIELD ROOM
 Operator: DS-KIM
 Test Specification: CISPR 22 CLASS B
 Comment: H

SCAN TABLE: "CISPR 22 Voltage"

Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer Bandw.
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	30.0 MHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "ITE_fin_QP"

5/8/2009 3:06PM

Frequency MHz	Level dB _μ V	Transd dB	Limit dB _μ V	Margin dB	Line PE
0.206000	38.40	10.1	63	24.9	---
0.266000	31.90	10.1	61	29.3	---
0.274000	32.60	10.1	61	28.4	---
0.338000	33.30	10.1	59	26.0	---
0.406000	31.20	10.1	58	26.5	---
0.474000	32.30	10.2	56	24.2	---
0.540000	32.30	10.2	56	23.7	---
0.576000	35.90	10.2	56	20.1	---
0.744000	30.70	10.2	56	25.3	---
0.944000	30.30	10.2	56	25.7	---
1.352000	29.90	10.3	56	26.1	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse			FCC ID: SSNMNC4U1186	Page 35 of 39



2.296000	29.80	10.4	56	26.2	---	---
5.468000	29.60	10.7	60	30.4	---	---
5.604000	29.40	10.7	60	30.6	---	---
5.672000	31.10	10.8	60	28.9	---	---
5.808000	29.70	10.8	60	30.3	---	---
5.876000	30.10	10.8	60	29.9	---	---
5.944000	28.50	10.8	60	31.5	---	---

MEASUREMENT RESULT: "ITE_fin AV"

5/8/2009 3:06PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.206000	29.20	10.1	53	24.1	---	---
0.270000	28.60	10.1	51	22.5	---	---
0.274000	24.40	10.1	51	26.6	---	---
0.338000	26.00	10.1	49	23.2	---	---
0.406000	25.40	10.1	48	22.4	---	---
0.474000	27.60	10.2	46	18.8	---	---
0.540000	27.90	10.2	46	18.1	---	---
0.584000	32.10	10.2	46	13.9	---	---
0.744000	27.20	10.2	46	18.8	---	---
0.944000	26.90	10.2	46	19.1	---	---
1.148000	26.30	10.3	46	19.7	---	---
1.352000	25.20	10.3	46	20.8	---	---
5.468000	25.40	10.7	50	24.6	---	---
5.604000	25.00	10.7	50	25.0	---	---
5.672000	26.00	10.8	50	24.0	---	---
5.808000	24.30	10.8	50	25.7	---	---
5.876000	25.80	10.8	50	24.2	---	---
6.076000	24.70	10.8	50	25.3	---	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No. HCT-RF09-0616	Date of Issue: June 15, 2009	EUT Type: Wireless Mouse		FCC ID: SSNMNC4U1186	Page 36	of 39

Conducted emissions (Line 2 / Mid CH)


HCT

EMC TEST LAB

EUT: CM-400
 Manufacturer: LG ELECTRONICS INC.
 Operating Condition: NORMAL
 Test Site: SHIELD ROOM
 Operator: DS-KIM
 Test Specification: CISPR 22 CLASS B
 Comment: N

SCAN TABLE: "CISPR 22 Voltage"

Short Description:			EN 55022 Voltage			
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	30.0 MHz	2.5 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "ITE_fin_QP"

5/8/2009 3:00:00PM

Frequency MHz	Level dB _μ V	Transd dB	Limit dB _μ V	Margin dB	Line	PE
0.150000	33.30	10.1	66	32.7	---	---
0.202000	39.80	10.1	64	23.7	---	---
0.270000	35.30	10.1	61	25.8	---	---
0.274000	31.20	10.1	61	29.8	---	---
0.338000	30.50	10.1	59	28.7	---	---
0.478000	26.80	10.2	56	27.6	---	---
0.580000	36.20	10.2	56	19.8	---	---
1.216000	30.10	10.3	56	25.9	---	---
2.228000	28.20	10.4	56	27.8	---	---
2.972000	28.60	10.5	56	27.4	---	---
3.848000	29.70	10.6	56	26.3	---	---
4.728000	28.50	10.6	56	27.5	---	---
5.468000	31.50	10.7	60	28.5	---	---
5.536000	32.80	10.7	60	27.2	---	---
5.672000	32.70	10.8	60	27.3	---	---
5.740000	32.70	10.8	60	27.3	---	---
5.808000	31.40	10.8	60	28.6	---	---
5.872000	30.80	10.8	60	29.2	---	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type:			FCC ID:	
HCT-RF09-0616	June 15, 2009	Wireless Mouse			SSNMNC4U1186	Page 37 of 39



MEASUREMENT RESULT: "ITE_fin AV"

5/8/2009 3:00PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.154000	23.10	10.1	56	32.6	---	---
0.202000	31.10	10.1	54	22.4	---	---
0.270000	29.10	10.1	51	22.0	---	---
0.274000	25.20	10.1	51	25.8	---	---
0.406000	24.80	10.1	48	23.0	---	---
0.490000	25.30	10.2	46	20.8	---	---
0.584000	32.20	10.2	46	13.8	---	---
1.416000	24.30	10.3	46	21.7	---	---
2.968000	24.10	10.5	46	21.9	---	---
3.848000	24.90	10.6	46	21.1	---	---
4.456000	23.70	10.6	46	22.3	---	---
4.928000	23.90	10.7	46	22.1	---	---
5.336000	26.40	10.7	50	23.6	---	---
5.536000	28.00	10.7	50	22.0	---	---
5.672000	29.00	10.8	50	21.0	---	---
5.740000	29.20	10.8	50	20.8	---	---
5.808000	28.10	10.8	50	21.9	---	---
6.144000	26.20	10.8	50	23.8	---	---

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr	
Test Report No.	Date of Issue:	EUT Type:			FCC ID: SSNMNC4U1186	Page 38 of 39
HCT-RF09-0616	June 15, 2009	Wireless Mouse				



8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Cal Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	04/10/2010	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	Annual	06/13/2010	100329
Schwarzbeck	VULB 9160/ TRILOG Antenna	Biennial	12/18/2010	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	10/30/2009	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P/AMP	Annual	05/20/2010	1200937
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	03/26/2010	147
Rohde & Schwarz	6502/Loop Antenna	Biennial	12/26/2009	9009-2536
Rohde & Schwarz	FSP30/Spectrum Analyzer	Annual	07/31/2009	839117/011
Agilent	E4416A /Power Meter	Annual	01/21/2010	GB41291412
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	06/29/2010	1
Hewlett Packard	11636B/Power Divider	Annual	12/24/2009	11377
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	01/07/2010	3110117

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID: SSNMNC4U1186		Page 39 of 39
HCT-RF09-0616	June 15, 2009	Wireless Mouse			