

FCC PART 24 TYPE APPROVAL

EMI MEASUREMENT AND TEST REPORT

For

BBK COMMUNICATION EQUIPMENT CORP., LTD

23#, BBK Road, Wusha, Chang'an, Dongguan, Guangdong, China

FCC ID: SV5BBK302GM

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: GSM Fixed wireless phone
Test Engineer: Daniel Deng / 	
Report No.: R0501054	
Test Date: 2005-1-15	
Reviewed By: Ming Jing/ 	
Prepared By: Bay Area Compliance Laboratory Corporation (BACL) 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. Government.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SUMMARY OF TEST RESULTS	6
§2.1047 - MODULATION CHARACTERISTIC	7
APPLICABLE STANDARD	7
TEST PROCEDURE	7
TEST EQUIPMENT LIST AND DETAILS.....	7
ENVIRONMENTAL CONDITIONS	7
TEST RESULTS	7
§2.1053 - SPURIOUS RADIATED EMISSIONS	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	10
ENVIRONMENTAL CONDITIONS	10
TEST RESULT	11
§2.1046, & §24.232 - RF POWER OUTPUT	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	13
ENVIRONMENTAL CONDITIONS	13
TEST RESULTS	13
§2.1046, & §24.232 – CONDUCTED OUTPUT POWER	14
APPLICABLE STANDARD	14
TEST PROCEDURE	14
TEST EQUIPMENT LIST AND DETAILS.....	14
ENVIRONMENTAL CONDITIONS	14
TEST RESULTS	14
§2.1049, & §24.238 - OCCUPIED BANDWIDTH	17
APPLICABLE STANDARD	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	17
ENVIRONMENTAL CONDITIONS	17
TEST RESULTS	17
§2.1051, & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST EQUIPMENT LIST AND DETAILS.....	20
ENVIRONMENTAL CONDITIONS	20
TEST RESULTS	20
§2.1055 (A), §2.1055 (D), & §24.235 - FREQUENCY STABILITY	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST EQUIPMENT LIST AND DETAILS.....	24
ENVIRONMENTAL CONDITIONS	24
TEST RESULTS	25
§24.238 – BAND EDGE	26
APPLICABLE STANDARD	26

TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
ENVIRONMENTAL CONDITIONS	26
TEST RESULTS	26

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *BBK COMMUNICATION EQUIPMENT CORP., LTD*'s product, FCC ID: *SV5BBK302GM* or the "EUT" as referred to this report is a *GSM Fixed wireless phone* which measures approximately 190mmL x 200mmW x 80mmH.

** The test data gathered are from typical production sample, serial number: 001, provided by the manufacturer.*

Objective

This type approval report is prepared on behalf of *BBK COMMUNICATION EQUIPMENT CORP., LTD* in accordance with Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emission at antenna terminal, field strength of spurious radiation, frequency stability, and conducted and radiated margin.

Related Submittal(s)/Grant(s)

No Related Submittals

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following part:

Part 24 Subpart E - PCS

Applicable Standards: TIA EIA 137-A, TIA EIA 98-C, ANSI 63.4-2003, and TIA/EIA-603A.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp.

Test Facility

The Open Area Test site used by BACL Corp. to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at BACL Corp. has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules and Article 8 of the VCCI regulations. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2001.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234.

The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2001670.htm>

SUMMARY OF TEST RESULTS

Results reported relate only to the product tested, serial number: 001. The fresh battery was used during each test.

FCC RULE	DESCRIPTION OF TEST	RESULT
§ 2.1047	Modulation Characteristics	Compliant
§ 2.1053	Field Strength of Spurious Radiation	Compliant
§ 2.1093	RF Exposure	Compliant, Refer to SAR report
§ 2.1046, § 24.232	RF Output Power	Compliant
§ 2.1046, § 24.232	Conducted Output Power	Compliant
§ 2.1049 § 24.238	Out of Band Emission, Occupied Bandwidth	Compliant
§ 2.1051, § 24.238(a)	Spurious Emissions at Antenna Terminals	Compliant
§ 2.1055 (a) § 2.1055 (d) § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliant
§ 24.238	Band Edge	Compliant

§2.1047 - MODULATION CHARACTERISTIC

Applicable Standard

Requirement: FCC § 2.1047.

Test Procedure

GSM digital mode is used by EUT.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions


Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.


Test Results

Please refer to the hereinafter plots.


High Channel:



Middle Channel:



Low Channel:



§2.1053 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

Requirements: CFR 47, § 2.1053.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10}$ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
HP	Spectrum Analyzer	8568B	2601A02165	2004-07-03
HP	Amplifier	8447E	2944A10187	2004-09-23
HP	Quasi-Peak Adapter	85650A	3019A05393	2004-06-13
EMCO	Biconical Antenna	3110B	9309-1165	2004-10-11
EMCO	Log Periodic Antenna	3146	2101	2004-10-11
AH System	Horn Antenna	SAS-200/511	261	2004-08-02
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.

Test Result

Indicated		EUT			Substitution		Generator		Standard		
Frequency MHz	Ampl. dBuV/m	Table	Test Antenna	Polar H/V	Frequency MHz	Level dBm	Antenna Gain Corrected	Cable Loss dB	Absolute Level dBm	FCC Limit dBm	FCC Margin dB
1278.6	56.29	270	1.2	v	1278.6	-45.5	6.3	1.6	-40.5	-13	-27.5
1278.6	57.66	90	1.4	h	1278.6	-44.1	6.3	1.6	-39.4	-13	-26.4
2152.8	59.12	270	1.2	v	2152.8	-41.8	8.3	2.5	-36.0	-13	-23.0
2152.8	60.67	30	1.4	h	2152.8	-40.3	8.3	2.5	-34.5	-13	-21.5
3760.0	47.31	30	1.4	h	3760.0	-41.2	10.3	3.5	-34.4	-13	-21.4
3760.0	47.95	45	1.2	v	3760.0	-40.6	10.3	3.5	-33.8	-13	-20.8
1189.6	55.76	90	1.4	h	1189.6	-38.7	6.3	1.2	-33.6	-13	-20.6
1189.6	56.28	300	1.5	v	1189.6	-38.2	6.3	1.2	-33.1	-13	-20.1
1880.0	85.68	90	1.5	v	1880.0	22.5	8.3	2.2	28.6		
1880.0	84.71	30	1.4	h	1880.0	21.6	8.3	2.2	27.7		

Note: The EUT was tested in 3 orthogonal positions.

Sample calculation:

Absolute level = substitution reading + antenna gain - cable loss

For example:

$$-45.5 + 6.3 - 1.6 = -40.8$$

§2.1046, & §24.232 - RF POWER OUTPUT

Applicable Standard

According to FCC §2.1046 and §24.232 (1), mobile/portable stations are limited to 2 watts EIRP.

Test Procedure

1. On a test site, the EUT shall be placed at 1.5m height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3m from EUT to correspond to the frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the quasi-peak detector is used for the measurement.
4. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a horn (substitution antenna).
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
16. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
17. The measure of the effective radiated power is the large of the two levels recorded, at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
HP	Amplifier	8447E	2944A10187	2004-09-23
HP	Signal Generator	8657A	2026A00847	2004-08-19
EMCO	Biconical Antenna	3110B	9309-1165	2004-10-11
EMCO	Log Periodic Antenna	3146	2101	2004-10-11
AH System	Horn Antenna	SAS-200/511	261	2004-08-02
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.

Test Results

FREQUENCY (MHZ)	SUBSTITUTION READING (dBm)	SUBSTITUTION ANTENNA GAIN	SUBSTITUTION CALBE LOSS (dB)	EIRP (dBm)
1880	22.5	8.3	2.2	28.6

Sample calculation:

Absolute level = substitution reading + antenna gain - cable loss

For example:

$$22.5 + 8.3 - 2.2 = 28.6 \text{ dBm}$$

§2.1046, & §24.232 – CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §24.232 (b), Mobile/Portable Station are limited to 2 Watts e.i.r.p. Peak Power.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions


Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.


Test Results

Channel	Frequency (MHz)	Output Power in dBm	Output Power in W	Limit in W
LOW	1850.05	28.12	0.649	2
MIDDLE	1879.87	28.68	0.738	2
HIGH	1909.67	28.18	0.658	2


High Channel:



Middle Channel:



Low Channel:



§2.1049, & §24.238 - OCCUPIED BANDWIDTH

Applicable Standard

Requirements: CFR 47, Section 2.1049, and Section 24.238.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz and the 26 dB bandwidth was recorded.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions


Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.


Test Results

Please refer to the hereinafter plots.


High Channel:



Middle Channel:



Low Channel:



§2.1051, & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Requirements: CFR 47, § 2.1051 & §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1057.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions



Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.



Test Results

Please refer to the hereinafter plots.



High Channel:



Middle Channel:



Low Channel:



§2.1055 (a), §2.1055 (d), & §24.235 - FREQUENCY STABILITY

Applicable Standard

Requirements: FCC § 2.1055 (a), § 2.1055 (d) & following:

According to §24.235, The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Due Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.

Test Results

Frequency Stability Versus Temperature

Reference Frequency: 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapsed	
		Hz	PPM Error
50	3.7	1880.0015	0.798
40	3.7	1880.0016	0.851
30	3.7	1880.0013	0.691
20	3.7	1880.0011	0.585
10	3.7	1880.0011	0.585
0	3.7	1880.0003	0.160
-10	3.7	1880.0001	0.053
-20	3.7	1879.9996	-0.213
-30	3.7	1879.9991	-0.479

Battery nominal voltage: 3.7V

Frequency Stability Versus Battery Voltage

Reference Frequency: 1880MHz, Limit: 2.5ppm			
Power Supplied (Vdc)	Environment Temperature (° C)	Frequency Measure with Time Elapsed	
		Error (MHz)	Error (ppm)
3.4	20	1880.0011	0.585

Battery End Point: 3.4V

§24.238 – BAND EDGE

Applicable Standard

According to §24.238, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 30kHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date
Agilent	Spectrum Analyzer	E4464A	NS44300386	2004-11-10
Agilent	Communication Analyzer	E5515C	GB44051221	2004-04-05

* **Statement of Traceability:** **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Environmental Conditions


Temperature:	18° C
Relative Humidity:	48%
ATM Pressure:	1018 mbar

Testing was performed by Daniel Deng on 2005-1-15.

Test Results

Please refer to the following plots.

High Channel:



Low Channel:

