



FCC RF EXPOSURE REPORT

For

Thermal Camera

MODEL NUMBER: DH-TPC-BF1241

ADDITIONAL MODEL NUMBER:

DHa-TPC-BFxyzmn-bcdef-gh-i-jk; TPC-BFxyzmn-bcdef-gh-i-jk (a=l or blank; x=1~9; y=1~9; z=0~9; m=0~9; n=P, N or blank; b=T or blank; c=A~Z or blank; d=1~36 or blank; e=F or blank; f=1~36 or blank; g=A~Z or blank; h=A~Z or blank; i=L, R, NRE, WIFI, AC, DC, LED, 4G, HTM or blank; j=S or blank; k=1-99 or blank)

PROJECT NUMBER: 4790181283

REPORT NUMBER: 4790181283-2

FCC ID: SVN-TPC-BFXYZMN

ISSUE DATE: Mar. 18, 2022

Prepared for

Zhejiang Dahua Vision Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China

Tel: +86 512-6808 6400

Fax: +86 512-6808 4099

Website: www.ul.com

Form-ULID-008536-12 V1.0

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	03/18/2022	Initial Issue	

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. REQUIREMENT	6

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Zhejiang Dahua Vision Technology Co., Ltd.
Address: No.1199, Bin'an road, Binjiang District, Hangzhou, P.R. China.

Manufacturer Information

Company Name: Zhejiang Dahua Vision Technology Co., Ltd.
Address: No.1199, Bin'an road, Binjiang District, Hangzhou, P.R. China.

EUT Description

Product Name Thermal Camera
Model Name DH-TPC-BF1241
Additional No. DHa-TPC-BFxyzmn-bcdef-gh-i-jk; TPC-BFxyzmn-bcdef-gh-i-jk (a=I or blank; x=1~9; y=1~9; z=0~9; m=0~9; n=P, N or blank; b=T or blank; c=A~Z or blank; d=1~36 or blank; e=F or blank; f=1~36 or blank; g=A~Z or blank; h=A~Z or blank; i=L, R, NRE, WIFI, AC, DC, LED, 4G, HTM or blank; j=S or blank; k=1~99 or blank)
Model Difference The difference between models is name of the model.
Sample Number 4617825
Data of Receipt Sample Jan. 20, 2022
Test Date Jan. 20, 2022 ~ Mar. 16, 2022

APPLICABLE STANDARDS


STANDARD

TEST RESULTS

FCC Guidelines for Human Exposure IEEE
C95.1

Complies

Prepared By:




Kitty Li
Engineer

Reviewed By:



Leon Wu
Senior Project Engineer

Authorized By:



Chris Zhong
Laboratory Leader

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and FCC Guidelines for Human Exposure IEEE C95.1.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p>IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. REQUIREMENT

LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

$$S = PG/(4\pi R^2)$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation

WIFI (Worst case)							
Mode	Output Power to Antenna		Antenna Gain		Power Density	Limit	Test Result
11b	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm ²)	(mW/cm ²)	--
	15.0	31.62	2.34	1.71	0.0108	1	Complies

Note: the calculated distance is 20cm.

END OF REPORT