



FCC 47 CFR PART 15 SUBPART C
CERTIFICATION TEST REPORT

For

CONSUMER CAMERA

MODEL NUMBER: DH-IPC-HDBW1435EP-W-S2

ADDITIONAL MODEL NUMBER:

DH-IPC-HDBW1435EN-W-0280B-S2; DH-IPC-HDBW1435EN-W-0360B-S2;
DH-IPC-HDBW1435EP-W-0280B-S2; DH-IPC-HDBW1435EP-W-0360B-S2;
DH-IPC-HDBW1435EN-W-S2; DH-IPC-HDBW1435EP-W-S2;
DH-IPC-HDBW1435E-W-S2; IPC-HDBW1435E-W-0280B-S2;
IPC-HDBW1435E-W-0360B-S2; IPC-HDBW1435E-W-S2;
IPC-D42MP-0280B; IPC-D42MP-0360B; IPC-D42MN-0280B; IPC-D42MN-0360B;
IPC-D42M-0280B; IPC-D42M-0360B; IPC-D42M; IPC-D42MP; IPC-D42MN;

PROJECT NUMBER: 4789491215

REPORT NUMBER: 4789491215-1

FCC ID: SVNDH-IPC-HDB4X-W

ISSUE DATE: Jul. 19, 2020

Prepared for

Zhejiang Dahua Vision Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED
No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China
Tel: +86 512-6808 6400
Fax: +86 512-6808 4099
Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/19/2020	Initial Issue	

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	7
4.2. <i>MEASUREMENT UNCERTAINTY</i>	7
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	8
5.2. <i>MAXIMUM OUTPUT POWER</i>	9
5.3. <i>CHANNEL LIST</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION</i>	10
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	10
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	11
5.7. <i>THE WORSE CASE CONFIGURATIONS</i>	11
5.8. <i>TEST ENVIRONMENT</i>	12
5.9. <i>DESCRIPTION OF TEST SETUP</i>	13
5.10. <i>MEASURING INSTRUMENT AND SOFTWARE USED</i>	14
6. MEASUREMENT METHODS	15
7. ANTENNA PORT TEST RESULTS	16
7.1. <i>ON TIME AND DUTY CYCLE</i>	16
7.2. <i>6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	19
7.3. <i>CONDUCTED OUTPUT POWER</i>	27
7.4. <i>POWER SPECTRAL DENSITY</i>	29
7.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS</i>	37
7.6. <i>RADIATED TEST RESULTS</i>	67
7.6.1. <i>LIMITS AND PROCEDURE</i>	67
7.6.2. <i>TEST ENVIRONMENT</i>	72
7.6.3. <i>RESTRICTED BANDEDGE</i>	72
7.6.4. <i>SPURIOUS EMISSIONS</i>	89
8. AC POWER LINE CONDUCTED EMISSIONS	121
9. ANTENNA REQUIREMENTS	124



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Zhejiang Dahua Vision Technology Co., Ltd.
Address: No.1199, Bin'an road, Binjiang District, Hangzhou, P.R.China.

Manufacturer Information

Company Name: Zhejiang Dahua Vision Technology Co., Ltd.
Address: No.1199, Bin'an road, Binjiang District, Hangzhou, P.R.China.

EUT Description

Product Name: CONSUMER CAMERA
Model Name: DH-IPC-HDBW1435EP-W-S2;
Additional No. : DH-IPC-HDBW1435EN-W-0280B-S2;
DH-IPC-HDBW1435EN-W-0360B-S2;
DH-IPC-HDBW1435EP-W-0280B-S2;
DH-IPC-HDBW1435EP-W-0360B-S2;
DH-IPC-HDBW1435EN-W-S2; DH-IPC-HDBW1435EP-W-S2;
DH-IPC-HDBW1435E-W-S2; IPC-HDBW1435E-W-0280B-S2;
IPC-HDBW1435E-W-0360B-S2; IPC-HDBW1435E-W-S2;
IPC-D42MP-0280B; IPC-D42MP-0360B;
IPC-D42MN-0280B; IPC-D42MN-0360B;
IPC-D42M-0280B; IPC-D42M-0360B; IPC-D42M;
IPC-D42MP; IPC-D42MN;
Sample Number: 3133864
Data of Receipt Sample: Jun. 19, 2020
Date Tested: Jun. 21, 2020 ~ Jul. 13, 2020

APPLICABLE STANDARDS

STANDARD

TEST RESULTS

CFR 47 Part 15 Subpart C

PASS

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6dB Bandwidth	FCC Part 15.247 (a) (2)	Complied
2	Conducted Output Power	FCC Part 15.247 (b) (3)	Complied
3	Power Spectral Density	FCC Part 15.247 (e)	Complied
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Complied
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Complied
6	Conducted Emission Test For AC Power Port	FCC Part 15.207	Complied
7	Antenna Requirement	FCC Part 15.203	Complied

Remark:

1) The measurement result for the sample received is <Pass> according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C> when <Accuracy Method> decision rule is applied.

Prepared By:




Jason Yang
Engineer

Reviewed By:



Tom Tang
Engineer Project Associate

Authorized By:



Chris Zhong
Laboratory Leader

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p>IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.00dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	3.306dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	3.306dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	3.828dB (1GHz-18Gz) 4.130dB (18GHz-26.5Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Product Name:	CONSUMER CAMERA
Model No.:	DH-IPC-HDBW1435EP-W-S2
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n (HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Channels Step:	Channels with 5MHz step
Sample Type:	Fixed production
Test power grade:	N/A
Test software of EUT:	Secure CRT (manufacturer declare)
Antenna Type:	Rod Antenna
Antenna Gain:	4.01 dBi
Power Supply	Model:ADS-12AM-12 12012EPCU Input:100-240V-50/60Hz MAX 0.3A Output:12.0V=1.0A

Remark:

Model No.:

Number	Name	Number	Name	Number	Name
1	DH-IPC-HDBW1435EP-W-S2	2	DH-IPC-HDBW1435EN-W-0280B-S2	3	DH-IPC-HDBW1435EN-W-0360B-S2
4	DH-IPC-HDBW1435EP-W-0280B-S2	5	DH-IPC-HDBW1435EP-W-0360B-S2	6	DH-IPC-HDBW1435EN-W-S2
7	DH-IPC-HDBW1435EP-W-S2	8	DH-IPC-HDBW1435E-W-S2	9	IPC-HDBW1435E-W-0280B-S2
10	IPC-HDBW1435E-W-0360B-S2	11	IPC-HDBW1435E-W-S2	12	IPC-D42MP-0280B
13	IPC-D42MP-0360B	14	IPC-D42MN-0280B	15	IPC-D42MN-0360B
16	IPC-D42M-0280B	17	IPC-D42M-0360B; IPC-D42M	18	IPC-D42MP
19	IPC-D42MN				

Only the main model DH-IPC-HDBW1435EP-W-S2 was tested and only the data of this model is shown in this test report. Since Their electrical circuit design, layout, components used and internal wiring are identical, only the model name and selling area are different.

5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Channel Number	Max Peak Conducted Power (dBm)	Max AVG Conducted Power (dBm)
1	IEEE 802.11B	1-11[11]	14.79	11.78
1	IEEE 802.11G	1-11[11]	17.07	8.89
1	IEEE 802.11nHT20	1-11[11]	17.14	8.63
1	IEEE 802.11nHT40	3-9[7]	N/A	6.57

5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452		

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447		

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel (MHz)
IEEE 802.11B	LCH: CH01 2412
	MCH: CH06 2437
	HCH: CH11 2462
IEEE 802.11G	LCH: CH01 2412
	MCH: CH06 2437
	HCH: CH11 2462
IEEE 802.11n HT20	LCH: CH01 2412
	MCH: CH06 2437
	HCH: CH11 2462
IEEE 802.11n HT40	LCH: CH03 2422
	MCH: CH06 2437
	HCH: CH09 2452

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		SecureCRT					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	N/A	N/A	N/A	/		
802.11g	1	N/A	N/A	N/A			
802.11n HT20	1	N/A	N/A	N/A			
802.11n HT40	1	/		N/A	N/A	N/A	

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2400-2483.5	Rod Antenna	4.01

Remark: The antenna gain is provided by customer and our lab isn't responsible for it.

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	The antenna can be used as transmitting/receiving antenna independently.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	The antenna can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT20)	<input checked="" type="checkbox"/> 1TX, 1RX	The antenna can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT40)	<input checked="" type="checkbox"/> 1TX, 1RX	The antenna can be used as transmitting/receiving antenna independently.

5.7. THE WORSE CASE CONFIGURATIONS

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11b mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0

5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	23 ~ 28°C
Voltage:	VL	N/A
	VN	AC 24V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature

5.9. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Description
1	Laptop	ThinkPad	E590	N/A

I/O PORT

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB to TTL	USB	100cm Length	N/A
2	LAN	LAN	LAN	100cm Length	N/A


ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	SD Card	Kingston	32GB	Supply by UL Lab
2	12V DC Adapter	HONOTO	ADS-12AM-12 12012EPCU	N/A

TEST SETUP

The EUT can work in an engineer mode with a software through a table PC.

SETUP DIAGRAM FOR TESTS





5.10. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	126700	2018-12-08	2019-12-07	2020-12-06
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	126701	2018-12-08	2019-12-07	2020-12-06
<input checked="" type="checkbox"/>	Artificial Mains Networks	R&S	ENY81	126711	2018-10-15	2019-10-14	2020-10-13
Software							
Used	Description		Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		R&S	EMC32	Ver. 9.25		
Radiated Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	MY57110128	2019-05-11	2020-05-10	2021-05-09
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR26	1267603	2018-12-08	2019-12-07	2020-12-06
<input checked="" type="checkbox"/>	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	513-265	2019-06-16	2020-06-15	2021-06-14
<input checked="" type="checkbox"/>	Receiver Antenna (30MHz-1GHz)	SunAR RF Motion	JB1	126704	N/A	2019-01-28	2022-01-27
<input checked="" type="checkbox"/>	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2018-01-28	2019-01-27	2022-01-26
<input checked="" type="checkbox"/>	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2018-01-06	2019-01-05	2022-01-04
<input checked="" type="checkbox"/>	Receiver Antenna (26.5GHz-40GHz)	TOYO	HAP 26-40W	00000012	2018-07-24	2019-07-23	2020-07-22
<input checked="" type="checkbox"/>	Pre-amplification (To 1GHz)	R&S	SCU-03D	134666	2018-12-08	2019-12-07	2020-12-06
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	Compliance Direction System Inc.	PAP-1G18-50	14140-13467	2019-02-21	2020-02-20	2021-02-19
<input checked="" type="checkbox"/>	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	134668	2019-01-03	2020-01-02	2021-01-01
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	1	2019-05-29	2020-05-28	2021-05-27
<input checked="" type="checkbox"/>	Highpass Filter	Wainwright	WHKX10-2700-3000-18000-40SS	2	2019-05-29	2020-05-28	2022-05-27
Software							
Used	Description		Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Tonscend	JS32	V1.0		
Other instruments							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	MY57110128	2019-05-11	2020-05-10	2021-05-09
<input checked="" type="checkbox"/>	Power Meter	Keysight	U2021XA	MY57110002	2019-05-11	2020-05-10	2021-05-09

6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 24V



RESULTS



Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)
11B	12.41	12.475	0.9948	99.48%	0.02	0.08
11G	2.063	2.3046	0.8952	89.52%	0.48	0.48
802.11n HT20	1.919	2.176	0.8819	88.19%	0.54	0.52
802.11n HT40	0.943	1.1845	0.7961	79.61%	0.99	1.06

Note: 1) Duty Cycle Correction Factor=10log(1/x).

2) Where: x is Duty Cycle (Linear)

3) Where: T is On Time (transmit duration)





7.2. 6 dB BANDWIDTH

LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5


TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100kHz
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple



Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



TEST SETUP







RESULTS



Test Mode	Test Channel	6dB bandwidth (MHz)	Result
11B	LCH	9.035	Pass
	MCH	8.567	Pass
	HCH	8.565	Pass
11G	LCH	16.36	Pass
	MCH	16.34	Pass
	HCH	16.37	Pass
11n HT20	LCH	17.56	Pass
	MCH	17.57	Pass
	HCH	17.56	Pass
11n HT40	LCH	36.29	Pass
	MCH	36.03	Pass
	HCH	36.07	Pass



Test Graphs












7.3. CONDUCTED OUTPUT POWER

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5

Note: For b/g/n HT20 mode the average data is for reference only.

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.

Measure the power of each channel.


Peak Detector used for Peak result.

AVG Detector used for AVG result.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 24V

TEST SETUP



RESULTS

Test Mode	Test Channel	Maximum Conducted Output Power (PK)	Maximum Conducted Output Power (AV)	LIMIT
		dBm	dBm	dBm
11B	LCH	14.79	11.78	30
	MCH	13.14	10.45	30
	HCH	13.59	10.89	30
11G	LCH	17.07	8.89	30
	MCH	16.42	8.16	30
	HCH	16.92	8.68	30
11n HT20	LCH	17.14	8.63	30
	MCH	16.47	7.97	30
	HCH	17.07	8.50	30
11n HT40	LCH	N/A	5.94	30
	MCH	N/A	5.87	30
	HCH	N/A	6.57	30

7.4. POWER SPECTRAL DENSITY

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST ENVIRONMENT



Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 24V



TEST SETUP







RESULTS



Test Mode	Test Channel	Maximum Peak power spectral density (dBm/30kHz)	Result
11B	LCH	-0.41	Pass
	MCH	-0.66	Pass
	HCH	-1.49	Pass
11G	LCH	-6.47	Pass
	MCH	-7.76	Pass
	HCH	-6.63	Pass
11n HT20	LCH	-6.76	Pass
	MCH	-7.44	Pass
	HCH	-6.76	Pass
11n HT40	LCH	-9.85	Pass
	MCH	-10.03	Pass
	HCH	-9.46	Pass



Test Graphs:












7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

LIMITS

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	For b/g/n HT20 modes: at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power For HT40 mode: at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times$ RBW
Span	$1.5 \times$ DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times$ RBW
measurement points	\geq span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUP**TEST ENVIRONMENT**

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 24V

Part I :Conducted Bandedge**RESULTS TABLE**

Test Mode	Test Channel	Carrier Power [dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	3.296	-41.30	-16.70	PASS
	HCH	2.758	-41.49	-17.24	PASS
11G	LCH	-1.802	-40.57	-21.80	PASS
	HCH	-2.014	-41.34	-22.01	PASS
11N HT20	LCH	-1.806	-41.87	-21.81	PASS
	HCH	-2.400	-41.15	-22.40	PASS
11N HT40	LCH	-4.967	-41.37	-34.97	PASS
	HCH	-4.655	-40.56	-34.66	PASS

TEST GRAPHS

Test Mode	Test Channel	Verdict
11B SISO	LCH	PASS

Spectrum Analyzer 1
 Swept SA

KEYSIGHT Input: RF Input Z: 50 Ω #Atten: 40 dB PNO: Fast
 Coupling: DC Corrections: Off Preamp: Off #Avg Type: Power (RMS)
 R.L. Align: Auto/No RF Freq Ref: Int (S) Gate: Off Avg|Hold: 100/100
 LN IF Gain: Low Trig: Free Run Sig Track: Off

1 Spectrum Ref Lvl Offset 8.55 dB Ref Level 30.00 dBm Mkr4 2.374 950 0 GHz -41.30 dBm

Scale/Div 10 dB Log 10.00 0.00 -10.00 -20.00 -30.00 -40.00 -50.00 -60.00

Center 2.40000 GHz #Video BW 300 kHz Span 100.0 MHz Sweep 0.60 ms (8001 pts)

5 Marker Table

Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.412 987 5 GHz	3.296 dBm		
2	N	1	f	2.400 000 0 GHz	-43.90 dBm		
3	N	1	f	2.390 000 0 GHz	-43.73 dBm		
4	N	1	f	2.374 950 0 GHz	-41.30 dBm		
5							
6							

Jun 19, 2020 7:44:45 PM

Frequency: 2.40000000 GHz
 Span: 100.000000 MHz
 Full Span
 Start Freq: 2.35000000 GHz
 Stop Freq: 2.45000000 GHz
 AUTO TUNE
 CF Step: 10.000000 MHz
 Auto
 Man
 Freq Offset: 0 Hz
 X Axis Scale: Log
 Signal Track (Span Zoom)

Test Mode	Test Channel	Verdict
11B SISO	HCH	PASS

Spectrum Analyzer 1
 Swept SA

KEYSIGHT Input: RF Input Z: 50 Ω #Atten: 40 dB PNO: Fast
 Coupling: DC Corrections: Off Preamp: Off #Avg Type: Power (RMS)
 R.L. Align: Auto/No RF Freq Ref: Int (S) Gate: Off Avg|Hold: 100/100
 LN IF Gain: Low Trig: Free Run Sig Track: Off

1 Spectrum Ref Lvl Offset 8.51 dB Ref Level 30.00 dBm Mkr4 2.488 600 0 GHz -41.49 dBm

Scale/Div 10 dB Log 10.00 0.00 -10.00 -20.00 -30.00 -40.00 -50.00 -60.00

Center 2.48350 GHz #Video BW 300 kHz Span 100.0 MHz Sweep 0.60 ms (8001 pts)

5 Marker Table

Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.462 500 0 GHz	2.758 dBm		
2	N	1	f	2.483 500 0 GHz	-43.77 dBm		
3	N	1	f	2.500 000 0 GHz	-44.44 dBm		
4	N	1	f	2.488 600 0 GHz	-41.49 dBm		
5							
6							

Jun 19, 2020 7:51:28 PM

Frequency: 2.48350000 GHz
 Span: 100.000000 MHz
 Full Span
 Start Freq: 2.43350000 GHz
 Stop Freq: 2.53350000 GHz
 AUTO TUNE
 CF Step: 10.000000 MHz
 Auto
 Man
 Freq Offset: 0 Hz
 X Axis Scale: Log
 Signal Track (Span Zoom)

