



Puw test Plot





Test Mode	Channel	Verdict
11G	MCH	PASS

Pref test Plot



Puw test Plot





Test Mode	Channel	Verdict
11G	HCH	PASS

Pref test Plot



Puw test Plot





Test Mode	Channel	Verdict
11N HT20	LCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11N HT20	MCH	PASS

Pref test Plot



Puw test Plot





Test Mode	Channel	Verdict
11N HT20	HCH	PASS

Pref test Plot




Puw test Plot





For Antenna 2 Part:

Test Mode	Channel	Verdict
11B	LCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11B	MCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11B	HCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11G	LCH	PASS

Pref test Plot



Puw test Plot





Test Mode	Channel	Verdict
11G	MCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11G	HCH	PASS

Pref test Plot

HCH SPURIOUS EMISSION




Puw test Plot





Test Mode	Channel	Verdict
11N HT20	LCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11N HT20	MCH	PASS

Pref test Plot




Puw test Plot





Test Mode	Channel	Verdict
11N HT20	HCH	PASS

Pref test Plot

HCH SPURIOUS EMISSION



Puw test Plot



7.7. RADIATED TEST RESULTS

7.7.1. LIMITS AND PROCEDURE

LIMITS

Please refer to FCC §15.205 and §15.209 (Transmitter)

Radiation Disturbance Test Limit for ISED(9KHz-1GHz)

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54


Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration)

ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK:3M AVG: See note6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements; and 1 MHz resolution bandwidth with video bandwidth $\geq 1/T$ but not less than the setting list in section 7.1 when use peak detector, max hold to be run for at least $[50^*(1/\text{Duty Cycle})]$ traces for average measurements. For the Duty Cycle need to refer the results in section 7.2.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (Z axis) data recorded in the report.

7.7.2. RESTRICTED BANDEDGE

TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests
Relative Humidity	59.6%
Atmospheric Pressure:	102.6kPa
Temperature	19.2°C

Test Result Table


Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B	Antenna 2	LCH	<Limit	PASS
		HCH	<Limit	PASS
11G	Antenna 2	LCH	<Limit	PASS
		HCH	<Limit	PASS
11N HT20 MIMO	Antenna 1+2	LCH	<Limit	PASS
		HCH	<Limit	PASS

Remark:

- 1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 mode can support both the SISO and MIMO technical.
- 2) Through pre-testing all the test modes of 11N HT20, including SISO and MIMO, but only the data of worse case is included in this test report.
- 3) Pre-testing both antenna 1 and antenna 2 of 11B and 11G modes, find antenna 2 which is worse case, so only the data of antenna 2 is included in this report.


Test Graphs:

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2360.6451	40.41	12.78	53.19	74.00	-20.81	peak
2	2390.0000	39.58	13.07	52.65	74.00	-21.35	peak


Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2385.6795	41.91	13.06	54.97	74.00	-19.03	peak
		28.86	13.06	41.92	54.00	-12.08	average
2	2390.0000	39.82	13.07	52.89	74.00	-21.11	peak


Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11B	HCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.5000	39.99	12.97	52.96	74.00	-21.04	peak
2	2542.9329	42.54	13.40	55.94	74.00	-18.06	peak
		29.05	13.40	42.45	54.00	-11.55	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
1	2483.5000	43.34	12.97	56.31	74.00	-17.69	peak
		29.13	12.97	42.10	54.00	-11.9	average
2	2498.6023	46.22	13.12	59.34	74.00	-14.66	peak
		29.22	13.12	42.34	54.00	-11.66	average

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS



No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2379.1536	42.92	13.05	55.97	74.00	-18.03	peak
		28.97	13.05	42.02	54.00	-11.98	average
2	2390.0000	39.91	13.07	52.98	74.00	-21.02	peak

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2378.3473	41.51	13.04	54.55	74.00	-19.45	peak
		29.01	13.04	42.05	54.00	-11.95	average
2	2390.0000	42.31	13.07	55.38	74.00	-18.62	peak
		29.14	13.07	42.21	54.00	-11.79	average


Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.5000	40.23	12.97	53.20	74.00	-20.8	peak
2	2510.3713	41.78	13.20	54.98	74.00	-19.02	peak
		29.28	13.20	42.48	54.00	-11.52	average


Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



No.	Frequency (MHz)	Reading Level	Correct Factor	Result	Limit	Margin	Remark
		(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1	2483.5000	42.36	12.97	55.33	74.00	-18.67	peak
		29.34	12.97	42.31	54.00	-11.69	average
2	2531.5464	42.13	13.42	55.55	74.00	-18.45	peak
		29.51	13.42	42.93	54.00	-11.07	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2350.1438	40.90	12.69	53.59	74.00	-20.41	peak
2	2390.0000	39.51	13.07	52.58	74.00	-21.42	peak

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2378.6098	41.95	13.04	54.99	74.00	-19.01	peak
		29.22	13.04	42.26	54.00	-11.74	average
2	2390.0000	42.52	13.07	55.59	74.00	-18.41	peak
		30.04	13.07	43.11	54.00	-10.89	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11N HT20	HCH	Horizontal	PASS



No.	Frequency (MHz)	Reading Level	Correct Factor	Result	Limit	Margin	Remark
		(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1	2483.5000	41.25	12.97	54.22	74.00	-19.78	peak
		29.23	12.97	42.20	54.00	-11.80	average
2	2514.9844	41.25	13.21	54.46	74.00	-19.54	peak
		29.45	13.21	42.66	54.00	-11.34	average

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
1	2483.5000	43.35	12.97	56.32	74.00	-17.68	peak
		30.44	12.97	43.41	54.00	-10.59	average
2	2506.9284	41.82	13.18	55.00	74.00	-19	peak
		29.29	13.18	42.47	54.00	-11.53	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

7.7.3. SPURIOUS EMISSIONS

Test Result Table:

1) For 1GHz~3GHz

Environment Parameter		Selected Values During Tests	
Relative Humidity		59.6%	
Atmospheric Pressure:		102.6kPa	
Temperature		19.2°C	

Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B SISO	Antenna 2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11G SISO	Antenna 2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11N HT20 MIMO	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS

Remark:

- 1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 mode can support both the SISO and MIMO technical.
- 2) Pre-testing both antenna 1 and antenna 2 of 11B and 11G modes, find antenna 2 which is worse case, so only the data of antenna 2 is included in this report.
- 3) Through pre-testing all the test modes of 11N HT20, including SISO and MIMO, but only the data of worse case is included in this test report.

2) For 3GHz~18GHz

Environment Parameter		Selected Values During Tests	
Relative Humidity		59.6%	
Atmospheric Pressure:		102.6kPa	
Temperature		19.2°C	

Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B SISO	Antenna 2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11G SISO	Antenna 2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11N HT20	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS



		HCH	<Limit	PASS
--	--	-----	--------	------

Remark:

1) For this product, it has two antennas, antenna1 and antenna2, but only the 802.11N HT20 mode can support both the SISO and MIMO technical.

2) Pre-testing both antenna 1 and antenna 2 of 11B and 11G modes, find antenna 2 which is worse case, so only the data of antenna 2 is included in this report.

3) Through pre-testing all the test modes of 11N HT20, including SISO and MIMO, but only the data of worse case is included in this test report.

3) For 18GHz~26.5GHz

Environment Parameter		Selected Values During Tests		
Relative Humidity		59.6%		
Atmospheric Pressure:		102.6kPa		
Temperature		19.2°C		

Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B	Antenna 2	LCH	<Limit	PASS

Remark:

1) Through pre-testing all the test modes, antennas and test channels, but only the data of the worst case is included in this test report.

4) For 30MHz~1GHz

Environment Parameter		Selected Values During Tests		
Relative Humidity		60.2%		
Atmospheric Pressure:		102.1kPa		
Temperature		18.6°C		

Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B	Antenna 2	LCH	<Limit	PASS

Remark:

1) Through pre-testing all the test modes, antennas and test channels, but only the data of the worst case is included in this test report.

5) For 9KHz~30MHz

Environment Parameter		Selected Values During Tests		
Relative Humidity		60.2%		
Atmospheric Pressure:		102.1kPa		
Temperature		18.6°C		


Test Mode	Test Antenna	Channel	Puw(dBm)	Verdict
11B	Antenna 2	LCH	<Limit	PASS

Remark:

1) Through pre-testing all the test modes, antennas and test channels, but only the data of the worst case is included in this test report.

Part I: 1GHz~3GHz**HARMONICS AND SPURIOUS EMISSIONS**

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1200.7500	43.39	-5.54	37.85	74.00	-36.15	peak
2	1417.5000	41.88	-5.69	36.19	74.00	-37.81	peak
3	1583.7500	41.59	-5.27	36.32	74.00	-37.68	peak
4	1792.5000	46.21	-3.76	42.45	74.00	-31.55	peak
5	2194.0000	44.74	-2.33	42.41	74.00	-31.59	peak
6	2870.5000	41.62	0.15	41.77	74.00	-32.23	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11B	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1247.5000	44.24	-5.64	38.60	74.00	-35.40	peak
2	1396.5000	47.59	-5.70	41.89	74.00	-32.11	peak
3	1792.2500	47.96	-3.76	44.20	74.00	-29.80	peak
4	1993.2500	46.91	-3.06	43.85	74.00	-30.15	peak
5	2292.5000	51.09	-1.92	49.17	74.00	-24.83	peak
6	2967.2500	41.29	1.07	42.36	74.00	-31.64	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11B	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1199.2500	44.31	-5.56	38.75	74.00	-35.25	peak
2	1277.2500	42.28	-5.57	36.71	74.00	-37.29	peak
3	1584.0000	42.80	-5.25	37.55	74.00	-36.45	peak
4	1797.2500	49.33	-3.82	45.51	74.00	-28.49	peak
5	2323.7500	43.68	-1.72	41.96	74.00	-32.04	peak
6	2967.5000	41.35	1.07	42.42	74.00	-31.58	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11B	MCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1199.5000	44.61	-5.56	39.05	74.00	-34.95	peak
2	1412.0000	41.98	-5.45	36.53	74.00	-37.47	peak
3	1598.7500	43.62	-5.15	38.47	74.00	-35.53	peak
4	1792.0000	48.69	-3.76	44.93	74.00	-29.07	peak
5	2279.7500	53.98	-1.94	52.04	74.00	-21.96	peak
6	2637.7500	43.67	-0.81	42.86	74.00	-31.14	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1	1197.7500	45.34	-5.56	39.78	74.00	-34.22	peak
2	1395.2500	42.11	-5.71	36.40	74.00	-37.60	peak
3	1798.7500	45.86	-3.83	42.03	74.00	-31.97	peak
4	2178.0000	42.53	-2.33	40.20	74.00	-33.80	peak
5	2321.7500	44.82	-1.69	43.13	74.00	-30.87	peak
6	2905.2500	41.61	0.39	42.00	74.00	-32.00	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11B	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1196.2500	45.24	-5.56	39.68	74.00	-34.32	peak
2	1401.5000	44.92	-5.61	39.31	74.00	-34.69	peak
3	1597.7500	42.40	-5.13	37.27	74.00	-36.73	peak
4	1792.5000	43.86	-3.76	40.10	74.00	-33.90	peak
5	2250.5000	48.15	-2.07	46.08	74.00	-27.92	peak
6	2627.0000	44.90	-0.58	44.32	74.00	-29.68	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1104.0000	43.37	-5.55	37.82	74.00	-36.18	peak
2	1193.5000	42.88	-5.57	37.31	74.00	-36.69	peak
3	1399.7500	44.60	-5.66	38.94	74.00	-35.06	peak
4	1792.5000	45.02	-3.76	41.26	74.00	-32.74	peak
5	2183.0000	43.97	-2.33	41.64	74.00	-32.36	peak
6	2903.5000	41.44	0.37	41.81	74.00	-32.19	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1129.5000	45.54	-5.46	40.08	74.00	-33.92	peak
2	1396.5000	43.52	-5.70	37.82	74.00	-36.18	peak
3	1796.0000	49.80	-3.80	46.00	74.00	-28.00	peak
4	1997.5000	44.42	-3.01	41.41	74.00	-32.59	peak
5	2278.0000	49.97	-1.97	48.00	74.00	-26.00	peak
6	2969.0000	41.53	1.09	42.62	74.00	-31.38	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1195.0000	49.98	-5.57	44.41	74.00	-29.59	peak
2	1353.5000	41.76	-5.46	36.30	74.00	-37.70	peak
3	1510.7500	42.16	-5.65	36.51	74.00	-37.49	peak
4	1796.2500	44.32	-3.80	40.52	74.00	-33.48	peak
5	2172.2500	43.25	-2.32	40.93	74.00	-33.07	peak
6	2958.5000	41.37	0.96	42.33	74.00	-31.67	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1149.2500	44.67	-5.61	39.06	74.00	-34.94	peak
2	1393.7500	45.18	-5.73	39.45	74.00	-34.55	peak
3	1596.5000	43.93	-5.10	38.83	74.00	-35.17	peak
4	1793.5000	49.04	-3.77	45.27	74.00	-28.73	peak
5	2303.2500	50.36	-1.79	48.57	74.00	-25.43	peak
6	2518.7500	47.44	-0.33	47.11	74.00	-26.89	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1104.0000	43.37	-5.55	37.82	74.00	-36.18	peak
2	1193.5000	42.88	-5.57	37.31	74.00	-36.69	peak
3	1399.7500	44.60	-5.66	38.94	74.00	-35.06	peak
4	1792.5000	45.02	-3.76	41.26	74.00	-32.74	peak
5	2183.0000	43.97	-2.33	41.64	74.00	-32.36	peak
6	2903.5000	41.44	0.37	41.81	74.00	-32.19	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11G	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1129.5000	45.54	-5.46	40.08	74.00	-33.92	peak
2	1396.5000	43.52	-5.70	37.82	74.00	-36.18	peak
3	1796.0000	49.80	-3.80	46.00	74.00	-28.00	peak
4	1997.5000	44.42	-3.01	41.41	74.00	-32.59	peak
5	2278.0000	49.97	-1.97	48.00	74.00	-26.00	peak
6	2969.0000	41.53	1.09	42.62	74.00	-31.38	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1198.5000	47.33	-5.56	41.77	74.00	-32.23	peak
2	1399.0000	42.82	-5.67	37.15	74.00	-36.85	peak
3	1596.2500	43.13	-5.09	38.04	74.00	-35.96	peak
4	1795.0000	45.73	-3.79	41.94	74.00	-32.06	peak
5	2195.5000	43.86	-2.33	41.53	74.00	-32.47	peak
6	2757.5000	41.88	-0.32	41.56	74.00	-32.44	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1196.2500	45.22	-5.56	39.66	74.00	-34.34	peak
2	1399.0000	47.53	-5.67	41.86	74.00	-32.14	peak
3	1597.5000	43.65	-5.12	38.53	74.00	-35.47	peak
4	1795.5000	49.37	-3.80	45.57	74.00	-28.43	peak
5	2300.2500	49.75	-1.85	47.90	74.00	-26.10	peak
6	2544.2500	47.63	-0.97	46.66	74.00	-27.34	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
11N HT20	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1195.0000	49.98	-5.57	44.41	74.00	-29.59	peak
2	1353.5000	41.76	-5.46	36.30	74.00	-37.70	peak
3	1510.7500	42.16	-5.65	36.51	74.00	-37.49	peak
4	1796.2500	44.32	-3.80	40.52	74.00	-33.48	peak
5	2172.2500	43.25	-2.32	40.93	74.00	-33.07	peak
6	2958.5000	41.37	0.96	42.33	74.00	-31.67	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
11N HT20	MCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1149.2500	44.67	-5.61	39.06	74.00	-34.94	peak
2	1393.7500	45.18	-5.73	39.45	74.00	-34.55	peak
3	1596.5000	43.93	-5.10	38.83	74.00	-35.17	peak
4	1793.5000	49.04	-3.77	45.27	74.00	-28.73	peak
5	2303.2500	50.36	-1.79	48.57	74.00	-25.43	peak
6	2518.7500	47.44	-0.33	47.11	74.00	-26.89	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	1198.5000	47.68	-5.56	42.12	74.00	-31.88	peak
2	1398.5000	44.35	-5.67	38.68	74.00	-35.32	peak
3	1599.2500	42.85	-5.16	37.69	74.00	-36.31	peak
4	1792.5000	44.97	-3.76	41.21	74.00	-32.79	peak
5	2214.7500	43.00	-2.28	40.72	74.00	-33.28	peak
6	2957.2500	41.31	0.93	42.24	74.00	-31.76	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. AVG: VBW refer to section 7.2.
6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
The proper operation of the transmitter prior to adding the filter to the measurement chain.
7. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.