

FCC REPORT

Applicant: SHENZHEN GOTRON ELECTRONIC CO.,LTD

Address of Applicant: Rm 24B,Block C of Electronic &Technology Building, 2070
ShenNan Middle Road,Shenzhen,China

Equipment Under Test (EUT)

Product Name: Ulefone Mobile Phone

Model No.: Armor 2, Armor 2X, Armor 2S

Trade mark: ulefone

FCC ID: SW9ARMOR2

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 21 Jun., 2017

Date of Test: 21 Jun., to 12 Jul., 2017

Date of report issued: 12 Jul., 2017

Test Result: Pass *

*In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	12 Jul., 2017	Original

Tested by:

M. Liang

Date:

12 Jul., 2017

Test Engineer

Reviewed by:

Ryan. Lee

Date:

12 Jul., 2017

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY.....	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST MODE.....	5
5.4	MEASUREMENT UNCERTAINTY.....	5
5.5	DESCRIPTION OF SUPPORT UNITS	6
5.6	LABORATORY FACILITY	6
5.7	LABORATORY LOCATION	6
5.8	TEST INSTRUMENTS LIST.....	7
6	TEST RESULTS AND MEASUREMENT DATA.....	8
6.1	CONDUCTED EMISSION.....	8
6.2	RADIATED EMISSION	11
7	TEST SETUP PHOTO	17
8	EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	SHENZHEN GOTRON ELECTRONIC CO.,LTD
Address of Applicant:	Rm 24B,Block C of Electronic &Technology Building, 2070 ShenNan Middle Road,Shenzhen,China
Manufacturer	SHENZHEN GOTRON ELECTRONIC CO.,LTD
Address of Manufacturer:	Rm 24B,Block C of Electronic &Technology Building, 2070 ShenNan Middle Road,Shenzhen,China

5.2 General Description of E.U.T.

Product Name:	Ulefone Mobile Phone
Model No.:	Armor 2, Armor 2X, Armor 2S
Power supply:	Rechargeable Li-ion Battery DC3.8V-4700mAh
AC adapter :	Model: APS-KI018WU-G Input: AC100-240V 50/60Hz 0.5A Output: DC 5V/7V/9V, 2000mA, DC 12V, 1500mA
Remark:	The No.: Armor 2, Armor 2X, Armor 2S were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.7 Laboratory Location

Shenzhen ZhongjianNanfang Testing Co., Ltd.
 Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Website: <http://www.ccis-cb.com>
 Tel: +86-755-23118282
 Fax: +86-755-23116366
 Email: info@ccis-cb.com


5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	02-25-2017	02-24-2018
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	02-25-2017	02-24-2018
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	02-25-2017	02-24-2018
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	02-25-2017	02-24-2018
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	02-25-2017	02-24-2018
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	02-25-2017	02-24-2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	N/A	N/A	CCIS0018	02-25-2017	02-24-2018
10	Coaxial Cable	N/A	N/A	CCIS0020	02-25-2017	02-24-2018

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	02-25-2017	02-24-2018
3	LISN	CHASE	MN2050D	CCIS0074	02-25-2017	02-24-2018
4	Coaxial Cable	CCIS	N/A	CCIS0086	02-25-2017	02-24-2018
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)	Limit (dBμV)				
		Quasi-peak		Average		
	0.15-0.5	66 to 56*		56 to 46*		
	0.5-5	56		46		
	0.5-30	60		50		
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014on conducted measurement.					
Test environment:	Temp.:	23°C	Humid.:	56%	Press.:	101kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

Measurement data:

Line:



Trace: 15


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test Mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: MT
 Remark :

	Freq	Read	LISN	Cable	Limit	Over	
	MHz	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dB	
1	0.154	32.24	0.14	10.78	43.16	65.78	-22.62 QP
2	0.154	27.35	0.14	10.78	38.27	55.78	-17.51 Average
3	0.258	25.59	0.16	10.75	36.50	61.51	-25.01 QP
4	0.262	22.61	0.16	10.75	33.52	51.38	-17.86 Average
5	2.993	25.86	0.33	10.92	37.11	56.00	-18.89 QP
6	2.993	24.12	0.33	10.92	35.37	46.00	-10.63 Average
7	3.642	21.72	0.34	10.90	32.96	46.00	-13.04 Average
8	4.158	25.93	0.34	10.88	37.15	56.00	-18.85 QP
9	10.125	24.91	0.30	10.94	36.15	50.00	-13.85 Average
10	10.288	31.50	0.30	10.94	42.74	60.00	-17.26 QP
11	23.387	33.79	0.35	10.89	45.03	60.00	-14.97 QP
12	23.511	25.89	0.35	10.88	37.12	50.00	-12.88 Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Trace: 13



Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test Mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: MT
 Remark :

	Freq	Read	LISN	Cable	Level	Limit	Over	
	MHz	Level	Factor	Loss	dBuV	Line	Limit	Remark
		dBuV	dB	dB		dBuV	dB	
1	0.158	22.92	0.13	10.78	33.83	55.56	-21.73	Average
2	0.170	33.23	0.13	10.77	44.13	64.94	-20.81	QP
3	0.182	17.33	0.14	10.77	28.24	54.42	-26.18	Average
4	0.258	28.75	0.17	10.75	39.67	61.51	-21.84	QP
5	0.258	16.67	0.17	10.75	27.59	51.51	-23.92	Average
6	3.584	16.84	0.33	10.90	28.07	56.00	-27.93	QP
7	9.966	11.38	0.24	10.94	22.56	50.00	-27.44	Average
8	10.397	19.26	0.24	10.94	30.44	60.00	-29.56	QP
9	16.750	18.62	0.27	10.91	29.80	50.00	-20.20	Average
10	16.839	25.61	0.27	10.91	36.79	60.00	-23.21	QP
11	23.511	28.08	0.24	10.88	39.20	60.00	-20.80	QP
12	23.636	21.46	0.24	10.88	32.58	50.00	-17.42	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 26000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:					Remark
	Frequency				Limit (dBuV/m @3m)
	30MHz-88MHz				40.0
	88MHz-216MHz				43.5
	216MHz-960MHz				46.0
	960MHz-1GHz				54.0
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25°C	Humid.:	55%	Press.:	101kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					
Remark:	All of the observed value above 6GHz were then noise floor, which were not recorded					

Measurement Data:

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test mode : PC mode
 Power Rating : AC120V / 60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp		Limit	Over	
	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	135.032	46.72	11.98	2.34	29.30	31.74	43.50	-11.76 QP
2	165.487	54.42	9.84	2.62	29.09	37.79	43.50	-5.71 QP
3	285.978	52.30	12.26	2.90	28.47	38.99	46.00	-7.01 QP
4	374.623	43.41	15.03	3.09	28.67	32.86	46.00	-13.14 QP
5	564.639	38.41	18.21	3.90	29.05	31.47	46.00	-14.53 QP
6	721.726	36.37	19.76	4.26	28.58	31.81	46.00	-14.19 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test mode : PC mode
 Power Rating : AC120V / 60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	47.659	42.07	16.22	1.27	29.84	29.72	40.00 -10.28 QP
2	165.487	52.82	9.84	2.62	29.09	36.19	43.50 -7.31 QP
3	285.978	52.86	12.26	2.90	28.47	39.55	46.00 -6.45 QP
4	374.623	43.38	15.03	3.09	28.67	32.83	46.00 -13.17 QP
5	432.546	43.25	16.10	3.16	28.84	33.67	46.00 -12.33 QP
6	721.726	36.88	19.76	4.26	28.58	32.32	46.00 -13.68 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test mode : PC mode
 Power Rating : AC120V / 60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
		Level	Factor	Loss	Factor	Level	Line
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	3339.610	48.62	27.14	5.56	41.37	39.95	74.00
2	3339.610	39.62	27.14	5.56	41.37	30.95	54.00
3	3895.981	50.14	31.44	6.10	41.80	45.88	74.00
4	3895.981	41.46	31.44	6.10	41.80	37.20	54.00
5	4830.532	49.36	36.12	6.82	41.82	50.48	74.00
6	4830.532	42.25	36.12	6.82	41.82	43.37	54.00

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Ulefone MobilePhone
 Model : Armor 2
 Test mode : PC mode
 Power Rating : AC120V / 60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: MT
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3245.229	48.63	26.72	5.47	41.40	39.42	74.00	-34.58	Peak
2	3245.229	39.23	26.72	5.47	41.40	30.02	54.00	-23.98	Average
3	3895.981	49.97	31.44	6.10	41.80	45.71	74.00	-28.29	Peak
4	3895.981	40.11	31.44	6.10	41.80	35.85	54.00	-18.15	Average
5	4979.933	48.26	36.77	6.92	41.87	50.08	74.00	-23.92	Peak
6	4979.933	39.58	36.77	6.92	41.87	41.40	54.00	-12.60	Average