

**King Chuang Tech & Electronic Co., Ltd.**

Application  
For  
Certification  
**(FCC ID: SWJKC-2616)**

PS3 Wireless Controller (Remote Controller Unit)

0715333(S1)  
BH/ SL  
August 24, 2007

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

**Intertek Testing Services Hong Kong Ltd.**

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.  
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: [www.hk.intertek-etlsemko.com](http://www.hk.intertek-etlsemko.com)

---

# INTERTEK TESTING SERVICES

---

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information



---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0 <u>General Description</u></b> .....	2
1.1 Product Description .....	2
1.2 Related Submittal(s) Grants .....	2
1.3 Test Methodology .....	3
1.4 Test Facility .....	3
<b>2.0 <u>System Test Configuration</u></b> .....	5
2.1 Justification .....	5
2.2 EUT Exercising Software .....	5
2.3 Special Accessories .....	5
2.4 Equipment Modification .....	6
2.5 Measurement Uncertainty .....	6
2.6 Support Equipment List and Description .....	6
<b>3.0 <u>Emission Results</u></b> .....	8
3.1 Field Strength Calculation .....	9
3.2 Radiated Emission Configuration Photograph .....	10
3.3 Radiated Emission Data .....	11
3.4 Conducted Emission Configuration Photograph .....	14
3.5 Conducted Emission Data .....	15
<b>4.0 <u>Equipment Photographs</u></b> .....	17
<b>5.0 <u>Product Labelling</u></b> .....	19
<b>6.0 <u>Technical Specifications</u></b> .....	21
<b>7.0 <u>Instruction Manual</u></b> .....	23
<b>8.0 <u>Miscellaneous Information</u></b> .....	25
8.1 Bandedge Plot .....	26
8.2 Discussion of Pulse Desensitization .....	27
8.3 Calculation of Average Factor .....	28
8.4 Emissions Test Procedures .....	29

---

## INTERTEK TESTING SERVICES

---

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.doc
Test Setup Photo	Conducted Emission	conducted photos.doc
Test Report	Conducted Emission Test Result	conducted.pdf
Test Report	Bandedge Plot	be.pdf
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Test Report	Timing Diagram	timing.pdf

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 1**

**GENERAL DESCRIPTION**

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a Transceiver operating at 2410.0 - 2469.2MHz and have 74 hopping channels auto select, channel spacing of 0.8MHz. Also, the receiver portion is operating at 2410.0 - 2469.2MHz. The EUT is powered by 3V d.c. (2 x 1.5V "AA" size alkaline batteries) or 2.4V d.c (2 x 1.2V "Ni-MH" rechargeable battery). It is a PS3's wireless remote controller. During normal use, it transmit control signal to the corresponding dongle unit and the dongle unit will scan for the channels used on the EUT. Once they are synchronised, EUT will send the control signal to the dongle unit and the dongle unit will control the game of PS3 or computer. The remote controller transmits at a fixed hopping sequence once correspondent dongle is connected. The worst-case transmit on time for particular channel shall be 2.1ms as per 10.88ms by applicant provided information. Also, the dongle unit will send out feedback signal to the remote controller.

Besides, it has a USB port is for charging function only for PS3 but not for PC.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is an application for certification of transmitter portion. The receiver portion, associated with this EUT, can be exempted from technical requirement of the FCC Part 15 standard.

The dongle unit, associated with this EUT, has FCC ID: SWJKC-2616B and has been filed at the same time.

## INTERTEK TESTING SERVICES

---

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 2**  
**SYSTEM TEST CONFIGURATION**

---

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered from 2 x 1.5V new "AA" batteries or 1 x 2.4V fully charged "Ni-MH" rechargeable battery pack when operated in standalone mode. Both have been tested and the worst case is shown on the report.

During battery charging, it is powered from USB port of PS3.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable or operated in recharging mode and placed in the rear of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes. For simplicity of testing, the unit was under manufacturer test mode to transmit continuously.

The frequency range from 9kHz to 25GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the button is depressed, the unit transmits the typical signal. For simplicity of testing, the unit was under manufacturer to transmit continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

---

## INTERTEK TESTING SERVICES

---

### 2.4 Equipment Modification

Any modifications installed previous to testing by King Chuang Tech & Electronic Co., Ltd. Will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

### 2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.6 Support Equipment List and Description

This product was tested in a system configuration.

1 x LCD TV receiver, Model: LS15M23C

1 x CRT TV receiver, Model: 14GX1517/57B

1 x Play Station 3.

1 x USB cable with length of 1.8 meter for charging function only.

All the items listed under section 2.0 of this report are

*Confirmed by:*

*Ho Wai Kin, Ben*

*Supervisor*

*Intertek Testing Services Hong Kong Ltd.*

*Agent for King Chuang Tech & Electronic Co., Ltd.*



\_\_\_\_\_  
Signature

\_\_\_\_\_  
August 24, 2007

\_\_\_\_\_  
Date

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 3**  
**EMISSION RESULTS**

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
at  
39.625 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.doc.

## INTERTEK TESTING SERVICES

---

### 3.5 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 9.0 dB

#### **TEST PERSONNEL:**



---

*Signature*

Mark Cheung, Compliance Engineer  
*Typed/Printed Name*

August 24, 2007  
*Date*

## INTERTEK TESTING SERVICES

Applicant: King Chuang Tech & Electronic Co., Ltd.  
 Model: KC-2616  
 Mode: TX (Remote Controller Unit)

Date of Test: July 05, 2007

Table 1

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Average Factor (-dB)	Average at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Channel 00								
H	2410.015	88.6	29.4	33	14.2	70.8	94.0	-23.2
H	4820.030	50.8	34.9	33	14.2	38.5	54.0	-15.5
H	7230.045	51.9	37.9	33	14.2	42.6	54.0	-11.4
H	9640.060	46.2	40.4	33	14.2	39.4	54.0	-14.6
H	12050.075	43.8	40.5	33	14.2	37.1	54.0	-16.9
Channel 37								
H	2440.137	90.0	29.4	33	14.2	72.2	94.0	-21.8
H	4880.274	51.1	34.9	33	14.2	38.8	54.0	-15.2
H	7320.411	52.1	37.9	33	14.2	42.8	54.0	-11.2
H	9760.548	45.6	40.4	33	14.2	38.8	54.0	-15.2
H	12200.685	43.5	40.5	33	14.2	36.8	54.0	-17.2
Channel 73								
H	2469.237	92.6	29.4	33	14.2	74.8	94.0	-19.2
H	4938.474	50.3	34.9	33	14.2	38.0	54.0	-16.0
H	7407.711	52.9	37.9	33	14.2	43.6	54.0	-10.4
H	9876.948	45.0	40.4	33	14.2	38.2	54.0	-15.8
H	12346.185	42.9	40.5	33	14.2	36.2	54.0	-17.8

- Notes:
1. Negative value in the margin column shows emission below limit.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Horn antenna is used for the emission over 1000MHz.
  4. Peak Detector Data unless otherwise stated.

Test Engineer: Mark Cheung

## INTERTEK TESTING SERVICES

Applicant: King Chuang Tech & Electronic Co., Ltd.  
 Model: KC-2616  
 Mode: TX (Remote Controller Unit)

Date of Test: July 05, 2007

Table 2

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Peak at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Channel 00							
H	2410.015	102.9	29.4	33	85.0	114.0	-29.0
H	4820.030	65.1	34.9	33	52.7	74.0	-21.3
H	7230.045	66.2	37.9	33	56.8	74.0	-17.2
H	9640.060	60.5	40.4	33	53.6	74.0	-20.4
H	12050.075	58.1	40.5	33	51.3	74.0	-22.7
Channel 37							
H	2440.137	104.3	29.4	33	86.4	114.0	-27.6
H	4880.274	65.4	34.9	33	53.0	74.0	-21.0
H	7320.411	66.4	37.9	33	57.0	74.0	-17.0
H	9760.548	59.9	40.4	33	53.0	74.0	-21.0
H	12200.685	57.8	40.5	33	51.0	74.0	-23.0
Channel 73							
H	2469.237	106.9	29.4	33	89.0	114.0	-25.0
H	4938.474	64.6	34.9	33	52.2	74.0	-21.8
H	7407.711	67.2	37.9	33	57.8	74.0	-16.2
H	9876.948	59.3	40.4	33	52.4	74.0	-21.6
H	12346.185	57.2	40.5	33	50.4	74.0	-23.6

- Notes:
1. Negative value in the margin column shows emission below limit.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Horn antenna is used for the emission over 1000MHz.
  4. Peak Detector Data unless otherwise stated.

Test Engineer: Mark Cheung

FCC ID: SWJKC-2616

---

## INTERTEK TESTING SERVICES

---

Applicant: King Chuang Tech & Electronic Co., Ltd.  
Model: KC-2616  
Mode: Charging  
Worst case: with PS3

Date of Test: July 05, 2007

Table 3

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	39.625	37.0	10.0	16	31.0	40.0	-9.0
V	41.375	36.8	10.0	16	30.8	40.0	-9.2
V	45.250	35.9	10.0	16	29.9	40.0	-10.1
V	47.125	34.6	11.0	16	29.6	40.0	-10.4
V	50.001	33.8	11.0	16	28.8	40.0	-11.2
V	55.870	33.7	11.0	16	28.7	40.0	-11.3
V	58.750	34.0	11.0	16	29.0	40.0	-11.0
V	65.750	35.5	9.0	16	28.5	40.0	-11.5

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Mark Cheung

## INTERTEK TESTING SERVICES

---

### 3.5 Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration  
at  
0.735 MHz

For electronic filing, the worst case line-conducted configuration photograph are saved with filename: conducted photos.doc.

## INTERTEK TESTING SERVICES

---

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgement: Passed by 6.2 dB

#### **TEST PERSONNEL:**



---

*Signature*

Mark Cheung, Compliance Engineer  
*Typed/Printed Name*

August 24, 2007  
*Date*

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 4**

**EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.doc & internal photos.doc.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 5**

**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 6**

**TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 7**  
**INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 8**

**MISCELLANEOUS INFORMATION**

## INTERTEK TESTING SERVICES

---

### 8.0 **Miscellaneous Information**

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

---

## INTERTEK TESTING SERVICES

---

### 8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: be.pdf. From the plot, the field strength of any emissions appearing between the bandedges and up to 10 kHz above and below the band edges are attenuated at least 50dB below the level of the unmodulated carrier. It fulfil the requirement of 15.249(d).

#### Peak measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot A & Bandedge Plot B).

Resultant field strength= Fundamental emissions (peak value) - delta from the plot A

$$= 85.0\text{dB}\mu\text{V/m} - 44.40\text{dB}$$

$$= 40.60\text{dB}\mu\text{V/m}$$

Resultant field strength= Fundamental emissions (peak value) - delta from the plot B

$$= 89.0\text{dB}\mu\text{V/m} - 47.58\text{dB}$$

$$= 41.42\text{dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu$ V/m.

#### Average measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot A & Bandedge Plot B).

Resultant field strength= Fundamental emissions (average value) - delta from the plot A

$$= 70.8\text{dB}\mu\text{V/m} - 44.40\text{dB}$$

$$= 26.40\text{dB}\mu\text{V/m}$$

Resultant field strength= Fundamental emissions (average value) - delta from the plot B

$$= 74.8\text{dB}\mu\text{V/m} - 47.58\text{dB}$$

$$= 27.22\text{dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 54dB $\mu$ V/m.

## INTERTEK TESTING SERVICES

---

### 8.2 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

The effective period ( $T_{\text{eff}}$ ) was approximately 2.1 ms for a data frame, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

---

## INTERTEK TESTING SERVICES

---

### 8.3 Calculation of Average Factor

Averaging factor in dB =  $20 \log (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 10.88 ms

Effective period of the cycle = 2.1 ms

DC =  $2.1 \text{ ms} / 10.88 \text{ ms} = 0.193$

Therefore, the averaging factor is found by  $20 \log_{10} 0.191 = -14.2 \text{ dB}$

For electronic filing, the plot shows the transmission timing is saved with filename: timing.pdf.

---

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.