

849 NW State Road 45
Newberry, FL 32669 USA
Phone: 888.472.2424 or
352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

FCC PART 97 AMATEUR RADIO TEST REPORT

Applicant	M2 ANTENNA SYSTEMS	
Address	4402 N. SELLAND AVENUE	
	FRESNO CA 93722 USA	
FCC ID	6M-1K2	
Model Number	6M-1K2	
Product Description	6M HIGH POWER AMPLIFIER	
Date Sample Received	4/18/2013	
Date Tested	5/14/2013	
Tested By	Nam Nguyen	
Approved By	Mario de Aranzeta	
Report Number	658AUT13TestReport.doc	
Test Results	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.



Certificate # 0955-01



TABLE OF CONTENT

STATEMENT OF COMPLIANCE	3
GENERAL INFORMATION	4
EMC EQUIPMENT LIST.....	6
TEST PROCEDURES:.....	7
RF POWER OUTPUT	8
IN BAND GAIN	9
OUT OF BAND GAIN	12
STRENGTH OF SPURIOUS EMISSIONS.....	13
POWER LINE CONDUCTED INTERFERENCE.....	14
FCC EXPOSURE INFORMATION.....	17

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc



STATEMENT OF COMPLIANCE

This equipment has been tested in accordance with the standards identified in the referenced test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report and demonstrate that the equipment complies with the appropriate standards. No modifications were made to the equipment during testing in order to demonstrate compliance with these standards.

I attest that the necessary measurements were made by me or under my supervision, at TIMCO ENGINEERING, INC. located at 849 N.W. State Road 45, Newberry, Florida 32669 USA.

Tested by: Nam Nguyen



Signature:

Function: Testing Tech/Project Manager

Date: May 15, 2013

Authorized by:

Signature:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: May 15, 2013

GENERAL INFORMATION

DUT Specification

The test results relate only to the items tested.	
DUT Description	6M HIGH POWER AMPLIFIER
FCC ID	6M-1K2
Model Number	6M-1K2
Serial Number	N/A
Operating Frequency	50 to 54 MHz
Testing Frequency	50.5 and 53.5 MHz
Type of Emission	J3E, F3E, A3E
Modulation	FM, AM, SSB
DUT Power Source	<input checked="" type="checkbox"/> 180–264VAC/50– 60Hz
	<input checked="" type="checkbox"/> DC Power (48-50 VDC, 40A)
	<input type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input type="checkbox"/> Portable
Antenna Connector	N connector
Supporting Peripheral Equipment	HF/VHF/UHF Transceiver Model: IC-706MKIIG Manufacturer: Icom Inc.
Modifications to DUT:	<input type="checkbox"/> No <input checked="" type="checkbox"/> Yes (explanation below)
	Adding to the AC power line: 1. FN9246-12-06 Filter 2. Two ferrites (part #43 material)



APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc



Test Facility: The test sites used by Timco Engineering Inc. for radiated and conducted emission data are located at 849 NW State Road 45 Newberry, FL 32669 USA.

Test Condition: The DUT was tested in the laboratory in an environment with normal temperature and humidity. The temperature was 26°C with a relative humidity of 50%.

Modification to the DUT: No modification was made to the DUT during testing.

Test Exercise (e.g software description, test signal, etc.): The DUT was placed in continuous transmit mode of operation.

Applicable Standards: TIA 603 & ANSI C63.4 – 2003
FCC CFR 47 Part 97
FCC CRF 47 Part 15

Other information:

The amplifier is capable of operation in the amateur radio 6 meter band (50-54 MHz). The amplifier is NOT capable of operation on any frequency or frequencies between 26 MHz and 28 MHz as marketed.

- 1.. The amplifier requires 80 Watts of drive to obtain full output power. Reduction in RF input power reduces the output power as shown on Page 8.
2. The gain of the amplifier is under 15 dB and under all conditions.
3. The amplifier in the off or standby state does not amplify and merely passes through the exciter energy to the antenna port. The spurious emissions of the transceiver were unaffected.

EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/11	12/31/13
AC Voltmeter	HP	400FL	2213A14499	6/12/11	6/12/13
Hygro-Thermometer	Extech	445703	0602	6/15/11	6/15/13
Digital Multimeter	Fluke	FLUKE-77	35053830	9/9/11	9/9/13
DC Power Supply	Astron	VS-50M	9001191	01/19/13	01/19/15
Power Meter	Boonton Electronics	4531	11793	1/9/13	1/9/15
Sensor	Boonton	51072A	34647	01/19/13	01/19/15
Attenuator	Bird	8329-300	4980	2/26/13	2/26/15
EMI Receiver	Rohde & Schwarz	ESIB40	100274	3/16/12	3/16/14
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	10/28/11	10/28/13
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	10/28/11	10/28/13
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	10/28/11	10/28/13
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	10/28/11	10/28/13
Horn Antenna	ETS	3117	35923	12/7/11	12/7/13
Antenna	Electro metrics	LPA-25	1122	5/04/11	5/04/13
Antenna	Electro metrics	BIA-25	1096	5/04/11	5/04/13

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc



TEST PROCEDURES:

Radiation Interference: The test procedure used was TIA 603 using a Agilent spectrum analyzer with a pre-selector. In the frequency range 10 kHz to 30 MHz the RBW was 10 kHz and from 30-1000 MHz the RBW of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz.

Formula Of Conversion Factors: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.4 dB	= 30.76 dB μ V/m @ 3m

TIA 603 Measurement Procedures: The DUT was placed on a non-conducting table 80 cm above the ground plane with the DUT located in the center of the table. With the antenna vertical a preliminary scan was done at 1 meters distance, the DUT was moved to a 3.0-meter distance and the antenna height varied and also placed in a horizontal position. The frequency was scanned from 9.0 kHz to 1.0 GHz. When an emission was found, the table was rotated to produce the maximum signal strength.

Part 97.313

Power Output Power shall not exceed 1.5 kW PEP Watts into a 50 ohm resistive load. There are no user power controls.

Part 2.1033(c)(8)

DC Voltages and Current into Final Amplifier:

INPUT POWER - (50Volts)(40Amps) = 2000 Watts

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc


RF POWER OUTPUT

Rule Parts No.: Part 2.1046(a), Part 97.313

Requirements: 97.313

Test Procedure: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector with a nominal input voltage of 240 AC Volts. The transmitter was properly adjusted and the maximum RF output power was measured at 1250 Watts.

Test Setup:




Test Data:

Input Freq (MHz)	Input (W)	Output (W)
50.5	91.4	1213
52.0	93	1245
53.5	95	1270

IN BAND GAIN

Requirements: 97.317 (a) (2)

The ratio of the input to the output RF power of the amplifier is less than 15 dB.




Input/Output= 11.5 dB gain

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc




Input/Output= 11.2 dB gain

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc



Date: 22.APR.2013 10:32:04

Input/Output= 11.3 dB gain


APPLICANT: M2 ANTENNA SYSTEMS
 FCC ID: 6M-1K2
 REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc

OUT OF BAND GAIN

Requirements: 97.317 (a) (3)

The power amplifier shall exhibit no more than 0dB gain from 26 MHz to 28 MHz.

Test Procedure: The amplifier was set to its operation mode, and the gain was adjusted to maximum at the frequency band 50 – 54 MHz. An input signal was provided in the 26 – 28 MHz band.



Date: 19.APR.2013 16:21:44

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc


STRENGTH OF SPURIOUS EMISSIONS

Rule Parts No.: Part 2.1053 & Part 97.307 (d) (e)

Requirements: The FCC Limits for spurious emissions of a transmitter operating between 30 - 225 MHz, the RF spurious emissions must be at least 60 dB below the mean power of the fundamental.

Method Of Measurements:

Test Setup:



Test Data:

TF	EF	dB Below Carrier
50.5	101.00	62.7
	151.50	63.6
	202.00	82.2
	252.50	81.8
	303.00	85.1
	353.50	81.2
	404.00	85.5
	454.50	85.3
	505.00	87.7

TF	EF	dB Below Carrier
53.5	107.00	72.4
	160.50	67.0
	214.00	77.2
	267.50	79.1
	321.00	89.9
	374.50	89.2
	428.00	87.6
	481.50	80.4
	535.00	88.2

APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc

POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: Part 15.207


Requirements:

Frequency (MHz)	Quasi Peak Limits (dBuV)	Average Limits (dBuV)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5.0 – 30	60	50

Test Procedure: ANSI Standard C63.4-2003. The spectrum was scanned from 0.15 to 30 MHz.

Test Data: The attached graphs represent the emissions read for power line conducted for this device. The EUT was in TX mode. Both lines were observed.


POWERLINE CONDUCTED PLOT – LINE 1



Date: 14.MAY.2013 16:28:55

APPLICANT: M2 ANTENNA SYSTEMS
 FCC ID: 6M-1K2
 REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc

POWERLINE CONDUCTED PLOT – LINE 2



APPLICANT: M2 ANTENNA SYSTEMS

FCC ID: 6M-1K2

REPORT: M\ M2 ANTENNA\658AUT13\658AUT13TestReport.doc



FCC EXPOSURE INFORMATION

The FCC requires users to check their installations for compliance with published values for allowable exposure to RF fields. This information is in the ARRL publications, FCC printed rules, and on the web.

APPLICANT: M2 ANTENNA SYSTEMS
FCC ID: 6M-1K2
REPORT: M\M2 ANTENNA\658AUT13\658AUT13TestReport.doc