



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR FCC CLASS B CERTIFICATION

Test Report No. : E058R-025
Applicant : BAYON CO., LTD.
Address : 3F, Kumkang B/D, 32-1, Youngmun-Dong, Youngsan-Gu, Seoul, Korea
Manufacturer : BAYON CO., LTD.
Address : 3F, Kumkang B/D, 32-1, Youngmun-Dong, Youngsan-Gu, Seoul, Korea
Type of Equipment : USB MP3 PLAYER
FCC ID : SXU-UP3
Model Name : UP3
Multiple Model Name : UP3 PLUS
Serial number : N/A
Total page of Report : 11 pages (including this page)
Date of Incoming : July 29, 2005
Date of Issuing : August 17, 2005

SUMMARY

The equipment complies with the requirements of **FCC CFR 47 PART 15 SUBPART B, Class B**.

This test report contains only the results of a single test of the sample supplied for the examination. It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by:


Seung-Hyun, Nam / Project Engineer
EMC Div.
ONETECH Corp.

Reviewed by:


Gea-Won, Lee / Chief Engineer
EMC Div.
ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH.

FCC-003 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-705, Korea
(TEL: +82-31-746-8500, FAX: +82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Eup, Kwangju-City, Kyunggi-Do, 464-860, Korea. (TEL: +82-31-765-8289, FAX: +82-31-766-2904)



CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE.....	3
2. GENERAL INFORMATION.....	4
2.1 PRODUCT DESCRIPTION.....	4
2.2 MODEL DIFFERENCES.....	4
2.3 RELATED SUBMITTAL(S) / GRANT(S)	4
2.4 TEST SYSTEM DETAILS	4
2.5 TEST METHODOLOGY	4
2.6 TEST FACILITY.....	4
3. SYSTEM TEST CONFIGURATION.....	5
3.1 JUSTIFICATION	5
3.2 EUT EXERCISE SOFTWARE.....	5
3.3 CABLE DESCRIPTION	5
3.4 NOISE SUPPRESSION PARTS ON CABLE	5
3.5 EQUIPMENT MODIFICATIONS	6
3.6 CONFIGURATION OF TEST SYSTEM	6
4. PRELIMINARY TEST	6
4.1 AC POWER LINE CONDUCTED EMISSION TEST	6
4.2 RADIATED EMISSION TEST	6
5. FINAL RESULT OF MEASURMENT	7
5.1 CONDUCTED EMISSION TEST	7
5.2 RADIATED EMISSION TEST	9
6. FIELD STRENGTH CALCULATION.....	10
7. LIST OF TEST EQUIPMENT	11



1. VERIFICATION OF COMPLIANCE

- . APPLICANT : BAYON CO., LTD.
- . ADDRESS : 3F, Kumkang B/D, 32-1, Youngmun-Dong, Youngsan-Gu, Seoul, Korea
- . CONTACT PERSON : Mr. Chong-Sung, Park / President
- . TELEPHONE NO : +82-2-702-3437
- . FCC ID : SXU-UP3
- . MODEL NO/NAME : UP3
- . SERIAL NUMBER : N/A
- . DATE : August 17, 2005

EQUIPMENT CLASS	JBP - Peripheral Device for Class B Computing Device
E.U.T. DESCRIPTION	USB MP3 PLAYER – UNINTENTIONAL RADIATOR
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	ANSI C63.4: 2003
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15, SECTION 15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

- . This device has shown compliance with the conducted emissions limits in 15.107 adopted under FCC 02-107 (ET Docket 98-80). The device may be marketed after July 11, 2005 affected by the 15.37(j) transition provisions.
- . The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



2. GENERAL INFORMATION

2.1 Product Description

The BAYON CO., LTD., Model UP3 (referred to as the EUT in this report) is a USB MP3 PLAYER that is interfaced to personal computer via USB port. Product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
LIST OF EACH OSC. or CRY. FREQ.(FREQ.>=1MHz)	12 MHz
NUMBER OF LAYERS	4 Layers
EXTERNAL CONNECTOR	Audio Out, USB

2.2 Model Differences

- The difference(s) compared to the EUT is as follows:

	Model Name	Model Differences
Basic Model	UP3	-
Multiple Model	UP3 PLUS	Only type designation by color and function keys of the EUT.

2.3 Related Submittal(s) / Grant(s)

- Original submittal only

2.4 Test System Details

The model numbers for all the equipments that were used in the tested system is:

Model	Manufacturer	FCC ID	Description	Connected to
UP3	BAYON CO., LTD.	SXU-UP3	USB MP3 PLAYER (EUT)	PC
DCM	DELL Computer Corp.	DoC	PERSONAL COMPUTER	-
E551	DELL Computer Corp..	DoC	MONITOR	PC
MO56UO	Dongguan Primax Electronics	N/A	MOUSE	PC
SK-8110	DELL Computer Corp.	N/A	KEYBOARD	PC
UP-DP10	Sony Corporation	DoC	PRINTER	PC
020-0470	CARDINAL	GDE0196	MODEM	PC

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4: 2003. Radiated testing was performed at a distance of 3 meters from the EUT to the antenna.

2.6 Test Facility

The open area test site and conducted measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Eup, Kwangju-City, Kyunggi-Do, 464-080, Korea. Description details of test facilities were submitted to the Commission on April 04, 2003. (Registration Number: 340658)



3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN B'D	N/A	N/A	N/A

3.2 EUT exercise Software

After connecting the EUT to a personal computer, data were continuously read and written from the HDD of the personal computer to the EUT. And also, the EUT was operated with MP3 playing mode during the test. But worst case data was recorded in this report.

3.3 Cable Description

	Power Cord Shielded (Y/N)	I/O cable Shielded (Y/N)	Length (M)
USB MP3 PLAYER (EUT)	N/A	N/A	-
PERSONAL COMPUTER	N	-	1.8(P)
MONITOR	N	Y	1.5(P), 1.2(D)
MOUSE	N/A	N	1.2(D)
KEYBOARD	N/A	N	1.2(D)
PRINTER	N	Y	1.8(P), 1.2(D)
MODEM	N	Y	1.8(P), 1.2(D)

* The marked "(P)" means the Power Cable and "D" means the I/O Cable.

3.4 Noise Suppression Parts on Cable

	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
USB MP3 PLAYER (EUT)	N	N/A	N	N/A
PERSONAL COMPUTER	N/A	N/A	N/A	-
MONITOR	Y	BOTH END	Y	BOTH END
MOUSE	N	N/A	Y	PC END
KEYBOARD	N	N/A	Y	PC END
PRINTER	Y	PRINTER END	Y	BOTH END
MODEM	N	N/A	Y	BOTH END



3.5 Equipment Modifications

To achieve compliance to CLASS B levels, the following change(s) was made by ONETECH Corp. during compliance testing:

“There were no Modified items during EMI test”

3.6 Configuration of Test System

Line Conducted Test : The EUT was inserted to USB port of the PC and the power line of PC was connected to LISN. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.4: 2003 7.2.3 to determine the worse operating conditions.

Radiated Emission Test : Preliminary radiated emission test was conducted using the procedure in ANSI C63.4: 2003 8.3.1.1 to determine the worse operating conditions. Final radiated emission test was conducted at 3 meters open area test site.

4. PRELIMINARY TEST

4.1 AC Power line Conducted Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Data were continuously read and write via USB	X
MP3 Playing Mode	

4.2 Radiated Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Data were continuously read and write via USB	X
MP3 Playing Mode	



5. FINAL RESULT OF MEASUREMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level

5.1 Conducted Emission Test

Humidity Level	: <u>41 %</u>	Temperature: <u>21 °C</u>
Limits apply to	: <u>FCC CFR 47, PART 15, SUBPART B, SECTION 15.107 (a)</u>	
Type of Test	: <u>CLASS B</u>	
Result	: <u>PASSED BY -15.42 dB at 8.60 MHz</u>	

EUT	: USB MP3 PLAYER	Date: August 12, 2005
Operating Condition	: Data were continuously read and written.	
Detector	: CISPR Quasi-Peak (6 dB Bandwidth: 9 kHz)	

Frequency (MHz)	Line	Peak (dBuV)		Margin (dB)
		Emission level	Q.P Limits	
0.20	N	43.75	63.61	-19.86
7.96	H	42.91	60.00	-17.09
8.28	H	44.29	60.00	-15.71
8.60	N	44.58	60.00	-15.42
16.28	H	40.52	60.00	-19.48
17.68	N	41.45	60.00	-18.55
Frequency (MHz)	Line	Average (dBuV)		Margin (dB)
		Emission level	Limits	
-				
-				


Line Conducted Emission Tabulated Data

Remark : "H": Hot Line, "N": Neutral line

Average mode was not measured, because peak values were under the Average limit.

See next page for an overview sweep performed with peak detector.

Tested by: Eung-Chan, Kim / Test Engineer





5.2 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

Humidity Level	: <u>44 %</u>	Temperature: <u>24 °C</u>
Limits apply to	: <u>FCC CFR 47, PART 15, SUBPART B, SECTION 15.109 (a)</u>	
Type of Test	: <u>CLASS B</u>	
Result	: <u>PASSED BY -8.99 dB at 143.90 MHz</u>	

EUT	: USB MP3 PLAYER		Date: August 16, 2005
Operating Condition	: Data were continuously read and written.		
Detector	: CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)		
Frequency Range	: 30 MHz – 1000 MHz		
Distance	: 3 Meter		

Radiated Emissions		Ant	Correction Factors		Total	FCC CLASS B	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
120.00	13.40	V	12.96	2.00	28.36	43.52	-15.16
143.90	17.30	H	14.87	2.36	34.53	43.52	-8.99
158.80	14.50	H	15.28	2.39	32.17	43.52	-11.35
167.70	12.40	H	15.56	2.40	30.36	43.52	-13.16
198.40	14.30	H	15.88	2.80	32.98	43.52	-10.54
239.50	11.50	H	16.78	3.23	31.51	46.02	-14.51

Radiated Emissions Tabulated Data

Tested by: Eung-Chan, Kim / Test Engineer



6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading (dBuV)

+ Cable Loss (dB)

+ Antenna Factor (Loss) (dB/meter)

= Corrected Reading (dBuV/meter)

- Specification Limit (dBuV/meter)

= dB Relative to Spec (+/- dB)



7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUe CAL	USE
1.	Test receiver	R/S	ESVS10	827864/005	DEC/04	12MONTH	■
2.	Test receiver	R/S	ESHS 10	834467/007	MAY/05	12MONTH	■
3.	Spectrum analyzer	HP	8566B	3407A08547	JUL/05	12MONTH	
4.	Spectrum analyzer	HP	8568B	3109A05456	APR/05	12MONTH	■
5.	RF preselector	HP	85685A	3107A01264	APR/05	12MONTH	■
6.	Quasi-Peak Adapter	HP	8574B	2811A01432	APR/05	12MONTH	■
7.	TRILOG Broadband Antenna	Schwarzbeck	VULB9163	VULB9163 166	APR/05	12MONTH	
8.	Biconical antenna	EMCO	3110	9003-1121	FEB/05	12MONTH	
		Schwarzbeck	VHA9103	91031852	JAN/05		■
9.	Log Periodic antenna	EMCO	3146	9001-2614	FEB/05	12MONTH	
		Schwarzbeck	9108-A(494)	62281001	FEB/05		■
10.	LISN	EMCO	3825/2	9109-1867	JUL/04	12MONTH	
				9109-1869	NOV/04		■
		Schwarzbeck	NSLK 8128	8128-216	JUN/05		■
11.	Position Controller	HD GmbH	HD100	N/A	N/A	N/A	■
12.	Turn Table	HD GmbH	DS420S	N/A	N/A	N/A	■
13.	Antenna Master	HD GmbH	MA240	N/A	N/A	N/A	■