

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant:	Feit Electric Company
Address of applicant:	4901 Gregg Road Pico Rivera, California 90660, United States
Manufacturer:	Zhejiang Future Lighting Co., Ltd
Address of manufacturer:	No.99, Jingfeng Road, Haining Warp Knitting Industrial Zone, Zhejiang

General Description of EUT:

Product Name:	Self-Ballasted LED Lamps
Trade Name:	/
Model No.:	112U800100M0-70-6500 1130800100M0-XX; 1130800090M0-XX; 1130800070M0-XX; 1130800060M0-XX; 1130800050M0-XX; 1130800040M0-XX; 1130800088M0-XX; 1130800072M0-XX; 112U800100M0-XX-YYYY; 112U800090M0-XX-YYYY; 112U800070M0-XX-YYYY; 112U800060M0-XX-YYYY; 112U800050M0-XX-YYYY; 112U800040M0-XX-YYYY; 112U800088M0-XX-YYYY; 112U800072M0-XX-YYYY; OM60/927CA/AG (P1); OM60/927CA/AG/3 (P); OM60/950CA/AG (P1); OM60/950CA/AG/3 (P) ("XX" represents Ra, can be 70-100; "YYYY" represents the color temperature, can be 2000-6500)
Adding Model(s):	
Rated Voltage:	A120V/60Hz
Power Adapter	/
FCC ID:	SYW-A19AGT2R2
Equipment Type:	Fixed device

Technical Characteristics of EUT:

Wi-Fi

Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	17.4dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	1.9dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Wi-Fi

Maximum Tune-Up output power: 18(dBm)

Maximum peak output power at antenna input terminal: 63.10(mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 1.9 (dBi)

Directional gain (numeric gain): 1.55

The worst case is power density at prediction frequency at 20cm: 0.0194(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass