

FCC PART 15.247

TEST REPORT

For

Feit Electric Company

4901 Gregg Road, Pico Rivera, California 90660 United States

FCC ID: SYW-PLUG3WIFIN

Report Type: Original Report	Product Name: Plug
Report Number:	RKSB240506010-00B
Report Date:	2024-12-02
Reviewed By:	Jenny Yang
Approved By:	Kyle Xu
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	6
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	8
SUPPORT EQUIPMENT LIST AND DETAILS	12
EXTERNAL I/O CABLE.....	12
BLOCK DIAGRAM OF TEST SETUP	12
SUMMARY OF TEST RESULTS	16
TEST EQUIPMENT LIST	17
FCC §15.203 - ANTENNA REQUIREMENT.....	19
APPLICABLE STANDARD	19
ANTENNA CONNECTOR CONSTRUCTION	19
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	20
FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS.....	21
APPLICABLE STANDARD	21
TEST SYSTEM SETUP.....	21
EMI TEST RECEIVER SETUP.....	21
TEST PROCEDURE	22
TEST RESULTS SUMMARY	22
TEST DATA: SEE APPENDIX	22
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	23
APPLICABLE STANDARD	23
TEST SYSTEM SETUP.....	23
EMI TEST RECEIVER SETUP.....	25
TEST PROCEDURE	25
TEST RESULTS SUMMARY	25
TEST DATA: SEE APPENDIX	25
FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH.....	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA: SEE APPENDIX	26
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA: SEE APPENDIX	27
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA: SEE APPENDIX	28
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	29

APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA: SEE APPENDIX	29
Appendix - TEST DATA.....	30
ENVIRONMENTAL CONDITIONS & TEST INFORMATION	30
AC LINE CONDUCTED EMISSIONS	31
SPURIOUS EMISSIONS	35
6 dB EMISSION BANDWIDTH	71
OCCUPIED BANDWIDTH	79
POWER SPECTRAL DENSITY	87
TRANSMITTER OUTPUT POWER MEASUREMENT.....	95
OUT OF BAND EMISSIONS.....	98
EUT PHOTOGRAPHS.....	104
TEST SETUP PHOTOGRAPHS	105

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSB240506010-00B	R1V1	2024-12-02	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Feit Electric Company
Tested Model	PLUG3/WIFI/WP/2
Product Name	Plug
Power Supply	AC 120V
RF Function:	2.4G Wi-Fi; BLE
Maximum Peak Output Power:	2.4G Wi-Fi: 802.11b: 16.98 dBm 802.11g: 20.54 dBm 802.11n20:20.55 dBm BLE(1Mbps): 1.78 dBm
Operating Band/Frequency:	2.4G Wi-Fi: 2412~2462 MHz(802.11b/g/n20) BLE(1Mbps): 2402-2480 MHz
Channel Number:	2.4G Wi-Fi: 11(802.11b/g/n20) BLE: 40
Channel Separation:	2.4G Wi-Fi: 5 MHz BLE: 2 MHz
Modulation Type:	2.4G Wi-Fi: DSSS, OFDM BLE: GFSK
Antenna Type:	2.4G Wi-Fi /BLE: PCB Antenna
★Maximum Antenna Gain:	2.4G Wi-Fi /BLE: 2.21 dBi

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSB240506010-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-05-06.)

Objective

This report is prepared for *Feit Electric Company* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	/
13	2428	27	2456	/	/

EUT was tested with channel 0, 19 and 39.

Channel List for Wi-Fi Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

RF test software: Wifi Test Tool v1.6.0 release.exe


Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	★Power Level
802.11b	1 Mbps	Default
802.11g	6 Mbps	Default
802.11n-HT20	MCS0	Default
BLE(1Mbps)	1Mbps	Default

Note: The power level was declared by the applicant.


Duty Cycle:**802.11b Mode Middle Channel**

ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 11:57:14


802.11g Mode Middle Channel

ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 13:18:53

802.11n-HT20 Mode Middle Channel



BLE(1Mbps) Mode Middle Channel



Mode	Duty Cycle (%)	Ton(ms)	Ton+off(ms)	$10\log(1/x)$ (dB)
802.11b	98.14	8.319	8.477	/
802.11g	96.27	1.393	1.447	0.17
802.11n-HT20	95.77	1.289	1.346	0.19
BLE(1Mbps)	100	100	100	/

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Lamp Holder 1	/	/
/	Lamp Holder 2	/	/
/	Lamp Holder 3	/	/
/	incandescent light bulb 1	/	/
/	incandescent light bulb 2	/	/
/	incandescent light bulb 3	/	/
/	Debug board	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To Port
Power cable 1	1.0	AC Source/LISN	Socket
power cable 2	0.1	Socket	EUT
power cable 3	1.0	EUT	Lamp Holder
Data cable	0.1	EUT	Debug board

Block Diagram of Test Setup


For Conducted Emissions:




For Radiated Emissions (9 kHz - 30 MHz):



For Radiated Emissions (30 MHz - 1 GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
FCC §1.1310 & §2.1091	Maximum Permissible Exposure	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #3)					
Rohde & Schwarz	EMI Test Receiver	ESR3	102454	2024-04-23	2025-04-22
Sunol Sciences	Hybrid Antenna	JB3	A060217	2023-12-14	2024-12-13
Narda	6 dB Attenuator	773-6	10690812-2-2	2023-12-14	2024-12-13
Sonoma Instrument	Amplifier	310N	185700	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-18	018	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-19	019	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-20	020	2024-04-23	2025-04-22
Audix	Test Software	e3	V9	N/A	N/A
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2024-04-23	2025-04-22
ETS-LINDGREN	Loop Antenna	6512	108100	2023-11-09	2024-11-08
ETS-LINDGREN	Loop Antenna	6512	108100	2024-11-03	2027-11-02
Sonoma Instrument	Pre-amplifier	310N	171205	2024-04-23	2025-04-22
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-9	009	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-10	010	2024-04-23	2025-04-22
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2024-04-25	2025-04-24
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2023-12-02	2024-12-01
ETS-LINDGREN	Horn Antenna	3116	2516	2023-12-08	2024-12-07
A.H.Systems, inc	Amplifier	PAM-0118P	512	2024-04-25	2025-04-24
SELECTOR	Amplifier	EM18G40G	060726	2024-04-25	2025-04-24
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2024-04-25	2025-04-24
Narda	Attenuator	10dB	010	2024-04-25	2025-04-24
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-11	011	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-12	012	2024-04-25	2025-04-24
MICRO-COAX	Coaxial Cable	Cable-13	013	2024-04-25	2025-04-24
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2024-04-24	2025-04-23
Narda	Attenuator	10dB	010	2024-04-25	2025-04-24
Anritsu	Power Sensor	MA24418A	12621	2024-04-23	2025-04-22
XHFDZ	RG178 Coaxial Cable	SMA-178	XHF-1102	Each time	N/A

Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	101746	2024-04-23	2025-04-22
Rohde & Schwarz	LISN	ENV216	101115	2024-04-23	2025-04-22
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2024-04-23	2025-04-22
MICRO-COAX	Coaxial Cable	Cable-15	015	2024-04-25	2025-04-24

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB for 2.4G Wi-Fi & BLE, and the antenna gain is 2.21 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402~2480	2.21	1.66	2.0	1.58	20	0.0005	1.0
2.4G Wi-Fi	2412~2462	2.21	1.66	21.0	125.89	20	0.0416	1.0

Note:

1. For the above tune up power were declared by the manufacturer.
2. Wi-Fi and BLE cannot transmit simultaneously.


Result: The device meet FCC MPE at 20 cm distance.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz - 30 MHz	9 kHz	30 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

Test System Setup**9k - 30MHz:****30 MHz - 1 GHz:**

Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average
30 MHz – 1000 MHz	100 kHz	300 kHz	/	Peak
	/	/	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	/	Average

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Level & Over Limit Calculation

The Level is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Factor (dB/m)} &= \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)} \\ \text{Level (dB}\mu\text{V/m)} &= \text{Read level (dB}\mu\text{V)} + \text{Factor (dB/m)}\end{aligned}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data: See Appendix

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.3


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



For BLE:

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 * \text{RBW}$.
3. Set span $\geq 3 * \text{RBW}$
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data: See Appendix

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data: See Appendix

FCC §15.247(E) - POWER SPECTRAL DENSITY


Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.




Test Data: See Appendix

Appendix - TEST DATA

Environmental Conditions & Test Information

Test Item:	AC LINE CONDUCTED EMISSIONS	RADIATED EMISSIONS				
		9 kHz-30 MHz		30 MHz -1 GHz	1-18 GHz	18-25 GHz
Test Date:	2024-06-04	2024-06-07	2024-11-29	2024-05-23	2024-05-28	2024-06-04
Temperature:	23.0 °C	24.1 °C	22.5 °C	25.5 °C	20.3 °C	23.0 °C
Relative Humidity:	44 %	42 %	44 %	24 %	52 %	44 %
ATM Pressure:	100.6 kPa	100.9 kPa	102.0 kPa	100.5 kPa	100.6 kPa	100.6 kPa
Test Result:	Pass	Pass	Pass	Pass	Pass	Pass
Test Engineer:	Frank Liu	Leah Li	Jerry Yan	Cesium Cheng	Hugh Wu	Hugh Wu


Test Item:	6 DB EMISSION BANDWIDTH	OCCUPIED BANDWIDTH	POWER SPECTRAL DENSITY	TRANSMITTER OUTPUT POWER MEASUREMENT	OUT OF BAND EMISSIONS	DUTY CYCLE
Test Date:	2024-06-03 to 2024-11-28					
Temperature:	21.7-22.7 °C					
Relative Humidity:	43-50 %					
ATM Pressure:	100.4-102.0 kPa					
Test Result:	Pass					
Test Engineer:	Hardy Huang & Neil Zhou					

AC LINE CONDUCTED EMISSIONS**For Wi-Fi Mode:***EUT operation mode: Transmitting in maximum output power mode 802.11n20 mode High channel***Line:**

Site : CE
Condition : limit\FCC Part15.207
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Phase : L
Voltage : 120V/60Hz
Mode : WIFI Transmitting
Test Equipment : ENV216,ESR
Temperature : 23.0℃
Humidity : 44%
Atmospheric pressure: 101.6kPa
Test Engineer : Frank Liu


	Read		Limit	Over	
Freq	Level	Factor	Level	Line	Limit Remark
MHz	dBuV	dB	dBuV	dBuV	dB
1	0.152	32.07	19.96	52.03	65.92 -13.89 Peak
2	0.205	26.21	20.04	46.25	63.39 -17.14 Peak
3	0.263	21.05	20.04	41.09	61.32 -20.23 Peak
4	0.411	16.54	20.01	36.55	57.64 -21.09 Peak
5	1.625	9.57	19.90	29.47	56.00 -26.53 Peak
6	1.822	9.97	19.97	29.94	56.00 -26.06 Peak

Neutral:




Site : CE
Condition : limit\FCC Part15.207
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Phase : N
Voltage : 120V/60Hz
Mode : WIFI Transmitting
Test Equipment : ENV216,ESR
Temperature : 23.0°C
Humidity : 44%
Atmospheric pressure: 101.6kPa
Test Engineer : Frank Liu

	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.152	32.83	19.96	52.79	65.88	-13.09 Peak
2	0.213	25.61	20.04	45.65	63.10	-17.45 Peak
3	0.293	19.12	20.03	39.15	60.45	-21.30 Peak
4	0.381	17.19	20.01	37.20	58.26	-21.06 Peak
5	2.433	13.32	20.04	33.36	56.00	-22.64 Peak
6	2.609	13.75	20.05	33.80	56.00	-22.20 Peak

For BLE Mode:*EUT operation mode: Transmitting in maximum output power mode High channel***Line**

Site : CE
Condition : limit\FCC Part15.207
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Phase : L
Voltage : 120V/60Hz
Mode : BT Transmitting
Test Equipment : ENV216,ESR
Temperature : 23.0°C
Humidity : 44%
Atmospheric pressure: 101.6kPa
Test Engineer : Frank Liu

Neutral



SPURIOUS EMISSIONS

Test Result: Compliant

EUT operation mode: Transmitting


After pre-scan in the X, Y and Z axes of orientation, the worst case in the X axes of orientation is below:

For 2.4 GHz Wi-Fi:

9 kHz-30 MHz: (Transmitting in maximum output power mode 802.11n20 mode high channel)

Parallel (worst case):


9 kHz-150 kHz



Project No. RKSB240506010
Date: 7.JUN.2024 17:07:17

Tester: Leah Li

150 kHz -30 MHz



Project No. RKSB240506010
Date: 7.JUN.2024 17:10:22

Tester: Leah Li

9 kHz-150 kHz

Frequency (MHz)	Corrected Amplitude (dBuV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBuV/m) @3m	Margin (dB)
0.010128	65.55	PK	56.28	127.49	61.94
0.015486	65.13	PK	52.87	123.81	58.68
0.02028	65.62	PK	49.92	121.46	55.84
0.03438	65.26	PK	46.06	116.88	51.62

150 kHz -30 MHz


Frequency (MHz)	Corrected Amplitude (dBuV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBuV/m) @3m	Margin (dB)
0.15000	52.73	PK	50.90	104.08	51.35
0.38880	43.75	PK	26.16	95.81	52.06
1.88130	37.97	PK	12.86	69.54	31.57
4.32900	32.72	PK	15.48	69.54	36.82

For BLE:


9 kHz-30 MHz: (Transmitting in maximum output power mode BLE 1M mode high channel)

Parallel (worst case):

9 kHz-150kHz



150 kHz -30 MHz



9 kHz-150 kHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.010974	63.06	PK	55.74	126.80	63.74
0.012384	65.53	PK	54.85	125.75	60.22
0.017742	62.69	PK	51.44	122.62	59.93
0.019998	62.52	PK	50.00	121.58	59.06

150 kHz -30 MHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.15000	54.64	PK	50.90	104.08	49.44
0.86640	41.86	PK	18.88	68.85	26.99
4.32900	31.56	PK	15.48	69.54	37.98
6.47820	29.46	PK	7.01	69.54	40.08

For 2.4 GHz Wi-Fi:

30 MHz - 1 GHz (Transmitting in maximum output power mode 802.11n20 mode):

Low Channel: 2412 MHz


Horizontal:



Site : 966 Chamber #3
 Condition : FCC Part 15.205/15.209/15.247 3m horizontal
 : DET:Peak
 Project No. : RKSB240506010
 Model : PLUG3/WIFI/WP/2
 Mode : WIFI Transmitting
 Test equipment : JB3,310N,ESR
 Ambient temperature : 25.5℃
 Relative humidity : 54%
 Atmospheric pressure: 101.2kPa
 Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	142.82	54.20	-11.87	42.33	43.50	-1.17	200	159	QP
2	191.07	49.49	-12.83	36.66	43.50	-6.84	100	164	QP
3	214.51	55.00	-13.08	41.92	43.50	-1.58	100	164	QP
4	239.15	54.61	-12.95	41.66	46.00	-4.34	100	184	QP
5	285.98	51.00	-10.62	40.38	46.00	-5.62	100	184	QP
6	640.61	43.50	-3.37	40.13	46.00	-5.87	100	221	QP

Vertical:




Site : 966 Chamber #3
 Condition : FCC Part 15.205/15.209/15.247 3m vertical
 : DET:Peak
 Project No. : RKSB240506010
 Model : PLUG3/WIFI/WP/2
 Mode : WIFI Transmitting
 Test equipment : J83,310N,ESR
 Ambient temperature : 25.5°C
 Relative humidity : 54%
 Atmospheric pressure: 101.2kPa
 Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	143.33	46.89	-11.89	35.00	43.50	-8.50	200	244	Peak
2	191.07	44.66	-12.83	31.83	43.50	-11.67	200	244	Peak
3	214.51	47.24	-13.08	34.16	43.50	-9.34	200	244	Peak
4	238.31	44.07	-12.98	31.09	46.00	-14.91	200	235	Peak
5	640.61	42.60	-3.37	39.23	46.00	-6.77	100	246	Peak
6	801.79	32.58	-0.39	32.19	46.00	-13.81	100	269	Peak

Middle Channel: 2437 MHz


Horizontal:



Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m horizontal
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : WIFI Transmitting
Test equipment : J83,310N,ESR
Ambient temperature : 25.5℃
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng

	Read			Limit	Over	APos	TPos	
	Freq	Level	Factor	Level	Line	Limit		Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	143.33	54.60	-11.89	42.71	43.50	-0.79	200	176 QP
2	191.07	49.89	-12.83	37.06	43.50	-6.44	100	164 QP
3	214.51	55.40	-13.08	42.32	43.50	-1.18	100	164 QP
4	238.31	54.70	-12.98	41.72	46.00	-4.28	100	184 QP
5	285.98	49.60	-10.62	38.98	46.00	-7.02	100	164 QP
6	640.61	43.20	-3.37	39.83	46.00	-6.17	100	221 QP

Vertical:




Site : 966 Chamber #3
 Condition : FCC Part 15.205/15.209/15.247 3m vertical
 : DET:Peak
 Project No. : RKSB240506010
 Model : PLUG3/WIFI/WP/2
 Mode : WIFI Transmitting
 Test equipment : JB3,310N,ESR
 Ambient temperature : 25.5°C
 Relative humidity : 54%
 Atmospheric pressure: 101.2kPa
 Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	143.33	46.71	-11.89	34.82	43.50	-8.68	200	269	Peak
2	191.07	44.15	-12.83	31.32	43.50	-12.18	200	217	Peak
3	214.51	47.42	-13.08	34.34	43.50	-9.16	200	247	Peak
4	238.31	44.14	-12.98	31.16	46.00	-14.84	200	231	Peak
5	640.61	43.21	-3.37	39.84	46.00	-6.16	100	256	Peak
6	801.79	32.77	-0.39	32.38	46.00	-13.62	100	272	Peak

High Channel: 2462 MHz


Horizontal:



Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m horizontal
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : WIFI Transmitting
Test equipment : JB3,310N,ESR
Ambient temperature : 25.5℃
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	142.82	54.00	-11.87	42.13	43.50	-1.37	200	171	QP
2	191.07	50.49	-12.83	37.66	43.50	-5.84	200	327	QP
3	214.51	55.30	-13.08	42.22	43.50	-1.28	100	169	QP
4	238.31	54.30	-12.98	41.32	46.00	-4.68	100	169	QP
5	250.30	50.80	-12.49	38.31	46.00	-7.69	100	169	QP
6	285.98	50.80	-10.62	40.18	46.00	-5.82	100	177	QP

Vertical:




Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m vertical
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : WIFI Transmitting
Test equipment : JB3,310N,ESR
Ambient temperature : 25.5℃
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	142.82	45.40	-11.87	33.53	43.50	-9.97	200	68	QP
2	191.07	42.99	-12.83	30.16	43.50	-13.34	200	228	QP
3	214.51	47.10	-13.08	34.02	43.50	-9.48	200	236	QP
4	238.31	43.00	-12.98	30.02	46.00	-15.98	200	17	QP
5	640.61	42.60	-3.37	39.23	46.00	-6.77	100	249	QP
6	801.79	31.30	-0.39	30.91	46.00	-15.09	200	303	QP

1-18 GHz:**802.11b Mode:****Low Channel: 2412 MHz****Common Information**


Project No.: RKSB240506010
 Test Mode: 2.4G WIFI 802.11b Mode Low channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2239.300000	---	30.95	54.00	23.05	H	-11.0
2239.300000	38.02	---	74.00	35.98	H	-11.0
3036.600000	---	28.17	54.00	25.83	H	-8.3
3036.600000	38.53	---	74.00	35.47	H	-8.3
5527.100000	---	34.36	54.00	19.64	V	-0.3
5527.100000	44.37	---	74.00	29.63	V	-0.3
8797.900000	---	40.23	54.00	13.77	H	5.4
8797.900000	48.81	---	74.00	25.19	H	5.4
12114.600000	---	42.58	54.00	11.42	V	9.1
12114.600000	52.23	---	74.00	21.77	V	9.1
16371.400000	---	42.53	54.00	11.47	V	10.4
16371.400000	52.28	---	74.00	21.72	V	10.4

Middle Channel: 2437 MHz**Common Information**


Project No.: RKSB240506010
 Test Mode: 2.4G WIFI 802.11b Mode Middle channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1341.700000	---	22.42	54.00	31.58	V	-15.0
1341.700000	29.59	---	74.00	44.41	V	-15.0
2990.700000	---	29.80	54.00	24.20	V	-8.5
2990.700000	37.26	---	74.00	36.74	V	-8.5
4872.600000	---	37.37	54.00	16.63	H	-2.9
4872.600000	43.83	---	74.00	30.17	H	-2.9
7633.400000	---	38.26	54.00	15.74	V	3.9
7633.400000	48.36	---	74.00	25.64	V	3.9
11206.800000	---	42.25	54.00	11.75	V	7.9
11206.800000	52.12	---	74.00	21.88	V	7.9
16949.400000	---	42.70	54.00	11.30	H	12.1
16949.400000	52.00	---	74.00	22.00	H	12.1

High Channel: 2462 MHz**Common Information**

Project No.: RKSB240506010
 Test Mode: 2.4G WIFI 802.11b Mode High channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1134.300000	---	21.36	54.00	32.64	H	-15.3
1134.300000	28.91	---	74.00	45.09	H	-15.3
1970.700000	---	26.02	54.00	27.98	H	-11.9
1970.700000	35.06	---	74.00	38.94	H	-11.9
4942.300000	---	33.89	54.00	20.11	H	-2.7
4942.300000	42.52	---	74.00	31.48	H	-2.7
7638.500000	---	39.60	54.00	14.40	H	3.9
7638.500000	49.10	---	74.00	24.90	H	3.9
12605.900000	---	43.00	54.00	11.00	H	9.7
12605.900000	53.19	---	74.00	20.81	H	9.7
17624.300000	---	44.45	54.00	9.55	V	11.6
17624.300000	53.61	---	74.00	20.39	V	11.6

802.11g Mode:**Low Channel: 2412 MHz****Common Information**

Project No.:
Test Mode:
Standard:
Test Engineer:

RKSB240506010
2.4G WIFI 802.11g Mode Low channel
FCC Part 15.247 & FCC 15.205 & FCC 15.209
Hugh Wu


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1452.200000	---	23.28	54.00	30.72	H	-14.8
1452.200000	31.94	---	74.00	42.06	H	-14.8
2978.800000	---	28.33	54.00	25.67	V	-8.5
2978.800000	38.42	---	74.00	35.58	V	-8.5
4825.000000	---	33.11	54.00	20.89	H	-3.1
4825.000000	42.82	---	74.00	31.18	H	-3.1
7228.800000	---	41.94	54.00	12.06	H	3.2
7228.800000	49.09	---	74.00	24.91	H	3.2
11203.400000	---	42.04	54.00	11.96	V	7.9
11203.400000	51.04	---	74.00	22.96	V	7.9
17539.300000	---	43.03	54.00	10.97	H	11.6
17539.300000	52.73	---	74.00	21.27	H	11.6

Middle Channel: 2437 MHz**Common Information**

Project No.: RKSB240506010
 Test Mode: 2.4G WIFI 802.11g Mode Middle channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu


Fundamental Test
with notch filter

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1564.400000	29.62	---	74.00	44.38	V	-14.3
1564.400000	---	24.17	54.00	29.83	V	-14.3
2239.300000	---	31.12	54.00	22.88	H	-11.0
2239.300000	37.19	---	74.00	36.81	H	-11.0
4605.700000	---	32.79	54.00	21.21	V	-3.9
4605.700000	41.16	---	74.00	32.84	V	-3.9
7696.300000	---	39.87	54.00	14.13	H	3.9
7696.300000	48.59	---	74.00	25.41	H	3.9
11810.300000	---	40.52	54.00	13.48	H	8.9
11810.300000	50.21	---	74.00	23.79	H	8.9
16303.400000	---	44.23	54.00	9.77	H	10.2
16303.400000	53.90	---	74.00	20.10	H	10.2

High Channel: 2462 MHz**Common Information**

Project No.: RKSB240506010
 Test Mode: 2.4G WIFI 802.11g Mode High channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1550.800000	---	22.17	54.00	31.83	H	-14.4
1550.800000	33.05	---	74.00	40.95	H	-14.4
3067.200000	---	29.31	54.00	24.69	H	-8.1
3067.200000	39.02	---	74.00	34.98	H	-8.1
5263.600000	---	35.63	54.00	18.37	H	-1.3
5263.600000	44.36	---	74.00	29.64	H	-1.3
8806.400000	---	39.15	54.00	14.85	V	5.4
8806.400000	48.97	---	74.00	25.03	V	5.4
12061.900000	---	43.01	54.00	10.99	V	9.1
12061.900000	52.41	---	74.00	21.59	V	9.1
16808.300000	51.01	---	74.00	22.99	H	11.7
16808.300000	---	43.98	54.00	10.02	H	11.7

802.11n-HT20 Mode:

Low Channel: 2412 MHz

Common Information


Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11n20 Mode Low channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1401.200000	---	20.90	54.00	33.10	V	-14.9
1401.200000	29.19	---	74.00	44.81	V	-14.9
2178.100000	---	25.04	54.00	28.96	V	-11.2
2178.100000	34.72	---	74.00	39.28	V	-11.2
3170.900000	---	29.69	54.00	24.31	H	-7.7
3170.900000	37.76	---	74.00	36.24	H	-7.7
5251.700000	---	35.72	54.00	18.28	V	-1.4
5251.700000	44.57	---	74.00	29.43	V	-1.4
9347.000000	---	39.90	54.00	14.10	V	5.4
9347.000000	48.75	---	74.00	25.25	V	5.4
16311.900000	53.31	---	74.00	20.69	H	10.3
16313.600000	---	44.92	54.00	9.08	H	10.3

Middle Channel: 2437 MHz**Common Information**

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11n20 Mode Middle channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1394.400000	---	22.92	54.00	31.08	V	-14.9
1394.400000	31.31	---	74.00	42.69	V	-14.9
2239.300000	---	31.50	54.00	22.50	H	-11.0
2239.300000	38.21	---	74.00	35.79	H	-11.0
3832.200000	---	30.40	54.00	23.60	V	-6.1
3832.200000	40.24	---	74.00	33.76	V	-6.1
7665.700000	---	38.85	54.00	15.15	V	3.9
7665.700000	48.63	---	74.00	25.37	V	3.9
12111.200000	---	42.55	54.00	11.45	V	9.1
12111.200000	51.78	---	74.00	22.22	V	9.1
16311.900000	---	44.64	54.00	9.36	H	10.3
16311.900000	52.93	---	74.00	21.07	H	10.3

High Channel: 2462 MHz**Common Information**

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11n20 Mode High channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Fundamental Test
with notch filter

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1819.400000	---	23.39	54.00	30.61	H	-12.8
1819.400000	34.21	---	74.00	39.79	H	-12.8
3237.200000	---	30.13	54.00	23.87	H	-7.4
3237.200000	38.85	---	74.00	35.15	H	-7.4
5309.500000	---	35.09	54.00	18.91	V	-1.1
5309.500000	44.35	---	74.00	29.65	V	-1.1
7647.000000	---	40.79	54.00	13.21	V	3.9
7647.000000	49.54	---	74.00	24.46	V	3.9
12109.500000	---	44.05	54.00	9.95	V	9.1
12109.500000	52.28	---	74.00	21.72	V	9.1
16306.800000	---	45.22	54.00	8.78	H	10.3
16306.800000	54.06	---	74.00	19.94	H	10.3

Transmitting in maximum output power 802.11n20 mode high channel

1 PK
MAX

2 AV
MAX

Ref 117 dBμV

Att 10 dB

SWT 45 ms

Marker 1 [T1]
58.40 dBμV
24.865384615 GHz

O2 75 dBμV

Start 18 GHz

700 MHz/

Stop 25 GHz

Project No : RKS240506010

Tester: Hugh Wu

Date: 4.JUN.2024 09:51:08

1 PK
MOCH

2 ΔV
MOCH

Ref 117 dBμV Att 10 dB SWT 45 ms

Marker 1 [T1]
58.86 dBμV
24.809294872 GHz

D2 78 dBμV

Start 18 GHz 700 MHz/ Stop 25 GHz

1
60B
AC

2

Project No : RKS240506010
Date: 4.JUN.2024 09:35:35


Tester: Hugh Wu

Note: The test distance is 3m. The limit is 74dBuV/m(Peak) and 54dBuV/m(Average).

Band Edge:**802.11b Mode:****Low Channel****Common Information**

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11b Mode Low channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2325.610000	48.93	---	74.00	25.07	V	-0.8
2325.610000	---	39.13	54.00	14.87	V	-0.8
2378.684000	45.34	---	74.00	28.66	V	-0.6
2378.684000	---	40.38	54.00	13.62	V	-0.6

High Channel

Common Information

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11b Mode High channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum



Critical Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.944000	49.97	---	74.00	24.03	H	-0.3
2483.944000	---	39.03	54.00	14.97	H	-0.3
2486.332000	46.05	---	74.00	27.95	H	-0.2
2486.332000	---	40.75	54.00	13.25	H	-0.2


802.11g Mode :

Low Channel

Common Information

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11g Mode Low channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum




Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2389.366000	52.05	---	74.00	21.95	H	-0.6
2389.366000	---	40.36	54.00	13.64	H	-0.6
2389.814000	49.15	---	74.00	24.85	H	-0.6
2389.814000	---	42.25	54.00	11.75	H	-0.6

High Channel**Common Information**

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11b Mode High channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.686000	50.75	---	74.00	23.25	H	-0.3
2483.686000	---	40.33	54.00	13.67	H	-0.3
2483.794000	48.27	---	74.00	25.73	H	-0.3
2483.794000	---	41.64	54.00	12.36	H	-0.3


802.11n-HT20 Mode:

Low Channel

Common Information

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11n20 Mode Low channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum




Critical Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2388.274000	---	41.25	54.00	12.75	H	-0.6
2388.274000	45.95	---	74.00	28.05	H	-0.6
2389.716000	---	38.53	54.00	15.47	H	-0.6
2389.716000	50.47	---	74.00	23.53	H	-0.6

High Channel**Common Information**

Project No.: RKSB240506010
Test Mode: 2.4G WIFI 802.11n20 Mode High channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.968000	49.14	---	74.00	24.86	H	-0.3
2483.968000	---	40.37	54.00	13.63	H	-0.3
2484.406000	48.29	---	74.00	25.71	H	-0.3
2484.406000	---	41.73	54.00	12.27	H	-0.3

For BLE:

30 MHz-1 GHz:

Low Channel: 2402 MHz


Horizontal:



Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m horizontal
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : BLE Transmitting
Test equipment : JB3,310N,ESR
Ambient temperature : 25.5℃
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	143.33	54.30	-11.89	42.41	43.50	-1.09	200	162	QP
2	191.07	50.09	-12.83	37.26	43.50	-6.24	200	327	QP
3	214.51	55.50	-13.08	42.42	43.50	-1.08	100	185	QP
4	239.15	54.51	-12.95	41.56	46.00	-4.44	100	185	QP
5	262.90	50.59	-11.58	39.01	46.00	-6.99	100	185	QP
6	286.98	49.31	-10.61	38.70	46.00	-7.30	100	214	QP

Vertical:




Site : 966 Chamber #3
 Condition : FCC Part 15.205/15.209/15.247 3m vertical
 : DET:Peak
 Project No. : RKSB240506010
 Model : PLUG3/WIFI/WP/2
 Mode : BLE Transmitting
 Test equipment : J83,310N,ESR
 Ambient temperature : 25.5°C
 Relative humidity : 54%
 Atmospheric pressure: 101.2kPa
 Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	143.33	46.13	-11.89	34.24	43.50	-9.26	200	234	Peak
2	166.65	41.92	-12.93	28.99	43.50	-14.51	200	227	Peak
3	191.07	45.64	-12.83	32.81	43.50	-10.69	200	227	Peak
4	214.51	47.32	-13.08	34.24	43.50	-9.26	200	242	Peak
5	238.31	43.83	-12.98	30.85	46.00	-15.15	200	227	Peak
6	640.61	40.79	-3.37	37.42	46.00	-8.58	100	265	Peak

Middle Channel: 2440 MHz


Horizontal:



Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m horizontal
 : DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : BLE Transmitting
Test equipment : J83,310N,ESR
Ambient temperature : 25.5℃
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	142.82	54.00	-11.87	42.13	43.50	-1.37	200	167	QP
2	191.07	50.59	-12.83	37.76	43.50	-5.74	100	164	QP
3	214.51	55.70	-13.08	42.62	43.50	-0.88	100	173	QP
4	239.15	54.31	-12.95	41.36	46.00	-4.64	100	173	QP
5	262.90	49.79	-11.58	38.21	46.00	-7.79	100	192	QP
6	285.98	51.30	-10.62	40.68	46.00	-5.32	100	192	QP

Vertical:




Site : 966 Chamber #3
Condition : FCC Part 15.205/15.209/15.247 3m vertical
: DET:Peak
Project No. : RKSB240506010
Model : PLUG3/WIFI/WP/2
Mode : BLE Transmitting
Test equipment : JB3,310N,ESR
Ambient temperature : 25.5°C
Relative humidity : 54%
Atmospheric pressure: 101.2kPa
Test by : Cesium Cheng


	Read			Limit	Over	APos	TPos	
Freq	Level	Factor	Level	Line	Limit			Remark
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	143.33	46.63	-11.89	34.74	43.50	-8.76	200	248 Peak
2	167.24	41.23	-12.96	28.27	43.50	-15.23	200	220 Peak
3	191.07	44.32	-12.83	31.49	43.50	-12.01	200	59 Peak
4	214.51	47.46	-13.08	34.38	43.50	-9.12	200	230 Peak
5	239.15	43.61	-12.95	30.66	46.00	-15.34	200	230 Peak
6	640.61	41.53	-3.37	38.16	46.00	-7.84	100	259 Peak

High Channel: 2480 MHz

Horizontal:



Vertical:



Site : 966 Chamber #3
 Condition : FCC Part 15.205/15.209/15.247 3m vertical
 : DET:Peak
 Project No. : RKSB240506010
 Model : PLUG3/WIFI/WP/2
 Mode : BLE Transmitting
 Test equipment : JB3,310N,ESR
 Ambient temperature : 25.5℃
 Relative humidity : 54%
 Atmospheric pressure: 101.2kPa
 Test by : Cesium Cheng


	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	119.44	39.45	-11.99	27.46	43.50	-16.04	200	243	Peak
2	143.33	47.32	-11.89	35.43	43.50	-8.07	200	262	Peak
3	166.65	41.90	-12.93	28.97	43.50	-14.53	200	233	Peak
4	191.07	44.77	-12.83	31.94	43.50	-11.56	200	243	Peak
5	214.51	47.18	-13.08	34.10	43.50	-9.40	200	233	Peak
6	640.61	39.81	-3.37	36.44	46.00	-9.56	100	259	Peak

1-18 GHz:

Low Channel: 2402 MHz

Common Information


Project No.: RKSB240506010
Test Mode: BLE Mode Low Channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1385.900000	---	21.81	54.00	32.19	V	-14.9
1385.900000	31.88	---	74.00	42.12	V	-14.9
2239.300000	---	31.33	54.00	22.67	H	-11.0
2239.300000	36.96	---	74.00	37.04	H	-11.0
3473.500000	---	30.69	54.00	23.31	H	-6.5
3473.500000	40.80	---	74.00	33.20	H	-6.5
6618.500000	---	37.14	54.00	16.86	V	1.0
6618.500000	46.78	---	74.00	27.22	V	1.0
11211.900000	---	41.73	54.00	12.27	V	8.0
11211.900000	50.26	---	74.00	23.74	V	8.0
16765.800000	---	44.39	54.00	9.61	V	11.6
16765.800000	53.05	---	74.00	20.95	V	11.6

Middle Channel: 2440MHz**Common Information**


Project No.: RKSB240506010
Test Mode: BLE Mode Middle Channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

**Critical Freqs**



Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1238.000000	---	23.30	54.00	30.70	H	-15.1
1238.000000	31.98	---	74.00	42.02	H	-15.1
2239.300000	---	30.89	54.00	23.11	H	-11.0
2239.300000	37.37	---	74.00	36.63	H	-11.0
4571.700000	---	33.07	54.00	20.93	H	-4.0
4571.700000	42.48	---	74.00	31.52	H	-4.0
8721.400000	---	40.56	54.00	13.44	V	5.4
8721.400000	49.63	---	74.00	24.37	V	5.4
12118.000000	---	42.62	54.00	11.38	V	9.1
12118.000000	52.74	---	74.00	21.26	V	9.1
16303.400000	---	44.06	54.00	9.94	V	10.2
16303.400000	53.09	---	74.00	20.91	V	10.2

High Channel: 2480 MHz**Common Information**

Project No.: RKSB240506010
 Test Mode: BLE Mode High Channel
 Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
 Test Engineer: Hugh Wu

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1382.500000	---	22.42	54.00	31.58	H	-14.9
1382.500000	32.93	---	74.00	41.07	H	-14.9
2089.700000	---	25.88	54.00	28.12	H	-11.5
2089.700000	34.77	---	74.00	39.23	H	-11.5
4704.300000	---	33.71	54.00	20.29	V	-3.5
4704.300000	43.66	---	74.00	30.34	V	-3.5
8000.600000	---	40.34	54.00	13.66	H	3.9
8000.600000	49.32	---	74.00	24.68	H	3.9
12155.400000	---	43.76	54.00	10.24	H	9.2
12155.400000	52.80	---	74.00	21.20	H	9.2
17206.100000	---	45.05	54.00	8.95	V	12.0
17206.100000	56.75	---	74.00	17.25	V	12.0


18-25 GHz:*Transmitting in maximum output power BLE 1M mode high channel***Horizontal:****Vertical:**

Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

Band Edge:**Low Channel****Common Information**

Project No.: RKSB240506010
Test Mode: BLE Model Low Channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2383.248000	---	40.82	54.00	13.18	H	-0.6
2383.248000	45.99	---	74.00	28.01	H	-0.6
2389.632000	---	38.58	54.00	15.42	H	-0.6
2389.632000	48.09	---	74.00	25.91	H	-0.6

High Channel**Common Information**

Project No.: RKSB240506010
Test Mode: BLE Mode High Channel
Standard: FCC Part 15.247 & FCC 15.205 & FCC 15.209
Test Engineer: Hugh Wu

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2485.240000	---	43.36	54.00	10.64	H	-0.2
2485.240000	47.84	---	74.00	26.16	H	-0.2
2486.326000	---	41.29	54.00	12.71	H	-0.2
2486.326000	50.61	---	74.00	23.39	H	-0.2

6 dB EMISSION BANDWIDTH**Test Result:** Compliant.*EUT operation mode: Transmitting***For Wi-Fi Mode:**


Mode	Test Frequency (MHz)	Value (MHz)	Limit (MHz)	Result
802.11b	2412	8.160	0.5	Pass
	2437	8.120	0.5	Pass
	2462	8.160	0.5	Pass
802.11g	2412	15.520	0.5	Pass
	2437	15.200	0.5	Pass
	2462	15.400	0.5	Pass
802.11n20	2412	15.200	0.5	Pass
	2437	15.200	0.5	Pass
	2462	15.400	0.5	Pass

802.11b Mode Low Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
 Date: 28.NOV.2024 11:48:46

802.11b Mode Middle Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
 Date: 28.NOV.2024 11:58:38

802.11b Mode High Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
 Date: 28.NOV.2024 12:26:56

802.11g Mode Low Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
 Date: 28.NOV.2024 13:10:07

802.11g Mode Middle Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 13:20:17

802.11g Mode High Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 13:30:12

802.11n-HT20 Mode Low Channel




ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 13:46:07

802.11n-HT20 Mode Middle Channel



ProjectNo.:RKSB240506010 Tester:Neil Zhou
Date: 28.NOV.2024 13:55:43


802.11n-HT20 Mode High Channel




Mode	Value (MHz)	Limit (MHz)	Result
Low	0.693	0.5	Pass
Middle	0.699	0.5	Pass
High	0.703	0.5	Pass

[illegible]

Middle Channel




High Channel




OCCUPIED BANDWIDTH*EUT operation mode: Transmitting***For Wi-Fi Mode:**

Mode	99% OBW (MHz)
b_2412MHz	13.080
b_2437MHz	13.040
b_2462MHz	13.000
g_2412MHz	16.560
g_2437MHz	16.560
g_2462MHz	16.560
n20_2412MHz	17.600
n20_2437MHz	17.640
n20_2462MHz	17.640


802.11b Mode Low Channel




802.11b Mode Middle Channel



802.11b Mode High Channel



802.11g Mode Low Channel



Ref 35.5 dBm Att 35 dB SWT 5 ms

Marker 1 [T1] 2.438280000 GHz 4.71 dBm

OSW 2.560000000 MHz

Temp 1 [T1] 0.00 dBm

2.428760000 GHz

Temp 2 [T1] 0.00 dBm

2.445320000 GHz


Center 2.437 GHz 4 MHz/ Span 40 MHz

Project No.:RKSB240506010 Tester:Neil Zhou


Date: 28.NOV.2024 13:19:16

[illegible]


802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




For BLE Mode:

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
Low	2402	1.041
Middle	2440	1.041
High	2480	1.041

Low Channel



Middle Channel



High Channel




POWER SPECTRAL DENSITY**Test Result:** Compliant.*EUT operation mode: Transmitting***For Wi-Fi Mode:**

Mode	Value (dBm/3kHz)	Limit (dBm/3kHz)	Result
b_2412MHz	-3.43	8.00	Pass
b_2437MHz	-3.15	8.00	Pass
b_2462MHz	-3.94	8.00	Pass
g_2412MHz	-9.37	8.00	Pass
g_2437MHz	-10.13	8.00	Pass
g_2462MHz	-9.05	8.00	Pass
n20_2412MHz	-9.75	8.00	Pass
n20_2437MHz	-10.19	8.00	Pass
n20_2462MHz	-10.13	8.00	Pass


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel




802.11n-HT20 High Channel




For BLE Mode:

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-12.52	≤8
Middle	2440	-12.08	≤8
High	2480	-12.25	≤8


Low Channel



Middle Channel



High Channel



TRANSMITTER OUTPUT POWER MEASUREMENT**2.4G Wi-Fi:**

Mode	Peak Output Power (dBm)	Limit (dBm)	Result
b_2412MHz	16.98	30.00	Pass
b_2437MHz	16.75	30.00	Pass
b_2462MHz	16.67	30.00	Pass
g_2412MHz	20.50	30.00	Pass
g_2437MHz	20.54	30.00	Pass
g_2462MHz	20.51	30.00	Pass
n20_2412MHz	19.85	30.00	Pass
n20_2437MHz	20.30	30.00	Pass
n20_2462MHz	20.55	30.00	Pass


BLE Mode:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Peak Output Power Limit (dBm)
Low	2402	1.12	≤30
Middle	2440	1.73	≤30
High	2480	1.78	≤30


Low Channel



Middle Channel




High Channel




OUT OF BAND EMISSIONS*EUT operation mode: Transmitting***For Wi-Fi Mode:**

Mode	Value (dB)	Limit (dB)	Result
b_2412MHz	43.96	20.00	Pass
b_2462MHz	51.17	20.00	Pass
g_2412MHz	35.25	20.00	Pass
g_2462MHz	44.01	20.00	Pass
n20_2412MHz	35.70	20.00	Pass
n20_2462MHz	44.19	20.00	Pass


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side



802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




BLE 1Mbps:

Mode	Value (dB)	Limit (dB)	Result
Low	42.98	20.00	Pass
High	43.34	20.00	Pass

Left Side



Right Side



EUT PHOTOGRAPHS

Please refer to the Project No.:RKSB240506010 attachment EXHIBIT A-EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the Project No.:RKSB240506010 attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******