

TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: tei@timcoengr.com



Test Report

Product Name: WIRELESS REMOTE CONTROL RECEIVER

FCC ID: SZ23360R49

Applicant:

**PLANET TOYS (HK) LTD.
1107 CHINACHEM GOLDEN PLAZA
77 MODY ROAD, TSIMSHATSUI EAST
KOWLOON
HONG KONG**

Date Receipt: 5/4/2006

Date Tested: 5/23/2006

APPLICANT: PLANET TOYS (HK) LTD.

FCC ID: SZ23360R49

REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

COVER SHEET

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: tei@timcoengr.com

TABLE OF CONTENTS LIST

APPLICANT: PLANET TOYS (HK) LTD.

FCC ID: SZ23360R49

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2.....TEST PROCEDURES
PAGE 3.....MODIFICATIONS
PAGE 4.....RADIATION INTERFERENCE TEST DATA
PAGE 5.....TEST SET UP PHOTO

EXHIBITS CONTAINING:

STATEMENT CONFIRMING MODIFICATION
BLOCK DIAGRAM
SCHEMATIC
INSTRUCTION MANUAL
LABEL SAMPLE
LABEL LOCATION
EXTERNAL PHOTOGRAPHS
INTERNAL PHOTOGRAPHS
CIRCUIT DESCRIPTION
TEST SET UP PHOTOGRAPH

APPLICANT: PLANET TOYS (HK) LTD.

FCC ID: SZ23360R49

REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

TABLE OF CONTENTS

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: tei@timcoengr.com

EMC Equipment List

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/27/04	3/26/07
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/06	1/10/09
Antenna: Biconnical	Eaton	94455-1	1057	CAL 12/12/05	12/12/07
Antenna: Biconnical	Eaton	94455-1	1096	CAL 8/17/04	8/17/06
Antenna: Biconnical	Electro-Metrics	BIA-25	1171	CAL 4/29/05	4/29/07
Analyzer	HP	85650A	2811A01279	CAL 4/13/05	4/13/07
Blue Tower Quasi-Peak Adapter					
Analyzer	HP	85685A	2926A00983	CAL 9/5/05	9/5/07
Blue Tower RF Preselector					
Analyzer	HP	8568B	2928A04729	CAL 4/13/05	4/13/07
Blue Tower Spectrum Analyzer					
LISN	Electro-Metrics	ANS-25/2	2604	CAL 8/27/04	8/27/06
LISN	Electro-Metrics	EM-7820	2682	CAL 4/28/05	4/28/07
Antenna: Log-Periodic	Eaton	96005	1243	CAL 12/14/05	12/14/07

APPLICANT: PLANET TOYS (HK) LTD.

FCC ID: SZ23360R49

REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: tei@timcoengr.com

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2003 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 KHZ with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHZ and the video bandwidth was 300KHZ. The ambient temperature of the UUT was 80°F with a humidity of 70%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.4-2003 12.1.1.1 SUPERREGENERATIVE RECEIVER: A Signal Generator was set to the unit under test operating frequency. An un-modulated continuous wave (CW) signal was radiated at the super-regenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

APPLICANT: PLANET TOYS (HK) LTD.
FCC ID: SZ23360R49
REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: tei@timcoengr.com

MODIFICATIONS:

In order to get passing results the following modifications were required:

Change the value of R1 to 330K.

APPLICANT: PLANET TOYS (HK) LTD.
FCC ID: SZ23360R49
REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: tei@timcoengr.com

APPLICANT: PLANET TOYS (HK) LTD.
FCC ID: SZ23360R49
NAME OF TEST: RADIATION INTERFERENCE
RULES PART NO.: 15.109

REQUIREMENTS: 30 to 88 MHz: 40.0 dBuV/M @ 3 METERS
88 to 216 MHz: 43.5 dBuV/M
216 to 960 MHz: 46.0 dBuV/M
ABOVE 960 MHz: 54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
49.9	45.83	22.6	H	0.48	11.20	34.28	5.72
49.9	46.00	29.1	V	0.48	10.30	39.88	0.12
49.9	48.62	25.1	H	0.49	11.20	36.79	3.21
49.9	48.68	28.5	V	0.49	10.84	39.83	0.17
49.9	51.37	26.0	V	0.50	11.29	37.79	2.21
49.9	51.38	25.4	H	0.50	11.20	37.10	2.90
49.9	52.99	25.7	H	0.51	11.20	37.41	2.59
49.9	53.07	27.8	V	0.51	11.53	39.84	0.16
49.9	54.61	24.4	H	0.52	11.20	36.12	3.88
49.9	54.67	27.5	V	0.52	11.75	39.77	0.23
49.9	55.91	20.9	H	0.52	11.18	32.60	7.40
49.9	55.96	27.6	V	0.52	11.74	39.86	0.14
49.9	57.04	15.4	H	0.52	11.16	27.08	12.92
49.9	57.18	22.3	V	0.52	11.67	34.49	5.51
49.9	58.47	15.5	V	0.53	11.59	27.62	12.38
49.9	89.35	29.8	V	0.62	9.28	39.70	3.80
49.9	89.54	21.3	H	0.62	8.11	30.03	13.47
49.9	93.52	23.4	V	0.63	10.34	34.37	9.13
49.9	96.56	18.9	V	0.64	10.98	30.52	12.98
49.9	99.42	16.7	V	0.65	11.50	28.85	14.65

SAMPLE CALCULATION: FSdBuV/m = MR (dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-2003. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: RICHARD BLOCK

DATE: 5/23/06

APPLICANT: PLANET TOYS (HK) LTD.
FCC ID: SZ23360R49
REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc

TIMCO ENGINEERING INC.


849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: tei@timcoengr.com

TEST SET UP PHOTO



APPLICANT: PLANET TOYS (HK) LTD.

FCC ID: SZ23360R49

REPORT #: P\PLANET_SZ2\639ZUT6\639ZUT6TestReport.doc