

Appendix B. SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 GPRS (Distance 0.5cm)

Report Date : 30-Jul-2008
Measurement Date : 30-Jul-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 30-Jul-2008
Temperature : 20.20 °C
Ambient Temp. : 20.80 °C
Humidity : 52.00 RH%
Epsilon : 56.12 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.021 W/kg
 Power Drift-Finish: 0.021 W/kg
 Power Drift (%) : -0.690

DUT Position : Touch EUT Front
 Channel : 128




1 gram SAR value : 0.049 W/kg
 10 gram SAR value : 0.031 W/kg
 Area Scan Peak SAR : 0.052 W/kg
 Zoom Scan Peak SAR : 0.096 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.031 W/kg
 Power Drift-Finish: 0.032 W/kg
 Power Drift (%) : 3.225

DUT Position : Touch EUT Front
 Channel : 189




1 gram SAR value : 0.057 W/kg
 10 gram SAR value : 0.039 W/kg
 Area Scan Peak SAR : 0.060 W/kg
 Zoom Scan Peak SAR : 0.085 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.035 W/kg
 Power Drift-Finish: 0.035 W/kg
 Power Drift (%) : -0.461

DUT Position : Touch EUT Front
 Channel : 251



1 gram SAR value : 0.037 W/kg
 10 gram SAR value : 0.031 W/kg
 Area Scan Peak SAR : 0.040 W/kg
 Zoom Scan Peak SAR : 0.076 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 GPRS (Distance 0.5cm)

Report Date : 30-Jul-2008
Measurement Date : 30-Jul-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 30-Jul-2008
Temperature : 20.20 °C
Ambient Temp. : 20.80 °C
Humidity : 52.00 RH%
Epsilon : 56.12 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.027 W/kg
 Power Drift-Finish: 0.027 W/kg
 Power Drift (%) : 0.537

DUT Position : Touch EUT Back
 Channel : 189



1 gram SAR value : 0.051 W/kg
 10 gram SAR value : 0.033 W/kg
 Area Scan Peak SAR : 0.053 W/kg
 Zoom Scan Peak SAR : 0.105 W/kg



SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 GPRS (Distance 0cm)

Report Date : 26-Sep-2008
Measurement Date : 26-Sep-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 26-Sep-2008
Temperature : 20.00 °C
Ambient Temp. : 20.70 °C
Humidity : 48.00 RH%
Epsilon : 56.52 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.074 W/kg
 Power Drift-Finish: 0.074 W/kg
 Power Drift (%) : -0.134

DUT Position : Touch EUT Front
 Channel : 128




1 gram SAR value : 0.092 W/kg
 10 gram SAR value : 0.037 W/kg
 Area Scan Peak SAR : 0.114 W/kg
 Zoom Scan Peak SAR : 0.160 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.083 W/kg
 Power Drift-Finish: 0.080 W/kg
 Power Drift (%) : -3.695

DUT Position : Touch EUT Front
 Channel : 189




1 gram SAR value : 0.101 W/kg
 10 gram SAR value : 0.039 W/kg
 Area Scan Peak SAR : 0.117 W/kg
 Zoom Scan Peak SAR : 0.165 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.070 W/kg
 Power Drift-Finish: 0.073 W/kg
 Power Drift (%) : 4.285

DUT Position : Touch EUT Front
 Channel : 251



1 gram SAR value : 0.085 W/kg
 10 gram SAR value : 0.035 W/kg
 Area Scan Peak SAR : 0.110 W/kg
 Zoom Scan Peak SAR : 0.152 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 GPRS (Distance 0cm)

Report Date : 26-Sep-2008

Measurement Date : 26-Sep-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 26-Sep-2008
Temperature : 20.00 °C
Ambient Temp. : 20.70 °C
Humidity : 48.00 RH%
Epsilon : 56.52 F/m
Sigma : 0.99 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.056 W/kg
 Power Drift-Finish: 0.054 W/kg
 Power Drift (%) : -3.596

DUT Position : Touch EUT Back
 Channel : 189



1 gram SAR value : 0.072 W/kg
 10 gram SAR value : 0.031 W/kg
 Area Scan Peak SAR : 0.079 W/kg
 Zoom Scan Peak SAR : 0.115 W/kg



SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 (Distance 0cm)

Report Date : 14-Oct-2008
Measurement Date : 14-Oct-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 74.5 mm
Width : 42.3 mm
Depth : 27.6 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 14-Oct-2008
Temperature : 20.10 °C
Ambient Temp. : 20.60 °C
Humidity : 49.00 RH%
Epsilon : 56.57 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 8
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.023 W/kg
 Power Drift-Finish: 0.023 W/kg
 Power Drift (%) : 0.090

DUT Position : Touch EUT Front
 Channel : 128




1 gram SAR value : 0.078 W/kg
 10 gram SAR value : 0.060 W/kg
 Area Scan Peak SAR : 0.120 W/kg
 Zoom Scan Peak SAR : 0.145 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.024 W/kg
 Power Drift-Finish: 0.024 W/kg
 Power Drift (%) : -0.456

DUT Position : Touch EUT Front
 Channel : 189




1 gram SAR value : 0.076 W/kg
 10 gram SAR value : 0.057 W/kg
 Area Scan Peak SAR : 0.110 W/kg
 Zoom Scan Peak SAR : 0.131 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.022 W/kg
 Power Drift-Finish: 0.022 W/kg
 Power Drift (%) : -0.974

DUT Position : Touch EUT Front
 Channel : 251



1 gram SAR value : 0.147 W/kg
 10 gram SAR value : 0.102 W/kg
 Area Scan Peak SAR : 0.262 W/kg
 Zoom Scan Peak SAR : 0.245 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-GSM 835 (Distance 0cm)

Report Date : 14-Oct-2008
Measurement Date : 14-Oct-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 850.00 MHz
Max. Transmit Pwr : 2 W
Drift Time : 0 min(s)
Length : 74.5 mm
Width : 42.3 mm
Depth : 27.6 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 322-B
Frequency : 835.00 MHz
Last Calib. Date : 14-Oct-2008
Temperature : 20.10 °C
Ambient Temp. : 20.60 °C
Humidity : 49.00 RH%
Epsilon : 56.57 F/m
Sigma : 0.98 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 835.00 MHz
Duty Cycle Factor: 8
Conversion Factor: 6.6
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.023 W/kg
 Power Drift-Finish: 0.023 W/kg
 Power Drift (%) : -0.253


DUT Position : Touch EUT Back
 Channel : 128



1 gram SAR value : 0.067 W/kg
 10 gram SAR value : 0.054 W/kg
 Area Scan Peak SAR : 0.110 W/kg
 Zoom Scan Peak SAR : 0.102 W/kg



GSM 835 (Distance 0cm) EUT Front Z-Axis plot
Channel: 251



SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-PCS 1900 GPRS (Distance 0.5cm)

Report Date : 30-Jul-2008
Measurement Date : 30-Jul-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 30-Jul-2007
Temperature : 20.20 °C
Ambient Temp. : 20.80 °C
Humidity : 52.00 RH%
Epsilon : 53.76 F/m
Sigma : 1.53 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.038 W/kg
 Power Drift-Finish: 0.038 W/kg
 Power Drift (%) : 0.357

DUT Position : Touch EUT Front
 Channel : 512




1 gram SAR value : 0.074 W/kg
 10 gram SAR value : 0.041 W/kg
 Area Scan Peak SAR : 0.080 W/kg
 Zoom Scan Peak SAR : 0.152 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.102 W/kg
 Power Drift-Finish: 0.099 W/kg
 Power Drift (%) : -2.941

DUT Position : Touch EUT Front
 Channel : 661




1 gram SAR value : 0.123 W/kg
 10 gram SAR value : 0.065 W/kg
 Area Scan Peak SAR : 0.150 W/kg
 Zoom Scan Peak SAR : 0.256 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.127 W/kg
 Power Drift-Finish: 0.131 W/kg
 Power Drift (%) : -3.149

DUT Position : Touch EUT Front
 Channel : 810



1 gram SAR value : 0.151 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.180 W/kg
 Zoom Scan Peak SAR : 0.269 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-PCS 1900 GPRS (Distance 0.5cm)

Report Date : 30-Jul-2008
Measurement Date : 30-Jul-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 30-Jul-2007
Temperature : 20.20 °C
Ambient Temp. : 20.80 °C
Humidity : 52.00 RH%
Epsilon : 53.76 F/m
Sigma : 1.53 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.20 °C
 Ambient Temp. : 20.80 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.111 W/kg
 Power Drift-Finish: 0.107 W/kg
 Power Drift (%) : -4.284

DUT Position : Touch EUT Back
 Channel : 661



1 gram SAR value : 0.092 W/kg
 10 gram SAR value : 0.043 W/kg
 Area Scan Peak SAR : 0.120 W/kg
 Zoom Scan Peak SAR : 0.178 W/kg



SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-PCS 1900 GPRS (Distance 0cm)

Report Date : 26-Sep-2008
Measurement Date : 26-Sep-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 26-Sep-2007
Temperature : 20.00 °C
Ambient Temp. : 20.70 °C
Humidity : 48.00 RH%
Epsilon : 54.21 F/m
Sigma : 1.55 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.204 W/kg
 Power Drift-Finish: 0.201 W/kg
 Power Drift (%) : -1.470

DUT Position : Touch EUT Front
 Channel : 512




1 gram SAR value : 0.286 W/kg
 10 gram SAR value : 0.074 W/kg
 Area Scan Peak SAR : 0.320 W/kg
 Zoom Scan Peak SAR : 0.511 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.221 W/kg
 Power Drift-Finish: 0.216 W/kg
 Power Drift (%) : -2.560

DUT Position : Touch EUT Front
 Channel : 661




1 gram SAR value : 0.301 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.320 W/kg
 Zoom Scan Peak SAR : 0.510 W/kg




Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.197 W/kg
 Power Drift-Finish: 0.191 W/kg
 Power Drift (%) : -2.993

DUT Position : Touch EUT Front
 Channel : 810



1 gram SAR value : 0.312 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.350 W/kg
 Zoom Scan Peak SAR : 0.535 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories
SAR Test Report-PCS 1900 GPRS (Distance 0cm)

Report Date : 26-Sep-2008
Measurement Date : 26-Sep-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 63.1 mm
Width : 43.6 mm
Depth : 21.4 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 26-Sep-2007
Temperature : 20.00 °C
Ambient Temp. : 20.70 °C
Humidity : 48.00 RH%
Epsilon : 54.21 F/m
Sigma : 1.55 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 4
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 4
 Tissue Temp. : 20.00 °C
 Ambient Temp. : 20.70 °C
 Area Scan : 6x6x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.140 W/kg
 Power Drift-Finish: 0.137 W/kg
 Power Drift (%) : -2.556

DUT Position : Touch EUT Back
 Channel : 810



1 gram SAR value : 0.195 W/kg
 10 gram SAR value : 0.079 W/kg
 Area Scan Peak SAR : 0.220 W/kg
 Zoom Scan Peak SAR : 0.321 W/kg



SAR measurement Data

ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-PCS 1900 (Distance 0cm)

Report Date : 14-Oct-2008

Measurement Date : 14-Oct-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 74.5 mm
Width : 42.3 mm
Depth : 27.6 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 14-Oct-2008
Temperature : 20.10 °C
Ambient Temp. : 20.60 °C
Humidity : 49.00 RH%
Epsilon : 54.19 F/m
Sigma : 1.54 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 8
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.040 W/kg
 Power Drift-Finish: 0.040 W/kg
 Power Drift (%) : -0.357

DUT Position : Touch EUT Front
 Channel : 512




1 gram SAR value : 0.298 W/kg
 10 gram SAR value : 0.185 W/kg
 Area Scan Peak SAR : 0.350 W/kg
 Zoom Scan Peak SAR : 0.533 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.035 W/kg
 Power Drift-Finish: 0.035 W/kg
 Power Drift (%) : -0.305

DUT Position : Touch EUT Front
 Channel : 661




1 gram SAR value : 0.291 W/kg
 10 gram SAR value : 0.185 W/kg
 Area Scan Peak SAR : 0.342 W/kg
 Zoom Scan Peak SAR : 0.503 W/kg




Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.038 W/kg
 Power Drift-Finish: 0.038 W/kg
 Power Drift (%) : -0.943

DUT Position : Touch EUT Front
 Channel : 810



1 gram SAR value : 0.282 W/kg
 10 gram SAR value : 0.168 W/kg
 Area Scan Peak SAR : 0.336 W/kg
 Zoom Scan Peak SAR : 0.497 W/kg



ALSAS-10U VER 2.3.6 APREL Laboratories

SAR Test Report-PCS 1900 (Distance 0cm)

Report Date : 14-Oct-2008
Measurement Date : 14-Oct-2008

Product Data

Device Name : navibe
Type : Other
Model : GT701
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 74.5 mm
Width : 42.3 mm
Depth : 27.6 mm
Antenna Type : Internal

Phantom Data

Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Location : Center

Tissue Data

Type : BODY
Serial No. : 324-B
Frequency : 1900.00 MHz
Last Calib. Date : 14-Oct-2008
Temperature : 20.10 °C
Ambient Temp. : 20.60 °C
Humidity : 49.00 RH%
Epsilon : 54.19 F/m
Sigma : 1.54 S/m
Density : 1000.00 kg/cu. m


Probe Data

Name : Probe 265
Model : E020
Type : E-Field Triangle
Serial No. : 265
Last Calib. Date : 09-May-2008
Frequency : 1900.00 MHz
Duty Cycle Factor: 8
Conversion Factor: 5.1
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{m})^2$
Compression Point: 95.00 mV
Offset : 1.56 mm


Measurement Data

Crest Factor : 8
 Tissue Temp. : 20.10 °C
 Ambient Temp. : 20.60 °C
 Area Scan : 6x5x1 : Measurement x=12mm, y=12mm, z=4mm
 Zoom Scan : 5x5x4 : Measurement x=8mm, y=8mm, z=4mm
 Power Drift-Start : 0.049 W/kg
 Power Drift-Finish: 0.049 W/kg
 Power Drift (%) : 0.031

DUT Position : Touch EUT Back
 Channel : 661



1 gram SAR value : 0.285 W/kg
 10 gram SAR value : 0.173 W/kg
 Area Scan Peak SAR : 0.342 W/kg
 Zoom Scan Peak SAR : 0.506 W/kg



PCS 1900 GPRS (Distance 0cm) EUT Front Z-Axis plot
Channel: 810

