



FCC RADIO TEST REPORT

FCC ID : SZG-G99E5
Equipment : Wireless Device
Model Name : G99E5
Applicant : Weifang Goertek Electronics Co., Ltd
Gaoxin 2 Road, Free Trade Zone, Weifang, Shandong,
261205, P.R.China
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 23, 2025 and testing was performed from May 26, 2025 to Jun. 21, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	9
3 Test Result.....	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	11
3.3 Power Spectral Density Measurement	12
3.4 Conducted Band Edges and Spurious Emission Measurement	13
3.5 Radiated Band Edges and Spurious Emission Measurement	14
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR550853D	01	Initial issue of report	Jul. 02, 2025
FR550853D	02	Revise List of Measuring Equipment This report is an updated version, replacing the report issued on Jul. 02, 2025.	Jul. 10, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Avis Chuang

Report Producer: Shannon Huang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, BLE, Thread, Wi-Fi 802.11ax
Antenna Type Thread: PCB Antenna

EUT Information List	
S/N	Performed Test Item
1Y7G6501600802M154JS0801	RF Conducted Measurement
G2526506 (#6)	Radiated Spurious Emission
G2526510 (#8)	Conducted Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	4

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH20-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	11	2405	19	2445
	12	2410	20	2450
	13	2415	21	2455
	14	2420	22	2460
	15	2425	23	2465
	16	2430	24	2470
	17	2435	25	2475
	18	2440	26	2480

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Thread / GFSK
	Mode 1: Thread Tx CH11_2405 MHz
	Mode 2: Thread Tx CH18_2440 MHz
	Mode 3: Thread Tx CH25_2475 MHz
	Mode 4: Thread Tx CH26_2480 MHz
AC Conducted Emission	Mode 1: Thread Tx CH18 + AC Adapter
Remark:	
1. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	
2. The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Thread Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Type C to C cable	CableTech	N/A	N/A	N/A	N/A
2.	Fixture	Goertek	DG01	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “ADB v1.0.40” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.



3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

9. Method AVGSA-2

Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction:


If continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle D of the transmitter output signal as described in 11.6.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = RMS (power averaging), if $\text{span} / (\# \text{ of points in sweep}) \leq (\text{RBW} / 2)$.
Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.


Reduction of the measured emission amplitude levels to account for operational duty cycle is not permitted. Determining compliance is based on emission levels occurring during transmission; it is not based on an average across ON and OFF times of the transmitter.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECEPEL	TR-32	HE17XB2468	N/A	Mar. 13, 2025	May 27, 2025 Jun. 17, 2025	Mar. 12, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO 11 (NO:117)	10MHz~6GHz	Jan. 04, 2025	May 27, 2025 Jun. 17, 2025	Jan. 03, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	May 27, 2025 Jun. 17, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW191204 (BOX8)	N/A	Dec. 31, 2024	May 27, 2025 Jun. 17, 2025	Dec. 30, 2025	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jun. 11, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 11, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 23, 2024	Jun. 11, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 3, 2025	Jun. 11, 2025	Mar. 2, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Jun. 11, 2025	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Jun. 11, 2025	Sep. 22, 2025	Conduction (CO07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 16, 2024	May 26, 2025~ Jun. 21, 2025	Oct. 15, 2025	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	May 26, 2025~ Jun. 21, 2025	Aug. 28, 2025	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060871	18GHz~40GHz	Aug. 23, 2024	May 26, 2025~ Jun. 21, 2025	Aug. 22, 2025	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	May 26, 2025~ Jun. 21, 2025	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 26, 2025~ Jun. 21, 2025	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 26, 2025~ Jun. 21, 2025	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 09, 2024	May 26, 2025~ Jun. 21, 2025	Dec. 08, 2025	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	55606 & 08	30MHz~1GHz	Nov. 27, 2024	May 26, 2025~ Jun. 21, 2025	Nov. 26, 2025	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 01, 2024	May 26, 2025~ Jun. 21, 2025	Oct. 31, 2025	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1223	18GHz-40GHz	Jun. 24, 2024	May 26, 2025~ Jun. 21, 2025	Jun. 23, 2025	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Dec. 31, 2024	May 26, 2025~ Jun. 21, 2025	Dec. 30, 2025	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45S E	980792	N/A	Nov. 12, 2024	May 26, 2025~ Jun. 21, 2025	Nov. 11, 2025	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,804 015/2,804027 /2	N/A	Jan. 16, 2025	May 26, 2025~ Jun. 21, 2025	Jan. 15, 2026	Radiation (03CH20-HY)
Hygrometer	TECEPEL	DTM-303A	TP211382	N/A	Mar. 31, 2025	May 26, 2025~ Jun. 21, 2025	Mar. 30, 2026	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	May 26, 2025~ Jun. 21, 2025	N/A	Radiation (03CH20-HY)

**FCC RADIO TEST REPORT****Report No. : FR550853D**

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Attenuator	Woken	WATT-218FS-10	N/A	10dB	Sep. 25, 2024	May 26, 2025~ Jun. 21, 2025	Sep. 24, 2025	Radiation (03CH20-HY)
Notch Filter	Wainwright	WHKX12-2700 -3000-18000-6 0ST	SN8	3GHz High Pass Filter	Mar. 22, 2025	May 26, 2025~ Jun. 21, 2025	Mar. 21, 2026	Radiation (03CH20-HY)
Notch Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN27	1.53GHz Low Pass Filter	May 21, 2025	May 26, 2025~ Jun. 21, 2025	May 20, 2026	Radiation (03CH20-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Benny Ku	Temperature:	21~25	°C
Test Date:	2025/5/27~2025/6/17	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Thread	250K	1	11	2405	2.246	1.585	0.50	Pass
Thread	250K	1	18	2440	2.243	1.596	0.50	Pass
Thread	250K	1	25	2475	2.245	1.587	0.50	Pass
Thread	250K	1	26	2480	2.249	1.600	0.50	Pass





TEST RESULTS DATA
Average Power Table





Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Thread	250K	1	11	2405	21.00	30.00	4.00	25.00	36.00	Pass
Thread	250K	1	18	2440	21.00	30.00	4.00	25.00	36.00	Pass
Thread	250K	1	25	2475	20.90	30.00	4.00	24.90	36.00	Pass
Thread	250K	1	26	2480	2.70	30.00	4.00	6.70	36.00	Pass





TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
Thread	250K	1	11	2405	16.31	4.86	4.00	8.00	Pass
Thread	250K	1	18	2440	15.98	4.96	4.00	8.00	Pass
Thread	250K	1	25	2475	15.98	4.83	4.00	8.00	Pass
Thread	250K	1	26	2480	-1.05	-12.48	4.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**6dB Bandwidth****6 dB Bandwidth Plot on Channel 11****6 dB Bandwidth Plot on Channel 18****6 dB Bandwidth Plot on Channel 25****6 dB Bandwidth Plot on Channel 26**

**99% Occupied Bandwidth****99% Occupied Bandwidth Plot on Channel 11****99% Occupied Bandwidth Plot on Channel 18****99% Occupied Bandwidth Plot on Channel 25****99% Occupied Bandwidth Plot on Channel 26**


**Power Spectral Density (dBm/3kHz)****Power Density (dBm/3kHz) Plot Channel 11****Power Density (dBm/3kHz) Plot Channel 18****Power Density (dBm/3kHz) Plot Channel 25****Power Density (dBm/3kHz) Plot Channel 26**




Band Edge and Conducted Spurious Emission

Channel 11


100kHz PSD reference Level Plot




Plot on Channel 11



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 18

100kHz PSD reference Level Plot




Plot on Channel 18

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 25


100kHz PSD reference Level Plot




Plot on Channel 25



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 26


100kHz PSD reference Level Plot




Plot on Channel 26



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	22.7 ~ 26.4 °C
		Relative Humidity :	48.3 ~ 53.8 %

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

550853
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.154500	---	23.34	55.75	32.41	L1	FLO	20.0
0.154500	40.27	---	65.75	25.48	L1	FLO	20.0
0.177000	---	20.29	54.63	34.34	L1	FLO	20.0
0.177000	33.57	---	64.63	31.06	L1	FLO	20.0
0.194820	---	20.24	53.83	33.59	L1	FLO	20.0
0.194820	33.31	---	63.83	30.52	L1	FLO	20.0
0.739500	---	23.33	46.00	22.67	L1	FLO	20.0
0.739500	30.69	---	56.00	25.31	L1	FLO	20.0
0.757500	---	26.17	46.00	19.83	L1	FLO	20.0
0.757500	32.96	---	56.00	23.04	L1	FLO	20.0
12.827850	---	25.73	50.00	24.27	L1	FLO	20.5
12.827850	32.07	---	60.00	27.93	L1	FLO	20.5
21.702570	---	17.92	50.00	32.08	L1	FLO	20.9
21.702570	20.64	---	60.00	39.36	L1	FLO	20.9

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

550853
Mode 1
120Vac/60Hz
Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.150000	---	24.53	56.00	31.47	N	FLO	20.0
0.150000	40.78	---	66.00	25.22	N	FLO	20.0
0.181500	---	20.15	54.42	34.27	N	FLO	20.0
0.181500	36.18	---	64.42	28.24	N	FLO	20.0
0.206970	---	18.71	53.33	34.62	N	FLO	20.0
0.206970	31.18	---	63.33	32.15	N	FLO	20.0
0.295530	---	17.05	50.37	33.32	N	FLO	20.0
0.295530	28.98	---	60.37	31.39	N	FLO	20.0
0.759750	---	24.98	46.00	21.02	N	FLO	20.0
0.759750	36.53	---	56.00	19.47	N	FLO	20.0
12.936210	---	26.19	50.00	23.81	N	FLO	20.5
12.936210	31.89	---	60.00	28.11	N	FLO	20.5
21.527250	---	18.24	50.00	31.76	N	FLO	20.9
21.527250	21.02	---	60.00	38.98	N	FLO	20.9



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	John Chuang 、 David Dai ,and Sam Chou	Relative Humidity(%):	65.4 ~ 70.3
		Temperature(°C):	19.3 ~ 22.4

Note symbol

-L	Low channel location
-R	High channel location





C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Thread	11	2405	250kbps	-	-
Mode 2	2400-2483.5	1	Thread	18	2440	250kbps	-	-
Mode 3	2400-2483.5	1	Thread	25	2475	250kbps	-	-
Mode 4	2400-2483.5	1	Thread	26	2480	250kbps	-	-
Mode 5	2400-2483.5	1	Thread	18	2440	250kbps	-	LF
Mode 6	2400-2483.5	1	Thread	18	2440	250kbps	-	SHF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Thread	11	2365.20	44.10	54.00	-9.90	H	Avg.	Pass	-	Band Edge
	Thread	11	4810.00	44.23	74.00	-29.77	V	Peak	Pass	-	Harmonic
2	Thread	18	2495.26	44.82	54.00	-9.18	H	Avg.	Pass	-	Band Edge
	Thread	18	7320.00	38.67	54.00	-15.33	V	Avg.	Pass	-	Harmonic
3	Thread	25	2483.58	46.19	54.00	-7.81	H	Avg.	Pass	-	Band Edge
	Thread	25	7425.00	47.70	74.00	-26.30	H	Peak	Pass	-	Harmonic
4	Thread	26	2483.52	52.32	54.00	-1.68	H	Avg.	Pass	-	Band Edge
	Thread	26	-	-	-	-	-	-	-	-	Harmonic
5	Thread	18	84.32	29.77	40.00	-10.23	V	Peak	Pass	-	LF
6	Thread	18	19520.00	43.15	54.00	-10.85	V	Avg.	Pass	-	SHF



Mode	1																																																																																																													
	Band Edge																																																																																																													
	2400-2483.5_Thread_CH11_2405MHz																																																																																																													
ANT	1																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																							
Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2365.39</td><td>58.94</td><td>74.00</td><td>-15.06</td><td>49.64</td><td>27.30</td><td>8.58</td><td>36.26</td><td>9.68</td><td>320</td><td>289 Peak</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2365.39	58.94	74.00	-15.06	49.64	27.30	8.58	36.26	9.68	320	289 Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>117.77</td><td>-----</td><td>-----</td><td>108.25</td><td>27.46</td><td>8.65</td><td>36.27</td><td>9.68</td><td>320</td><td>289 Peak</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2405.00	117.77	-----	-----	108.25	27.46	8.65	36.27	9.68	320	289 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																				
1	2365.39	58.94	74.00	-15.06	49.64	27.30	8.58	36.26	9.68	320	289 Peak																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																				
1	2405.00	117.77	-----	-----	108.25	27.46	8.65	36.27	9.68	320	289 Peak																																																																																																			
Avg	Level (dBuV/m) Date: 2025-05-28  Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2365.20</td><td>44.10</td><td>54.00</td><td>-9.90</td><td>34.00</td><td>27.30</td><td>8.58</td><td>36.26</td><td>9.68</td><td>320</td><td>289 Average</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2365.20	44.10	54.00	-9.90	34.00	27.30	8.58	36.26	9.68	320	289 Average	Level (dBuV/m) Date: 2025-05-28  Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>111.36</td><td>-----</td><td>-----</td><td>101.86</td><td>27.44</td><td>8.65</td><td>36.27</td><td>9.68</td><td>320</td><td>289 Average</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2405.00	111.36	-----	-----	101.86	27.44	8.65	36.27	9.68	320	289 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																				
1	2365.20	44.10	54.00	-9.90	34.00	27.30	8.58	36.26	9.68	320	289 Average																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																				
1	2405.00	111.36	-----	-----	101.86	27.44	8.65	36.27	9.68	320	289 Average																																																																																																			



Mode	1																																																					
	Band Edge																																																					
	2400-2483.5_Thread_CH11_2405MHz																																																					
ANT	1																																																					
Pol.	Vertical																																																					
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2364.63</td><td>57.07</td><td>74.00</td><td>-16.93</td><td>47.78</td><td>27.30</td><td>8.57</td><td>36.26</td><td>9.68</td><td>122</td><td>98 Peak</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2364.63	57.07	74.00	-16.93	47.78	27.30	8.57	36.26	9.68	122	98 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2364.63	57.07	74.00	-16.93	47.78	27.30	8.57	36.26	9.68	122	98 Peak																																											
Fundamental	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>114.90</td><td>-----</td><td>-----</td><td>105.38</td><td>27.46</td><td>8.65</td><td>36.27</td><td>9.68</td><td>122</td><td>98 Peak</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2405.00	114.90	-----	-----	105.38	27.46	8.65	36.27	9.68	122	98 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2405.00	114.90	-----	-----	105.38	27.46	8.65	36.27	9.68	122	98 Peak																																											
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2369.14</td><td>43.62</td><td>54.00</td><td>-10.38</td><td>34.21</td><td>27.38</td><td>8.62</td><td>36.27</td><td>9.68</td><td>122</td><td>98 Average</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.14	43.62	54.00	-10.38	34.21	27.38	8.62	36.27	9.68	122	98 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2369.14	43.62	54.00	-10.38	34.21	27.38	8.62	36.27	9.68	122	98 Average																																											
Ave	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>107.99</td><td>-----</td><td>-----</td><td>98.49</td><td>27.44</td><td>8.65</td><td>36.27</td><td>9.68</td><td>122</td><td>98 Average</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2405.00	107.99	-----	-----	98.49	27.44	8.65	36.27	9.68	122	98 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2405.00	107.99	-----	-----	98.49	27.44	8.65	36.27	9.68	122	98 Average																																											



Mode	1																																																																																							
	Harmonic																																																																																							
	2400-2483.5_Thread_CH11_2405MHz																																																																																							
ANT	1																																																																																							
Pol.	Horizontal	Vertical																																																																																						
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91280_02360_241101 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4810.00</td><td>43.45</td><td>74.00</td><td>-30.55</td><td>35.80</td><td>32.28</td><td>12.26</td><td>37.52</td><td>0.63</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4810.00	43.45	74.00	-30.55	35.80	32.28	12.26	37.52	0.63	--	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91280_02360_241101 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4810.00</td><td>44.23</td><td>74.00</td><td>-29.77</td><td>36.58</td><td>32.28</td><td>12.26</td><td>37.52</td><td>0.63</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4810.00	44.23	74.00	-29.77	36.58	32.28	12.26	37.52	0.63	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	4810.00	43.45	74.00	-30.55	35.80	32.28	12.26	37.52	0.63	--	Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	4810.00	44.23	74.00	-29.77	36.58	32.28	12.26	37.52	0.63	--	Peak																																																																													



Mode	1	
	Harmonic	
	2400-2483.5_Thread_CH11_2405MHz	
ANT	1	
Pol.	Horizontal	Vertical
10G ~18G Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 HORIZONTAL	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 VERTICAL



Mode	2											
	Band Edge - L											
	2400-2483.5_Thread_CH18_2440MHz											
ANT	1											
Pol.	Horizontal						Fundamental					
Peak	Level (dBuV/m) Date: 2025-05-28											



Mode	2									
	Band Edge - R									
	2400-2483.5_Thread_CH18_2440MHz									
ANT	1									
Pol.	Horizontal					Fundamental				
Peak	<									



Mode	2																																																																																							
	Band Edge - L																																																																																							
	2400-2483.5_Thread_CH18_2440MHz																																																																																							
ANT	1																																																																																							
Pol.	Vertical	Fundamental																																																																																						
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2369.57</td><td>51.14</td><td>74.00</td><td>-22.86</td><td>41.85</td><td>27.30</td><td>8.57</td><td>36.26</td><td>9.68</td><td>100</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.57	51.14	74.00	-22.86	41.85	27.30	8.57	36.26	9.68	100	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>114.50</td><td>-----</td><td>-----</td><td>104.79</td><td>27.60</td><td>8.71</td><td>36.28</td><td>9.68</td><td>100</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	114.50	-----	-----	104.79	27.60	8.71	36.28	9.68	100	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																															
Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2369.57	51.14	74.00	-22.86	41.85	27.30	8.57	36.26	9.68	100	Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2440.00	114.50	-----	-----	104.79	27.60	8.71	36.28	9.68	100	Peak																																																																													
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2369.28</td><td>43.60</td><td>54.00</td><td>-10.40</td><td>34.30</td><td>27.30</td><td>8.58</td><td>36.26</td><td>9.68</td><td>100</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.28	43.60	54.00	-10.40	34.30	27.30	8.58	36.26	9.68	100	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>109.19</td><td>-----</td><td>-----</td><td>99.48</td><td>27.60</td><td>8.71</td><td>36.28</td><td>9.68</td><td>100</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	109.19	-----	-----	99.48	27.60	8.71	36.28	9.68	100	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																															
Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2369.28	43.60	54.00	-10.40	34.30	27.30	8.58	36.26	9.68	100	Average																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line Margin	Level Factor	Loss	Factor	Factor			Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2440.00	109.19	-----	-----	99.48	27.60	8.71	36.28	9.68	100	Average																																																																													



Mode	2											
	Band Edge - R											
	2400-2483.5_Thread_CH18_2440MHz											
ANT	1											
Pol.	Vertical						Fundamental					
Peak	<											







Mode	2																																																																																																																																							
	Harmonic																																																																																																																																							
	2400-2483.5_Thread_CH18_2440MHz																																																																																																																																							
ANT	1																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																						
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>44.39</td><td>74.00</td><td>-29.61</td><td>36.22</td><td>32.72</td><td>12.39</td><td>37.57</td><td>0.63</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>48.40</td><td>74.00</td><td>-25.60</td><td>34.30</td><td>36.78</td><td>15.38</td><td>38.48</td><td>0.42</td><td>249</td><td>65 Peak</td></tr><tr><td>3</td><td>7320.00</td><td>38.58</td><td>54.00</td><td>-15.42</td><td>24.48</td><td>36.78</td><td>15.38</td><td>38.48</td><td>0.42</td><td>249</td><td>65 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	44.39	74.00	-29.61	36.22	32.72	12.39	37.57	0.63	--	Peak	2	7320.00	48.40	74.00	-25.60	34.30	36.78	15.38	38.48	0.42	249	65 Peak	3	7320.00	38.58	54.00	-15.42	24.48	36.78	15.38	38.48	0.42	249	65 Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>44.31</td><td>74.00</td><td>-29.69</td><td>36.14</td><td>32.72</td><td>12.39</td><td>37.57</td><td>0.63</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>48.22</td><td>74.00</td><td>-25.78</td><td>34.12</td><td>36.78</td><td>15.38</td><td>38.48</td><td>0.42</td><td>165</td><td>88 Peak</td></tr><tr><td>3</td><td>7320.00</td><td>38.67</td><td>54.00</td><td>-15.33</td><td>24.57</td><td>36.78</td><td>15.38</td><td>38.48</td><td>0.42</td><td>165</td><td>88 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	44.31	74.00	-29.69	36.14	32.72	12.39	37.57	0.63	--	Peak	2	7320.00	48.22	74.00	-25.78	34.12	36.78	15.38	38.48	0.42	165	88 Peak	3	7320.00	38.67	54.00	-15.33	24.57	36.78	15.38	38.48	0.42	165	88 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																														
1	4880.00	44.39	74.00	-29.61	36.22	32.72	12.39	37.57	0.63	--	Peak																																																																																																																													
2	7320.00	48.40	74.00	-25.60	34.30	36.78	15.38	38.48	0.42	249	65 Peak																																																																																																																													
3	7320.00	38.58	54.00	-15.42	24.48	36.78	15.38	38.48	0.42	249	65 Average																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																														
1	4880.00	44.31	74.00	-29.69	36.14	32.72	12.39	37.57	0.63	--	Peak																																																																																																																													
2	7320.00	48.22	74.00	-25.78	34.12	36.78	15.38	38.48	0.42	165	88 Peak																																																																																																																													
3	7320.00	38.67	54.00	-15.33	24.57	36.78	15.38	38.48	0.42	165	88 Average																																																																																																																													



Mode	2	
	Harmonic	
	2400-2483.5_Thread_CH18_2440MHz	
ANT	1	
Pol.	Horizontal	Vertical
10G ~18G Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 HORIZONTAL	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 VERTICAL



Mode	3																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_Thread_CH25_2475MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-05-27  Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.60</td><td>54.33</td><td>74.00</td><td>-19.67</td><td>44.22</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>387</td><td>294 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.60	54.33	74.00	-19.67	44.22	27.94	8.79	36.30	9.68	387	294 Peak	Level (dBuV/m) Date: 2025-05-27  Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2475.00</td><td>118.16</td><td>-----</td><td>-----</td><td>108.13</td><td>27.86</td><td>8.78</td><td>36.29</td><td>9.68</td><td>387</td><td>294 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2475.00	118.16	-----	-----	108.13	27.86	8.78	36.29	9.68	387	294 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2483.60	54.33	74.00	-19.67	44.22	27.94	8.79	36.30	9.68	387	294 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2475.00	118.16	-----	-----	108.13	27.86	8.78	36.29	9.68	387	294 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-05-27  Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.58</td><td>46.19</td><td>54.00</td><td>-7.81</td><td>36.08</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>387</td><td>294 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.58	46.19	54.00	-7.81	36.08	27.94	8.79	36.30	9.68	387	294 Average	Level (dBuV/m) Date: 2025-05-27  Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2475.00</td><td>111.55</td><td>-----</td><td>-----</td><td>101.54</td><td>27.84</td><td>8.78</td><td>36.29</td><td>9.68</td><td>387</td><td>294 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2475.00	111.55	-----	-----	101.54	27.84	8.78	36.29	9.68	387	294 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2483.58	46.19	54.00	-7.81	36.08	27.94	8.79	36.30	9.68	387	294 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2475.00	111.55	-----	-----	101.54	27.84	8.78	36.29	9.68	387	294 Average																																																																																							



Mode	3																																																					
	Band Edge																																																					
	2400-2483.5_Thread_CH25_2475MHz																																																					
ANT	1																																																					
Pol.	Vertical																																																					
Peak	Level (dBuV/m) Date: 2025-05-27 PEAK_BE_74 Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.83</td><td>54.14</td><td>74.00</td><td>-19.86</td><td>44.02</td><td>27.94</td><td>8.80</td><td>36.30</td><td>9.68</td><td>116</td><td>97 Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.83	54.14	74.00	-19.86	44.02	27.94	8.80	36.30	9.68	116	97 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2483.83	54.14	74.00	-19.86	44.02	27.94	8.80	36.30	9.68	116	97 Peak																																											
Level (dBuV/m) Date: 2025-05-27 PEAK_74 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2475.00</td><td>116.21</td><td>-----</td><td>-----</td><td>106.18</td><td>27.86</td><td>8.78</td><td>36.29</td><td>9.68</td><td>116</td><td>97 Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2475.00	116.21	-----	-----	106.18	27.86	8.78	36.29	9.68	116	97 Peak	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2475.00	116.21	-----	-----	106.18	27.86	8.78	36.29	9.68	116	97 Peak																																											
Avg	Level (dBuV/m) Date: 2025-05-27 AVG_BE_54 Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.55</td><td>45.65</td><td>54.00</td><td>-8.35</td><td>35.54</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>116</td><td>97 Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.55	45.65	54.00	-8.35	35.54	27.94	8.79	36.30	9.68	116	97 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2483.55	45.65	54.00	-8.35	35.54	27.94	8.79	36.30	9.68	116	97 Average																																											
Level (dBuV/m) Date: 2025-05-27 AVG_54 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2475.00</td><td>110.04</td><td>-----</td><td>-----</td><td>100.03</td><td>27.84</td><td>8.78</td><td>36.29</td><td>9.68</td><td>116</td><td>97 Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2475.00	110.04	-----	-----	100.03	27.84	8.78	36.29	9.68	116	97 Average	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2475.00	110.04	-----	-----	100.03	27.84	8.78	36.29	9.68	116	97 Average																																											



Mode	3																																																																																																															
	Harmonic																																																																																																															
	2400-2483.5_Thread_CH25_2475MHz																																																																																																															
ANT	1																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4950.00</td><td>44.91</td><td>74.00</td><td>-29.09</td><td>36.30</td><td>33.10</td><td>12.52</td><td>37.63</td><td>0.62</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7425.00</td><td>47.70</td><td>74.00</td><td>-26.30</td><td>34.11</td><td>36.25</td><td>15.50</td><td>38.57</td><td>0.41</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4950.00	44.91	74.00	-29.09	36.30	33.10	12.52	37.63	0.62	--	Peak	2	7425.00	47.70	74.00	-26.30	34.11	36.25	15.50	38.57	0.41	--	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4950.00</td><td>44.25</td><td>74.00</td><td>-29.75</td><td>35.64</td><td>33.10</td><td>12.52</td><td>37.63</td><td>0.62</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7425.00</td><td>47.47</td><td>74.00</td><td>-26.53</td><td>33.88</td><td>36.25</td><td>15.50</td><td>38.57</td><td>0.41</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4950.00	44.25	74.00	-29.75	35.64	33.10	12.52	37.63	0.62	--	Peak	2	7425.00	47.47	74.00	-26.53	33.88	36.25	15.50	38.57	0.41	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	4950.00	44.91	74.00	-29.09	36.30	33.10	12.52	37.63	0.62	--	Peak																																																																																																					
2	7425.00	47.70	74.00	-26.30	34.11	36.25	15.50	38.57	0.41	--	Peak																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	4950.00	44.25	74.00	-29.75	35.64	33.10	12.52	37.63	0.62	--	Peak																																																																																																					
2	7425.00	47.47	74.00	-26.53	33.88	36.25	15.50	38.57	0.41	--	Peak																																																																																																					



Mode	3	
	Harmonic	
	2400-2483.5_Thread_CH25_2475MHz	
ANT	1	
Pol.	Horizontal	Vertical
10G ~18G Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 HORIZONTAL	Level (dBuV/m) Date: 2025-05-28 Site : 03CH20-HY Condition: AVG_54 3m HF_91280_02360_241101 VERTICAL



Mode	4																																																																																							
	Band Edge																																																																																							
	2400-2483.5_Thread_CH26_2480MHz																																																																																							
ANT	1																																																																																							
Pol.	Horizontal	Fundamental																																																																																						
Peak	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.54</td><td>59.65</td><td>74.00</td><td>-14.35</td><td>49.54</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>274</td><td>291 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.54	59.65	74.00	-14.35	49.54	27.94	8.79	36.30	9.68	274	291 Peak	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.46</td><td>-----</td><td>-----</td><td>90.38</td><td>27.90</td><td>8.79</td><td>36.29</td><td>9.68</td><td>274</td><td>291 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.46	-----	-----	90.38	27.90	8.79	36.29	9.68	274	291 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2483.54	59.65	74.00	-14.35	49.54	27.94	8.79	36.30	9.68	274	291 Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2480.00	100.46	-----	-----	90.38	27.90	8.79	36.29	9.68	274	291 Peak																																																																													
Avg	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>52.32</td><td>54.00</td><td>-1.68</td><td>42.21</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>274</td><td>291 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	52.32	54.00	-1.68	42.21	27.94	8.79	36.30	9.68	274	291 Average	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>95.36</td><td>-----</td><td>-----</td><td>85.28</td><td>27.90</td><td>8.79</td><td>36.29</td><td>9.68</td><td>274</td><td>291 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	95.36	-----	-----	85.28	27.90	8.79	36.29	9.68	274	291 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2483.52	52.32	54.00	-1.68	42.21	27.94	8.79	36.30	9.68	274	291 Average																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2480.00	95.36	-----	-----	85.28	27.90	8.79	36.29	9.68	274	291 Average																																																																													



Mode	4																																																																																							
	Band Edge																																																																																							
	2400-2483.5_Thread_CH26_2480MHz																																																																																							
ANT	1																																																																																							
Pol.	Vertical	Fundamental																																																																																						
Peak	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: PEAK_BE_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>57.72</td><td>74.00</td><td>-16.28</td><td>47.61</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>119</td><td>99 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	57.72	74.00	-16.28	47.61	27.94	8.79	36.30	9.68	119	99 Peak	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: PEAK_74 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>98.00</td><td>-----</td><td>-----</td><td>88.00</td><td>27.90</td><td>8.79</td><td>36.29</td><td>9.68</td><td>119</td><td>99 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	98.00	-----	-----	88.00	27.90	8.79	36.29	9.68	119	99 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2483.52	57.72	74.00	-16.28	47.61	27.94	8.79	36.30	9.68	119	99 Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2480.00	98.00	-----	-----	88.00	27.90	8.79	36.29	9.68	119	99 Peak																																																																													
Avg	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: AVG_BE_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>50.24</td><td>54.00</td><td>-3.76</td><td>40.13</td><td>27.94</td><td>8.79</td><td>36.30</td><td>9.68</td><td>119</td><td>99 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	50.24	54.00	-3.76	40.13	27.94	8.79	36.30	9.68	119	99 Average	Level (dBuV/m) Date: 2025-05-27 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>92.52</td><td>-----</td><td>-----</td><td>82.44</td><td>27.90</td><td>8.79</td><td>36.29</td><td>9.68</td><td>119</td><td>99 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	92.52	-----	-----	82.44	27.90	8.79	36.29	9.68	119	99 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2483.52	50.24	54.00	-3.76	40.13	27.94	8.79	36.30	9.68	119	99 Average																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2480.00	92.52	-----	-----	82.44	27.90	8.79	36.29	9.68	119	99 Average																																																																													



Mode	5																																																																																																																																																																																														
	LF																																																																																																																																																																																														
	2400-2483.5_Thread_CH18_2440MHz																																																																																																																																																																																														
ANT	1																																																																																																																																																																																														
Pol.	Horizontal						Vertical																																																																																																																																																																																								
QP/ Peak	Level (dBuV/m) Date: 2025-06-11 Site : 03CH20-HY Condition: QP 3m Bilog_55606 & 08_241127 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>84.32</td><td>25.05</td><td>40.00</td><td>-14.95</td><td>45.09</td><td>13.93</td><td>1.64</td><td>35.70</td><td>0.09 -- -- Peak</td></tr><tr><td>2</td><td>185.20</td><td>30.51</td><td>43.50</td><td>-12.99</td><td>48.54</td><td>14.95</td><td>2.42</td><td>35.53</td><td>0.13 -- -- Peak</td></tr><tr><td>3</td><td>235.64</td><td>23.83</td><td>46.00</td><td>-22.17</td><td>39.64</td><td>16.82</td><td>2.73</td><td>35.43</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>463.59</td><td>26.30</td><td>46.00</td><td>-19.70</td><td>33.85</td><td>23.39</td><td>3.81</td><td>34.86</td><td>0.11 -- -- Peak</td></tr><tr><td>5</td><td>747.80</td><td>31.85</td><td>46.00</td><td>-14.15</td><td>32.54</td><td>28.16</td><td>4.84</td><td>33.90</td><td>0.21 -- -- Peak</td></tr><tr><td>6</td><td>957.32</td><td>34.55</td><td>46.00</td><td>-11.45</td><td>30.93</td><td>30.99</td><td>5.45</td><td>33.13</td><td>0.31 -- -- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	84.32	25.05	40.00	-14.95	45.09	13.93	1.64	35.70	0.09 -- -- Peak	2	185.20	30.51	43.50	-12.99	48.54	14.95	2.42	35.53	0.13 -- -- Peak	3	235.64	23.83	46.00	-22.17	39.64	16.82	2.73	35.43	0.07 -- -- Peak	4	463.59	26.30	46.00	-19.70	33.85	23.39	3.81	34.86	0.11 -- -- Peak	5	747.80	31.85	46.00	-14.15	32.54	28.16	4.84	33.90	0.21 -- -- Peak	6	957.32	34.55	46.00	-11.45	30.93	30.99	5.45	33.13	0.31 -- -- Peak	Level (dBuV/m) Date: 2025-06-11 Site : 03CH20-HY Condition: QP 3m Bilog_55606 & 08_241127 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>84.32</td><td>29.77</td><td>40.00</td><td>-10.23</td><td>49.81</td><td>13.93</td><td>1.64</td><td>35.70</td><td>0.09 -- -- Peak</td></tr><tr><td>2</td><td>186.17</td><td>27.92</td><td>43.50</td><td>-15.58</td><td>45.95</td><td>14.95</td><td>2.43</td><td>35.53</td><td>0.12 -- -- Peak</td></tr><tr><td>3</td><td>220.12</td><td>22.72</td><td>46.00</td><td>-23.28</td><td>39.97</td><td>15.51</td><td>2.64</td><td>35.47</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>513.06</td><td>26.41</td><td>46.00</td><td>-19.59</td><td>33.05</td><td>24.00</td><td>4.00</td><td>34.73</td><td>0.09 -- -- Peak</td></tr><tr><td>5</td><td>751.68</td><td>31.62</td><td>46.00</td><td>-14.38</td><td>32.33</td><td>28.11</td><td>4.85</td><td>33.88</td><td>0.21 -- -- Peak</td></tr><tr><td>6</td><td>947.62</td><td>34.81</td><td>46.00</td><td>-11.19</td><td>31.67</td><td>30.59</td><td>5.42</td><td>33.17</td><td>0.30 -- -- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	84.32	29.77	40.00	-10.23	49.81	13.93	1.64	35.70	0.09 -- -- Peak	2	186.17	27.92	43.50	-15.58	45.95	14.95	2.43	35.53	0.12 -- -- Peak	3	220.12	22.72	46.00	-23.28	39.97	15.51	2.64	35.47	0.07 -- -- Peak	4	513.06	26.41	46.00	-19.59	33.05	24.00	4.00	34.73	0.09 -- -- Peak	5	751.68	31.62	46.00	-14.38	32.33	28.11	4.85	33.88	0.21 -- -- Peak	6	947.62	34.81	46.00	-11.19	31.67	30.59	5.42	33.17	0.30 -- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																					
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																						
1	84.32	25.05	40.00	-14.95	45.09	13.93	1.64	35.70	0.09 -- -- Peak																																																																																																																																																																																						
2	185.20	30.51	43.50	-12.99	48.54	14.95	2.42	35.53	0.13 -- -- Peak																																																																																																																																																																																						
3	235.64	23.83	46.00	-22.17	39.64	16.82	2.73	35.43	0.07 -- -- Peak																																																																																																																																																																																						
4	463.59	26.30	46.00	-19.70	33.85	23.39	3.81	34.86	0.11 -- -- Peak																																																																																																																																																																																						
5	747.80	31.85	46.00	-14.15	32.54	28.16	4.84	33.90	0.21 -- -- Peak																																																																																																																																																																																						
6	957.32	34.55	46.00	-11.45	30.93	30.99	5.45	33.13	0.31 -- -- Peak																																																																																																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																						
1	84.32	29.77	40.00	-10.23	49.81	13.93	1.64	35.70	0.09 -- -- Peak																																																																																																																																																																																						
2	186.17	27.92	43.50	-15.58	45.95	14.95	2.43	35.53	0.12 -- -- Peak																																																																																																																																																																																						
3	220.12	22.72	46.00	-23.28	39.97	15.51	2.64	35.47	0.07 -- -- Peak																																																																																																																																																																																						
4	513.06	26.41	46.00	-19.59	33.05	24.00	4.00	34.73	0.09 -- -- Peak																																																																																																																																																																																						
5	751.68	31.62	46.00	-14.38	32.33	28.11	4.85	33.88	0.21 -- -- Peak																																																																																																																																																																																						
6	947.62	34.81	46.00	-11.19	31.67	30.59	5.42	33.17	0.30 -- -- Peak																																																																																																																																																																																						




Mode	6																																																																																																																																																																					
	SHF																																																																																																																																																																					
	2400-2483.5_Thread_CH18_2440MHz																																																																																																																																																																					
ANT	1																																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																																															
Peak	Level (dBuV/m) Date: 2025-06-21 Site : 03CH20-HY Condition: PEAK_74 1m BBHA9170_1223_240624 HORIZONTAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 19520.00</td><td>47.30</td><td>74.00</td><td>-26.70</td><td>56.41</td><td>38.14</td><td>25.57</td><td>63.28</td><td>-9.54</td><td>150</td><td>316</td><td>10</td><td>Peak</td></tr><tr><td>2 19520.00</td><td>41.84</td><td>54.00</td><td>-12.16</td><td>50.95</td><td>38.14</td><td>25.57</td><td>63.28</td><td>-9.54</td><td>150</td><td>316</td><td>10</td><td>Average</td></tr><tr><td>3 21960.00</td><td>48.03</td><td>-----</td><td>-----</td><td>52.09</td><td>38.22</td><td>27.19</td><td>60.73</td><td>-9.54</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table> Level (dBuV/m) Date: 2025-06-21 Site : 03CH20-HY Condition: PEAK_74 1m BBHA9170_1223_240624 VERTICAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 19520.00</td><td>48.55</td><td>74.00</td><td>-25.45</td><td>57.66</td><td>38.14</td><td>25.57</td><td>63.28</td><td>-9.54</td><td>150</td><td>316</td><td>10</td><td>Peak</td></tr><tr><td>2 19520.00</td><td>43.15</td><td>54.00</td><td>-10.85</td><td>52.26</td><td>38.14</td><td>25.57</td><td>63.28</td><td>-9.54</td><td>150</td><td>316</td><td>10</td><td>Average</td></tr><tr><td>3 21960.00</td><td>49.98</td><td>-----</td><td>-----</td><td>54.04</td><td>38.22</td><td>27.19</td><td>60.73</td><td>-9.54</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table>														Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1 19520.00	47.30	74.00	-26.70	56.41	38.14	25.57	63.28	-9.54	150	316	10	Peak	2 19520.00	41.84	54.00	-12.16	50.95	38.14	25.57	63.28	-9.54	150	316	10	Average	3 21960.00	48.03	-----	-----	52.09	38.22	27.19	60.73	-9.54	--	--	--	Peak			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1 19520.00	48.55	74.00	-25.45	57.66	38.14	25.57	63.28	-9.54	150	316	10	Peak	2 19520.00	43.15	54.00	-10.85	52.26	38.14	25.57	63.28	-9.54	150	316	10	Average	3 21960.00	49.98	-----	-----	54.04	38.22	27.19	60.73	-9.54	--	--	--	Peak
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																											
1 19520.00	47.30	74.00	-26.70	56.41	38.14	25.57	63.28	-9.54	150	316	10	Peak																																																																																																																																																										
2 19520.00	41.84	54.00	-12.16	50.95	38.14	25.57	63.28	-9.54	150	316	10	Average																																																																																																																																																										
3 21960.00	48.03	-----	-----	52.09	38.22	27.19	60.73	-9.54	--	--	--	Peak																																																																																																																																																										
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																											
1 19520.00	48.55	74.00	-25.45	57.66	38.14	25.57	63.28	-9.54	150	316	10	Peak																																																																																																																																																										
2 19520.00	43.15	54.00	-10.85	52.26	38.14	25.57	63.28	-9.54	150	316	10	Average																																																																																																																																																										
3 21960.00	49.98	-----	-----	54.04	38.22	27.19	60.73	-9.54	--	--	--	Peak																																																																																																																																																										



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	Duty Factor(dB)
Thread	26.65	5.74



—THE END—