

Date: 2025-1-8

01_Bluetooth_DH5 1Mbps_Antenna Side_0mm_Ch78

Communication System: IEEE 802.15.1 Bluetooth (GFSK, DH5); Frequency: 2480.0 MHz; Duty Cycle: 1:1.3

Medium: HSL Medium parameters used: $f = 2480.0$ MHz; $\sigma = 1.84$ S/m; $\epsilon_r = 41.1$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.6°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(7.81, 7.71, 7.62); Calibrated: 2024-6-3
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn715; Calibrated: 2024-1-25
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2033; Section: Flat
- Measurement Software: 16.2.2.1588
- UID: Bluetooth, 10032-CAA

Area Scan (60.0 mm x 60.0 mm): Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 0.484 W/kg; SAR (10g) = 0.174 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm

Power Drift = -0.02 dB

SAR (1g) = 0.492 W/kg; SAR (10g) = 0.171 W/kg

Smallest distance from peaks to all points 3 dB below = 6.0 mm

Ratio of SAR at M2 to SAR at M1 = 75.0 %

