TESTREPORT

ISSUED BY Shenzhen BALUN Technology Co., Ltd.




FOR

Rego

ISSUED TO Trend Power Limited

Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Cheong, N.T. HK



Tested by: ON Zhang Yanqing (Chief Engineer) 1.18,2015

Report No.:

BL-SZ1570168-601

EUT Type:

Rego

Model Name:

Rego

Brand Name: Power Trend

Test Standard:

47 CFR Part 15 Subpart C

FCC ID: SZJ-REGO-01

Test conclusion: Pass

Test Date: Aug. 10, 2015 ~ Aug. 18, 2015

Date of Issue: Aug. 18, 2015

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.



Revision History

Version Rev. 01 Issue Date Aug. 18, 2015 Revisions Initial Issue

TABLE OF CONTENTS

TABLE OF CONTENTS	2
1 ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1 Identification of the Testing Laboratory	5
1.2 Identification of the Responsible Testing Location	5
1.3 Announce	5
2 PRODUCT INFORMATION	6
2.1 Applicant	6
2.2 Manufacturer	6
2.3 General Description for Equipment under Test (EUT)	6
2.4 Technical Information	6
2.5 Ancillary Equipment	6
3 SUMMARY OF TEST RESULTS	7
3.1 Test Standards	7
3.2 Verdict	7
4 GENERAL TEST CONFIGURATIONS	8
4.1 Test Environments	8
4.2 Test Equipment List	8
4.3 Test Configurations	9
4.4 Description of Test Setup	9
4.4.1 For Antenna Port Test	9
4.4.2 For AC Power Supply Port Test	9
4.4.3 For Radiated Test (Below 30 MHz)	10
4.4.4 For Radiated Test (30 MHz-1 GHz)	10
4.4.5 For Radiated Test (Above 1 GHz)	11
4.5 Test Conditions	11



5 TEST ITEMS	12
5.1 Antenna Requirements	12
5.1.1 Standard Applicable	12
5.1.2 Antenna Anti-Replacement Construction	12
5.1.3 Antenna Gain	12
5.2 Output Power	13
5.2.1 Test Limit	13
5.2.2 Test Setup	13
5.2.3 Test Procedure	13
5.2.4 Test Result	14
5.3 6 dB Bandwidth	15
5.3.1 Limit	15
5.3.2 Test Setup	15
5.3.3 Test Procedure	15
5.3.4 Test Result	15
5.4 Conducted Spurious Emission	16
5.4.1 Limit	16
5.4.2 Test Setup	16
5.4.3 Test Procedure	16
5.4.4 Test Result	17
5.5 Conducted Emission	18
5.5.1 Limit	18
5.5.2 Test Setup	18
5.5.3 Test Procedure	18
5.5.4 Test Result	18
5.6 Radiated Spurious Emission	19
5.6.1 Limit	19
5.6.2 Test Setup	19
5.6.3 Test Procedure	19
5.6.4 Test Result	22
5.7 Band Edge	23
5.7.1 Limit	23



5.7.2 Test Setup	23
5.7.3 Test Procedure	23
5.7.4 Test Result	24
5.8 Power Spectral density (PSD)	25
5.8.1 Limit	25
5.8.2 Test Setup	25
5.8.3 Test Procedure	25
5.8.4 Test Result	25
ANNEX A TEST RESULT	26
A.1 Output Power	26
A.2 Bandwidth	28
A.3 Conducted Spurious Emissions	29
A.4 Conducted Emissions	32
A.5 Radiated Emission	32
A.6 Band Edge	42
A.7 Power Spectral Density (PSD)	44
ANNEX B TEST SETUP PHOTOS	45
ANNEX C EUT EXTERNAL PHOTOS	45
ANNEX D FUT INTERNAL PHOTOS	45



1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.		
Addross	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,		
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China		
Phone Number +86 755 6683 3402			
Fax Number	+86 755 6182 4271		

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.				
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625. The laboratory has met the requirements of the IAS Accreditation Criteria for Testing Laboratories (AC89), has demonstrated compliance with ISO/IEC Standard 17025:2005. The accreditation certificate number is TL-588. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to				
Accreditation Certificate					
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055				

1.3 Announce

- (1) The test report reference to the report template version v1.0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



2 PRODUCT INFORMATION

2.1 Applicant

	Applicant	Trend Power Limited		
Address	Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Cheong,			
	N.T, HK			

2.2 Manufacturer

Manufacturer	Trend Power Limited		
Address	Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Cheong,		
	N.T, HK		

2.3 General Description for Equipment under Test (EUT)

EUT Type	Rego		
Model Name	Rego		
Hardware Version	V12		
Software Version	V39		
Network and Wireless connectivity	Bluetooth 4.0 Low Energy (BLE)		
About the Product	The equipment is ego, it contains Bluetooth module operating at 2.4 GHz ISM band. The Bluetooth 4.0 Low Energy (BLE) was tested in this report.		

2.4 Technical Information

Modulation Technology	FHSS		
Modulation Type	GFSK		
Transfer Rate	1 Mbps		
Fraguency Dange	The frequency range used is 2402 MHz – 2480 MHz;		
Frequency Range	The frequency block is 2400 MHz to 2483.5 MHz.		
Number of channel	40 (at intervals of 2 MHz)		
Tested Channel	0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz).		
Antenna Type	PCB Antenna		
Antenna Gain	0 dBi		

Note: The above EUT information in section 2.3 and 2.4 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.5 Ancillary Equipment

	Battery		
Ancillary Equipment 1	Brand Name	MALAK	
	Model No	CR2032	
	Serial No	(N/A. marked #1 by test site)	
	Capacitance	210 mAh	
	Rated Voltage	3 V	
	Extreme Voltage	Low: 2.0 V / High:3.3 V	



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title			
	47 CFR Part 15,				
1	Subpart C	Miscellaneous Wireless Communications Services			
	(10-1-14 Edition)				
2	KDB Publication	Guidance for Performing Compliance Measurements on			
	558074 D01v03r03	Digital Transmission Systems (DTS) Operating Under §15.247			
		American National Standard for Standard for Methods of			
3	ANSI C63.4-2009	Measurement of Radio-Noise Emissions from Low-Voltage Electrical			
		and Electronic Equipment in the Range of 9 kHz to 40 GHz			
4	ANSI C63.10-2009	American National Standard for Testing Unlicensed Wireless Devices			

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	Note 1	Pass
		15.247(b)		
2	Output Power	15.247(b)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	ANNEX A.2	Pass
4	4 Conducted Spurious Emission 15.247(d) ANNEX A.3		Pass	
5	Conducted Emission	15.207	ANNEX A.4	Pass
6	Padiated Sourious Emission	15.209	ANNEX A.5	Pass
0	Radiated Spurious Emission	15.247(d)		
7	Band Edge	15.209	ANNEX A.6	Pass
/		15.247(d)		Pass
8 Power spectral density (PSD)		15.247(e)	ANNEX A.7	Pass
Note 1: Please refer to section 5.1				



4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa -102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.0 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2015.07.16	2016.07.15
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2015.07.16	2016.07.15
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2015.07.01	2016.06.30
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2015.07.16	2016.07.15
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2014.10.18	2015.10.17
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2015.07.14	2016.07.13
LISN	SCHWARZBECK	NSLK 8127	8127-687	2015.07.14	2016.07.13
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2015.07.16	2016.07.15
Power Splitter	KMW	DCPD-LDC	1305003215	2015.07.01	2016.06.30
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2015.07.21	2016.07.20
Attenuator (20 dB)	KMW	ZA-S1-201	110617091		
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189		
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2015.07.17	2016.07.16
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2014.11.20	2015.11.19
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2016.02.27
Shielded Enclosure	ChangNing	CN-130701	130703		




4.3 Test Configurations


Test	Description		
Configurations	Signal Description	Operating Frequency	
(TC) NO.	Signal Description	Operating Frequency	
Transmitter			
TC01	FHSS modulation, GFSK	Ch No. 0/ 2402 MHz	
TC02	FHSS modulation, GFSK	Ch No. 19/ 2440 MHz	
TC03	FHSS modulation, GFSK	Ch No. 39/ 2480 MHz	

4.4 Description of Test Setup

4.4.1 For Antenna Port Test




4.4.2 For AC Power Supply Port Test



(Diagram 2)




4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)


4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)



4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Test Conditions

Test Case	Test Conditions			
Test Case	Test Env.	Test Setup Note 1	Test Configuration Note 2	
Peak Output Power	NTNV	Test Setup 1	TC01~TC03	
Occupied Bandwidth	NTNV	Test Setup 1	TC01~TC03	
Conducted Spurious Emission	NTNV	Test Setup 1	TC01~TC03	
Conducted Emission	NTNV	Test Setup 2	TC01~TC03	
		Test Setup 3		
Radiated Spurious Emission	NTNV	Test Setup 4	TC01~TC03	
		Test Setup 5		
Band Edge	NTNV	Test Setup 1	TC01, TC03	
Power spectral density (PSD)	NTNV	Test Setup 2	TC01~TC03	

Note:

- 1. Please refer to section 4.4 for test setup details.
- 2. Please refer to section 4.3 for test configuration details.



5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	An embedded-in antenna design is used.



5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW ≥ DTS bandwidth.

Set VBW ≥ 3 x RBW.

Set span ≥ 3 x RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T \leq 16.7 microseconds.)



5.2.4 Test Result

Please refer to ANNEX A.1.



5.36 dB Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.



5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to \geq 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement



Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.



5.5 Conducted Emission

5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Fraguency range (MHz)	Conducted	Limit (dBµV)
Frequency range (MHz)	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.5.4 Test Result

Please refer to ANNEX A.4.



5.6 Radiated Spurious Emission

5.6.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

- 1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK).

5.6.2 Test Setup

See section 4.4.1((Diagram 2)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).



- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

E = EIRP - 20log D + 104.8

where:

 $E = electric field strength in dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW \geq 3 x RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz



If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle \geq 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW \geq 3 x RBW.
- e) Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
- 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
- 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
- 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a



conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.6.4 Test Result

Please refer to ANNEX A.5.



5.7 Band Edge

5.7.1 Limit

FCC §15.209&15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle \geq 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥ $3 \times RBW$.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) \pm 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission \pm 0.5 MHz.



5.7.4 Test Result

Please refer to ANNEX A.6.



5.8 Power Spectral density (PSD)

5.8.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.8.2 Test Setup

See section 4.4.1((Diagram 1)for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.8.4 Test Result

Please refer to ANNEX A.7.



ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Band	Duty Cycle (%)	T (ms)	1/T(kHz)
GFSK	21.81	0.6267	1.600

Peak Power Test Data


Channel	Measured Output Peak Power		Limit		Verdict
Channel	dBm	mW	dBm	mW	verdict
Low	-4.48	0.36			Pass
Middle	-5.20	0.30	30	1000	Pass
High	-6.06	0.25			Pass

Peak Power Test Plots

LOW CHANNEL


Agilent Peak Search Mkr1 2.402 15 GHz -4.48 dBm Ref 10 dBm Peak Log 10 dB/ Offst 0.5 dB Atten 20 dB Next Peak Next Pk Right Next Pk Left Min Search LgAv Pk-Pk Search Mkr → CF More 1 of 2 2.402 00 GHz #VBW 6 MHz File Operation Status, C:/TMPIMAGE.GIF file saved

MIDDLE CHANNEL





HIGH CHANNEL







A.2 Bandwidth


Test Data

Channal	6 dB Bandwidth	Limits
Channel	(kHz)	(kHz)
Low Channel	685.791	≥500
Middle Channel	722.736	≥500
High Channel	761.503	≥500

Test plots










A.3 Conducted Spurious Emissions

Test Data


	Measured Max. Out of	Limit (dBm)		Modelin
Channel	Band Emission (dBm)	Carrier Level	Calculated 20 dBc Limit	Verdict
Low Channel	-45.04	-4.60	-24.6	Pass
Middle Channel	-44.76	-5.34	-25.3	Pass
High Channel	-50.74	-6.17	-26.2	Pass


Test Plots



LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz


LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz









MIDDLE CHANNEL CARRIER LEVEL



MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz


MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz









HIGH CHANNEL CARRIER LEVEL



HIGH CHANNEL, SPURIOUS 30 MHz ~ 3GHz

HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz







A.4 Conducted Emissions

Note: Note Applicable.

A.5 Radiated Emission

Antenna-port Conducted test data

E = EIRP - 20log D + 104.8

where:

 $E = electric field strength in dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0 dBi

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th ,3th, 3th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise


Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D(m)	Max gain(dBi)	Detector	E (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark	Verdict
0.01276	-100.72	6	3	2	QP	2.54	72.80	70.26	Note 2	Pass
2.54	-91.85	6	3	2	QP	11.41	72.80	61.39	Note 2	Pass
825.4	-73.95	4.7	3	2	QP	28.01	72.80	44.79	Note 2	Pass
975.8	-73.18	4.7	3	2	QP	28.78	69.54	40.76		Pass
1200	-51.06	0	3	2	PK	46.20	69.54	23.34		Pass
1200	N/A	U	3	2	AV	N/A	49.54	N/A	Note 3	Pass
13720	-53.49	0	3	2	PK	43.77	72.80	29.03	Note 2	Pass
13/20	N/A	0	3	2	AV	N/A	52.80	N/A	Note 3	Pass
2400	-4.46	0	3	2	PK	92.80	N/A	N/A	Note 1	N/A
2400	-29.31	0	3	2	AV	67.95	N/A	N/A	Note 1	N/A




Test Plots

LOW CHANNEL, SPURIOUS 9 kHz ~ 150 kHz


LOW CHANNEL, SPURIOUS 150 kHz ~ 30 MHz






LOW CHANNEL, SPURIOUS 30 MHz ~ 1 GHz

LOW CHANNEL, SPURIOUS 1 GHz ~ 25 GHz







The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0 dBi

- Note 1: The frequency is fundamental signal which can be ignored.
- Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.
- Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th ,3th, 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise


Frequenc y (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D(m)	Max gain(dBi)	Detector	E (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark	Verdict
0.009235	-99.65	6	3	2	QP	3.61	71.90	68.29	Note 2	Pass
13.18	-92.62	6	3	2	QP	10.64	71.90	61.26	Note 2	Pass
686.4	-72.99	4.7	3	2	QP	28.97	71.90	42.93	Note 2	Pass
838.2	-72.59	4.7	3	2	QP	29.37	71.90	42.53	Note 2	Pass
1240	-50.46	0	3	2	PK	46.80	69.54	22.74		Pass
1240	N/A	U	3	2	AV	N/A	49.54	N/A	Note 3	Pass
9760	-55.84	0	3	2	PK	41.42	71.90	30.48	Note 2	Pass
9700	N/A	U	3	2	AV	N/A	51.90	N/A	Note 3	Pass
2440	-5.36	0	3	2	PK	91.90	N/A	N/A	Note 1	N/A
2440	-30.21	0	3	2	AV	67.05	N/A	N/A	Note 1	N/A




Test Plots

MIDDLE CHANNEL, SPURIOUS 9 kHz ~ 150 kHz


MIDDLE CHANNEL, SPURIOUS 150 kHz ~ 30 MHz






MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 1 GHz

MIDDLE CHANNEL, SPURIOUS 1 GHz ~ 25 GHz







The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0 dBi

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th ,3t , 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise


Frequenc y (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D(m)	Max gain(dBi	Detector	E (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark	Verdict
0.009	-99.99	6	3	2	QP	3.27	70.95	67.68	Note 2	Pass
1.49	-91.12	6	3	2	QP	12.14	70.95	58.81	Note 2	Pass
697.7	-71.44	4.7	3	2	QP	30.52	70.95	40.43	Note 2	Pass
852.9	-72.4	4.7	3	2	QP	29.56	70.95	41.39	Note 2	Pass
13440	-45.31	0	3	2	PK	51.95	70.95	19.00	Note 2	Pass
13440	N/A	0	3	2	AV	N/A	50.95	N/A	Note 3	Pass
45040	-45.03	0	3	2	PK	52.23	70.95	18.72	Note 2	Pass
15240	N/A	0	3	2	AV	N/A	50.95	N/A	Note 3	Pass
2490	-6.31	0	3	2	PK	90.95	N/A	N/A	Note 1	N/A
2480	-31.16	0	3	2	AV	66.10	N/A	N/A	Note 1	N/A




Test Plots

HIGH CHANNEL, SPURIOUS 9 kHz ~ 150 kHz


HIGH CHANNEL, SPURIOUS 150 kHz ~ 30 MHz






HIGH CHANNEL, SPURIOUS 30 MHz ~ 1 GHz

HIGH CHANNEL, SPURIOUS 1 GHz ~ 25 GHz








Cabinet Radiated spurious emission test

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.4-2009, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	61.52	22.96	-20.23	40.0	17.04	Peak	263.60	100	Vertical	Pass
2	158.74	22.27	-23.12	43.5	21.23	Peak	32.70	100	Vertical	Pass
3	171.34	23.11	-22.64	43.5	20.39	Peak	10.50	100	Vertical	Pass
4	413.54	25.61	-14.73	46.0	20.39	Peak	32.70	100	Vertical	Pass
5	590.52	29.24	-11.02	46.0	16.76	Peak	4.40	100	Vertical	Pass
6	865.20	32.91	-6.30	46.0	13.09	Peak	54.80	100	Vertical	Pass




30 MHz to 1 GHz. ANT H



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	51.34	22.45	-18.64	40.0	17.55	Peak	231.50	100	Horizontal	Pass
2	97.16	19.67	-20.67	43.5	23.83	Peak	-0.00	100	Horizontal	Pass
3	139.82	28.82	-23.63	43.5	14.68	Peak	202.00	100	Horizontal	Pass
4	197.53	20.90	-20.45	43.5	22.60	Peak	95.30	100	Horizontal	Pass
5	334.50	23.76	-16.48	46.0	22.24	Peak	359.20	100	Horizontal	Pass
6	606.28	29.84	-10.61	46.0	16.16	Peak	264.70	100	Horizontal	Pass




1 GHz to 25 GHz, ANT V



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	1313.92	44.15	-4.89	74.0	29.85	Peak	317.00	100	Vertical	Pass
2	2785.05	48.52	1.62	74.0	25.48	Peak	169.30	100	Vertical	Pass
3	4807.80	52.17	13.83	74.0	21.83	Peak	157.20	100	Vertical	Pass
4	5650.59	52.98	15.71	74.0	21.02	Peak	359.50	100	Vertical	Pass
5	12289.52	51.43	20.65	74.0	22.57	Peak	281.00	100	Vertical	Pass
6	19219.63	50.38	14.00	74.0	23.62	Peak	360.00	100	Vertical	Pass



1 GHz to 25 GHz. ANT H



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdi
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		ct
1	2297.18	47.48	-0.33	74.0	26.52	Peak	206.70	100	Horizontal	Pass
2	2952.01	48.13	2.41	74.0	25.87	Peak	17.20	100	Horizontal	Pass
3	4807.05	51.83	13.77	74.0	22.17	Peak	114.70	100	Horizontal	Pass
4	5769.81	52.49	15.54	74.0	21.51	Peak	239.30	100	Horizontal	Pass
5	9717.55	49.48	17.74	74.0	24.52	Peak	1.50	100	Horizontal	Pass
6	19449.25	50.23	12.80	74.0	23.77	Peak	359.80	100	Horizontal	Pass



A.6 Band Edge

Test Data


The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Data

	Measured Max. Band	Limit			
Channel	Edge Emission (dBm)	Carrier Level	Calculated 20 dBc Limit	Verdict	
Low Channel	-40.24	-4.60	-24.6	Pass	
High Channel	-38.61	-6.17	-26.2	Pass	

Test Plots


LOW CHANNEL, Carrier leve



LOW CHANNEL, Reference level


* Agilent Marker 2.335 83 GH -44.87 dBm Select Marker Ref 10 dBm Atten 20 dB Log 10 dB/ Offst 0.5 dB Normal Delta Delta Pair _gAv Stop 2.410 00 GHz Sweep 9.56 ms (601 pts) Start 2.310 00 GHz Span Pair #VBW 300 kHz #Res BW 100 kHz Center X Axis 2.400 00 GHz 2.335 83 GHz Off More File Operation Status, C:/TMPIMAGE.GIF file saved

LOW CHANNEL, Band Edge







High CHANNEL, Carrier level





HIGH CHANNEL, Band Edge








A.7 Power Spectral Density (PSD)

Test Data


Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-17.67	8	Pass
Middle Channel	-19.61	8	Pass
High Channel	-20.24	8	Pass

Test plots





HIGH CHANNEL





ANNEX B TEST SETUP PHOTOS

Please refer the document "SRD TEST SETUP PHOTOS.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "EUT EXTERNAL PHOTOS.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "EUT INTERNAL PHOTOS.PDF".

--END OF REPORT--