

FCC
RF
TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.




FOR
Share Foil

ISSUED TO
Trend Power Limited

Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Chung, N.T.,
HK



Prepared by: 
Zhang Yang
(Reporting Specialist)
Date: 
Nov 26, 2014
Approved by: 
Wei Yanquan
(Chief Engineer)
Date: 
Nov 26, 2014



Report No.: BL-SZ14A0119-601
EUT Type: Share Foil
Model Name: SHAREFOIL-1403-01Y,
SHAREFOIL-1403-01B,
SHAREFOIL-1403-01G,
SHAREFOIL-1403-01O,
SHAREFOIL-1403-01P
Brand Name: Power Trend
Test Standard: 47 CFR Part 15 Subpart C
FCC ID: SZJ-SHAREFOIL01
Test conclusion: PASS
Test Date: Nov 4, 2014 ~ Nov 25, 2014
Date of Issue: Nov 26, 2014

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Nov 26, 2014</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory.....	5
1.2	Identification of the Responsible Testing Location	5
1.3	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant	6
2.2	Manufacturer	6
2.3	General Description for Equipment under Test (EUT)	6
2.4	Technical Information	7
2.5	Ancillary Equipment.....	8
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards.....	9
3.2	Verdict.....	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List.....	10
4.3	Test Configurations	11
4.4	Description of Test Setup	11
4.4.1	For Antenna Port Test	11
4.4.2	For AC Power Supply Port Test.....	12
4.4.3	For Radiated Test (Below 30MHz).....	12
4.4.4	For Radiated Test (30MHz-1GHz)	13
4.4.5	For Radiated Test (Above 1GHz)	13
4.5	Test Conditions	14
5	TEST ITEMS	15
5.1	Antenna Requirements.....	15

5.1.1	Standard Applicable	15
5.1.2	Antenna Anti-Replacement Construction	15
5.1.3	Antenna Gain	15
5.2	Output Power	16
5.2.1	Test Limit.....	16
5.2.2	Test Procedure.....	16
5.3	6dB Bandwidth	18
5.3.1	Limit.....	18
5.3.2	Test Procedure.....	18
5.4	Conducted Spurious Emission	19
5.4.1	Limit.....	19
5.4.2	Test Procedure.....	19
5.5	Conducted Emission	21
5.5.1	Limit.....	21
5.5.2	Test Procedure.....	21
5.6	Radiated Spurious Emission	22
5.6.1	Limit.....	22
5.6.2	Test Procedure.....	22
5.7	Band Edge	24
5.7.1	Limit.....	24
5.7.2	Test Procedure.....	24
5.8	Power Spectral density (PSD)	25
5.8.1	Limit.....	25
5.8.2	Test Procedure.....	25
ANNEX A	TEST RESULT	26
A.1	Output Power	26
A.2	Bandwidth	33
A.3	Conducted Spurious Emissions.....	39
A.4	Conducted Emissions.....	65
A.5	Radiated Emission	67
A.6	Band Edge	93

A.7	Power Spectral Density (PSD)	99
ANNEX B	TEST SETUP PHOTOS	105
B.1.	Conducted Test Photo	105
B.2.	Conducted Emissions Test Photo	105
B.3.	Radiated Test Photo	106
ANNEX C	EUT PHOTOS	108
C.1	Appearance of the EUT	108
C.2	Inside of the EUT	111

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province,P. R. China
Phone Number	+86 755 6683 3402
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province,P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625. The laboratory has met the requirements of the IAS Accreditation Criteria for Testing Laboratories (AC89), has demonstrated compliance with ISO/IEC Standard 17025:2005. The accreditation certificate number is TL-588. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Announce

- (1) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (2) The test report is invalid if there is any evidence and/or falsification.
- (3) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (4) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant

Applicant	Trend Power Limited
Address	Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Chung, N.T., HK

2.2 Manufacturer

Applicant	Trend Power Limited
Address	Flat 1, 3/F, Kwai Cheong Ctr, 40-52 Kwai Cheong Rd, Kwai Chung, N.T., HK

2.3 General Description for Equipment under Test (EUT)

EUT Type	Share Foil
Brand Name	Power Trend
The Under Test Model Name	SHAREFOIL-1403-01Y
Series Model Name	SHAREFOIL-1403-01Y, SHAREFOIL-1403-01B, SHAREFOIL-1403-01G, SHAREFOIL-1403-01O, SHAREFOIL-1403-01P
Description of Model name differentiation	The equipment model SHAREFOIL-1403-01Y and SHAREFOIL-1403-01B, SHAREFOIL-1403-01G, SHAREFOIL-1403-01O, SHAREFOIL-1403-01P are Sharebeat, the electrical parameters and internal structure of circuit are same, only the color is different.
Hardware Version	V0.4
Software Version	V1403.112
Network and Wireless connectivity	WIFI 802.11b, 802.11g and 802.11n (HT20/40)
About the Product	The EUT is the Share Stick with two Antennas, We define as Antenna 0 and Antenna 1, and two antennas can be fired at the same time, we test the two Antennas separately.

2.4 Technical Information

TX/ RX Operating Range		802.11b/g/n(20MHz): 2.412GHz - 2.462GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = “Operating Frequency” in MHz, - N = “Channel Number” with the range from 1 to 11. 802.11n(40MHz): 2.422GHz - 2.452GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = “Operating Frequency” in MHz, - N = “Channel Number” with the range from 3 to 9.
Modulation Type		DSSS, OFDM
Antenna Type	Antenna 0 Antenna 1	Patch Antenna
Antenna Gain	Antenna 0 Antenna 1	3dBi

Modulation technology	Modulation Type	Transfer Rate (Mbps)	The Frequency Equal to the Transmission Rate of Modulation Signal
DSSS (802.11b)	DBPSK	1	1MHz
	DQPSK	2	
	CCK	5.5/ 11	1.375MHz
OFDM (802.11g)	BPSK	6 / 9	1MHz
	QPSK	12 / 18	
	16QAM	24 / 36	
	64QAM	48 / 54	
OFDM (802.11n-20MHz)	BPSK	6.5	1MHz
	QPSK	13/19.5	
	16QAM	26/39	
	64QAM	52/58.5/65	
OFDM (802.11n-40MHz)	BPSK	13.5	1MHz
	QPSK	27/40.5	
	16QAM	54/81/108	
	64QAM	121.5/135	

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
6dB Bandwidth	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
Conducted Emission	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
Band Edge	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b / 11g/11n20/11n40	11/54/65/135Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.3 and 2.4 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No	516780
	Serial No	N/A
	Capacitance	6600mAh
	Rated Voltage	3.7V
	Extreme Voltage	Low: 3.3V / High:4.2V

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (12-30-13 Edition)	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v03r02	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
3	ANSI C63.4-2014	American National Standard for Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203 15.247(b)	Note1	PASS
2	Output Power	15.247(b)	ANNEX A.1	PASS
3	6dB Bandwidth	15.247(a)	ANNEX A.2	PASS
4	Conducted Spurious Emission	15.247(d)	ANNEX A.3	PASS
5	Conducted Emission	15.207	ANNEX A.4	PASS
6	Radiated Spurious Emission	15.209 15.247(d)	ANNEX A.5	PASS
7	Band Edge	15.209 15.247(d)	ANNEX A.6	PASS
8	Power spectral density (PSD)	15.247(e)	ANNEX A.7	PASS
Note 1: Please refer to section 5.1				

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Description	EUT working conditions		Test site follow standard of requirements	The actual record Conditions of Site
Relative Humidity (%)	45 to 55		30 to 60	45 to 55
Atmospheric Pressure (kPa)	90 to 96		86 to 106	90 to 96
Temperature (°C)	NT(Normal Temperature)	23 to 25	15 to 35	23 to 25
Working Voltage of the EUT (V)	NV (Normal Voltage)	3.7	NOTE	NOTE

NOTE: The normal/extremes the power source voltage range as declared by the manufacturer.

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2014.07.07	2015.07.06
Spectrum Analyzer	ROHDE&SCHWARZ	FSL3	103640/003	2014.07.07	2015.07.06
Power Splitter	KMW	DCPD-LDC	1305003215	2014.07.07	2015.07.06
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2014.07.07	2015.07.06
Attenuator (20dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2014.07.07	2015.07.06
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2014.07.07	2015.07.06
Test Antenna-Loop(9kHz-30MHz)	SCHWARZBECK	FMZB 1519	1519-037	2013.07.02	2015.07.01
Test Antenna-Bi-Log(30MHz-3GHz)	SCHWARZBECK	VULB 9163	9163-624	2013.07.03	2015.07.02
Test Antenna-Horn(1-18GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2013.07.02	2015.07.01
Test Antenna-Horn(15-26.5GHz)	SCHWARZBECK	BBHA 9170	9170-305	2013.07.02	2015.07.01
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2014.10.07	2015.10.06

4.3 Test Configurations

Test Configurations (TC) NO.	Description	
	Signal Description	Operating Frequency
Transmitter		
TC01	DSSS modulation, 802.11b	Ch No. 1/ 2412MHz
TC02	DSSS modulation, 802.11b	Ch No. 6/ 2437MHz
TC03	DSSS modulation, 802.11b	Ch No. 11/ 2462MHz
TC04	OFDM modulation, 802.11g	Ch No. 1/ 2412MHz
TC05	OFDM modulation, 802.11g	Ch No. 6/ 2437MHz
TC06	OFDM modulation, 802.11g	Ch No. 11/ 2462MHz
TC07	OFDM modulation, 802.11n(20MHz)	Ch No. 1/ 2412MHz
TC08	OFDM modulation, 802.11n(20MHz)	Ch No. 6/ 2437MHz
TC09	OFDM modulation, 802.11n(20MHz)	Ch No. 11/ 2462MHz
TC10	OFDM modulation, 802.11n(40MHz)	Ch No. 3/ 2422MHz
TC11	OFDM modulation, 802.11n(40MHz)	Ch No. 6/ 2437MHz
TC12	OFDM modulation, 802.11n(40MHz)	Ch No. 9/ 2452MHz


4.4 Description of Test Setup

4.4.1 For Antenna Port Test




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30MHz)




(Diagram 3)

4.4.4 For Radiated Test (30MHz-1GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1GHz)



(Diagram 5)

4.5 Test Conditions

Test Case	Test Conditions		
	Test Env.	Test Setup ^{Note 1}	Test Configuration ^{Note 2}
Peak Output Power	NTNV	Test Setup 1	TC01~TC12
Occupied Bandwidth	NTNV	Test Setup 1	TC01~TC12
Conducted Spurious Emission	NTNV	Test Setup 1	TC01~TC12
Conducted Emission	NTNV	Test Setup 2	TC01~TC12
Radiated Spurious Emission	NTNV	Test Setup 3 Test Setup 4 Test Setup 5	TC01~TC12
Band Edge	NTNV	Test Setup 1	TC01, TC03, TC04, TC06, TC07, TC09, TC10, TC12
Power spectral density (PSD)	NTNV	Test Setup 2	TC01~TC12
Note: 1. Please refer to section 4.4 for test setup details. 2. Please refer to section 4.3 for test setup details.			

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in.	These two antennas are embedded-in antenna design is used.

Reference Documents	Item
Photo	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Procedure

Maximum peak conducted output power

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.

Set the RBW = 1 MHz

Set the VBW $\geq$ 3 RBW

Set the span $\geq$ 1.5 x DTS bandwidth.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector).

Maximum conducted (average) output power (Reporting Only)

This method applied by the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than $\pm$ 2 percent.

Measure the duty cycle, x, of the transmitter output signal as described in 6.0(KDB Publication 558074 D01v03r01).

Set span to at least 1.5 times the OBW.

Set RBW = 1-5% of the OBW, not to exceed 1 MHz.

Set VBW $\geq$ 3 x RBW.

Number of points in sweep $\geq$ 2 span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

Sweep time = auto.

Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

Do not use sweep triggering. Allow the sweep to “free run”.

Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.

Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \log (1/0.25) = 6$ dB if the duty cycle is 25 %.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.3 6dB Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.5 Conducted Emission

5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.6 Radiated Spurious Emission

5.6.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.6.2 Test Procedure

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.7 Band Edge

5.7.1 Limit

FCC §15.209&15.247(d)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (f_{emission}) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by f_{emission} ± 0.5 MHz.

5.8 Power Spectral density (PSD)

5.8.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.8.2 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

ANTENNA	Mode	Duty Cycle (%)	T(μs)	1/T(kHz)
ANT 0	802.11b	82.2	0.95	1.05
	802.11g	46.6	0.18	5.65
	802.11n HT20	45.4	0.17	5.95
	802.11n HT40	33.1	0.10	10.00
ANT 1	802.11b	82.2	0.95	1.05
	802.11b	46.6	0.18	5.65
	802.11n HT20	45.4	0.17	5.95
	802.11n HT40	33.1	0.10	10.00

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power Of ANT 0		Measured Output Peak Power Of ANT 1		Total of output power		Limit		Verdict
	dBm	mW	dBm	mW	dBm	mW	dBm	mW	
Low	18.85	76.74	20.75	118.85	22.91	195.59	30	1000	PASS
Middle	19.49	88.92	19.78	95.06	22.65	183.98			PASS
High	22.03	159.59	21.31	135.21	24.70	294.80			PASS

802.11g Mode:

Channel	Measured Output Peak Power Of ANT 0		Measured Output Peak Power Of ANT 1		Total of output power		Limit		Verdict
	dBm	mW	dBm	mW	dBm	mW	dBm	mW	
Low	18.53	71.29	20.96	124.74	22.92	196.03	30	1000	PASS
Middle	19.09	81.10	19.58	90.78	22.35	171.88			PASS
High	21.30	134.90	20.75	118.85	24.04	253.75			PASS

802.11n-20MHz Mode:

Channel	Measured Output Peak Power Of ANT 0		Measured Output Peak Power Of ANT 1		Total of output power		Limit		Verdict
	dBm	mW	dBm	mW	dBm	mW	dBm	mW	
Low	18.47	70.31	20.80	120.23	22.80	190.54	30	1000	PASS
Middle	18.95	78.52	19.50	89.13	22.24	167.65			PASS
High	21.10	128.82	21.02	126.47	24.07	255.29			PASS

802.11n-40MHz Mode:

Channel	Measured Output Peak Power Of ANT 0		Measured Output Peak Power Of ANT 1		Total of output power		Limit		Verdict
	dBm	mW	dBm	mW	dBm	mW	dBm	mW	
Low	17.68	58.61	19.83	96.16	21.90	154.77	30	1000	PASS
Middle	18.15	65.31	19.51	89.33	21.89	154.64			PASS
High	19.09	81.10	20.69	117.22	22.97	198.32			PASS

Average Power Test Data (Reporting Only)

802.11b Mode:

Channel	Duty Factor(10 log (1/x))		Measured Output Average Power Of ANT 0		Measured Output Average Power Of ANT 1		Total of output power		Verdict
	ANT 0	ANT 1	dBm	mW	dBm	mW	dBm	mW	
Low	0.85	0.85	12.45	17.58	14.11	25.76	16.37	43.34	PASS
Middle	0.85	0.85	13.11	20.46	13.20	20.89	16.16	41.35	PASS
High	0.85	0.85	15.59	36.22	14.98	31.48	18.31	67.70	PASS

802.11g Mode:

Channel	Duty Factor(10 log (1/x))		Measured Output Average Power Of ANT 0		Measured Output Average Power Of ANT 1		Total of output power		Verdict
	ANT 0	ANT 1	dBm	mW	dBm	mW	dBm	mW	
Low	3.32	3.32	9.49	8.89	11.88	15.42	13.86	24.31	PASS
Middle	3.32	3.32	9.84	9.64	10.58	11.43	13.24	21.07	PASS
High	3.32	3.32	12.21	16.63	12.34	17.14	15.29	33.77	PASS

802.11n-20MHz Mode:


Channel	Duty Factor(10 log (1/x))		Measured Output Average Power Of ANT 0		Measured Output Average Power Of ANT 1		Total of output power		Verdict
	ANT 0	ANT 1	dBm	mW	dBm	mW	dBm	mW	
Low	3.43	3.43	9.56	9.04	11.99	15.81	13.95	24.85	PASS
Middle	3.43	3.43	9.92	9.82	10.70	11.75	13.34	21.57	PASS
High	3.43	3.43	12.45	17.58	12.41	17.42	15.44	35.00	PASS

802.11n-40MHz Mode:


Channel	Duty Factor(10 log (1/x))		Measured Output Average Power Of ANT 0		Measured Output Average Power Of ANT 1		Total of output power		Verdict
	ANT 0	ANT 1	dBm	mW	dBm	mW	dBm	mW	
Low	4.80	4.80	9.97	9.93	11.18	13.12	13.63	23.05	PASS
Middle	4.80	4.80	10.19	10.45	10.68	11.69	13.45	22.14	PASS
High	4.80	4.80	11.39	13.77	11.61	14.49	14.51	28.26	PASS

Peak Power Test Plots (ANT 0)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n 20MHz LOW CHANNEL




802.11 n 20MHz MID CHANNEL




802.11 n 20MHz HIGH CHANNEL




802.11 n 40MHz LOW CHANNEL



802.11 n 40MHz MID CHANNEL




802.11 n 40MHz HIGH CHANNEL




Peak Power Test Plots (Ant 1)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n 20MHz LOW CHANNEL




802.11 n 20MHz MID CHANNEL




802.11 n 20MHz HIGH CHANNEL




802.11 n 40MHz LOW CHANNEL



802.11 n 40MHz MID CHANNEL



802.11 n 40MHz HIGH CHANNEL



A.2 Bandwidth

Test Data (ANT 0)

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	9.30	≥ 500	PASS
Middle	9.20	≥ 500	PASS
High	9.10	≥ 500	PASS

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	16.55	≥ 500	PASS
Middle	16.55	≥ 500	PASS
High	16.55	≥ 500	PASS

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	17.70	≥ 500	PASS
Middle	17.75	≥ 500	PASS
High	17.75	≥ 500	PASS

802.11n-40MHz Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	32.58	≥ 500	PASS
Middle	33.83	≥ 500	PASS
High	33.75	≥ 500	PASS

Test Data (ANT 1)

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	9.20	≥ 500	PASS
Middle	9.17	≥ 500	PASS
High	9.27	≥ 500	PASS

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	16.55	≥ 500	PASS
Middle	16.55	≥ 500	PASS
High	16.60	≥ 500	PASS

802.11n-20MHz Mode:


Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	17.70	≥ 500	PASS
Middle	17.75	≥ 500	PASS
High	17.70	≥ 500	PASS

802.11n-40MHz Mode:


Channel	6 dB Bandwidth (MHz)	Limits (kHz)	Verdict
Low	32.58	≥ 500	PASS
Middle	32.58	≥ 500	PASS
High	32.58	≥ 500	PASS

Test plots (ANT 0)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n-20MHz LOW CHANNEL




802.11 n-20MHz MID CHANNEL




802.11n-20MHz HIGH CHANNEL




802.11n-40MHz LOW CHANNEL



802.11n-40MHz MID CHANNEL




802.11n-40MHz HIGH CHANNEL




Test plots (ANT 1)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n-20MHz LOW CHANNEL




802.11 n-20MHz MID CHANNEL




802.11n-20MHz HIGH CHANNEL




802.11n-40MHz LOW CHANNEL



802.11n-40MHz MID CHANNEL



802.11n-40MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data (ANT 0)

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-45.18	4.74	-15.3	PASS
Middle	-46.22	5.68	-14.3	PASS
High	-46.60	8.02	-12.0	PASS

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-47.93	0.68	-19.3	PASS
Middle	-48.94	1.31	-18.7	PASS
High	-48.60	3.91	-16.1	PASS

802.11n-20MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-48.52	1.02	-19.0	PASS
Middle	-48.55	1.27	-18.7	PASS
High	-48.39	3.92	-16.1	PASS

802.11n-40MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-52.71	-1.09	-21.1	PASS
Middle	-51.80	-0.79	-20.8	PASS
High	-53.14	0.40	-19.6	PASS

Test Data (ANT 1)

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-33.55	6.82	-13.2	PASS
Middle	-34.25	5.62	-14.4	PASS
High	-32.02	7.03	-13.0	PASS

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-44.38	2.99	-17.0	PASS
Middle	-45.69	1.49	-18.5	PASS
High	-42.60	3.35	-16.6	PASS

802.11n-20MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-47.55	3.03	-17.0	PASS
Middle	-48.63	1.46	-18.5	PASS
High	-41.01	3.38	-16.6	PASS

802.11n-40MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-45.93	0.04	-20	PASS
Middle	-45.05	-0.61	-20.6	PASS
High	-44.48	0.40	-19.6	PASS

Test Plots (ANT 0)


802.11b LOW CHANNEL CARRIER LEVEL




802.11b LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11b LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11b MID CHANNEL CARRIER LEVEL




802.11b MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11b MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11b HIGH CHANNEL CARRIER LEVEL




802.11b HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11b HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11g LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11g MID CHANNEL CARRIER LEVEL




802.11g MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11g MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11g HIGH CHANNEL CARRIER LEVEL




802.11g HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11g HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11n 20MHz LOW CHANNEL CARRIER LEVEL




802.11 n 20MHz LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 20MHz MID CHANNEL CARRIER LEVEL




802.11 n 20MHz MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 20MHz HIGH CHANNEL CARRIER LEVEL




802.11 n 20MHz HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11n 40MHz LOW CHANNEL CARRIER LEVEL




802.11 n 40MHz LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 40MHz LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 40MHz MID CHANNEL CARRIER LEVEL




802.11 n 40MHz MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 40MHz MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 40MHz HIGH CHANNEL CARRIER LEVEL



802.11 n 40MHz HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 40MHz HIGH CHANNEL, SPURIOUS 2GHz~25GHz




Test Plots (ANT 1)


802.11b LOW CHANNEL CARRIER LEVEL




802.11b LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11b LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11b MID CHANNEL CARRIER LEVEL




802.11b MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11b MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11b HIGH CHANNEL CARRIER LEVEL




802.11b HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11b HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11g LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11g MID CHANNEL CARRIER LEVEL




802.11g MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11g MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11g HIGH CHANNEL CARRIER LEVEL




802.11g HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11g HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11n 20MHz LOW CHANNEL CARRIER LEVEL




802.11 n 20MHz LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 20MHz MID CHANNEL CARRIER LEVEL




802.11 n 20MHz MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 20MHz HIGH CHANNEL CARRIER LEVEL




802.11 n 20MHz HIGH CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 20MHz HIGH CHANNEL, SPURIOUS 2GHz~25GHz




802.11n 40MHz LOW CHANNEL CARRIER LEVEL




802.11 n 40MHz LOW CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 40MHz LOW CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 40MHz MID CHANNEL CARRIER LEVEL




802.11 n 40MHz MID CHANNEL, SPURIOUS 30MHz~3GHz




802.11 n 40MHz MID CHANNEL, SPURIOUS 2GHz~25GHz




802.11 n 40MHz HIGH CHANNEL CARRIER LEVEL



802.11 n 40MHz HIGH CHANNEL, SPURIOUS 30MHz~3GHz



802.11 n 40MHz HIGH CHANNEL, SPURIOUS 2GHz~25GHz




A.4 Conducted Emissions

Note: All configurations have been tested, only the worst configuration (802.11b High Channel) shown here.


Test Data and Plots

802.11b HIGH CHANNEL PHASE L



Frequency (MHz)	Peak Level (dBuV)	Q-peak Level (dBuV)	Average Level (dBuV)	Factor (dB)	QP Limit (dBuV)	AV Limit (dBuV)	Margin (dB)	Line	Verdict
0.17	61.5	--	47.0	10.00	65.4	55.4	8.40	L Line	PASS
0.28	49.5	--	36.5	10.00	62.4	52.4	15.90	L Line	PASS
0.49	40.5	--	27.8	10.00	56.3	46.3	18.50	L Line	PASS
1.50	39.0	--	28.2	10.00	56.0	46.0	17.80	L Line	PASS
4.24	44.0	--	27.8	10.00	56.0	46.0	18.20	L Line	PASS
18.05	47.2	--	35.8	10.00	60.0	50.0	14.20	L Line	PASS

802.11b HIGH CHANNEL PHASE N



Frequency (MHz)	Peak Level (dBuV)	Q-peak Level (dBuV)	Average Level (dBuV)	Factor (dB)	QP Limit (dBuV)	AV Limit (dBuV)	Margin (dB)	Line	Verdict
0.17	60.6	--	45.3	10.00	65.5	55.5	10.20	N Line	PASS
0.28	47.9	--	29.8	10.00	62.4	52.4	22.60	N Line	PASS
0.92	36.6	--	21.3	10.00	56.0	46.0	24.70	N Line	PASS
1.57	36.6	--	24.6	10.00	56.0	46.0	21.40	N Line	PASS
4.12	41.6	--	25.1	10.00	56.0	46.0	20.90	N Line	PASS
18.02	48.2	--	35.6	10.00	60.0	50.0	14.40	N Line	PASS

A.5 Radiated Emission


Note 1: The symbol of “--” in the table which means not application.

Note 2: For the test data above 1GHz, According the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


Note 4: All configurations have been tested, only the worst configuration (802.11b High Channel) shown here.

802.11g HIGH CHANNEL 30MHz to 1GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.94	33.14	-23.90	40.0	6.86	Peak	265.80	100	Vertical	PASS
2	119.94	40.57	-21.90	43.5	2.93	Peak	133.00	100	Vertical	PASS
3	148.07	39.30	-23.48	43.5	4.20	Peak	4.20	100	Vertical	N/A
4	239.95	33.29	-19.12	46.0	12.71	Peak	171.90	100	Vertical	PASS
5	479.97	42.94	-14.05	46.0	3.06	Peak	360.00	100	Vertical	PASS
6	960.00	43.34	-5.36	46.0	2.66	Peak	357.80	100	Vertical	PASS

802.11g HIGH CHANNEL 30MHz to 1GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	71.94	25.89	-23.90	40.0	14.11	Peak	10.10	100	Horizontal	PASS
2	119.94	36.58	-21.90	43.5	6.92	Peak	297.70	100	Horizontal	PASS
3	148.31	34.78	-23.78	43.5	8.72	Peak	355.40	100	Horizontal	N/A
4	359.96	43.42	-16.19	46.0	2.58	Peak	114.90	100	Horizontal	PASS
5	445.54	34.61	-14.48	46.0	11.39	Peak	131.60	100	Horizontal	PASS
6	960.00	43.74	-5.36	46.0	2.26	Peak	359.80	100	Horizontal	PASS

Note: The marked spikes near 2400MHz with circle should be ignored because they are Fundamental signal.

Test Data and Plots

802.11b LOW CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1207.59	42.70	-5.53	74.0	31.30	Peak	-0.00	100	Vertical	PASS
2	1850.30	43.93	-3.48	74.0	30.07	Peak	60.10	100	Vertical	PASS
3	2409.18	98.53	-0.95	74.0	-24.53	Peak	8.40	100	Vertical	N/A
4	4820.36	50.89	13.21	74.0	23.11	Peak	105.80	100	Vertical	PASS
5	5856.29	49.02	15.02	74.0	24.98	Peak	284.80	100	Vertical	PASS
6	11020.38	50.83	20.14	74.0	23.17	Peak	285.90	100	Vertical	PASS

802.11b LOW CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1211.58	43.10	-5.34	74.0	30.90	Peak	76.70	100	Horizontal	PASS
2	1914.17	43.57	-3.08	74.0	30.43	Peak	44.20	100	Horizontal	PASS
3	2409.18	96.79	-0.95	74.0	-22.79	Peak	-0.00	100	Horizontal	N/A
4	4820.36	49.89	13.21	74.0	24.11	Peak	109.60	100	Horizontal	PASS
5	5892.22	49.13	15.21	74.0	24.87	Peak	30.80	100	Horizontal	PASS
6	9638.93	47.99	17.49	74.0	26.01	Peak	291.20	100	Horizontal	PASS

802.11b MID CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1339.32	43.53	-4.85	74.0	30.47	Peak	36.90	100	Vertical	PASS
2	1870.26	43.17	-3.39	74.0	30.83	Peak	121.80	100	Vertical	PASS
3	2433.13	95.57	-0.82	74.0	-21.57	Peak	17.90	100	Vertical	N/A
4	4874.25	50.56	13.25	74.0	23.44	Peak	93.60	100	Vertical	PASS
5	7527.45	46.46	14.18	74.0	27.54	Peak	189.40	100	Vertical	PASS
6	10200.50	49.85	18.95	74.0	24.15	Peak	358.60	100	Vertical	PASS

802.11b MID CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1251.50	43.49	-5.41	74.0	30.51	Peak	127.90	100	Horizontal	PASS
2	1782.43	43.02	-4.22	74.0	30.98	Peak	66.70	100	Horizontal	PASS
3	2433.13	94.53	-0.82	74.0	-20.53	Peak	1.40	100	Horizontal	N/A
4	4874.25	51.05	13.25	74.0	22.95	Peak	94.00	100	Horizontal	PASS
5	6842.35	45.44	14.21	74.0	28.56	Peak	357.50	100	Horizontal	PASS
6	11020.38	50.73	20.14	74.0	23.27	Peak	285.90	100	Horizontal	PASS

802.11b HIGH CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1339.32	43.22	-4.85	74.0	30.78	Peak	76.60	100	Vertical	PASS
2	1926.15	43.58	-3.02	74.0	30.42	Peak	43.40	100	Vertical	PASS
3	2457.09	94.92	-0.64	74.0	-20.92	Peak	24.70	100	Vertical	N/A
4	3598.80	44.27	9.54	74.0	29.73	Peak	129.10	100	Vertical	PASS
5	4922.16	52.65	13.38	74.0	21.35	Peak	75.20	100	Vertical	PASS
6	7347.75	46.52	14.20	74.0	27.48	Peak	1.70	100	Vertical	PASS

802.11b HIGH CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1403.19	42.26	-4.82	74.0	31.74	Peak	60.90	100	Horizontal	PASS
2	1974.05	44.06	-2.47	74.0	29.94	Peak	0.40	100	Horizontal	PASS
3	2457.09	93.50	-0.64	74.0	-19.50	Peak	2.30	100	Horizontal	N/A
4	4922.16	52.80	13.38	74.0	21.20	Peak	93.40	100	Horizontal	PASS
5	7347.75	46.15	14.20	74.0	27.85	Peak	1.70	100	Horizontal	PASS
6	11638.10	51.17	20.38	74.0	22.83	Peak	340.00	100	Horizontal	PASS

802.11g LOW CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1207.59	42.98	-5.53	74.0	31.02	Peak	213.40	100	Vertical	PASS
2	1518.96	42.36	-4.75	74.0	31.64	Peak	251.50	100	Vertical	PASS
3	2405.19	100.86	-1.01	74.0	-26.86	Peak	23.90	100	Vertical	N/A
4	3431.14	43.97	8.82	74.0	30.03	Peak	321.10	100	Vertical	PASS
5	4850.30	49.64	13.11	74.0	24.36	Peak	171.70	100	Vertical	PASS
6	6932.20	47.07	14.23	74.0	26.93	Peak	205.80	100	Vertical	PASS

802.11g LOW CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1163.67	42.82	-6.12	74.0	31.18	Peak	203.80	100	Horizontal	PASS
2	1694.61	42.10	-4.37	74.0	31.90	Peak	75.90	100	Horizontal	PASS
3	2405.19	100.86	-1.01	74.0	-26.86	Peak	23.90	100	Horizontal	N/A
4	3772.45	44.82	10.03	74.0	29.18	Peak	167.20	100	Horizontal	PASS
5	4850.30	49.64	13.11	74.0	24.36	Peak	171.70	100	Horizontal	PASS
6	11638.10	51.22	20.38	74.0	22.78	Peak	340.00	100	Horizontal	PASS

802.11g MID CHANNEL 1GHz to 25GHz, ANT V

RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1295.41	43.05	-5.18	74.0	30.95	Peak	4.60	100	Vertical	PASS
2	1974.05	43.50	-2.47	74.0	30.50	Peak	313.50	100	Vertical	PASS
3	2429.14	98.73	-1.09	74.0	-24.73	Peak	24.10	100	Vertical	N/A
4	3700.60	44.31	9.83	74.0	29.69	Peak	203.80	100	Vertical	PASS
5	7426.37	46.51	14.22	74.0	27.49	Peak	334.50	100	Vertical	PASS
6	16285.77	47.97	11.59	74.0	26.03	Peak	227.60	100	Vertical	PASS

802.11g MID CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1143.71	42.70	-6.23	74.0	31.30	Peak	65.30	100	Horizontal	PASS
2	1746.51	42.34	-4.29	74.0	31.66	Peak	165.10	100	Horizontal	PASS
3	2433.13	95.70	-0.82	74.0	-21.70	Peak	17.80	100	Horizontal	N/A
4	4874.25	53.66	13.25	74.0	20.34	Peak	26.50	100	Horizontal	PASS
5	8392.26	46.60	15.04	74.0	27.40	Peak	66.80	100	Horizontal	PASS
6	18032.86	48.60	13.23	74.0	25.40	Peak	216.60	100	Horizontal	PASS

802.11g HIGH CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1291.42	44.63	-5.24	74.0	29.37	Peak	147.40	100	Vertical	PASS
2	1778.44	43.15	-4.04	74.0	30.85	Peak	357.80	100	Vertical	PASS
3	2457.09	95.22	-0.64	74.0	-21.22	Peak	6.80	100	Vertical	N/A
4	4922.16	56.95	13.38	74.0	17.05	Peak	305.20	100	Vertical	PASS
4*	4922.16	46.87	13.38	54.0	7.13	AV	305.20	100	Vertical	PASS
5	8965.06	46.94	17.01	74.0	27.06	Peak	0.00	100	Vertical	PASS
6	13665.14	49.01	9.63	74.0	24.99	Peak	-0.20	100	Vertical	PASS

802.11g HIGH CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1151.70	42.52	-6.51	74.0	31.48	Peak	202.60	100	Horizontal	PASS
2	1618.76	43.20	-4.54	74.0	30.80	Peak	98.80	100	Horizontal	PASS
3	2457.09	94.86	-0.64	74.0	-20.86	Peak	17.90	100	Horizontal	N/A
4	4922.16	53.61	13.38	74.0	20.39	Peak	9.60	100	Horizontal	PASS
5	8886.44	48.02	16.71	74.0	25.98	Peak	61.20	100	Horizontal	PASS
6	14174.71	48.60	9.64	74.0	25.40	Peak	66.90	100	Horizontal	PASS

802.11n-20MHz LOW CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1183.63	43.35	-5.66	74.0	30.65	Peak	289.90	100	Vertical	PASS
2	1886.23	44.33	-3.28	74.0	29.67	Peak	124.30	100	Vertical	PASS
3	2401.20	97.60	-1.26	74.0	-23.60	Peak	10.10	100	Vertical	N/A
4	4664.67	48.34	12.61	74.0	25.66	Peak	287.50	100	Vertical	PASS
5	8875.21	48.10	16.68	74.0	25.90	Peak	146.50	100	Vertical	PASS
6	14174.71	48.81	9.64	74.0	25.19	Peak	66.90	100	Vertical	PASS

802.11n-20MHz LOW CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1187.62	42.94	-5.74	74.0	31.06	Peak	256.10	100	Horizontal	PASS
2	1578.84	42.49	-4.42	74.0	31.51	Peak	303.30	100	Horizontal	PASS
3	2401.20	96.08	-1.26	74.0	-22.08	Peak	0.30	100	Horizontal	N/A
4	4832.34	49.25	13.13	74.0	24.75	Peak	305.00	100	Horizontal	PASS
5	8875.21	47.83	16.68	74.0	26.17	Peak	146.50	100	Horizontal	PASS
6	14174.71	48.60	9.64	74.0	25.40	Peak	66.90	100	Horizontal	PASS

802.11n-20MHz MID CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1215.57	43.51	-5.40	74.0	30.49	Peak	203.90	100	Vertical	PASS
2	1982.04	44.19	-2.58	74.0	29.81	Peak	232.30	100	Vertical	PASS
3	2425.15	93.74	-1.00	74.0	-19.74	Peak	24.10	100	Vertical	N/A
4	4449.10	48.54	11.85	74.0	25.46	Peak	345.60	100	Vertical	PASS
5	6932.20	46.97	14.23	74.0	27.03	Peak	205.80	100	Vertical	PASS
6	16150.58	48.27	10.92	74.0	25.73	Peak	120.40	100	Vertical	PASS

802.11n-20MHz MID CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1283.43	42.80	-5.05	74.0	31.20	Peak	39.10	100	Horizontal	PASS
2	1826.35	42.87	-3.96	74.0	31.13	Peak	109.90	100	Horizontal	PASS
3	2429.14	94.14	-1.09	74.0	-20.14	Peak	358.90	100	Horizontal	N/A
4	4491.02	49.03	12.14	74.0	24.97	Peak	50.40	100	Horizontal	PASS
5	8392.26	46.65	15.04	74.0	27.35	Peak	66.80	100	Horizontal	PASS
6	13665.14	48.99	9.63	74.0	25.01	Peak	-0.20	100	Horizontal	PASS

802.11n-20MHz HIGH CHANNEL 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1319.36	43.26	-4.96	74.0	30.74	Peak	33.10	100	Vertical	PASS
2	1962.08	43.64	-2.79	74.0	30.36	Peak	1.90	100	Vertical	PASS
3	2453.09	93.62	-0.68	74.0	-19.62	Peak	14.70	100	Vertical	N/A
4	4922.16	59.51	13.38	74.0	14.49	Peak	236.90	100	Vertical	PASS
4*	4922.16	48.96	13.38	54.0	5.04	AV	236.90	100	Vertical	PASS
5	7055.74	46.20	14.33	74.0	27.80	Peak	109.40	100	Vertical	PASS
6	12042.43	52.19	20.83	74.0	21.81	Peak	216.60	100	Vertical	PASS

802.11n-20MHz HIGH CHANNEL 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1307.38	42.82	-4.93	74.0	31.18	Peak	351.50	100	Horizontal	PASS
2	2109.78	45.10	-1.87	74.0	28.90	Peak	359.70	100	Horizontal	PASS
3	2453.09	93.50	-0.68	74.0	-19.50	Peak	1.90	100	Horizontal	N/A
4	4413.17	47.36	11.64	74.0	26.64	Peak	178.50	100	Horizontal	PASS
5	7246.67	46.80	14.31	74.0	27.20	Peak	183.90	100	Horizontal	PASS
6	11020.38	51.50	20.14	74.0	22.50	Peak	285.90	100	Horizontal	PASS

802.11n-40MHz LOW MODE 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1211.58	42.87	-5.34	74.0	31.13	Peak	345.30	100	Vertical	PASS
2	1606.79	42.80	-4.66	74.0	31.20	Peak	180.40	100	Vertical	PASS
3	2409.18	94.88	-0.95	74.0	-20.88	Peak	24.10	100	Vertical	N/A
4	4335.33	47.06	11.72	74.0	26.94	Peak	100.50	100	Vertical	PASS
5	8875.21	47.27	16.68	74.0	26.73	Peak	146.50	100	Vertical	PASS
6	13665.14	48.83	9.63	74.0	25.17	Peak	-0.20	100	Vertical	PASS

802.11n-40MHz LOW MODE 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1235.53	43.00	-5.50	74.0	31.00	Peak	278.30	100	Horizontal	PASS
2	1814.37	42.77	-4.13	74.0	31.23	Peak	154.90	100	Horizontal	PASS
3	2409.18	95.82	-0.95	74.0	-21.82	Peak	3.00	100	Horizontal	N/A
4	4718.56	49.04	12.82	74.0	24.96	Peak	175.10	100	Horizontal	PASS
5	8235.02	46.22	14.90	74.0	27.78	Peak	358.60	100	Horizontal	PASS
6	13665.14	48.58	9.63	74.0	25.42	Peak	-0.20	100	Horizontal	PASS

802.11n-40MHz MID MODE 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1127.74	41.75	-6.18	74.0	32.25	Peak	212.90	100	Vertical	PASS
2	1858.28	43.60	-3.49	74.0	30.40	Peak	99.60	100	Vertical	PASS
3	2425.15	92.66	-1.00	74.0	-18.66	Peak	18.50	100	Vertical	N/A
4	4473.05	47.51	12.00	74.0	26.49	Peak	226.70	100	Vertical	PASS
5	7426.37	46.07	14.22	74.0	27.93	Peak	334.50	100	Vertical	PASS
6	16306.57	48.56	11.64	74.0	25.44	Peak	243.80	100	Vertical	PASS

802.11n-40MHz MID MODE 1GHz to 25GHz, ANT H


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1283.43	43.30	-5.05	74.0	30.70	Peak	174.60	100	Horizontal	PASS
2	1818.36	42.74	-3.97	74.0	31.26	Peak	302.50	100	Horizontal	PASS
3	2425.15	92.75	-1.00	74.0	-18.75	Peak	358.80	100	Horizontal	N/A
4	4353.29	47.18	11.70	74.0	26.82	Peak	43.50	100	Horizontal	PASS
5	8336.11	46.59	15.06	74.0	27.41	Peak	23.80	100	Horizontal	PASS
6	13675.54	48.30	9.64	74.0	25.70	Peak	136.60	100	Horizontal	PASS

802.11n-40MHz HIGH MODE 1GHz to 25GHz, ANT V


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1207.59	42.37	-5.53	74.0	31.63	Peak	24.80	100	Vertical	PASS
2	1826.35	44.01	-3.96	74.0	29.99	Peak	218.80	100	Vertical	PASS
3	2437.13	86.15	-0.83	74.0	-12.15	Peak	20.10	100	Vertical	N/A
4	3580.84	45.67	9.59	74.0	28.33	Peak	45.90	100	Vertical	PASS
5	5838.32	48.45	14.91	74.0	25.55	Peak	356.50	100	Vertical	PASS
6	9257.07	47.44	16.96	74.0	26.56	Peak	183.90	100	Vertical	PASS

802.11n-40MHz HIGH MODE 1GHz to 25GHz, ANT H

RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1171.66	42.37	-6.00	74.0	31.63	Peak	169.70	100	Horizontal	PASS
2	1934.13	43.49	-2.87	74.0	30.51	Peak	287.80	100	Horizontal	PASS
3	2437.13	91.77	-0.83	74.0	-17.77	Peak	2.20	100	Horizontal	N/A
4	4257.48	46.83	11.39	74.0	27.17	Peak	247.30	100	Horizontal	PASS
5	6932.20	47.07	14.23	74.0	26.93	Peak	205.80	100	Horizontal	PASS
6	14767.47	47.23	9.08	74.0	26.77	Peak	354.10	100	Horizontal	PASS


A.6 Band Edge

Test Data


The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Plots (ANT 0)


802.11b LOW CHANNEL, Reference level




802.11b LOW CHANNEL, Band Edge




802.11b HIGH CHANNEL, Reference level




802.11b HIGH CHANNEL, Band Edge




802.11g LOW CHANNEL, Reference level




802.11g LOW CHANNEL, Band Edge




802.11g HIGH CHANNEL, Reference level




802.11g HIGH CHANNEL, Band Edge




802.11n-20MHz LOW CHANNEL, Reference level




802.11n-20MHz LOW CHANNEL, Band Edge




802.11n-20MHz HIGH CHANNEL, Reference level




802.11n-20MHz HIGH CHANNEL, Band Edge




802.11n-40MHz LOW CHANNEL, Reference level




802.11n-40MHz LOW CHANNEL, Band Edge



802.11n-40MHz HIGH CHANNEL, Reference level





802.11n-40MHz HIGH CHANNEL, Band Edge



Test Plots (ANT 1)



802.11b LOW CHANNEL, Reference level

802.11b LOW CHANNEL, Band Edge





802.11b HIGH CHANNEL, Reference level

802.11b HIGH CHANNEL, Band Edge




802.11g LOW CHANNEL, Reference level


802.11g LOW CHANNEL, Band Edge




802.11g HIGH CHANNEL, Reference level




802.11g HIGH CHANNEL, Band Edge




802.11n-20MHz LOW CHANNEL, Reference level




802.11n-20MHz LOW CHANNEL, Band Edge




802.11n-20MHz HIGH CHANNEL, Reference level




802.11n-20MHz HIGH CHANNEL, Band Edge




802.11n-40MHz LOW CHANNEL, Reference level




802.11n-40MHz LOW CHANNEL, Band Edge



802.11n-40MHz HIGH CHANNEL, Reference level



802.11n-40MHz HIGH CHANNEL, Band Edge



A.7 Power Spectral Density (PSD)

Test Data (ANT 0)

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-10.25	8	PASS
Middle	-9.48	8	PASS
High	-7.68	8	PASS

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-15.56	8	PASS
Middle	-15.56	8	PASS
High	-13.73	8	PASS

802.11n-20MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-16.67	8	PASS
Middle	-15.20	8	PASS
High	-14.07	8	PASS

802.11n-40MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-18.09	8	PASS
Middle	-18.28	8	PASS
High	-16.79	8	PASS

Test Data (ANT 1)

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-8.30	8	PASS
Middle	-9.60	8	PASS
High	-7.92	8	PASS

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-14.00	8	PASS
Middle	-14.77	8	PASS
High	-13.46	8	PASS

802.11n-20MHz Mode:


Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-13.85	8	PASS
Middle	-15.76	8	PASS
High	-13.39	8	PASS

802.11n-40MHz Mode:


Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-16.06	8	PASS
Middle	-17.39	8	PASS
High	-15.66	8	PASS

Test plots (ANT 0)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n-20MHz LOW CHANNEL




802.11 n-20MHz MID CHANNEL




802.11n-20MHz HIGH CHANNEL




802.11n-40MHz LOW CHANNEL



802.11n-40MHz MID CHANNEL




802.11n-40MHz HIGH CHANNEL




Test plots (ANT 1)


802.11b LOW CHANNEL




802.11b MID CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MID CHANNEL




802.11g HIGH CHANNEL




802.11n-20MHz LOW CHANNEL




802.11 n-20MHz MID CHANNEL




802.11n-20MHz HIGH CHANNEL




802.11n-40MHz LOW CHANNEL



802.11n-40MHz MID CHANNEL



802.11n-40MHz HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

B.1. Conducted Test Photo



B.2. Conducted Emissions Test Photo




B.3. Radiated Test Photo



Below 30MHz



30MHz to 1GHz



Above 1GHz

ANNEX C EUT PHOTOS

C.1 Appearance of the EUT



THE FRONT OF EUT



THE BACK OF EUT



THE LEFT OF EUT



THE RIGHT OF EUT




THE UP OF EUT




THE DOWN OF EUT


C.2 Inside of the EUT




EUT UNCOVER VIEW 1




EUT UNCOVER VIEW 2




MAIN BOARD TOP VIEW 1



MAIN BOARD TOP VIEW 2




MAIN BOARD BACK VIEW2




MAIN BOARD TOP VIEW 3





MAIN BOARD VIEW 6



BATTERY

--END OF REPORT--