

RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
			(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	7.5	1.43	-0.72	6.78	4.76	0.2	768
BLE	2402-2480	4.0	1.43	-0.72	3.28	2.13	0.2	768
2.4G Wi-Fi	2412-2462	21.5	1.43	-0.72	20.78	119.67	0.2	768
5.2G Wi-Fi	5180-5240	10.0	0.75	-1.40	8.60	7.24	0.2	768
5.3G Wi-Fi	5260-5320	10.0	1.53	-0.62	9.38	8.67	0.2	768
5.6G Wi-Fi	5500-5720	11.5	3.12	0.97	12.47	17.66	0.2	768
5.8G Wi-Fi	5745-5825	11.5	1.77	-0.38	11.12	12.94	0.2	768
LTE B2	1850-1910	25.0	2.23	0.08	25.08	322.11	0.2	768
LTE B4	1710-1755	25.0	2.39	0.24	25.24	334.20	0.2	768
LTE B12	699-716	25.0	0.62	-1.53	23.47	222.33	0.2	358
LTE B13	777-787	25.0	-0.35	-2.50	22.50	177.83	0.2	398

Note:

1. The tune up conducted power and antenna gain was declared by the applicant.
2. 0dBd=2.15dBi
3. The BT, 2.4G and 5G Wi-Fi cannot transmit at same time.
4. The device contains a certified WWAN model (model: LE910C4-NFX, FCC ID: RI7LE910CXNF)

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{2.4G\ Wi-Fi}/limit + ERP_{LTE\ B12}/limit = 119.67/768 + 222.33/358 = 0.78 < 1.0$

So simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant