



FCC 47 CFR PART 15 SUBPART C AND ANSI C63.4 : 2003

TEST REPORT

For

Skype cordless phone

Model : CT-101

Issued for

Tecline Technology Corp.

6F, No.110, Song-Long Road, Taipei City, Taiwan, R.O.C.

Issued by

Compliance Certification Services Inc.

Hsinchu Lab.

Rm. 258, Bldg. 17, NO.195, Sec.4 Chung Hsing Rd.,
ChuTung Chen, Hsinchu, Taiwan 310, R.O.C

TEL: (03) 591-0068

FAX: (03) 582-5720



NVLAP LAB CODE 200118-0



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
2.1 DESCRIPTION OF EUT & POWER.....	4
3. DESCRIPTION OF TEST MODES.....	5
4. TEST METHODOLOGY.....	5
5. FACILITIES AND ACCREDITATIONS.....	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
5.3 LABORATORY ACCREDITATIONS LISTINGS.....	6
5.4 TABLE OF ACCREDITATIONS AND LISTINGS	7
6. CALIBRATION AND UNCERTAINTY.....	8
6.1 MEASURING INSTRUMENT CALIBRATION	8
6.2 MEASUREMENT UNCERTAINTY.....	8
7. SETUP OF EQUIPMENT UNDER TEST.....	9
8. APPLICABLE LIMITS AND TEST RESULTS	10
8.1 20dB BANDWIDTH FOR HOPPING.....	10-12
8.2 MAXIMUM PEAK OUTPUT POWER.....	13-15
8.3 HOPPING CHANNEL SEPARATION.....	16-17
8.4 NUMBER OF HOPPING FREQUENCY USED	18-19
8.5 AVERAGE TIME OF OCCUPANCY.....	20-21
8.6 CONDUCTED SPURIOUS EMISSION.....	22-25
8.7 RADIATED EMISSIONS.....	26
8.7.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS	26-29
8.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz	30
8.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz.....	31-33
8.7.4 RESTRICTED BAND EDGES	34-35
8.8 POWERLINE CONDUCTED EMISSIONS	36
9. ANTENNA REQUIREMENT	36
9.1 STANDARD APPLICABLE.....	36
9.2 ANTENNA CONNECTED CONSTRUCTION.....	36
APPENDIX SETUP PHOTOS.....	37-39



1. TEST REPORT CERTIFICATION

Applicant : Tecline Technology Corp.
Address : 6F, No.110, Song-Long Road, Taipei City, Taiwan, R.O.C.
Equipment Under Test : Skype cordless phone
Model : CT-101
Tested Date : November 29, 2005 ~ February 20, 2006

APPLICABLE STANDARD	
STANDARD	TEST RESULT
FCC Part 15 Subpart C: 2004 AND ANSI C63.4:2003	No non-compliance noted

Approved by:

C. F. Wu

C. F. Wu
Manager of Hsinchu Laboratory
Compliance Certification Services Inc.

Reviewed by:

Angus Wu

Angus Wu
Test Engineer of Hsinchu Laboratory
Compliance Certification Services Inc.



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



2. EUT DESCRIPTION

2.1 DESCRIPTION OF EUT & POWER

Product Name	Skype cordless phone
Model Number	CT-101 (Handheld)
Frequency Range	2401.808203MHz to 2479.398926MHz
Transmit Power	8.75 dBm
Channel Spacing	893.848kHz(for even number channel), 889.893kHz(for odd number channel)
Channel Number	88
Air Data Rate	GFSK (576kbps)
Type of Modulation	Frequency Hopping Spread Spectrum
Frequency Selection	By software / firmware
Transmitter Classification	portable device
Antenna Type	Dipole Antenna, Antenna Gain : 1.5 dBi
Power Source	3.6VDC(Battery Powered)
RF Exposure Evaluation	Since the EUT is classed portable device, and the maximum peak power is 8 dBm (<13.6dBm), the MPE evaluation is not required and no SAR consideration applied.

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: T2S-CT-101A filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.
3. For more details, please refer to the User's manual of the EUT.



3. DESCRIPTION OF TEST MODES

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2401.808203
Middle	2432.131787
High	2479.398926

The field strength of spurious emission was measured in the following position : EUT stand-up position (Z axis), lie-down position (X,Y axis), The worst emission was found in lie-down position (Y axis) and the worst case was recorded.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd., Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200118-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: 90585 and 90584).



5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP	EN 55014-1, AS/NZS 1044, CNS 13783-1, IEC/CISPR 14-1, IEC/CISPR 22, EN 55022, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, AS/NZS CISPR 22, AS/NZS 3548, IEC 61000-4-2/3/4/5/6/8/11	 200118-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 90585, 90584
Japan	VCCI	3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-1229/1189 C-1250/1294
Taiwan	TAF	FCC Method-47 CFR Part 15 Subpart C,D,E CISPR 11, FCC METHOD-47 CFR Part 18, EN 55011, CNS 13803, CISPR 13, CNS 13439, FCC Method-47 CFR Part 15 Subpart B, CISPR 14-1, EN 55014-1, CNS 13783-1, EN 55015, CNS 14115, CISPR 22, EN 55022, VCCI CNS 13438, EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 0240
Taiwan	BSMI	CNS 13803, CNS 13438, CNS 13439, CNS 13783-1, CNS 14115	 SL2-IS-E-0002 SL2-IN-E-0002 SL2-A1-E-0002 SL2-R1-E-0002 SL2-R2-E-0002 SL2-L1-E-0002
Canada	Industry Canada	RSS212, Issue 1	 IC 4417-1

* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.



6. CALIBRATION AND UNCERTAINTY

6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

6.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 1000 MHz	+/- 3.2 dB
Radiated Emission, 1 to 26.5GHz	+/- 3.2 dB
Power Line Conducted Emission	+/- 2.1 dB

Uncertainty figures are valid to a confidence level of 95%

7. SETUP OF EQUIPMENT UNDER TEST

SETUP DIAGRAM FOR TESTS



on table
under table

EUT OPERATING CONDITION

1. Setup all equipments like the setup diagram.
2. Establish connection between EUT and fixture.
3. Run HS_Cmndr_4.15
4. TX mode

Type the following commands in “command” text box.

e80e
e900
e8c4
e905
e80f
e9ff
e80c
→ e98c(channel low)
→ e9ae(channel middle)
→ e9e3(channel high)

5. RX mode

Type the following commands in “command” text box.

e80e
e900
e80b
e98c
→ e98c(channel low)
→ e9e3(channel high)

6. All of the functions are under run.
7. Disconnect EUT and the fixture.
8. Start test.



8. APPLICABLE LIMITS AND TEST RESULTS

8.1 20dB BANDWIDTH FOR HOPPING

LIMIT

Limit : N/A

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2006

TEST SETUP




TEST PROCEDURE


The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.

TEST RESULTS

No non-compliance noted

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Pass / Fail
Low	2401.808203	690	N/A
Middle	2432.131787	705	N/A
High	2479.398926	692	N/A

20dB BANDWIDTH





8.2 MAXIMUM PEAK OUTPUT POWER


LIMIT

§15.247(b)(1) The Maximum Peak Output Power Measurement is 125mW for frequency hopping systems operating in 2400~2483.5 MHz employing at least 15 hopping channels.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2005

TEST SETUP




TEST PROCEDURE


The RF power output was measured with a Spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. A spectrum analyzer was used to record the shape of the transmit signal.

TEST RESULTS

No non-compliance noted

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2401.808203	6.05	20.97	PASS
Middle	2432.131787	8.45	20.97	PASS
High	2479.398926	8.75	20.97	PASS

MAXIMUM PEAK OUTPUT POWER





8.3 HOPPING CHANNEL SEPARATION

LIMIT

§15.247(a)(1) Frequency hopping system operating in 2400-2483.5MHz. Band may have hopping channel carrier frequencies that are separated by 25kHz or two-third of 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2006

TEST SETUP



TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of adjacent channels.
4. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.
5. Repeat above procedures until all frequencies measured were complete.


TEST RESULTS

No non-compliance noted

Refer to section 8.1, 20dB bandwidth measurement, the measured channel separation should be greater than two-third of 20dB bandwidth or Minimum bandwidth.

Channel	Adjacent Hopping Channel Separation (kHz)	Two -third of 20dB bandwidth (kHz)	Minimum Bandwidth	Result
2432.131787 MHz (Mid)	891	470	25 kHz	PASS
2432.131787 MHz (Mid)	888	470	25 kHz	PASS

HOPPING CHANNEL SEPARATION



8.4 NUMBER OF HOPPING FREQUENCY USED


LIMIT

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz bands shall use at least 15 hopping frequencies

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2005

TEST SETUP



TEST PROCEDURE


- 1 Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2 Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3 Set the spectrum analyzer on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- 4 Set the spectrum analyzer on View mode and then plot the result on spectrum analyzer screen.
- 5 Repeat above procedures until all frequencies measured were complete.

TEST RESULTS

No non-compliance noted

Refer to the attached plot.

There are 88 hopping frequencies in a hopping sequence.

NUMBER OF HOPPING FREQUENCY USED

8.5 AVERAGE TIME OF OCCUPANCY


LIMIT

§15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2005

TEST SETUP



TEST PROCEDURE

1. The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.52 second scan, to enable resolution of each occurrence.
2. The average time of occupancy in the specified 31.6 second period (88 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.52 \text{ s}) * \text{pulse width}$.

TEST RESULTS


No non-compliance noted

Pulse width = 1.07 ms


of pulses in 3.52s = 25

The average time of occupancy in the specified 35.2 second period = $10 * 25 * 1.07 \text{ ms} = 267.5 \text{ ms}$
(<400ms)

PULSE WIDTH



NUMBER OF PULSES IN 3.52 SECOND OBSERVATION PERIOD





8.6 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

TEST RESULTS

No non-compliance noted

**BAND EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS****OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT**







8.7 RADIATED EMISSIONS

8.7.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS

LIMITS

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz, However, operation within these frequency bands is permitted under other sections of this Part, e-g, Sections 15.231 and 15.241.

§ 15.209 (b) In the emission table above, the tighter limit applies at the band edges.


TEST EQUIPMENTS

The following test equipments are utilized in making the measurements contained in this report.


Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2817	March 22, 2005	1 Year	FINAL
R/S SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005	1 Year	FINAL
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	January 27, 2005	1 Year	FINAL
R/S EMI TEST RECEIVER	ESCS30	835418/008	August 24, 2005	1 Year	FINAL
OPEN SITE	-----	No.2	May 07, 2005	1 Year	FINAL
N TYPE COAXIAL CABLE	9913-30M	-----	July 28, 2005	1 Year	FINAL
Horn Antenna	AH-118	10089	August 10, 2005	1 Year	FINAL
Horn Antenna	AH-840	03077	February 25, 2005	1 Year	FINAL
Agilent Pre-amplifier	8449B	3008A01471	December 07, 2005	1 Year	FINAL
HP Amplifier	8447D	1937A02748	December 07, 2005	1 Year	FINAL
HP High pass filter	84300/80038	002	CAL. ON USE	1 Year	FINAL
HP High pass filter	84300/80039	003	CAL. ON USE	1 Year	FINAL

TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.





TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 1 meters away from the interference-receiving antenna
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

TEST RESULTS

No non-compliance noted



8.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz

Product Name	Skype cordless phone		Test Date	2006/1/16	
Model Name	CT-101 (Handheld)		Test By	Angus Wu	
Test Mode	CH Low TX		TEMP & Humidity	20°C ,90%	

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dB μ V)		Limits (dB μ V/m)	Emission Level at 3m(dB μ V/m)	
			Horizontal	Vertical		Horizontal	Vertical
124.09	13.45	1.47	6.30	5.40	43.50	21.22	20.32
331.67	15.09	2.31	6.80	6.50	46.00	24.20	23.90
415.09	17.27	2.62	6.50	6.40	46.00	26.39	26.29
540.67	19.08	3.08	10.20	7.10	46.00	32.36	29.26
608.12	19.60	3.38	7.00	6.90	46.00	29.97	29.87
773.99	21.37	3.80	6.30	6.20	46.00	31.47	31.37

Remark:

1. Emission level (dB μ V/m) =Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dB μ V).
2. According to technical experience, all spurious emission at channel Low, Middle and High are almost the same below 1GHz, so the spurious emission test result of the channel Low was chosen as representative in final test.

**8.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz**

Product Name	Skype cordless phone					Test Date	2005/12/22		
Model Name	CT-101 (Handheld)					Test By	Angus Wu		
Test Mode	CH Low TX					TEMP & Humidity	15°C , 51%		

Measurement Distance at 3m Horizontal polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4804.11	64.99	34.33	6.32	35.14	9.50	0.37	61.37	74.00	-12.63	P	1.00
4804.11	35.05	34.33	6.32	35.14	9.50	0.37	31.43	54.00	-22.57	A	1.00
7205.94	56.14	39.35	8.26	35.66	9.50	0.93	59.52	74.00	-14.48	P	1.00
7205.94	33.15	39.35	8.26	35.66	9.50	0.93	36.53	54.00	-17.47	A	1.00
9606.58	58.19	39.50	9.27	36.37	9.50	0.53	61.62	74.00	-12.38	P	1.00
9606.58	33.70	39.50	9.27	36.37	9.50	0.53	37.13	54.00	-16.87	A	1.00
12010.09	62.33	41.71	10.58	35.79	9.50	0.45	69.77	74.00	-4.23	P	1.00
12010.09	33.69	41.71	10.58	35.79	9.50	0.45	41.13	54.00	-12.87	A	1.00

Measurement Distance at 3m Vertical polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4804.11	71.29	34.33	6.32	35.14	9.50	0.37	67.67	74.00	-6.33	P	1.00
4804.11	35.67	34.33	6.32	35.14	9.50	0.37	32.05	54.00	-21.95	A	1.00
7205.94	55.94	39.35	8.26	35.66	9.50	0.93	59.32	74.00	-14.68	P	1.00
7205.94	33.33	39.35	8.26	35.66	9.50	0.93	36.71	54.00	-17.29	A	1.00
9606.58	62.97	39.50	9.27	36.37	9.50	0.53	66.40	74.00	-7.60	P	1.00
9606.58	34.63	39.50	9.27	36.37	9.50	0.53	38.06	54.00	-15.94	A	1.00
12010.09	59.44	41.71	10.58	35.79	9.50	0.45	66.88	74.00	-7.12	P	1.00
12010.09	33.28	41.71	10.58	35.79	9.50	0.45	40.72	54.00	-13.28	A	1.00

Remark:

1. The measurement was searched to 10th harmonic.
2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation is as follow:
Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level-Limit
6. The other emission levels were 20dB below the limit
7. The test limit distance is 3M limit.



Product Name	Skype cordless phone						Test Date	2005/12/22		
Model Name	CT-101 (Handheld)						Test By	Angus Wu		
Test Mode	CH Middle TX						TEMP & Humidity	15°C , 51%		

Measurement Distance at 3m Horizontal polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4863.98	68.30	34.54	6.32	35.19	9.50	0.31	64.77	74.00	-9.23	P	1.00
4863.98	38.62	34.54	6.32	35.19	9.50	0.31	35.09	54.00	-18.91	A	1.00
7295.98	65.85	39.55	8.29	35.64	9.50	0.85	69.40	74.00	-4.60	P	1.00
7295.98	35.91	39.55	8.29	35.64	9.50	0.85	39.46	54.00	-14.54	A	1.00
9727.79	65.23	39.50	9.50	36.56	9.50	0.57	68.74	74.00	-5.26	P	1.00
9727.79	34.52	39.50	9.50	36.56	9.50	0.57	38.03	54.00	-15.97	A	1.00
12160.81	57.86	41.86	10.53	35.64	9.50	0.40	65.51	74.00	-8.49	P	1.00
12160.81	34.29	41.86	10.53	35.64	9.50	0.40	41.94	54.00	-12.06	A	1.00

Measurement Distance at 3m Vertical polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4863.98	72.10	34.54	6.32	35.19	9.50	0.31	68.57	74.00	-5.43	P	1.00
4863.98	36.49	34.54	6.32	35.19	9.50	0.31	32.96	54.00	-21.04	A	1.00
7295.98	63.42	39.55	8.29	35.64	9.50	0.85	66.97	74.00	-7.03	P	1.00
7295.98	35.46	39.55	8.29	35.64	9.50	0.85	39.01	54.00	-14.99	A	1.00
9727.79	64.10	39.50	9.50	36.56	9.50	0.57	67.61	74.00	-6.39	P	1.00
9727.79	34.25	39.50	9.50	36.56	9.50	0.57	37.76	54.00	-16.24	A	1.00
12160.81	61.13	41.86	10.53	35.64	9.50	0.40	68.78	74.00	-5.22	P	1.00
12160.81	33.53	41.86	10.53	35.64	9.50	0.40	41.18	54.00	-12.82	A	1.00

Remark:

1. The measurement was searched to 10th harmonic.
2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation is as follow:
Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level-Limit
6. The other emission levels were 20dB below the limit
7. The test limit distance is 3M limit.



Product Name	Skype cordless phone				Test Date	2005/12/22
Model Name	CT-101(Handheld)				Test By	Angus Wu
Test Mode	CH High TX				TEMP & Humidity	15°C , 51%

Measurement Distance at 3m Horizontal polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4957.57	69.67	34.86	6.32	35.27	9.50	0.21	66.29	74.00	-7.71	P	1.00
4957.57	37.86	34.86	6.32	35.27	9.50	0.21	34.48	54.00	-19.52	A	1.00
7438.33	57.40	39.86	8.35	35.61	9.50	0.72	61.22	74.00	-12.78	P	1.00
7438.33	33.25	39.86	8.35	35.61	9.50	0.72	37.07	54.00	-16.93	A	1.00
12383.02	62.67	42.08	10.47	35.42	9.50	0.33	70.63	74.00	-3.37	P	1.00
12383.02	39.41	42.08	10.47	35.42	9.50	0.33	47.37	54.00	-6.63	A	1.00

Measurement Distance at 3m Vertical polarity											
Freq. (MHz)	Reading (dB μ V)	AF (dB μ V)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	Level 3m (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
4957.57	72.48	34.86	6.32	35.27	9.50	0.21	69.10	74.00	-4.90	P	1.00
4957.57	35.08	34.86	6.32	35.27	9.50	0.21	31.70	54.00	-22.30	A	1.00
7438.33	63.92	39.86	8.35	35.61	9.50	0.72	67.74	74.00	-6.26	P	1.00
7438.33	34.65	39.86	8.35	35.61	9.50	0.72	38.47	54.00	-15.53	A	1.00
12383.02	60.31	42.08	10.47	35.42	9.50	0.33	68.27	74.00	-5.73	P	1.00
12383.02	33.70	42.08	10.47	35.42	9.50	0.33	41.66	54.00	-12.34	A	1.00


Remark:

1. The measurement was searched to 10th harmonic.
2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$
6. The other emission levels were 20dB below the limit
7. The test limit distance is 3M limit.

8.7.4 RESTRICTED BAND EDGES


Detector mode : Peak



Polarity : Horizontal



Detector mode : Average

Polarity : Horizontal



Detector mode : Peak
Polarity : Vertical

Detector mode : Average
Polarity : Vertical




8.8 POWERLINE CONDUCTED EMISSIONS

None. (Battery powered)

9. ANTENNA REQUIREMENT

9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is [Dipole](#) antenna. The maximum Gain of the antenna only [1.5dBi](#).