47 CFR PART 15 C - BLUETOOTH

TEST REPORT

of

Cell phone

Brand Name:	PCD, Forum Telecom, Forum Tel, ASSIST-CARD, GLOBAL1TOUCH
Model Name:	C1011C, FCLX100LC
Report No.:	SZ10090031E03
FCC ID.:	T38PCD1011C

prepared for

Cellon Communications Technology(ShenZhen)Co., Ltd.
13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen

prepared by

Shenzhen Morlab Communications Technology Co., Ltd.
Morlab Laboratory
3/F, Electronic Testing Building, Shahe Road, Xili,
Nanshan District, Shenzhen, 518055 P. R. China
Tel: +86 755 86130398
Fax: +86 755 86130218

CTIA Authorized Test Lab
LAB CODE 20081223-00

NOTE: *This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.*

TABLE OF CONTENTS

1. TEST CERTIFICATION 4

2. GENERAL INFORMATION 5

2.1 EUT Description 5

2.2 Test Standards and Results 6

2.3 Facilities and Accreditations 7

2.3.1 Facilities 7

2.3.2 Test Environment Conditions 7

3. 47 CFR PART 15C REQUIREMENTS 8

3.1 Number of Hopping Frequency 8

3.1.1 Requirement 8

3.1.2 Test Description 8

3.1.3 Test Result 8

3.2 Peak Output Power 10

3.2.1 Requirement 10

3.2.2 Test Description 10

3.2.3 Test Result 10

3.3 20dB Bandwidth 13

3.3.1 Definition 13

3.3.2 Test Description 13

3.3.3 Test Result 13

3.4 Carried Frequency Separation 16

3.4.1 Definition 16

3.4.2 Test Description 16

3.4.3 Test Result 16

3.5 Time of Occupancy (Dwell time) 17

3.5.1 Requirement 17

3.5.2 Test Description 17

3.5.3 Test Result 17

3.6 Conducted Spurious Emissions 19

3.6.1 Requirement 19

3.6.2 Test Description 19

3.6.3 Test Result 19
3.7 Band Edge 23
3.7.1 Requirement 23
3.7.2 Test Description 23
3.7.3 Test Result 24
3.8 Conducted Emission 27
3.8.1 Requirement 27
3.8.2 Test Description 27
3.8.3 Test Result 28
3.9 Radiated Emission 30
3.9.1 Requirement 30
3.9.2 Test Description 30
3.9.3 Test Result 31

Change History		
Issue	Date	Reason for change
1.0	September 28, 2010	First edition

1. TEST CERTIFICATION

Equipment under Test:	Cell phone
Brand Name:	PCD, Forum Telecom,Forum Tel, ASSIST-CARD, GLOBAL1TOUCH
Model Name:	C1011C, FCLX100LC
FCC ID:	T38PCD1011C
Applicant:	Cellon Communications Technology (ShenZhen)Co., Ltd. 13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen
Manufacturer:	Cellon Communications Technology(ShenZhen)Co., Ltd. 13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen
Test Standards:	47 CFR Part 15 Subpart C
Test Date(s):	September 15, 2010 - September 20, 2010
Test Result:	PASS

*** We Hereby Certify That:**

The equipment under test was tested by Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: ..... Cao Shaodong ..... Dated: 2010.9.28

Reviewed by: ..... Ni Yong ..... Dated: 2010.09.28

Approved by: ..... Shu Luan ..... Dated: 2010.9.28

2. GENERAL INFORMATION

2.1 EUT Description

EUT Type.....:	Cell phone
Model Name .....:	C1011C, FCLX100LC
Serial No.....:	(n.a, marked #1 by test site)
Hardware Version .....:	P1
Software Version .....:	C1011C_1.8
Modulation Type.....:	Frequency Hopping Spread Spectrum (FHSS)
Frequency .....:	The frequency range used is 2402MHz - 2480MHz (79 channels, at intervals of 1MHz); The frequency block is 2400MHz to 2483.5MHz.
Power Supply.....:	Battery Model Name: BTR2096 Brand name: PCD, Forum Tel, Forum Telecom Capacitance: 1050mAh Rated voltage: 3.7V Manufacturer: Xwoda Electronic Co., Ltd Manufacturer Address: Building 2-4, Tongfuyu lndustrial zone, shiyan Street, Baoan District, shenzhen
Ancillary Equipments.....:	AC Adapter (Charger for Battery) Model Name: DSA-3RNA-05 FUS 050065 Brand Name: PCD, Forum Tel Serial No.: (n.a. marked #1 by test site) Rated Input: ~ 100-240V, 50- 60Hz, 200mA, Max 48W Rated Output: ⎓ 5.0V, 650mA, Max 3.25W Manufacturer: DEE VAN Electronics(ShenZhen) CO., LTD. Manufacturer Address: 5th industrial District, Gong Ming Town, Baoan county, Shen Zhen, Guang Dong, CHINA

Note 1: The EUT is a Mobile Phone, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is F(MHz)=2402+1*n (0<=n<=78). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.247(a)	Number of Hopping Frequency	PASS
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	20dB Bandwidth	PASS
4	15.247(a)	Carrier Frequency Separation	PASS
5	15.247(a)	Time of Occupancy (Dwell time)	PASS
6	15.247(c)	Conducted Spurious Emission	PASS
7	15.247(c)	Band Edge	PASS
8	15.207	Conducted Emission	PASS
9	15.209 15.247(c)	Radiated Emission	PASS

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (℃):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

3. 47 CFR PART 15C REQUIREMENTS

3.1 Number of Hopping Frequency

3.1.1 Requirement

According to FCC section 15.247(a)(1)(ii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 75 hopping frequencies.

3.1.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Service Simulator	Agilent	E5515C	GB43130131	2009.09	2year
Spectrum Analyzer	Agilent	E7405A	US44210471	2009.09	2year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)

3.1.3 Test Result

The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

A. Test Verdict:

Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
2400 - 2483.5	79	75	Plot A	PASS

B. Test Plot:



(Plot A: 2402MHz to 2480MHz)

3.2 Peak Output Power

3.2.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.2.2 Test Description

See section 3.1.2 of this report.

3.2.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power			Limit		Verdict
		dBm	W	Refer to Plot	dBm	W	
0	2402	-7.271	0.19E-3	Plot A	30	1	PASS
39	2441	-4.768	0.33E-3	Plot B			PASS
78	2480	-6.361	0.23E-3	Plot C			PASS

B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.3 20dB Bandwidth

3.3.1 Definition

The 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth (10*log1% = 20dB) taking the total RF output power.

3.3.2 Test Description

See section 3.1.2 of this report.

3.3.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

A. Test Verdict:

The maximum 20dB bandwidth measured is 926.25KHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (KHz)	Refer to Plot
0	2402	922.50	Plot A
39	2441	922.50	Plot B
78	2480	926.25	Plot C

B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.4 Carried Frequency Separation

3.4.1 Definition

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.4.2 Test Description

See section 3.1.2 of this report.

3.4.3 Test Result

The Bluetooth Module operates at hopping-on test mode.

For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (926.25KHz, refer to section 3.3.3), whichever is greater. So, the verdict is PASS.



(Plot A: Carried Frequency Separation)

3.5 Time of Occupancy (Dwell time)

3.5.1 Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.5.2 Test Description

See section 3.1.2 of this report.

3.5.3 Test Result

The average time of occupancy on any channel within the Period can be calculated with formulas (for DH5 package type):

{Total of Dwell} = {Pulse Time} * (1600 / 6) / {Number of Hopping Frequency} * {Period}

{Period} = 0.4s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

A. Test Verdict:

Channel	Frequency (MHz)	Pulse Time		Total of Dwell (ms)	Limit (ms)	Verdict
		ms	Refer to Plot			
0	2402	2.875	Plot A	306.67	400	PASS
39	2441	2.875	Plot B	306.67		PASS
78	2480	2.875	Plot C	306.67		PASS

B. Test Plot:

Note: the following plots record the Pulse Time of the Module carrier.



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.6 Conducted Spurious Emissions

3.6.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2 Test Description

See section 3.1.2 of this report.

3.6.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-50.35	Plot A.1/A.2	-8.294	-28.3	PASS
39	2441	-50.9	Plot B.1/B.2	-5.707	-25.7	PASS
78	2480	-52.08	Plot C.1/C.2	-7.118	-27.1	PASS

B. Test Plot:

Note: the power of the Module transmitting frequency should be ignored.



(Plot A.1: Channel = 0, 30MHz to 4GHz)



(Plot A.2: Channel = 0, 4GHz to 25GHz)



(Plot B.1: Channel = 39, 30MHz to 4GHz)



(Plot B.2: Channel = 39, 4GHz to 25GHz)



(Plot C.1: Channel = 78, 30MHz to 4GHz)



(Plot C.2: Channel = 78, 4GHz to 25GHz)

3.7 Band Edge

3.7.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.7.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength..

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2009.9	2year
Receiver	Agilent	E7405A	US44210471	2009.9	2year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2009.9	2year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2009.9	2year

3.7.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:.

Channel	Frequency (MHz)	Max. Emission in the Restricted Bands (dBμV/m)		Limit (dBμV/m)		Verdict
		PK	AV	PK	AV	
0	2402	39.91	35.7	74	54	PASS
78	2480	38.74	37.46	74	54	PASS

B. Test Plot:



(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVERAGE)



(Plot B1: Channel = 78 PEAK)



(Plot B2: Channel = 78 AVERAGE)

3.8 Conducted Emission

3.8.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

NOTE:
(a) The lower limit shall apply at the band edges.
(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2003

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2009.09	2year
LISN	Schwarzbeck	NSLK 8127	812744	2009.09	2year
Service Supplier	R&S	CMU200	100448	2009.09	2year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)

3.8.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.



No	Frequency	PeakAp	QP-Limit	AV-Limit	Quasi-P	Avera-P	Result
1	1.31 M	45.96 DBuV	56.00	46.00	41.65	34.24	Pass
2	210 K	48.84 DBuV	63.22	53.22	--	--	--
3	4.12 M	45.31 DBuV	56.00	46.00	--	--	--
4	4.72 M	45.52 DBuV	56.00	46.00	--	--	--
5	7.82 M	42.77 DBuV	60.00	50.00	--	--	--

(Plot A: L Phase)



No	Frequency	PeakAp	QP-Limit	AV-Limit	Quasi-P	Avera-P	Result
1	299 K	50.90 DBuV	60.26	50.26	33.06	26.74	Pass
2	389 K	50.14 DBuV	58.09	48.09	48.64	42.18	Pass
3	1.25 M	51.25 DBuV	56.00	46.00	49.61	41.26	Pass
4	1.82 M	50.83 DBuV	56.00	46.00	46.72	33.76	Pass
5	4.69 M	49.99 DBuV	56.00	46.00	48.77	35.00	Pass
6	5.73 M	50.54 DBuV	60.00	50.00	48.26	33.06	Pass

(Plot B: N Phase)

3.9 Radiated Emission

3.9.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)	Detector
30 - 88	100	3	QP
88 - 216	150	3	QP
216 - 960	200	3	QP
960 - 1000	500	3	QP
Above 1000	500	3	AV

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

3.9.2 Test Description

A. Test Setup:



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength, the azimuth range of turntable was 0^o to 360^o, the receive antenna has two polarizations horizontal and vertical. When doing measurements above 1GHz, the EUT was placed within the 3dB beam width range of the horn antenna, and the EUT was tested in 3 orthogonal positions as recommended in ANSI C63.4 for Radiated Emissions and the worst-case data was presented.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2009.9	2year
Receiver	Agilent	E7405A	US44210471	2009.9	2year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2009.9	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2009.9	2year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2009.9	2year
Test Antenna - circular	R&S	AC004R1	0749.3000.03	2009.6	2year

3.9.3 Test Result

A. Test Verdict for Harmonics:

The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dBμV/m)		Antenna Polarization	Refer to Plot
		PK	AV		
0	2402	82.93	77.54	Horizontal	Plot A.1
		88.78	83.07	Vertical	Plot A.2
39	2441	87.98	82.66	Horizontal	Plot B.1
		88.16	83.91	Vertical	Plot B.2
78	2480	86.09	80.12	Horizontal	Plot C.1
		87.01	83.03	Vertical	Plot C.2

The un-wanted Emissions:

Test result of channel: 0 (2402MHz)

Frequency (MHz)	PK Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Antenna Polarization
36.8 M	24.91	40	-15.09	100	37	Horizontel
240.5 M	27.94	46	-18.06	100	79	Horizontel
379.2 M	33.19	46	-12.81	100	0	Horizontel
960.2 M	33.08	54	-20.92	100	34	Horizontel
2793 M	48.42	54	-5.58	100	68	Horizontel
14200 M	44.4	54	-9.6	100	68	Horizontel
36.8 M	25.19	40	-14.81	100	32	Vertical
66.9 M	23.64	40	-16.36	100	1	Vertical
240.5 M	26.66	46	-19.34	100	13	Vertical
960.2 M	34.41	54	-19.59	100	21	Vertical
2928 M	47.13	54	-6.87	100	67	Vertical
7923 M	45.06	54	-8.94	100	67	Vertical
14088 M	43.25	54	-10.75	100	19	Vertical

Test result of channel: 39 (2442MHz)

Frequency (MHz)	PK Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Antenna Polarization
36.8 M	24.52	40	-15.48	100	336	Horizontel
66.9 M	24.13	40	-15.87	100	277	Horizontel
240.5 M	29.6	46	-16.4	100	344	Horizontel
379.2 M	35.24	46	-10.76	100	355	Horizontel
664.4 M	30.91	46	-15.09	100	285	Horizontel
2793 M	45.63	54	-8.37	100	316	Horizontel
8125 M	44.24	54	-9.76	100	339	Horizontel
36.8 M	24.89	40	-15.11	100	85	Vertical
66.9 M	24.27	40	-15.73	100	10	Vertical
240.5 M	27.08	46	-18.92	100	88	Vertical
379.2 M	27.66	46	-18.34	100	107	Vertical
960.2 M	35.03	54	-18.97	100	18	Vertical
2500 M	48.57	54	-5.43	100	332	Vertical
7090 M	44.06	54	-9.94	100	211	Vertical

Test result of channel: 78 (2480MHz)

Frequency (MHz)	PK Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Antenna Polarization
36.8 M	24.43	40	-15.57	100	13	Horizontel
240.5 M	28.92	46	-17.08	100	89	Horizontel
379.2 M	34.67	46	-11.33	100	4	Horizontel
720.6 M	30.43	46	-15.57	100	58	Horizontel
960.2 M	33.57	54	-20.43	100	52	Horizontel
2703 M	47.28	54	-6.72	100	69	Horizontel
7990 M	44.52	54	-9.48	100	93	Horizontel
13998 M	43.47	54	-10.53	100	166	Horizontel
36.8 M	25.67	40	-14.33	38	100	Vertical
66.9 M	27.64	40	-12.36	331	100	Vertical
240.5 M	27.59	46	-18.41	271	100	Vertical
960.2 M	35.68	54	-18.32	358	100	Vertical
2658 M	47.91	54	-6.09	43	100	Vertical
7832 M	43.8	54	-10.2	43	100	Vertical
13975 M	43.22	54	-10.78	43	100	Vertical

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



(Plot A.0: 9kHz to 30MHz)



(Plot A.1: Antenna Horizonta)



(Plot A.2: Antenna Vertical)

Plot for Channel = 39



(Plot B.0: 9kHz to 30MHz)



(Plot B.1: Antenna Horizontal)



(Plot B.2: Antenna Vertical)

Plot for Channel = 78



(Plot C.0: 9kHz to 30MHz)



(Plot C.1: Antenna Horizontal)



(Plot C.2: Antenna Vertical)

** END OF REPORT **