

## 47 CFR PART 15 C - BLUETOOTH

# TEST REPORT

of

### Cell phone

Trade Name: Telefonica(Movistar), PCD, Cellon  
Model Name: C2097B, TTX38, TTX38GT, TTX38NI,  
TTX38SV, TTX38MT, TTX38PA  
Report No.: SZ10020050E03  
FCC ID.: T38UT2097B

*prepared for*

**Cellon Communications Technology(ShenZhen)Co., Ltd.**

13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen

*prepared by*  
**Shenzhen Electronic Product Quality Testing Center**

**Morlab Laboratory**

3/F, Electronic Testing Building, Shao Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



**Bluetooth®**

**CTIA Authorized Test Lab**

LAB CODE 20081223-00

**NOTE:** This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

## TABLE OF CONTENTS

|            |                                             |           |
|------------|---------------------------------------------|-----------|
| <b>1.</b>  | <b>TEST CERTIFICATION.....</b>              | <b>4</b>  |
| <b>2.</b>  | <b>GENERAL INFORMATION .....</b>            | <b>5</b>  |
| <b>2.1</b> | <b>EUT Description.....</b>                 | <b>5</b>  |
| <b>2.2</b> | <b>Test Standards and Results.....</b>      | <b>6</b>  |
| <b>2.3</b> | <b>Facilities and Accreditations .....</b>  | <b>7</b>  |
| 2.3.1      | Facilities .....                            | 7         |
| 2.3.2      | Test Environment Conditions .....           | 7         |
| <b>3.</b>  | <b>47 CFR PART 15C REQUIREMENTS.....</b>    | <b>8</b>  |
| <b>3.1</b> | <b>Number of Hopping Frequency .....</b>    | <b>8</b>  |
| 3.1.1      | Requirement .....                           | 8         |
| 3.1.2      | Test Description.....                       | 8         |
| 3.1.3      | Test Result .....                           | 8         |
| <b>3.2</b> | <b>Peak Output Power .....</b>              | <b>10</b> |
| 3.2.1      | Requirement .....                           | 10        |
| 3.2.2      | Test Description.....                       | 10        |
| 3.2.3      | Test Result .....                           | 10        |
| <b>3.3</b> | <b>20dB Bandwidth.....</b>                  | <b>13</b> |
| 3.3.1      | Definition.....                             | 13        |
| 3.3.2      | Test Description.....                       | 13        |
| 3.3.3      | Test Result .....                           | 13        |
| <b>3.4</b> | <b>Carried Frequency Separation .....</b>   | <b>16</b> |
| 3.4.1      | Definition.....                             | 16        |
| 3.4.2      | Test Description.....                       | 16        |
| 3.4.3      | Test Result .....                           | 16        |
| <b>3.5</b> | <b>Time of Occupancy (Dwell time) .....</b> | <b>17</b> |
| 3.5.1      | Requirement .....                           | 17        |
| 3.5.2      | Test Description.....                       | 17        |
| 3.5.3      | Test Result .....                           | 17        |
| <b>3.6</b> | <b>Conducted Spurious Emissions.....</b>    | <b>19</b> |
| 3.6.1      | Requirement .....                           | 19        |
| 3.6.2      | Test Description.....                       | 19        |

|            |                                |           |
|------------|--------------------------------|-----------|
| 3.6.3      | Test Result .....              | 19        |
| <b>3.7</b> | <b>Band Edge .....</b>         | <b>23</b> |
| 3.7.1      | Requirement .....              | 23        |
| 3.7.2      | Test Description.....          | 23        |
| 3.7.3      | Test Result .....              | 24        |
| <b>3.8</b> | <b>Conducted Emission.....</b> | <b>27</b> |
| 3.8.1      | Requirement .....              | 27        |
| 3.8.2      | Test Description.....          | 27        |
| 3.8.3      | Test Result .....              | 28        |
| <b>3.9</b> | <b>Radiated Emission.....</b>  | <b>30</b> |
| 3.9.1      | Requirement .....              | 30        |
| 3.9.2      | Test Description.....          | 30        |
| 3.9.3      | Test Result .....              | 31        |

| Change History |                |                   |
|----------------|----------------|-------------------|
| Issue          | Date           | Reason for change |
| 1.0            | March 16, 2010 | First edition     |
|                |                |                   |

## 1. TEST CERTIFICATION

Equipment under Test: Cell phone

Trade Name: Telefonica(Movistar), PCD, Cellon

Model Name: C2097B, TTX38, TTX38GT, TTX38NI, TTX38SV, TTX38MT, TTX38PA

FCC ID: T38UT2097B

Applicant: Cellon Communications Technology(ShenZhen)Co., Ltd.

13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen

Manufacturer: Cellon Communications Technology(ShenZhen)Co., Ltd.

13/F, Skyworth Building C Gaoxin S. Ave. 1st, High-Tech industrial Park NanShan, ShenZhen

Test Standards: 47 CFR Part 15 Subpart C

Test Date(s): February 24, 2010 - March 15, 2010


Test Result: PASS

### \* We Hereby Certify That:

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.


Tested by:

  
Cao Shadong

Dated:

2010.3.16


Reviewed by:

  
Wei Yanquan

Dated:

2010.3.16

Approved by:

  
Zeng Dexin

Dated:

2010.03.16



## 2. GENERAL INFORMATION

### 2.1 EUT Description

EUT Type .....: Cell phone  
Model Name .....: C2097B, TTX38, TTX38GT, TTX38NI, TTX38SV, TTX38MT, TTX38PA  
Serial No.....: (n.a, marked #1 by test site)  
Hardware Version .....: P3  
Software Version .....: V1.10  
Modulation Type.....: Frequency Hopping Spread Spectrum (FHSS)  
Frequency .....: The frequency range used is 2402MHz - 2480MHz (79 channels, at intervals of 1MHz);  
The frequency block is 2400MHz to 2483.5MHz.  
Power Supply .....: Battery  
Model Name: BTR2096  
Brand name: PCD  
Capacitance: 1050mAh  
Rated voltage: 3.7V  
Manufacturer: Shenzhen BAK Battery Co.,Ltd  
Ancillary Equipments.....: AC Adapter (Charger for Battery)  
Model Name: DSA-3RNA-05 FUS 050065  
Brand Name: PCD  
Serial No.: (n.a. marked #1 by test site)  
Rated Input: ~ 110-240V, 50/60Hz, Max48W  
Rated Output: = 5.0V, 650mA, Max 3.25W  
Manufacturer: DEE VAN Electronics(ShenZhen) CO., LTD  
Manufacturer Address: 5th industrial District, Gong Ming Town, Baoan county, Shen Zhen, Guang Dong, CHINA

*Note 1:* The EUT is a Mobile Phone, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is  $F(\text{MHz})=2402+1*n$  ( $0 \leq n \leq 78$ ). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).

*Note 2:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

| No. | Identity                            | Document Title          |
|-----|-------------------------------------|-------------------------|
| 1   | 47 CFR Part 15<br>(10-1-05 Edition) | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section             | Description                    | Result |
|-----|---------------------|--------------------------------|--------|
| 1   | 15.247(a)           | Number of Hopping Frequency    | PASS   |
| 2   | 15.247(b)           | Peak Output Power              | PASS   |
| 3   | 15.247(a)           | 20dB Bandwidth                 | PASS   |
| 4   | 15.247(a)           | Carrier Frequency Separation   | PASS   |
| 5   | 15.247(a)           | Time of Occupancy (Dwell time) | PASS   |
| 6   | 15.247(c)           | Conducted Spurious Emission    | PASS   |
| 7   | 15.247(c)           | Band Edge                      | PASS   |
| 8   | 15.207              | Conducted Emission             | PASS   |
| 9   | 15.209<br>15.247(c) | Radiated Emission              | PASS   |

## 2.3 Facilities and Accreditations

### 2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### 2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

|                             |         |
|-----------------------------|---------|
| Temperature (°C):           | 20 - 25 |
| Relative Humidity (%):      | 40 - 60 |
| Atmospheric Pressure (kPa): | 96      |



### 3. 47 CFR PART 15C REQUIREMENTS


#### 3.1 Number of Hopping Frequency

##### 3.1.1 Requirement

According to FCC section 15.247(a)(1)(ii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 75 hopping frequencies.

##### 3.1.2 Test Description

###### A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

###### B. Equipments List:

| Description       | Manufacturer | Model  | Serial No. | Cal. Date | Cal. Due |
|-------------------|--------------|--------|------------|-----------|----------|
| Service Simulator | Agilent      | E5515C | GB43130131 | 2009.09   | 1year    |
| Spectrum Analyzer | Agilent      | E7405A | US44210471 | 2009.09   | 1year    |
| Power Splitter    | Weinschel    | 1506A  | NW521      | (n.a.)    | (n.a.)   |
| Attenuator 1      | Resnet       | 20dB   | (n.a.)     | (n.a.)    | (n.a.)   |
| Attenuator 2      | Resnet       | 3dB    | (n.a.)     | (n.a.)    | (n.a.)   |

##### 3.1.3 Test Result


The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.



### A. Test Verdict:

| Frequency Block (MHz) | Measured Channel Numbers | Min. Limit | Refer to Plot | Verdict |
|-----------------------|--------------------------|------------|---------------|---------|
| 2400 - 2483.5         | 79                       | 75         | Plot A        | PASS    |

### B. Test Plot:



(Plot A: 2402MHz to 2480MHz)

## 3.2 Peak Output Power

### 3.2.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

### 3.2.2 Test Description

See section 3.1.2 of this report.


### 3.2.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


#### A. Test Verdict:

| Channel | Frequency (MHz) | Measured Output Peak Power |          |               | Limit |   | Verdict |
|---------|-----------------|----------------------------|----------|---------------|-------|---|---------|
|         |                 | dBm                        | W        | Refer to Plot | dBm   | W |         |
| 0       | 2402            | 12.47                      | 17.66E-3 | Plot A        | 30    | 1 | PASS    |
| 39      | 2441            | 11.34                      | 13.61E-3 | Plot B        |       |   | PASS    |
| 78      | 2480            | 11.74                      | 14.92E-3 | Plot C        |       |   | PASS    |


#### B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

### 3.3 20dB Bandwidth

#### 3.3.1 Definition

The 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ( $10 \cdot \log 1\% = 20\text{dB}$ ) taking the total RF output power.

#### 3.3.2 Test Description

See section 3.1.2 of this report.

#### 3.3.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

##### A. Test Verdict:


The maximum 20dB bandwidth measured is 1.024MHz according to the table below.

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | Refer to Plot |
|---------|-----------------|----------------------|---------------|
| 0       | 2402            | 1.005                | Plot A        |
| 39      | 2441            | 1.005                | Plot B        |
| 78      | 2480            | 1.005                | Plot C        |


##### B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)



### 3.4 Carried Frequency Separation

#### 3.4.1 Definition

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.


#### 3.4.2 Test Description

See section 3.1.2 of this report.

#### 3.4.3 Test Result

The Bluetooth Module operates at hopping-on test mode.

For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (1.005MHz, refer to section 3.3.3), whichever is greater. So, the verdict is PASS.



(Plot A: Carried Frequency Separation)

### 3.5 Time of Occupancy (Dwell time)

#### 3.5.1 Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

#### 3.5.2 Test Description

See section 3.1.2 of this report.

#### 3.5.3 Test Result

The average time of occupancy on any channel within the Period can be calculated with formulas (for DH5 package type):

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4\text{s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$




The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

##### A. Test Verdict:

| Channel | Frequency (MHz) | Pulse Time |               | Total of Dwell (ms) | Limit (ms) | Verdict |
|---------|-----------------|------------|---------------|---------------------|------------|---------|
|         |                 | ms         | Refer to Plot |                     |            |         |
| 0       | 2402            | 2.8        | Plot A        | 298.6               | 400        | PASS    |
| 39      | 2441            | 2.82       | Plot B        | 300.8               |            | PASS    |
| 78      | 2480            | 2.82       | Plot C        | 300.8               |            | PASS    |

##### B. Test Plot:

Note: the following plots record the Pulse Time of the Module carrier.



### 3.6 Conducted Spurious Emissions

#### 3.6.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 3.6.2 Test Description

See section 3.1.2 of this report.

#### 3.6.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

##### A. Test Verdict:


| Channel | Frequency (MHz) | Measured Max. Out of Band Emission (dBm) | Refer to Plot | Limit (dBm)   |                         | Verdict |
|---------|-----------------|------------------------------------------|---------------|---------------|-------------------------|---------|
|         |                 |                                          |               | Carrier Level | Calculated -20dBc Limit |         |
| 0       | 2402            | -34.48                                   | Plot A.1/A.2  | 12.9          | -7.1                    | PASS    |
| 39      | 2441            | -36.64                                   | Plot B.1/B.2  | 11.6          | -8.4                    | PASS    |
| 78      | 2480            | -37.15                                   | Plot C.1/C.2  | 12.1          | -7.9                    | PASS    |

##### B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 0, 30MHz to 3GHz)




(Plot A.2: Channel = 0, 3GHz to 25GHz)




(Plot B.1: Channel = 39, 30MHz to 3GHz)



(Plot B.2: Channel = 39, 3GHz to 25GHz)



(Plot C.1: Channel = 78, 30MHz to 3GHz)



(Plot C.2: Channel = 78, 3GHz to 25GHz)


### 3.7 Band Edge

#### 3.7.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 3.7.2 Test Description

##### A. Test Setup:



The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength..



## B. Equipments List:

| Description           | Manufacturer | Model      | Serial No. | Cal. Date | Cal. Due |
|-----------------------|--------------|------------|------------|-----------|----------|
| System Simulator      | R&S          | CMU200     | 100448     | 2009.9    | 1year    |
| Receiver              | Agilent      | E7405A     | US44210471 | 2009.9    | 1year    |
| Full-Anechoic Chamber | Albatross    | 9m*6m*6m   | (n.a.)     | 2009.9    | 2year    |
| Test Antenna - Horn   | Schwarzbeck  | BBHA 9120C | 9120C-384  | 2009.9    | 1year    |


## 3.7.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.


### A. Test Verdict:.

| Channel | Frequency (MHz) | Max. Emission in the Restricted Bands (dB $\mu$ V/m) |       | Limit (dB $\mu$ V/m) |    | Verdict |
|---------|-----------------|------------------------------------------------------|-------|----------------------|----|---------|
|         |                 | PK                                                   | AV    | PK                   | AV |         |
| 0       | 2402            | 47.93                                                | 38.28 | 74                   | 54 | PASS    |
| 78      | 2480            | 44.17                                                | 38.41 | 74                   | 54 | PASS    |


### B. Test Plot:




(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVERAGE)



(Plot B1: Channel = 78 PEAK)



(Plot B2: Channel = 78 AVERAGE)

### 3.8 Conducted Emission

#### 3.8.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


| Frequency range (MHz) | Conducted Limit (dB $\mu$ V) |          |
|-----------------------|------------------------------|----------|
|                       | Quai-peak                    | Average  |
| 0.15 - 0.50           | 66 to 56                     | 56 to 46 |
| 0.50 - 5              | 56                           | 46       |
| 0.50 - 30             | 60                           | 50       |

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

#### 3.8.2 Test Description

##### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2003


The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

## B. Equipments List:


| Description          | Manufacturer | Model       | Serial No. | Cal. Date | Cal. Due |
|----------------------|--------------|-------------|------------|-----------|----------|
| Receiver             | Agilent      | E7405A      | US44210471 | 2009.09   | 1year    |
| LISN                 | Schwarzbeck  | NSLK 8127   | 812744     | 2009.09   | 1year    |
| Service Supplier     | R&S          | CMU200      | 100448     | 2009.09   | 1year    |
| Pulse Limiter (20dB) | Schwarzbeck  | VTSD 9561-D | 9391       | (n.a.)    | (n.a.)   |

## 3.8.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.



(Plot A: L Phase)



(Plot B: N Phase)

### 3.9 Radiated Emission

#### 3.9.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu\text{V/m}$ ) | Measurement Distance (m) | Detector |
|-----------------|------------------------------------|--------------------------|----------|
| 30 - 88         | 100                                | 3                        | QP       |
| 88 - 216        | 150                                | 3                        | QP       |
| 216 - 960       | 200                                | 3                        | QP       |
| 960 - 1000      | 500                                | 3                        | QP       |
| Above 1000      | 500                                | 3                        | AV       |

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

#### 3.9.2 Test Description

##### A. Test Setup:



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength, the azimuth range of turntable was 0° to 360°, the receive antenna has two polarizations horizontal and vertical. When doing measurements above 1GHz, the EUT was placed within the 3dB beam width range of the horn antenna, and the EUT was tested in 3 orthogonal positions as recommended in ANSI C63.4 for Radiated Emissions and the worst-case data was presented.

## B. Equipments List:

| Description             | Manufacturer | Model      | Serial No.   | Cal. Date | Cal. Due |
|-------------------------|--------------|------------|--------------|-----------|----------|
| System Simulator        | R&S          | CMU200     | 100448       | 2009.9    | 1year    |
| Receiver                | Agilent      | E7405A     | US44210471   | 2009.9    | 1year    |
| Full-Anechoic Chamber   | Albatross    | 9m*6m*6m   | (n.a.)       | 2009.9    | 2year    |
| Test Antenna - Bi-Log   | Schwarzbeck  | VULB 9163  | 9163-274     | 2009.9    | 1year    |
| Test Antenna - Horn     | Schwarzbeck  | BBHA 9120C | 9120C-384    | 2009.9    | 1year    |
| Test Antenna - circular | R&S          | AC004R1    | 0749.3000.03 | 2009.6    | 1year    |

## 3.9.3 Test Result

### A. Test Verdict for Harmonics:

#### The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

| Channel | Frequency (MHz) | Fundamental Emission (dBμV/m) |       | Antenna Polarization | Refer to Plot |
|---------|-----------------|-------------------------------|-------|----------------------|---------------|
|         |                 | PK                            | AV    |                      |               |
| 0       | 2402            | 87.05                         | 80.41 | Horizontal           | Plot A.1      |
|         |                 | 93.78                         | 85.32 | Vertical             | Plot A.2      |
| 39      | 2441            | 89.31                         | 82.94 | Horizontal           | Plot B.1      |
|         |                 | 94.57                         | 86.72 | Vertical             | Plot B.2      |
| 78      | 2480            | 86.12                         | 78.96 | Horizontal           | Plot C.1      |
|         |                 | 91.24                         | 83.70 | Vertical             | Plot C.2      |



### The un-wanted Emissions:

#### Test result of channel: 0 (2402MHz)

| Frequency (MHz) | PK Level (dB $\mu$ V/m) | Limits (dB $\mu$ V/m) | Margin (dB) | Height (cm) | Azimuth (deg) | Antenna Polarization |
|-----------------|-------------------------|-----------------------|-------------|-------------|---------------|----------------------|
| 624.6 M         | 33.91                   | 46                    | -12.09      | 100         | 0             | Horizontal           |
| 120.2 M         | 24.14                   | 43.5                  | -19.36      | 100         | 64            | Horizontal           |
| 624.6 M         | 33.72                   | 46                    | -12.28      | 100         | 350           | Vertical             |
| 120.2 M         | 24.34                   | 43.5                  | -19.16      | 100         | 0             | Vertical             |

#### Test result of channel: 39 (2442MHz)


| Frequency (MHz) | PK Level (dB $\mu$ V/m) | Limits (dB $\mu$ V/m) | Margin (dB) | Height (cm) | Azimuth (deg) | Antenna Polarization |
|-----------------|-------------------------|-----------------------|-------------|-------------|---------------|----------------------|
| 624.6 M         | 33.05                   | 46                    | -12.95      | 100         | 52            | Horizontal           |
| 120.2 M         | 27.82                   | 43.5                  | -15.68      | 100         | 58            | Horizontal           |
| 624.6 M         | 33.56                   | 46                    | -12.44      | 100         | 314           | Vertical             |
| 120.2 M         | 28.51                   | 43.5                  | -14.99      | 100         | 47            | Vertical             |

#### Test result of channel: 78 (2480MHz)


| Frequency (MHz) | PK Level (dB $\mu$ V/m) | Limits (dB $\mu$ V/m) | Margin (dB) | Height (cm) | Azimuth (deg) | Antenna Polarization |
|-----------------|-------------------------|-----------------------|-------------|-------------|---------------|----------------------|
| 624.6 M         | 33.21                   | 46                    | -12.79      | 100         | 353           | Horizontal           |
| 240.5 M         | 25.84                   | 46                    | -20.16      | 100         | 124           | Horizontal           |
| 120.2 M         | 28.16                   | 43.5                  | -15.34      | 100         | 66            | Horizontal           |
| 624.6 M         | 33.39                   | 46                    | -12.61      | 100         | 207           | Vertical             |
| 120.2 M         | 30.13                   | 43.5                  | -13.37      | 100         | 37            | Vertical             |

## B. Test Plots for the Whole Measurement Frequency Range:


### Plots for Channel = 0



(Plot A.0: 9kHz to 30MHz)




(Plot A.1: Antenna Horizontal)




(Plot A.2: Antenna Vertical)


Plot for Channel = 39



(Plot B.0: 9kHz to 30MHz)




(Plot B.1: Antenna Horizontal)




(Plot B.2: Antenna Vertical)


Plot for Channel = 78



(Plot C.0: 9kHz to 30MHz)



(Plot C.1: Antenna Horizontal)



(Plot C.2: Antenna Vertical)

\*\* END OF REPORT \*\*