



NVLAP LAB CODE 200707-0



FCC PART 15.247

MEASUREMENT AND TEST REPORT



For

Cellon Communications Technology (Shenzhen) Co., Ltd.

13/F, Skyworth C Building, Gaoxin S.Ave1, Hi-Tech Industrial Park,

Nanshan, Shenzhen, Guangdong 518057, China

FCC ID: T38UT5160C

Report Type: Original Report	Product Type: GSM&GPRS Mobile Phone
Test Engineer:	Phoenix Liu 
Report Number:	RSZ09042701-15.247
Report Date:	2009-06-01
	Merry Zhao 
Reviewed By:	EMC Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “*” (Rev. 2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
CFR47 §15.247 (i) and §2.1093 - RF EXPOSURE	9
STANDARD APPLICABLE	9
RESULT:	9
CFR47 §15.203 - ANTENNA REQUIREMENT.....	10
STANDARD APPLICABLE	10
ANTENNA CONNECTOR CONSTRUCTION	10
CFR47 §15.205, §15.209, §15.247 - RADIATED EMISSIONS.....	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	13
TEST DATA	13
CFR47 §15.247(a) (1)-CHANNEL SEPARATION TEST	17
APPLICABLE STANDARD	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
TEST DATA	17
CFR47 §15.247(a) (1) – 20dB BANDWIDTH TESTING.....	20
APPLICABLE STANDARD	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST PROCEDURE	20
TEST DATA	20
CFR47 §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	23
APPLICABLE STANDARD	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST PROCEDURE	23

TEST DATA	23
CFR47 §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	25
TEST DATA	25
CFR47 §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	32
APPLICABLE STANDARD	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST PROCEDURE	32
TEST DATA	33
CFR47 §15.247(d) - BAND EDGES TESTING	35
APPLICABLE STANDARD	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST PROCEDURE	35
TEST DATA	36
DECLARATION LETTER	38

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Cellon Communications Technology (Shenzhen) Co., Ltd.*'s product, model number: *C5160C (FCC IC: T38UT5160C)* or the "EUT" as referred to in this report is a *GSM&GPRS Mobile Phone*, which measures approximately: 8.9 cm L x 4.5 cm W x 2.1 cm H, rated input voltage: DC 3.7V battery.

Frequency Range:

Cellular Band: 824-849 MHz (TX), 869-894 MHz (RX)
PCS Band: 1850-1910 MHz (TX), 1930-1990 MHz (RX)
Bluetooth: 2400-2483.5 MHz (Tx/ Rx)

Modulation Mode: GMSK (GSM/DCS), GFSK (Bluetooth)

Transmitter Output Power:

Cellular Band: 33±2 dBm
PCS Band: 30±2 dBm
Bluetooth: -6~4 dBm

** All measurement and test data in this report was gathered from production sample serial number: 0904074(Assigned by BACL). The EUT was received on 2009-04-27.*

Objective

This Type approval report is prepared on behalf of *Cellon Communications Technology (Shenzhen) Co., Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

This measurement and test report only pertains to the Bluetooth portion of the EUT; for measurement and test results to the GSM 1900 function please refer to report RSZ09031601-2224 issued by Shenzhen BACL.

Related Submittal(s)/Grant(s)

FCC Part 22H and 24E submission with FCC ID: T38UT5160C.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at
<http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Equipment Modifications


No modification was made to the unit tested.

Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
IBM	Leptop	2373	N/A	DOC
R & S	Universal Radio commutation tester	CMU200	109038	DoC


Configuration of Test Setup

Radiated Emission:



Block Diagram of Test Setup

Radiated Emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	Conducted Emissions	N/A
§15.205, §15.209, §15.109, §15.247(d)	Radiated Emissions	Compliant*
§15.247 (a)(1)	20 dB Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Note: * Within measurement uncertainty.

CFR47 §15.247 (i) and §2.1093 - RF EXPOSURE

Standard Applicable

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

According to FCC Exclusion list, In the following table, f_{GHz} is mid-band frequency in GHz, and d is the distance to a person's body, excluding hands, wrists, feet, and ankles.

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(120/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(900/f_{\text{GHz}})$ mW, $d < 20$ cm
occupational	$(375/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(900/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(2250/f_{\text{GHz}})$ mW, $d < 20$ cm

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Result:

Two antennas are available for the EUT, one is GSM/PCS antenna and the other is Bluetooth antenna, the distance between them is ≥ 5.0 cm, according to FCC KDB 648474 D01 SAR Handsets Multi Xmitter and ant. V01r05 released on September 2008, the Max peak output power is $2.15 \text{ mW} < P_{\text{Ref}}$ (24 mw) stand-alone SAR is not required for Bluetooth antenna.

The SAR measurement is exempt.

CFR47 §15.203 - ANTENNA REQUIREMENT

Standard Applicable

According to CFR47 § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an integral antenna (component) soldered on PCB, the gain is less than -1.5 dBi, please refer to the EUT internal photos.

Result: Compliant.


CFR47 §15.205, §15.209, §15.247 - RADIATED EMISSIONS**Applicable Standard**

CFR47 §15.205; §15.209; §15.247 (d)

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup

The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>
30MHz – 1000 MHz	100 kHz	300 kHz
1000 MHz – 25 GHz	1 MHz	3 MHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2008-08-02	2009-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
HP	Amplifier	8449B	3008A00277	2008-09-12	2009-09-11
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

Transmitting mode (Below 1GHz):

8.8 dB at **756.030400 MHz** in the **Vertical** polarization

Transmitting mode (Above 1 GHz):

2.41 dB at **4804.00 MHz** in the **Horizontal** polarization (Low Channel)
2.94 dB at **4882.00 MHz** in the **Horizontal** polarization (Middle Channel)
3.89 dB at **4960.00 MHz** in the **Vertical** polarization (High Channel)


Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

** The testing was performed by Phoenix Liu on 2009-05-18.*

Test Mode: Transmitting (below 1 GHz)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
756.030400	37.2	111.0	V	181.0	-5.9	46.0	8.8
701.062775	34.5	116.0	V	193.0	-6.9	46.0	11.5
819.050325	34.3	113.0	V	198.0	-4.9	46.0	11.7
905.608925	31.2	340.0	H	164.0	-3.6	46.0	14.8
41.453225	20.9	118.0	V	52.0	-16.2	40.0	19.1
32.039000	20.6	120.0	V	316.0	-10.0	40.0	19.4

Test Mode: Transmitting (Above 1 GHz)

Frequency (MHz)	S.A. Reading (dBμV/m)	Detector PK/QP/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	Remarks
Low Channel (2402 MHz)												
4804.00	41.43	AV	90	1.0	H	36.3	7.56	33.7	51.59	54	2.41*	harmonic
4804.00	42.12	AV	90	1.0	V	35.0	7.56	33.7	50.98	54	3.02*	harmonic
7206.00	34.33	AV	120	1.2	H	39.2	9.12	33.6	49.05	54	4.95	harmonic
7206.00	35.41	AV	120	1.2	V	38.0	9.12	33.6	48.93	54	5.07	harmonic
4804.00	48.85	PK	180	1.2	H	36.3	7.56	33.7	59.01	74	14.99	harmonic
7206.00	43.79	PK	120	1.2	H	39.2	9.12	33.6	58.51	74	15.49	harmonic
4804.00	49.58	PK	180	1.2	V	35.0	7.56	33.7	58.44	74	15.56	harmonic
7206.00	44.32	PK	120	1.2	V	38.0	9.12	33.6	57.84	74	16.16	harmonic
1134.26	39.40	AV	180	1.2	V	25.8	5.11	34.8	35.51	54	18.49	spurious
1448.89	36.10	AV	180	1.2	H	26.7	5.37	34.6	33.57	54	20.43	spurious
1134.26	52.10	PK	45	1.2	V	25.8	5.11	34.8	48.21	74	25.79	spurious
1448.89	50.29	PK	45	1.2	H	26.7	5.37	34.6	47.76	74	26.24	spurious
Middle Channel (2441 MHz)												
4882.00	40.90	AV	142	1.6	H	36.3	7.56	33.7	51.06	54	2.94*	harmonic
7323.00	32.23	AV	80	1.0	H	39.2	9.12	33.6	46.95	54	7.05	harmonic
7323.00	32.15	AV	80	1.0	V	38.0	9.12	33.6	45.67	54	8.33	harmonic
4882.00	35.50	AV	243	1.4	V	35.0	7.56	33.7	44.36	54	9.64	harmonic
4882.00	51.60	PK	234	1.8	H	36.3	7.56	33.7	61.76	74	12.24	harmonic
7323.00	45.11	PK	120	1.2	H	39.2	9.12	33.6	59.83	74	14.17	harmonic
1134.26	41.84	AV	135	1.3	H	25.9	5.11	34.8	38.05	54	15.95	spurious
7323.00	44.24	PK	120	1.2	V	38.0	9.12	33.6	57.76	74	16.24	harmonic
1134.26	40.25	AV	85	1.5	V	25.8	5.11	34.8	36.36	54	17.64	spurious
4882.00	46.21	PK	153	1.5	V	35.0	7.56	33.7	55.07	74	18.93	harmonic
1134.26	51.65	PK	156	1.4	H	25.9	5.11	34.8	47.86	74	26.14	spurious
1134.26	50.35	PK	265	1.4	V	25.8	5.11	34.8	46.46	74	27.54	spurious
High Channel (2480 MHz)												
4960.00	41.25	AV	142	1.5	V	35.0	7.56	33.7	50.11	54	3.89*	harmonic
4960.00	37.56	AV	256	1.8	H	36.3	7.56	33.7	47.72	54	6.28	harmonic
7440.00	32.18	AV	80	1.2	H	39.2	9.12	33.6	46.90	54	7.10	harmonic
7440.00	31.75	AV	80	1.0	V	38.0	9.12	33.6	45.27	54	8.73	harmonic
4960.00	49.60	PK	142	1.4	V	35.0	7.56	33.7	58.46	74	15.54	harmonic
4960.00	47.58	PK	145	1.4	H	36.3	7.56	33.7	57.74	74	16.26	harmonic
7440.00	42.96	PK	120	1.0	H	39.2	9.12	33.6	57.68	74	16.32	harmonic
7440.00	42.88	PK	120	1.2	V	38.0	9.12	33.6	56.40	74	17.60	harmonic
1134.26	40.12	AV	210	1.2	V	25.8	5.11	34.8	36.23	54	17.77	spurious
1134.26	38.74	AV	156	1.2	H	25.9	5.11	34.8	34.95	54	19.05	spurious
1134.26	51.19	PK	240	1.4	V	25.8	5.11	34.8	47.30	74	26.70	spurious
1134.26	49.85	PK	128	1.5	H	25.9	5.11	34.8	46.06	74	27.94	spurious

* Within measurement uncertainty.

Spurious emission in restricted band

Frequency (MHz)	S.A. Reading (dBμV/m)	Detector (PK/AV)	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/209	
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)
Out of left side band (2310 – 2390 MHz)											
2384.36	36.57	AV	120	1.5	V	30.6	6.6	33.9	39.87	54	14.13
2385.12	35.15	AV	180	1.2	H	30.9	6.6	33.9	38.75	54	15.25
2384.36	45.89	PK	120	1.5	V	30.6	6.6	33.9	49.19	74	24.81
2385.12	44.51	PK	180	1.2	H	30.9	6.6	33.9	48.11	74	25.89
Out of right side band (2483.5 – 2500 MHz)											
2485.98	43.87	PK	125	1.7	H	30.9	6.6	33.9	47.47	74	26.53
2483.60	34.63	AV	125	1.7	H	30.9	6.6	33.9	38.23	54	15.77
2485.98	44.10	PK	264	1.5	V	30.6	6.6	33.9	47.40	74	26.60
2483.60	42.56	PK	125	1.7	H	30.9	6.6	33.9	46.16	74	27.84

CFR47 §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

** The testing was performed by Phoenix Liu on 2009-05-19.*

Test Result: Compliant.


Please refer to following tables and plots

Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2402	1.004	0.501	Pass
Adjacent Channel	2403			
Mid Channel	2441	1.004	0.509	Pass
Adjacent Channel	2442			
High Channel	2480	1.004	0.512	Pass
Adjacent Channel	2479			


Please refer to the following plots.

Low Channel




channel separation low channel

Date: 19.MAY.2009 13:33:37

Middle Channel

channel separation middle channel

Date: 19.MAY.2009 13:34:47

High Channel

channel separation high channel

Date: 19.MAY.2009 13:36:16

CFR47 §15.247(a) (1) – 20dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

* The testing was performed by Phoenix Liu on 2009-05-19.

Test Result: Compliant.


Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	0.752
Middle	2441	0.764
High	2480	0.768

Please refer to the following plots.

Low Channel



20dB bandwidth low channel
Date: 19.MAY.2009 13:31:47

Ref 11.2 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz SWT 2.5 ms

Marker 1 [T1] -0.01 dBm 2.440984000 GHz

10 Offset 1.2 dB

1 PK MAXH

dB [T1] 20.00 dB
BW 764.0000000 kHz
Temp 1 [T1 ndB] -20.24 dBm
2.440628000 GHz
Temp 2 [T1 ndB] -20.05 dBm
2.441392000 GHz

Center 2.441 GHz 200 kHz/ Span 2 MHz

Date: 19.MAY.2009 13:31:02

Ref 11.2 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz SWT 2.5 ms

Marker 1 [T1] 2.479988000 GHz 20.00 dB 768.000000000 kHz -16.72 dBm 2.479632000 GHz -17.02 dBm 2.480400000 GHz

1 PK MAXH

Center 2.48 GHz 200 kHz/ Span 2 MHz

Date: 19.MAY.2009 13:30:26

CFR47 §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

The testing was performed by Phoenix Liu on 2009-05-19.


Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels



hopping channels

Date: 19.MAY.2009 13:39:47

CFR47 §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

** The testing was performed by Phoenix Liu on 2009-05-19.*

Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting

DH 1 Mode:

Channel	Pulse Width (ms)	Dwell Time (Sec)	Limit (Sec)	Result
Low	0.425	0.1360	0.4	Pass
Middle	0.425	0.1360	0.4	Pass
High	0.425	0.1360	0.4	Pass

Note: Dwell time=Pulse width (ms) $\times$ (1600 $\div$ 2 $\div$ 79) $\times$ 31.6 Second

DH 3 Mode:

Channel	Pulse Width (ms)	Dwell Time (Sec)	Limit (Sec)	Result
Low	1.700	0.2720	0.4	Pass
Middle	1.700	0.2720	0.4	Pass
High	1.690	0.2704	0.4	Pass

Note: Dwell time=Pulse width (ms) $\times$ (1600 $\div$ 4 $\div$ 79) $\times$ 31.6 Second


DH 5 Mode:

Channel	Pulse Width (ms)	Dwell Time (Sec)	Limit (Sec)	Result
Low	2.980	0.3179	0.4	Pass
Middle	2.960	0.3157	0.4	Pass
High	2.980	0.3179	0.4	Pass

Note: Dwell time=Pulse width (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6 Second


Please refer to the following plots.

Low Channel for DH1




dwell time low channel DH1
Date: 19.MAY.2009 14:41:11

Middle Channel for DH1




dwell time middle channel DH1
Date: 19.MAY.2009 14:42:01

High Channel for DH1


dwell time high channel DH1

Date: 19.MAY.2009 14:43:27

Low Channel for DH3


dwell time low channel DH3

Date: 19.MAY.2009 14:44:34

Middle Channel for DH3

dwell time middle channel DH3


Date: 19.MAY.2009 14:45:38

High Channel for DH3

dwell time high channel DH3

Date: 19.MAY.2009 14:46:32


Low Channel for DH5



dwell time low channel DH5

Date: 19.MAY.2009 14:47:35


Middle Channel for DH5



dwell time middle channel DH5

Date: 19.MAY.2009 14:48:28

High Channel for DH5



dwll time high channel DH5

Date: 19.MAY.2009 14:49:03

CFR47 §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**


Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

* The testing was performed by Phoenix Liu on 2009-05-19.

Test Result: Compliant.

Test Mode: Transmitting


channel	Channel frequency (MHz)	Reading power (dBm)	Power output (mw)	Limit (mw)
Low channel	2402	0.33	1.08	125
Middle channel	2441	0.27	1.06	125
High channel	2480	3.32	2.15	125

Low Channel

peak of output power low channel


Date: 19.MAY.2009 14:36:39

Middle Channel



peak of output power middle channel
Date: 19.MAY.2009 14:37:41

High Channel



peak of output power high channel
Date: 19.MAY.2009 14:38:41

CFR47 §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa


**The testing was performed by Phoenix Liu on 2009-05-19.*

Test Result: Compliant

Please refer to the following table and plots.


Test Mode: Transmitting

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.900	46.33	20
2483.600	48.96	20

Band Edge: Left Side

band edge left

Date: 19.MAY.2009 14:33:57

Band Edge: Right Side

band edge right

Date: 19.MAY.2009 14:35:05

DECLARATION LETTER



Cellon Communications Technology (Shenzhen) Co., Ltd.
13/F, Skyworth C Building, Gaoxin S.Ave1, Hi-Tech Industrial Park, Nanshan
518057 China

Product Similarity Declaration

To Whom It May Concern,

We, Cellon Communications Technology (Shenzhen) Co., Ltd., hereby declare that our GSM&GPRS Mobile Phone, Model Number: GPF158, GPF159, GPF158L, GPF159L, GPF158LCL, GPF159LCL, GPF158LT, GPF159LT, GPF158LWOC, GPF159LWOC, GPF158LTG, GPF159LTG are electrically identical with the Model Number: C5160C that was certified by BACL. They are named differently due to marketing purposes.

Please contact me if you have any question.

Signature:

Maggie.xu 2009.4.27

Typed or Printed Name: Maggie.xu

Title: Manager

Company Name: Cellon Communications Technology (Shenzhen) Co., Ltd.

***** END OF REPORT *****