



FCC TEST REPORT

REPORT NO.: 060312FIA01

MODEL NO.: SW0001A

RECEIVED: Mar. 8, 2006

TESTED: Mar. 8 ~ Apr. 12, 2006

ISSUED: Apr. 13, 2006

APPLICANT: Giant Creation Ltd

ADDRESS: Flat E-F, 13/F, Block 2, Golden Dragon Industrial Centre,
162 Tai Lin Pai Road, Kwai Chung, Hong Kong

ISSUED BY: ADT (Shanghai) Corporation

ADDRESS: 2F, Building C, No.1618, Yishan Rd., 201103,
Shanghai, China

This test report consists of 20 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

ADT (Shanghai) Corporation.



Table of Contents

1	CERTIFICATION	3
2	SUMMARY OF TEST RESULTS	4
2.1	MEASUREMENT UNCERTAINTY	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT.....	5
3.2	DESCRIPTION OF TEST MODES.....	5
3.3	DESCRIPTION OF SUPPORT UNITS.....	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	7
4	EMISSION TEST	8
4.1	CONDUCTED EMISSION MEASUREMENT.....	8
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
4.1.2	TEST RESULT	8
4.2	20DB OCCUPIED BANDWIDTH MEASUREMENT.....	9
4.2.1	LIMITS OF BAND EDGES MEASUREMENT	9
4.2.2	TEST INSTRUMENTS	9
4.2.3	TEST PROCEDURES	9
4.2.4	DEVIATION FROM TEST STANDARD	9
4.2.5	TEST SETUP	9
4.2.6	TEST RESULTS	10
4.3	RADIATED EMISSION MEASUREMENT	11
4.3.1	LIMITS OF RADIATED EMISSION MEASUREMENT	11
4.3.2	TEST INSTRUMENTS	13
4.3.3	TEST PROCEDURE	14
4.3.4	DEVIATION FROM TEST STANDARD	14
4.3.5	TEST SETUP	15
4.3.6	EUT OPERATING CONDITIONS	15
4.3.7	TEST RESULTS	16
5	APPENDIX - INFORMATION ON THE TESTING LABORATORIES.....	20



1 CERTIFICATION

PRODUCT: WIRELESS REMOTE SENSOR WITH 433 MHZ
MODEL NO.: SW0001A
APPLICANT: Giant Creation Ltd
TESTED: Mar. 8 ~ Apr. 12, 2006
TEST ITEM: Engineering Sample
STANDARDS: FCC Part 15:2005,
Subpart C (Section 15.209 and 15.231),
ANSI C63.4-2003

The above equipment has been tested by **ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**TECHNICAL
ACCEPTANCE** : _____, **DATE:** APR. 13, 2006
Responsible for EMI (Steven Qian)

APPROVED BY : _____, **DATE:** APR. 13, 2006
Director of Operations (Wallace Pan, Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Paragraph	Test Type	Result	Remarks
15.207	Conducted Emission Test	N/A	
15.231(c)	20dB Occupied Bandwidth Measurement	PASS	Meet the requirement of limit
15.209 15.231(e)	Radiated Emission Test	PASS	Minimum passing AV margin is -0.29dB at 1296.000MHz

Note: This report contains data that were produced under subcontract by Laboratory ADT (Shanghai) Corporation.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Value
Conducted emissions	1.8 dB
Radiated emissions	3.2 dB



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WIRELESS REMOTE SENSOR WITH 433 MHZ
MODEL NO.	SW0001A
POWER SUPPLY	3Vdc from battery
MODULATION TYPE	ASK
CARRIER FREQUENCY OF EACH CHANNEL	433.92 MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Printed
DATA CABLE SUPPLIED	N/A
I/O PORTS	N/A

NOTE: The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

One channel is provided to this EUT:

Channel	Frequency
1	433.92 MHz

Test Mode Applicability AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APM	
-	-	√	√	--	N/A

Where PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APM: Antenna Port Measurement

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, and X.Y.Z. axis.
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Type	Axis
1	1	ASK	X

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, and X.Y.Z. axis.
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Type	Axis
1	1	ASK	X

3.3 DESCRIPTION OF SUPPORT UNITS


The EUT is a kind of device to monitor the temperature. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.231)
ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent.



4 EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15: 2005, Subpart C (Section: 15.207)

FREQUENCY (MHz)	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTES: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST RESULT

Since the EUT does not have AC port, the test item is not applicable.

4.2 20dB OCCUPIED BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF BAND EDGES MEASUREMENT

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for device operating above 70 MHz and below 900 MHz.

Fundamental Frequency (MHz)	Limit of 20 dB Bandwidth(kHz)
433.92	1084.8

4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER Agilent	E4403B	E1S1001	Jan. 13, 2007

NOTE: The calibration interval of the above test instruments is 12 months.


4.2.3 TEST PROCEDURES

1. The EUT was placed on the turning table.
2. The signal was coupled to the spectrum analyzer through an antenna.
3. Set the resolution bandwidth to 10 kHz and video bandwidth to 1MHz then select Peak function to scan the channel frequency.
4. The 20dB bandwidth was measured and recorded.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation


4.2.5 TEST SETUP



4.2.6 TEST RESULTS

Frequency (MHz)	20 dB bandwidth (kHz)	Maximum limit (kHz)	PASS/FAIL
433.92	435	1084.8	PASS

The plot of test result is attached as below.



4.3 RADIATED EMISSION MEASUREMENT

4.3.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15: 2005, Subpart C (Section: 15.205)

FCC Part 15: 2005, Subpart C (Section: 15.209)

FCC Part 15: 2005, Subpart C [Section: 15.231(e)]

According to 15.231 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental		Field Strength of Spurious	
	uV/meter	dBuV/meter	uV/meter	dBuV/meter
40.66 – 40.70	1000	60.00	100	40.00
70 – 130	500	53.98	50	36.98
130 – 174	500 to 1500	53.98 to 63.52	50 to 150	36.98 to 43.52
174 – 260	1500	63.52	150	43.52
260 – 470	1500 to 5000	63.52 to 73.98	150 to 500	43.52 to 53.98
Above 470	5000	73.98	500	53.98

NOTE: (1) Where F is the frequency in MHz, the formula for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $22.72727(F) - 2454.545$; for the band 260-470 MHz, uV/m at 3 meters = $16.6667(F) - 2833.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

(2) The above field strength limits are specified at a distance of 3meters. The tighter limits apply at the band edges. Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	$2400/F(\text{kHz})$	300
0.490-1.705	$24000/F(\text{kHz})$	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

FREQUENCY RANGE OF RADIATED MEASUREMENT**(For unintentional radiators)**

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	E1R1001	Apr. 19, 2006
BILOG Antenna SCHWARZBECK	VULB9168	E1A1001	Sep. 26, 2006
Preamplifier Agilent	8447D	E1A2001	Jan. 27, 2007
Preamplifier Agilent	8449B	E1A2002	Jan. 27, 2007
Double Ridged Broadband Horn Antenna Schwarzbeck	BBHA 9120D	E1A1002	Feb. 15, 2007
*Spectrum Analyzer Agilent	E4403B	E1S1001	Jan. 13, 2007
*Spectrum Analyzer ROHDE & SCHWARZ	FSP30	E1S1002	May. 15, 2006
RF signal cable Woken	RG-402	E1CBH01	May. 30, 2006
RF signal cable Woken	RG-402	E1CBH02	May. 30, 2006
RF signal cable Woken	RG-402	E1CBH03	May. 30, 2006
RF signal cable Woken	RG-412	E1CBL02	May. 30, 2006
RF signal cable Woken	RG-412	E1CBL03	May. 30, 2006
RF signal cable Woken	RG-412	E1CBL04	May. 30, 2006
Software ADT	ADT_Radiated_V7.5	N/A	N/A

NOTE:

1. The calibration interval of the above test instruments is 12 months.
2. “*” = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The Spectrum Analyzer (model: FSP30) and RF signal cable (SERIAL: E1CBH02&E1CBH03) are used only for the measurement of emission frequency above 2GHz if tested.

4.3.3 TEST PROCEDURE


- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

NOTE: 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

Put the EUT WIRELESS REMOTE SENSOR at the centre of the test table and power it on.

4.3.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	WIRELESS REMOTE SENSOR WITH 433 MHZ	MODEL NO.	SW0001A
CHANNEL	Channel 1	FREQUENCY RANGE	30 ~ 1000 MHz
MODULATION TYPE	ASK	INPUT POWER (SYSTEM)	3 Vdc from battery
ENVIRONMENTAL CONDITIONS	25 deg. C, 58 % RH, 1013 hPa	DETECTOR FUNCTION	Quasi-Peak / Peak/ Average
TESTED BY	BRIGHT		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Factor (dB/M)	Reading (dBuV/M)	Emission (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Ant. Height (cm)	Table Angle (Deg.)
1	143.970 QP	16.52	-7.91	8.60	43.50	-34.90	281.00	159.00
2	318.570 QP	16.99	-8.00	8.99	46.00	-37.01	364.00	229.00
3*	434.980 PK	19.74	52.26	72.00	92.90	-20.90	123.00	236.00
3*	434.980 AV	19.74	46.77	66.51	72.90	-6.39	123.00	236.00
4	553.800 QP	22.15	-8.01	14.13	46.00	-31.87	344.00	318.00
5	687.170 QP	24.37	-7.68	16.70	46.00	-29.30	255.00	19.00
6	791.450 QP	25.75	-8.09	17.67	46.00	-28.33	128.00	323.00
7	869.050 PK	26.45	23.20	49.64	72.90	-23.26	121.00	258.00
7	869.050 AV	26.45	17.70	44.15	52.90	-8.75	121.00	258.00
8	927.250 QP	27.69	-7.50	20.19	46.00	-25.81	100.00	193.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Factor (dB/M)	Reading (dBuV/M)	Emission (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Ant. Height (cm)	Table Angle (Deg.)
1	156.100 QP	17.03	-8.11	8.92	43.50	-34.58	187.00	302.00
2	267.650 QP	15.41	-7.73	7.68	46.00	-38.32	169.00	168.00
3	352.520 QP	17.54	-7.64	9.91	46.00	-36.09	167.00	140.00
4*	434.980 PK	19.74	44.46	64.19	92.90	-28.71	103.00	123.00
4*	434.980 AV	19.74	38.96	58.70	72.90	-14.20	103.00	123.00
5	536.830 QP	21.71	-8.18	13.54	46.00	-32.46	132.00	307.00
6	645.950 QP	23.84	-8.27	15.58	46.00	-30.42	192.00	243.00
7	769.620 QP	25.56	-8.27	17.28	46.00	-28.72	208.00	12.00
8	869.050 PK	26.45	14.92	41.37	72.90	-31.53	118.00	168.00
8	869.050 AV	26.45	9.43	35.88	52.90	-17.02	118.00	168.00

NOTE:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB) = Antenna Factor (dB) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*” = Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

$$20\log(\text{Duty cycle}) = 20\log \frac{49*0.425+23*1.425}{100\text{ms}} = -5.49\text{dB}$$

please see page 19 for plotted duty

FCC ID: T4HSW0001

**Above 1GHz Worst-Case Data**

EUT	WIRELESS REMOTE SENSOR WITH 433 MHZ	MODEL NO.	SW0001A
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz – 5GHz
MODULATION TYPE	ASK	INPUT POWER (SYSTEM)	3Vdc from battery
ENVIRONMENTAL CONDITIONS	25 deg. C, 58 % RH, 1013 hPa	DETECTOR FUNCTION	Peak/ Average
TESTED BY	BRIGHT		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Factor (dB/M)	Reading (dBuV/M)	Emission (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Ant. Height (cm)	Table Angle (Deg.)
1	1296.000 PK	31.29	24.51	55.81	72.90	-17.09	400.00	19.00
1	1296.000 AV	31.29	19.03	50.32	52.90	-2.58	400.00	19.00
2	1590.240 AV	31.55	6.71	38.26	54.00	-15.74	125.00	46.00
3	1656.000 PK	31.63	19.45	51.08	74.00	-22.92	190.00	59.00
4	1897.280 AV	32.54	5.47	38.01	54.00	-15.99	257.00	258.00
5	2024.000 PK	33.66	17.91	51.56	74.00	-22.44	270.00	310.00
6	2168.000 PK	35.57	21.20	56.77	72.90	-16.13	300.00	219.00
6	2168.000 AV	35.57	15.71	51.28	52.90	-1.62	300.00	219.00
7	2430.560 AV	36.25	3.25	39.50	54.00	-14.50	247.00	82.00
8	2616.000 PK	36.27	17.19	53.47	72.90	-19.43	370.00	129.00
8	2616.000 AV	36.27	11.71	47.98	52.90	-4.92	370.00	129.00
9	2721.440 AV	36.34	3.06	39.40	54.00	-14.60	283.00	49.00
10	2832.000 PK	36.92	14.99	51.90	74.00	-22.10	358.00	137.00
11	2963.840 AV	37.13	3.49	40.63	54.00	-13.37	258.00	62.00
12	3160.000 PK	37.63	14.79	52.41	74.00	-21.59	116.00	159.00
13	3335.520 AV	37.81	3.21	41.02	54.00	-12.98	105.00	228.00
14	3360.000 PK	37.93	14.35	52.28	74.00	-21.72	351.00	236.00



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Factor (dB/M)	Reading (dBuV/M)	Emission (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Ant. Height (cm)	Table Angle (Deg.)
1	1296.000 PK	31.29	26.81	58.10	72.90	-14.8	269.00	39.00
1	1296.000 AV	31.29	21.32	52.61	52.90	-0.29	269.00	39.00
2	1566.000 AV	31.61	6.80	38.41	54.00	-15.59	172.00	156.00
3	1816.000 PK	32.23	22.18	54.41	74.00	-19.59	229.00	173.00
4	1873.040 AV	32.50	5.17	37.67	54.00	-16.33	304.00	127.00
5	2168.000 PK	35.57	20.62	56.19	72.90	-16.71	182.00	227.00
5	2168.000 AV	35.57	15.13	50.70	52.90	-2.20	182.00	227.00
6	2398.240 AV	36.22	3.96	40.18	54.00	-13.82	173.00	204.00
7	2480.000 PK	36.31	16.34	52.65	74.00	-21.35	128.00	238.00
8	2689.120 AV	36.20	3.33	39.53	54.00	-14.47	238.00	79.00
9	2880.000 PK	36.99	15.73	52.72	74.00	-21.28	331.00	283.00
10	3004.240 AV	37.22	4.57	41.79	54.00	-12.21	328.00	68.00
11	3224.000 PK	37.65	15.46	53.11	74.00	-20.89	371.00	171.00
12	3230.480 AV	37.65	3.57	41.22	54.00	-12.78	106.00	159.00
13	3360.000 PK	37.93	14.11	52.04	74.00	-21.96	139.00	206.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

$$20\log(\text{Duty cycle}) = 20\log \frac{49*0.425+23*1.425}{100\text{ms}} = -5.49\text{dB}$$

please see page 19 for plotted duty





5 APPENDIX - INFORMATION ON THE TESTING LABORATORIES

We, ADT (Shanghai) Corp., were founded in 2003 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

JAPAN

USA

Norway

VCCI

FCC, A2LA

DNV



Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.cnadt.com

If you have any comments, please feel free to contact us at the following:

ADT (Shanghai) Corporation

TEL :86-21-6465-9091

Fax : 86-21-6465-9092

Email: adtsh@vip.163.com

Web Site: www.cnadt.com