



# FCC Radio Test Report

**FCC ID: T58WF2190R**

This report concerns (check one):  Original Grant  Class II Change

**Issued Date** : Nov. 13, 2013  
**Project No.** : 1307C140A  
**Equipment** : AC1200 Wireless Dual Band USB Adapter  
**Model Name** : WF2190  
**Applicant** : NETIS SYSTEMS CO., LTD  
**Address** : 4F&5F R&D Building, Oriental Cyberport,  
High-Tech Industrial Park, Nanshan,  
Shenzhen, China.

**Tested by:** Neutron Engineering Inc. EMC Laboratory

**Date of Receipt:** Sep. 25, 2013

**Date of Test:** Sep. 25, 2013~ Nov. 12, 2013

**Testing Engineer** : David Mao  
(David Mao)  
  
**Technical Manager** : Leo Hung  
(Leo Hung)  
  
**Authorized Signatory** : Steven Lu  
(Steven Lu)

**Neutron Engineering Inc.**

No.3,Jinshagang 1st Road, ShiXia,  
Dalang Town, Dong Guan, China.

TEL: 0769-8318-3000

FAX: 0769-8319-6000



## Declaration

**Neutron** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

**Neutron**'s reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

**Neutron**'s reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

**Neutron**'s laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

## Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



| Table of Contents  | Page      |
|--|-----------|
| <b>1 . CERTIFICATION</b>   | <b>6</b>  |
| <b>2 . SUMMARY OF TEST RESULTS</b>                                 | <b>7</b>  |
| <b>2.1 TEST FACILITY</b>   | <b>8</b>  |
| <b>2.2 MEASUREMENT UNCERTAINTY</b>                                 | <b>8</b>  |
| <b>3 . GENERAL INFORMATION</b>                                     | <b>9</b>  |
| <b>3.1 GENERAL DESCRIPTION OF EUT</b>                              | <b>9</b>  |
| <b>3.2 DESCRIPTION OF TEST MODES</b>                               | <b>11</b> |
| <b>3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING</b>            | <b>12</b> |
| <b>3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b> | <b>13</b> |
| <b>3.5 DESCRIPTION OF SUPPORT UNITS</b>                            | <b>14</b> |
| <b>4 . EMC EMISSION TEST</b>                                       | <b>15</b> |
| <b>4.1 CONDUCTED EMISSION MEASUREMENT</b>                          | <b>15</b> |
| <b>4.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>                  | <b>15</b> |
| <b>4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>              | <b>15</b> |
| <b>4.1.3 TEST PROCEDURE</b>  | <b>16</b> |
| <b>4.1.4 DEVIATION FROM TEST STANDARD</b>                          | <b>16</b> |
| <b>4.1.5 TEST SETUP</b>  | <b>16</b> |
| <b>4.1.6 EUT OPERATING CONDITIONS</b>                              | <b>16</b> |
| <b>4.1.7 TEST RESULTS</b>  | <b>17</b> |
| <b>4.2 RADIATED EMISSION MEASUREMENT</b>                           | <b>20</b> |
| <b>4.2.1 RADIATED EMISSION LIMITS</b>                              | <b>20</b> |
| <b>4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING</b>              | <b>21</b> |
| <b>4.2.3 TEST PROCEDURE</b>  | <b>21</b> |
| <b>4.2.4 DEVIATION FROM TEST STANDARD</b>                          | <b>21</b> |
| <b>4.2.5 TEST SETUP</b>  | <b>22</b> |
| <b>4.2.6 EUT OPERATING CONDITIONS</b>                              | <b>24</b> |
| <b>4.2.7 TEST RESULTS (BELOW 30MHZ)</b>                            | <b>25</b> |
| <b>4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)</b>                  | <b>26</b> |
| <b>4.2.9 TEST RESULTS (ABOVE 1000 MHZ)</b>                         | <b>39</b> |
| <b>5 . BANDWIDTH TEST</b>  | <b>95</b> |
| <b>5.1 APPLIED PROCEDURES / LIMIT</b>                              | <b>95</b> |
| <b>5.1.1 MEASUREMENT INSTRUMENTS LIST</b>                          | <b>95</b> |
| <b>5.1.2 TEST PROCEDURE</b>  | <b>95</b> |
| <b>5.1.3 DEVIATION FROM STANDARD</b>                               | <b>95</b> |
| <b>5.1.4 TEST SETUP</b>  | <b>95</b> |
| <b>5.1.5 EUT OPERATION CONDITIONS</b>                              | <b>95</b> |
| <b>5.1.6 TEST RESULTS</b>  | <b>96</b> |



**Table of Contents**

|  | <b>Page</b> |
|--|-------------|
| <b>6 . MAXIMUM OUTPUT POWER TEST</b>           | <b>107</b>  |
| <b>6.1 APPLIED PROCEDURES / LIMIT</b>          | <b>107</b>  |
| <b>6.1.1 MEASUREMENT INSTRUMENTS LIST</b>      | <b>107</b>  |
| <b>6.1.2 TEST PROCEDURE</b>                    | <b>107</b>  |
| <b>6.1.3 DEVIATION FROM STANDARD</b>           | <b>107</b>  |
| <b>6.1.4 TEST SETUP</b>                        | <b>107</b>  |
| <b>6.1.5 EUT OPERATION CONDITIONS</b>          | <b>107</b>  |
| <b>6.1.6 TEST RESULTS</b>                      | <b>108</b>  |
| <b>7 . ANTENNA CONDUCTED SPURIOUS EMISSION</b> | <b>114</b>  |
| <b>7.1 APPLIED PROCEDURES / LIMIT</b>          | <b>114</b>  |
| <b>7.1.1 MEASUREMENT INSTRUMENTS LIST</b>      | <b>114</b>  |
| <b>7.1.2 TEST PROCEDURE</b>                    | <b>114</b>  |
| <b>7.1.3 DEVIATION FROM STANDARD</b>           | <b>114</b>  |
| <b>7.1.4 TEST SETUP</b>                        | <b>115</b>  |
| <b>7.1.5 EUT OPERATION CONDITIONS</b>          | <b>115</b>  |
| <b>7.1.6 TEST RESULTS</b>                      | <b>116</b>  |
| <b>8 . POWER SPECTRAL DENSITY TEST</b>         | <b>161</b>  |
| <b>8.1 APPLIED PROCEDURES / LIMIT</b>          | <b>161</b>  |
| <b>8.1.1 MEASUREMENT INSTRUMENTS LIST</b>      | <b>161</b>  |
| <b>8.1.2 TEST PROCEDURE</b>                    | <b>161</b>  |
| <b>8.1.3 DEVIATION FROM STANDARD</b>           | <b>161</b>  |
| <b>8.1.4 TEST SETUP</b>                        | <b>161</b>  |
| <b>8.1.5 EUT OPERATION CONDITIONS</b>          | <b>161</b>  |
| <b>8.1.6 TEST RESULTS</b>                      | <b>162</b>  |
| <b>9 . EUT TEST PHOTO</b>                      | <b>187</b>  |



**REPORT ISSUED HISTORY**

| Issued No.           | Description     | Issued Date   |
|----------------------|-----------------|---------------|
| NEI-FCCP-3-1307C140A | Original Issue. | Nov. 13, 2013 |



## 1. CERTIFICATION

Equipment : AC1200 Wireless Dual Band USB Adapter  
Brand Name : netis  
Model Name : WF2190  
Applicant : NETIS SYSTEMS CO., LTD  
Manufacture : Shenzhen Netcore Industrial Ltd.  
Address : 4F&5F R&D Building, Oriental Cyberport, High-Tech Industrial Park, Nanshan, Shenzhen, China.  
Factory : Dongguan City Netcore Network Technology Co., Ltd.  
Address : No.10-1,Sankeng Road,Qinghutou,Tangxia Town, Dongguan City  
Date of Test : Sep. 25, 2013~ Nov. 12, 2013  
Test Item : ENGINEERING SAMPLE  
Standard(s) : FCC Part15, Subpart C(15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-3-1307C140A) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

**Test result included in this report is only for the 5745~5825MHz part of the product.**



## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| <b>Applied Standard(s): FCC Part15 (15.247) , Subpart C</b> |               |                                     |          |
|---|---------------|-------------------------------------|----------|
| Standard(s)   | Section       | Test Item                           | Judgment |
|   | 15.207        | Conducted Emission                  | PASS     |
|   | 15.247(d)     | Antenna conducted Spurious Emission | PASS     |
|   | 15.247(a)(2)  | 6dB Bandwidth                       | PASS     |
|   | 15.247(b)(3)  | Peak Output Power                   | PASS     |
|   | 15.247(e)     | Power Spectral Density              | PASS     |
|   | 15.203        | Antenna Requirement                 | PASS     |
|   | 15.209/15.205 | Transmitter Radiated Emissions      | PASS     |

NOTE:

- (1)" N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r01 (Measurement Guidelines of DTS)



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792  
Neutron's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 % .

### A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U , (dB) | NOTE |
|-----------|--------|-----------------------------|----------|------|
| DG-C02    | CISPR  | 150 KHz ~ 30MHz             | 1.94     |      |

### B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U , (dB) | NOTE |
|-----------|--------|-----------------------------|------------|----------|------|
| DG-CB03   | CISPR  | 9KHz~30MHz                  | V          | 3.79     |      |
|           |        | 9KHz~30MHz                  | H          | 3.57     |      |
|           |        | 30MHz ~ 200MHz              | V          | 3.82     |      |
|           |        | 30MHz ~ 200MHz              | H          | 3.60     |      |
|           |        | 200MHz ~ 1,000MHz           | V          | 3.86     |      |
|           |        | 200MHz ~ 1,000MHz           | H          | 3.94     |      |
|           |        | 1GHz~18GHz                  | V          | 3.12     |      |
|           |        | 1GHz~18GHz                  | H          | 3.68     |      |
|           |        | 18GHz~40GHz                 | V          | 4.15     |      |
|           |        | 18GHz~40GHz                 | H          | 4.14     |      |



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                        |   |   |
|------------------------|---|---|
| Equipment              | AC1200 Wireless Dual Band USB Adapter   |   |
| Brand Name             | netis   |   |
| Model Name             | WF2190  |   |
| Model Different        | N/A   |   |
| Product Description    | Operation Frequency   | 5745~5825 MHz   |
|                        | Modulation Technology   | 802.11a/n:OFDM  |
|                        | Bit Rate of Transmitter   | 867Mbps   |
|                        | Number of Channel   | 5 CH, Please see note 2.(Page 10)   |
|                        | Antenna Designation   | Please see note 3.(Page 10)   |
|                        | Antenna Gain(Peak)  |   |
|                        | Output Power (Max.)   | 802.11a: 21.96dBm<br>802.11n (20M): 21.41dBm<br>802.11n (40M): 20.74dBm<br>802.11ac (20M): 20.92dBm<br>802.11ac (40M): 20.91dBm<br>802.11ac (80M): 20.81dBm |
|                        | More details of EUT technical specification, please refer to the User's Manual. |   |
| Power Source           | Supplied from host system.  |   |
| Power Rating           | I/P: AC 120V/60Hz O/P: DC 5V  |   |
| Connecting I/O Port(s) | Please refer to the User's Manual.  |   |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

| 802.11a / 802.11n 20M/802.11ac 20M |                 |            |                 |            |                 |
|------------------------------------|-----------------|------------|-----------------|------------|-----------------|
| Channel                            | Frequency (MHz) | Channel    | Frequency (MHz) | Channel    | Frequency (MHz) |
| <b>149</b>                         | <b>5745</b>     | 153        | 5765            | <b>157</b> | <b>5785</b>     |
| 161                                | 5805            | <b>165</b> | <b>5825</b>     |            |                 |

| 802.11n 40M/802.11ac 40M |                 |            |                 |
|--------------------------|-----------------|------------|-----------------|
| Channel                  | Frequency (MHz) | Channel    | Frequency (MHz) |
| <b>151</b>               | <b>5755</b>     | <b>159</b> | <b>5795</b>     |

| 802.11ac 80M |                 |  |  |
|--------------|-----------------|--|--|
| Channel      | Frequency (MHz) |  |  |
| <b>155</b>   | <b>5775</b>     |  |  |

3. Antenna Specification:

| Ant. | Brand | Model Name | Antenna Type   | Connector | Gain (dBi) | Note  |
|------|-------|------------|----------------|-----------|------------|-------|
| 0    |       | N/A        | Dipole Antenna | N/A       | 5.2        | TX/RX |
| 1    |       | N/A        | Dipole Antenna | N/A       | 5.2        | TX/RX |

Note:

The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R). all transmit signals are completely uncorrelated, then, **Direction gain = G<sub>ANT</sub>**, that is Directional gain=5.2dBi

4.

| Operating Mode  | 1TX                | 2TX               |
|-----------------|--------------------|-------------------|
| 802.11a         | V (ANT 0 or ANT 1) | -                 |
| 802.11n(20MHz)  | -                  | V (ANT 0 + ANT 1) |
| 802.11n(40MHz)  | -                  | V (ANT 0 + ANT 1) |
| 802.11ac(20MHz) | -                  | V (ANT 0 + ANT 1) |
| 802.11ac(40MHz) | -                  | V (ANT 0 + ANT 1) |
| 802.11ac(80MHz) | -                  | V (ANT 0 + ANT 1) |



### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description                        |
|--------------|------------------------------------|
| Mode 1       | TX A Mode Channel 149/157/165      |
| Mode 2       | TX N20 Mode Channel 149/157/165    |
| Mode 3       | TX N40 Mode Channel 151/159        |
| Mode 4       | TX AC N20 Mode Channel 149/157/165 |
| Mode 5       | TX AC N40 Mode Channel 151/159     |
| Mode 6       | TX AC N80 Mode Channel 155         |
| Mode 7       | TX Mode                            |

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

| For Conducted Test |             |
|--------------------|-------------|
| Final Test Mode    | Description |
| Mode 7             | TX Mode     |

| For Radiated Test |                                    |
|-------------------|------------------------------------|
| Final Test Mode   | Description                        |
| Mode 1            | TX A Mode Channel 149/157/165      |
| Mode 2            | TX N20 Mode Channel 149/157/165    |
| Mode 3            | TX N40 Mode Channel 151/159        |
| Mode 4            | TX AC N20 Mode Channel 149/157/165 |
| Mode 5            | TX AC N40 Mode Channel 151/159     |
| Mode 6            | TX AC N80 Mode Channel 155         |

Note: For radiated below 1G test, the 802.11a and 802.11ac N20 mode is found to be the worst case and recorded.



### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product

| Test software version | MPTool   |          |         |
|-----------------------|----------|----------|---------|
| Frequency             | 5745 MHz | 5785 MHz | 5825MHz |
| TX A Mode             | 50       | 51       | 52      |
| TX N20 Mode           | 45       | 45       | 45      |
| TX AC N20 Mode        | 46       | 46       | 46      |


| Test software version | MPTool   |         |
|-----------------------|----------|---------|
| Frequency             | 5745 MHz | 5825MHz |
| TX N40 Mode           | 44       | 44      |
| TX AC N40 Mode        | 44       | 44      |

| Test software version | MPTool   |  |
|-----------------------|----------|--|
| Frequency             | 5775 MHz |  |
| TX AC N80 Mode        | 48       |  |




### 3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Conducted TX Mode:



#### Radiated TX Mode:



**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment                             | Mfr/Brand | Model/Type No. | FCC ID      | Series No.               | Note |
|------|---------------------------------------|-----------|----------------|-------------|--------------------------|------|
| E-1  | AC1200 Wireless Dual Band USB Adapter | netis     | WF2190         | T58WF2190 R | N/A                      | EUT  |
| E-2  | Modem                                 | ACEEX     | DM-1414V       | IFAXDM14 14 | 0603002131               |      |
| E-3  | LCD monitor                           | DELL      | E177FPc        | DOC         | CNOFJ179-64180-6 AG-1WNS |      |
| E-4  | Printer                               | SII       | DPU-414        | DOC         | 3018507 B                |      |
| E-5  | USB Keyboard                          | DELL      | SK-8115        | DOC         | MY-0DJ325-71619-77N-1526 |      |
| E-6  | USB Mouse                             | DELL      | MO56UC         | DOC         | G0R000XN                 |      |
| E-7  | PC                                    | DELL      | 745            | DOC         | G7K832X                  |      |
| E-8  | Router                                | Net.Core  | NW705S         | DOC         | NA                       |      |
| E-9  | Notebook                              | HP        | HSTNN-169C-3   | DOC         | CNU02203XG               |      |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| C-1  | YES           | NO           | 1.5m   |      |
| C-2  | YES           | YES          | 1.5m   |      |
| C-3  | YES           | NO           | 1.5m   |      |
| C-4  | YES           | YES          | 1.8m   |      |
| C-5  | YES           | NO           | 1.8m   |      |

Note:

(1) For detachable type I/O cable should be specified the length in m in 『Length』 column.



## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) |         | Class B (dBuV) |           | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
|                 | Quasi-peak     | Average | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 79.0           | 66.0    | 66 - 56 *      | 56 - 46 * | CISPR    |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | CISPR    |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | CISPR    |

|           |       |       |           |           |     |
|-----------|-------|-------|-----------|-----------|-----|
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00     | 46.00     | FCC |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00     | 50.00     | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

#### 4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | LISN              | EMCO         | 3816/2   | 00052765   | Apr. 25, 2014    |
| 2    | LISN              | R&S          | ENV216   | 100087     | Nov.16, 2013     |
| 3    | Test Cable        | N/A          | C_17     | N/A        | Mar.15, 2014     |
| 4    | EMI TEST RECEIVER | R&S          | ESCS30   | 826547/022 | Apr. 25, 2014    |
| 5    | 50Ω Terminator    | SHX          | TF2-3G-A | 08122902   | Apr. 25, 2014    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |


#### 4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

#### 4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT was programmed to be in continuously transmitting/TX mode.




#### **4.1.7 TEST RESULTS**

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “\*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.




|              |                                       |                    |        |
|--------------|---------------------------------------|--------------------|--------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190 |
| Temperature: | 25 °C                                 | Relative Humidity: | 50 %   |
| Test Power:  | AC 120V/60Hz                          | Phase:             | Line   |
| Test Mode:   |                                       | TX Mode            |        |



| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
|     |     |         | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 0.1922  | 35.11   | 9.76    | 44.87    | 63.94 | -19.07 |          | peak    |
| 2   |     | 0.2550  | 29.28   | 9.74    | 39.02    | 61.59 | -22.57 |          | peak    |
| 3   |     | 0.8316  | 23.90   | 9.71    | 33.61    | 56.00 | -22.39 |          | peak    |
| 4   |     | 1.7854  | 26.75   | 9.69    | 36.44    | 56.00 | -19.56 |          | peak    |
| 5   | *   | 3.9560  | 33.02   | 9.76    | 42.78    | 56.00 | -13.22 |          | peak    |
| 6   |     | 10.6651 | 28.37   | 9.82    | 38.19    | 60.00 | -21.81 |          | peak    |



|              |                                       |                    |         |
|--------------|---------------------------------------|--------------------|---------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190  |
| Temperature: | 25 °C                                 | Relative Humidity: | 50 %    |
| Test Power:  | AC 120V/60Hz                          | Phase:             | Neutral |
| Test Mode:   | TX Mode                               |                    |         |



| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
|     |     |         | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 0.1922  | 34.76   | 9.75    | 44.51    | 63.94 | -19.43 |          | peak    |
| 2   |     | 0.2550  | 28.64   | 9.73    | 38.37    | 61.59 | -23.22 |          | peak    |
| 3   |     | 0.6982  | 22.99   | 9.69    | 32.68    | 56.00 | -23.32 |          | peak    |
| 4   |     | 1.2715  | 26.66   | 9.69    | 36.35    | 56.00 | -19.65 |          | peak    |
| 5   | *   | 3.1827  | 31.93   | 9.71    | 41.64    | 56.00 | -14.36 |          | peak    |
| 6   |     | 15.9596 | 28.55   | 9.85    | 38.40    | 60.00 | -21.60 |          | peak    |



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz-1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(KHz)                       | 300                           |
| 0.490~1.705     | 24000/F(KHz)                      | 30                            |
| 1.705~30.0      | 30                                | 30                            |
| 30~88           | 100                               | 3                             |
| 88~216          | 150                               | 3                             |
| 216~960         | 200                               | 3                             |
| 960~1000        | 500                               | 3                             |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | (dBuV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                       | Setting  |
|--|--|
| Attenuation                              | Auto   |
| Start Frequency                          | 1000 MHz                                       |
| Stop Frequency                           | 10th carrier harmonic                          |
| RB / VB<br>(Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                           |
|------------------------|-----------------------------------|
| Attenuation            | Auto                              |
| Start ~ Stop Frequency | 9kHz~90kHz for PK/AVG detector    |
| Start ~ Stop Frequency | 90kHz~110kHz for QP detector      |
| Start ~ Stop Frequency | 110kHz~490kHz for PK/AVG detector |
| Start ~ Stop Frequency | 490kHz~30MHz for QP detector      |
| Start ~ Stop Frequency | 30MHz~1000MHz for QP detector     |

**4.2.2 MEASUREMENT INSTRUMENTS LIST AND SETTING**

| Item | Kind of Equipment       | Manufacturer | Type No.  | Serial No. | Calibrated until |
|------|-------------------------|--------------|-----------|------------|------------------|
| 1    | Antenna                 | Schwarbeck   | VULB9160  | 9160-3232  | Apr. 25, 2014    |
| 2    | Amplifier               | HP           | 8447D     | 2944A09673 | Apr. 25, 2014    |
| 3    | Test Receiver           | R&S          | ESCI      | 100382     | Apr. 25, 2014    |
| 4    | Test Cable              | N/A          | C-01_CB03 | N/A        | Jul. 02, 2014    |
| 5    | Antenna                 | ETS          | 3115      | 00075789   | Apr. 25, 2014    |
| 6    | Amplifier               | Agilent      | 8449B     | 3008A02274 | Apr. 25, 2014    |
| 7    | Spectrum                | Agilent      | E4408B    | US39240143 | Nov. 16, 2013    |
| 8    | Test Cable              | HUBER+SUHNER | C-45      | N/A        | Apr. 30, 2014    |
| 9    | Controller              | CT           | SC100     | N/A        | N/A              |
| 10   | Horn Antenna            | EMCO         | 3115      | 9605-4803  | Apr. 25, 2014    |
| 11   | Active Loop Antenna     | R&S          | HFH2-Z2   | 830749/020 | Apr. 25, 2014    |
| 12   | Broad-Band Horn Antenna | Schwarzbeck  | BBHA 9170 | 9170319    | Oct. 22, 2014    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

**4.2.3 TEST PROCEDURE**


- a. The measuring distance of at 1.5 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**4.2.4 DEVIATION FROM TEST STANDARD**


No deviation

#### 4.2.5 TEST SETUP

##### (A) Radiated Emission Test Set-Up Frequency Below 1 GHz



##### (B) Radiated Emission Test Set-Up Frequency Above 1 GHz





**Neutron Engineering Inc.**



**Neutron Engineering Inc.**



**4.2.7**  
**TEST**  
**RESULT**  
**S**  
**(BELOW**  
**30MHZ)•**  
 • •

|               |                                       |                    |        |
|---------------|---------------------------------------|--------------------|--------|
| EUT:          | AC1200 Wireless Dual Band USB Adapter | Model Name:        | WF2190 |
| Temperature:  | 24 °C                                 | Relative Humidity: | 55 %   |
| Test Voltage: | AC 120V/60Hz                          |                    |        |
| Test Mode:    | TX B MODE CHANNEL 01                  |                    |        |

| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0096         | 0°             | 25.16                 | 24.30                   | 49.46                    | 127.96                 | -78.00         | AVG  |
| 0.0096         | 0°             | 27.35                 | 24.30                   | 51.65                    | 147.96                 | -94.13         | PK   |
| 0.0352         | 0°             | 21.46                 | 23.34                   | 44.80                    | 116.67                 | -72.64         | AVG  |
| 0.0352         | 0°             | 23.05                 | 23.34                   | 46.39                    | 136.67                 | -90.12         | PK   |
| 0.0391         | 0°             | 22.85                 | 23.09                   | 45.94                    | 115.76                 | -71.89         | AVG  |
| 0.0391         | 0°             | 24.56                 | 23.09                   | 47.65                    | 135.76                 | -89.16         | PK   |
| 0.0475         | 0°             | 20.13                 | 22.56                   | 42.69                    | 114.07                 | -69.40         | AVG  |
| 0.0475         | 0°             | 22.85                 | 22.56                   | 45.41                    | 134.07                 | -84.95         | PK   |
| 0.4265         | 0°             | 19.65                 | 19.98                   | 39.63                    | 95.01                  | -58.43         | AVG  |
| 0.4265         | 0°             | 22.03                 | 19.98                   | 42.01                    | 115.01                 | -75.09         | PK   |
| 1.9560         | 0°             | 28.46                 | 19.50                   | 47.96                    | 69.54                  | -16.93         | QP   |

| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0097         | 90°            | 20.54                 | 24.30                   | 44.84                    | 127.87                 | -84.81         | AVG  |
| 0.0097         | 90°            | 23.56                 | 24.30                   | 47.86                    | 147.87                 | -102.03        | PK   |
| 0.0251         | 90°            | 19.58                 | 23.98                   | 43.56                    | 119.61                 | -82.07         | AVG  |
| 0.0251         | 90°            | 22.14                 | 23.98                   | 46.12                    | 139.61                 | -99.76         | PK   |
| 0.0463         | 90°            | 19.53                 | 22.63                   | 42.16                    | 114.29                 | -71.94         | AVG  |
| 0.0463         | 90°            | 22.05                 | 22.63                   | 44.68                    | 134.29                 | -89.27         | PK   |
| 0.0589         | 90°            | 21.74                 | 22.22                   | 43.96                    | 112.20                 | -67.37         | AVG  |
| 0.0589         | 90°            | 23.12                 | 22.22                   | 45.34                    | 132.20                 | -84.45         | PK   |
| 0.2875         | 90°            | 23.51                 | 20.31                   | 43.82                    | 98.43                  | -55.72         | AVG  |
| 0.2875         | 90°            | 25.69                 | 20.31                   | 46.00                    | 118.43                 | -72.26         | PK   |
| 1.6540         | 90°            | 24.75                 | 19.53                   | 44.28                    | 63.23                  | -18.69         | QP   |

Remark :

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);.
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.




#### **4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)**

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz .
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (3) Measuring frequency range from 30MHz to 1000MHz .
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table .



|                               |                                       |                    |          |
|-------------------------------|---------------------------------------|--------------------|----------|
| EUT:                          | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:                  | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage :                | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode : TX A Mode 5745MHz |                                       |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over     |         |
|-----|-----|----------|---------|---------|----------|-------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |          |         |
|     |     | MHz      | dBuV    | dB      | dBuV/m   | dB    | Detector | Comment |
| 1   | *   | 78.5000  | 49.18   | -17.29  | 31.89    | 40.00 | -8.11    | peak    |
| 2   |     | 122.1500 | 43.79   | -13.77  | 30.02    | 43.50 | -13.48   | peak    |
| 3   |     | 174.5300 | 39.75   | -12.78  | 26.97    | 43.50 | -16.53   | peak    |
| 4   |     | 431.5800 | 40.66   | -9.27   | 31.39    | 46.00 | -14.61   | peak    |
| 5   |     | 640.1300 | 35.65   | -6.06   | 29.59    | 46.00 | -16.41   | peak    |
| 6   |     | 749.7400 | 39.32   | -4.91   | 34.41    | 46.00 | -11.59   | peak    |



|                               |                                       |                    |            |
|-------------------------------|---------------------------------------|--------------------|------------|
| EUT:                          | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:                  | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage :                | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode : TX A Mode 5745MHz |                                       |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over     |         |
|-----|-----|----------|---------|---------|----------|-------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |          |         |
|     |     | MHz      | dBuV    | dB      | dBuV/m   | dB    | Detector | Comment |
| 1   |     | 172.5900 | 43.10   | -12.75  | 30.35    | 43.50 | -13.15   | peak    |
| 2   | *   | 205.5700 | 46.19   | -15.23  | 30.96    | 43.50 | -12.54   | peak    |
| 3   |     | 297.7200 | 40.63   | -11.37  | 29.26    | 46.00 | -16.74   | peak    |
| 4   |     | 429.6400 | 38.29   | -9.31   | 28.98    | 46.00 | -17.02   | peak    |
| 5   |     | 640.1300 | 35.95   | -6.06   | 29.89    | 46.00 | -16.11   | peak    |
| 6   |     | 749.7400 | 36.84   | -4.91   | 31.93    | 46.00 | -14.07   | peak    |




|                               |                                       |                    |          |
|-------------------------------|---------------------------------------|--------------------|----------|
| EUT:                          | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:                  | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage :                | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode : TX A Mode 5785MHz |                                       |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   | *   | 120.2100 | 47.00   | -13.88  | 33.12    | 43.50 | -10.38 | peak     |         |
| 2   |     | 181.3200 | 44.34   | -13.04  | 31.30    | 43.50 | -12.20 | peak     |         |
| 3   |     | 299.6600 | 40.67   | -11.27  | 29.40    | 46.00 | -16.60 | peak     |         |
| 4   |     | 361.7400 | 39.86   | -11.09  | 28.77    | 46.00 | -17.23 | peak     |         |
| 5   |     | 432.5500 | 41.19   | -9.24   | 31.95    | 46.00 | -14.05 | peak     |         |
| 6   |     | 749.7400 | 40.40   | -4.91   | 35.49    | 46.00 | -10.51 | peak     |         |



|                               |                                       |                    |            |
|-------------------------------|---------------------------------------|--------------------|------------|
| EUT:                          | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:                  | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage :                | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode : TX A Mode 5785MHz |                                       |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 100.8100 | 47.88   | -16.10  | 31.78    | 43.50 | -11.72 | peak     |         |
| 2   |     | 181.3200 | 45.50   | -13.04  | 32.46    | 43.50 | -11.04 | peak     |         |
| 3   | *   | 205.5700 | 47.80   | -15.23  | 32.57    | 43.50 | -10.93 | peak     |         |
| 4   |     | 301.6000 | 42.95   | -11.26  | 31.69    | 46.00 | -14.31 | peak     |         |
| 5   |     | 640.1300 | 36.63   | -6.06   | 30.57    | 46.00 | -15.43 | peak     |         |
| 6   |     | 763.3200 | 37.13   | -4.42   | 32.71    | 46.00 | -13.29 | peak     |         |




|                               |                                       |                    |          |
|-------------------------------|---------------------------------------|--------------------|----------|
| EUT:                          | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:                  | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage :                | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode : TX A Mode 5825MHz |                                       |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit  | Over   |          |         |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |        |        |          |         |
|     |     | MHz      | dBuV    | dB      | dBuV/m   | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 72.6800  | 50.95   | -16.55  | 34.40    | 40.00  | -5.60  | peak     |         |
| 2   |     | 100.8100 | 51.05   | -16.10  | 34.95    | 43.50  | -8.55  | peak     |         |
| 3   |     | 121.1800 | 47.91   | -13.83  | 34.08    | 43.50  | -9.42  | peak     |         |
| 4   |     | 430.6100 | 38.51   | -9.29   | 29.22    | 46.00  | -16.78 | peak     |         |
| 5   |     | 640.1300 | 34.71   | -6.06   | 28.65    | 46.00  | -17.35 | peak     |         |
| 6   |     | 749.7400 | 37.72   | -4.91   | 32.81    | 46.00  | -13.19 | peak     |         |




|                |                                       |                    |            |
|----------------|---------------------------------------|--------------------|------------|
| EUT:           | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:   | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage : | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode :    | TX A Mode 5825MHz                     |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit  | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |        |        |          |         |
|     |     | MHz      | dBuV    | dB      | dBuV/m   | dBuV/m | dB     |          |         |
| 1   |     | 100.8100 | 48.40   | -16.10  | 32.30    | 43.50  | -11.20 | peak     |         |
| 2   | *   | 204.6000 | 48.64   | -15.23  | 33.41    | 43.50  | -10.09 | peak     |         |
| 3   |     | 281.2300 | 45.54   | -12.45  | 33.09    | 46.00  | -12.91 | peak     |         |
| 4   |     | 300.6300 | 44.34   | -11.25  | 33.09    | 46.00  | -12.91 | peak     |         |
| 5   |     | 424.7900 | 39.43   | -9.39   | 30.04    | 46.00  | -15.96 | peak     |         |
| 6   |     | 640.1300 | 35.78   | -6.06   | 29.72    | 46.00  | -16.28 | peak     |         |




|                |                                       |                    |          |
|----------------|---------------------------------------|--------------------|----------|
| EUT:           | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:   | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage : | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode :    | TX AC N20 Mode 5745MHz                |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 42.6100  | 46.61   | -14.39  | 32.22    | 40.00 | -7.78  | peak     |         |
| 2   | *   | 78.5000  | 51.94   | -17.29  | 34.65    | 40.00 | -5.35  | peak     |         |
| 3   |     | 122.1500 | 46.05   | -13.77  | 32.28    | 43.50 | -11.22 | peak     |         |
| 4   |     | 174.5300 | 41.01   | -12.78  | 28.23    | 43.50 | -15.27 | peak     |         |
| 5   |     | 422.8500 | 42.56   | -9.44   | 33.12    | 46.00 | -12.88 | peak     |         |
| 6   |     | 749.7400 | 40.08   | -4.91   | 35.17    | 46.00 | -10.83 | peak     |         |




|                |                                       |                    |            |
|----------------|---------------------------------------|--------------------|------------|
| EUT:           | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:   | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage : | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode :    | TX AC N20 Mode 5745MHz                |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit  | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |        |        |          |         |
|     |     | MHz      | dBuV    | dB      | dBuV/m   | dBuV/m | dB     |          |         |
| 1   |     | 114.3900 | 45.03   | -14.37  | 30.66    | 43.50  | -12.84 | peak     |         |
| 2   | *   | 172.5900 | 45.18   | -12.75  | 32.43    | 43.50  | -11.07 | peak     |         |
| 3   |     | 205.5700 | 46.77   | -15.23  | 31.54    | 43.50  | -11.96 | peak     |         |
| 4   |     | 297.7200 | 40.21   | -11.37  | 28.84    | 46.00  | -17.16 | peak     |         |
| 5   |     | 640.1300 | 35.54   | -6.06   | 29.48    | 46.00  | -16.52 | peak     |         |
| 6   |     | 749.7400 | 36.42   | -4.91   | 31.51    | 46.00  | -14.49 | peak     |         |




|                                    |                                       |                    |          |
|------------------------------------|---------------------------------------|--------------------|----------|
| EUT:                               | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:                       | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage :                     | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode : TX AC N20 Mode 5785MHz |                                       |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   | *   | 78.5000  | 50.54   | -17.29  | 33.25    | 40.00 | -6.75  | peak     |         |
| 2   |     | 122.1500 | 45.65   | -13.77  | 31.88    | 43.50 | -11.62 | peak     |         |
| 3   |     | 174.5300 | 40.61   | -12.78  | 27.83    | 43.50 | -15.67 | peak     |         |
| 4   |     | 431.5800 | 40.02   | -9.27   | 30.75    | 46.00 | -15.25 | peak     |         |
| 5   |     | 640.1300 | 35.01   | -6.06   | 28.95    | 46.00 | -17.05 | peak     |         |
| 6   |     | 749.7400 | 39.18   | -4.91   | 34.27    | 46.00 | -11.73 | peak     |         |




|                |                                       |                    |            |
|----------------|---------------------------------------|--------------------|------------|
| EUT:           | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:   | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage : | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode :    | TX AC N20 Mode 5785MHz                |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 172.5900 | 44.74   | -12.75  | 31.99    | 43.50 | -11.51 | peak     |         |
| 2   | *   | 205.5700 | 47.83   | -15.23  | 32.60    | 43.50 | -10.90 | peak     |         |
| 3   |     | 232.7300 | 44.72   | -14.57  | 30.15    | 46.00 | -15.85 | peak     |         |
| 4   |     | 429.6400 | 37.43   | -9.31   | 28.12    | 46.00 | -17.88 | peak     |         |
| 5   |     | 640.1300 | 35.60   | -6.06   | 29.54    | 46.00 | -16.46 | peak     |         |
| 6   |     | 749.7400 | 35.48   | -4.91   | 30.57    | 46.00 | -15.43 | peak     |         |




|                                    |                                       |                    |          |
|------------------------------------|---------------------------------------|--------------------|----------|
| EUT:                               | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190   |
| Temperature:                       | 25°C                                  | Relative Humidity: | 58 %     |
| Test Voltage :                     | AC 120V/60Hz                          | Phase:             | Vertical |
| Test Mode : TX AC N20 Mode 5825MHz |                                       |                    |          |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 42.6100  | 44.48   | -14.39  | 30.09    | 40.00 | -9.91  | peak     |         |
| 2   | *   | 78.5000  | 48.81   | -17.29  | 31.52    | 40.00 | -8.48  | peak     |         |
| 3   |     | 122.1500 | 44.42   | -13.77  | 30.65    | 43.50 | -12.85 | peak     |         |
| 4   |     | 296.7500 | 36.31   | -11.43  | 24.88    | 46.00 | -21.12 | peak     |         |
| 5   |     | 431.5800 | 39.29   | -9.27   | 30.02    | 46.00 | -15.98 | peak     |         |
| 6   |     | 749.7400 | 39.45   | -4.91   | 34.54    | 46.00 | -11.46 | peak     |         |



|                |                                       |                    |            |
|----------------|---------------------------------------|--------------------|------------|
| EUT:           | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190     |
| Temperature:   | 25°C                                  | Relative Humidity: | 58 %       |
| Test Voltage : | AC 120V/60Hz                          | Phase:             | Horizontal |
| Test Mode :    | TX AC N20 Mode 5825MHz                |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Detector | Comment |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|---------|
|     |     |          | Level   | Factor  | ment     |       |        |          |         |
| 1   |     | 114.3900 | 44.07   | -14.37  | 29.70    | 43.50 | -13.80 | peak     |         |
| 2   |     | 172.5900 | 44.22   | -12.75  | 31.47    | 43.50 | -12.03 | peak     |         |
| 3   | *   | 205.5700 | 47.31   | -15.23  | 32.08    | 43.50 | -11.42 | peak     |         |
| 4   |     | 297.7200 | 41.75   | -11.37  | 30.38    | 46.00 | -15.62 | peak     |         |
| 5   |     | 640.1300 | 37.58   | -6.06   | 31.52    | 46.00 | -14.48 | peak     |         |
| 6   |     | 749.7400 | 36.96   | -4.91   | 32.05    | 46.00 | -13.95 | peak     |         |

**4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  |                                       | TX A Mode 5745MHz  |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| #5725.00       | V               | 23.54          | 8.57         | 44.34             | 67.88            | 52.91          | 84.30            | 76.90          | X/E        |
| <b>5738.60</b> | <b>V</b>        | <b>59.90</b>   | <b>52.50</b> | <b>44.40</b>      | <b>104.30</b>    | <b>96.90</b>   |                  |                | <b>X/F</b> |
| 11489.52       | V               | 41.55          | 27.89        | 18.47             | 60.02            | 46.36          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode 5745MHz                     |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | H               | 29.86          | 15.05        | 44.34             | 74.20            | 59.39          | 89.05            | 81.00          | X/E        |
| <b>5752.00</b> | <b>H</b>        | <b>64.61</b>   | <b>56.56</b> | <b>44.44</b>      | <b>109.05</b>    | <b>101.00</b>  |                  |                | <b>X/F</b> |
| 11491.02       | H               | 41.58          | 28.74        | 18.47             | 60.05            | 47.21          | 74.00            | 54.00          | X/H        |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode 5785MHz                     |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5780.50        | V               | 59.91          | 52.61        | 44.54             | 104.45           | 97.15          |                  |                | X/F  |
| 11570.89       | V               | 41.36          | 27.85        | 18.67             | 60.03            | 46.52          | 74.00            | 54.00          | X/H  |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode 5785MHz                     |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5778.40        | H               | 63.45          | 56.25        | 44.54             | 107.99           | 100.79         |                  |                | X/F  |
| 11570.54       | H               | 42.03          | 28.95        | 18.67             | 60.70            | 47.62          | 74.00            | 54.00          | X/H  |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode 5825MHz                     |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5818.60        | V               | 60.53          | 53.16        | 44.67             | 105.20           | 97.83          |                  |                | X/F  |
| #5850.00       | V               | 18.25          | 5.09         | 44.78             | 63.03            | 49.87          | 85.20            | 77.83          | X/E  |
| 11650.74       | V               | 41.67          | 27.58        | 18.87             | 60.54            | 46.45          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode 5825MHz                     |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5817.80        | H               | 63.84          | 56.25        | 44.66             | 108.50           | 100.91         |                  |                | X/F  |
| #5850.00       | H               | 20.53          | 8.50         | 44.78             | 65.31            | 53.28          | 88.50            | 80.91          | X/E  |
| 11649.79       | H               | 42.15          | 28.26        | 18.86             | 61.01            | 47.12          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5745MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | V               | 10.25          | 0.49         | 44.34             | 54.59            | 44.83          | 81.49            | 72.78          | X/E        |
| <b>5739.40</b> | <b>V</b>        | <b>57.09</b>   | <b>48.38</b> | <b>44.40</b>      | <b>101.49</b>    | <b>92.78</b>   |                  |                | <b>X/F</b> |
| 11490.51       | V               | 41.22          | 28.79        | 18.47             | 59.69            | 47.26          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5745MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol. | Reading        |              | Ant./CF      | Act.             |                | Limit            |                | Note       |
|----------------|----------|----------------|--------------|--------------|------------------|----------------|------------------|----------------|------------|
|                |          | Peak<br>(dBuV) | AV<br>(dBuV) |              | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | H        | 13.02          | 2.42         | 44.34        | 57.36            | 46.76          | 86.47            | 77.90          | X/E        |
| <b>5751.00</b> | <b>H</b> | <b>62.03</b>   | <b>53.46</b> | <b>44.44</b> | <b>106.47</b>    | <b>97.90</b>   |                  |                | <b>X/F</b> |
| 11490.82       | H        | 42.50          | 29.14        | 18.47        | 60.97            | 47.61          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5785MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5780.60        | V               | 55.62          | 47.22        | 44.54             | 100.16           | 91.76          |                  |                | X/F  |
| 11570.55       | V               | 41.69          | 28.35        | 18.67             | 60.36            | 47.02          | 74.00            | 54.00          | X/H  |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5785MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5779.50        | H               | <b>62.27</b>   | <b>52.65</b> | <b>44.54</b>      | <b>106.81</b>    | <b>97.19</b>   |                  |                | X/F  |
| 11570.25       | H               | 41.57          | 28.76        | 18.67             | 60.24            | 47.43          | 74.00            | 54.00          | X/H  |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5825MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5830.80        | V               | 57.32          | 48.44        | 44.71             | 102.03           | 93.15          |                  |                | X/F  |
| #5850.00       | V               | 9.32           | -0.32        | 44.78             | 54.10            | 44.46          | 82.03            | 73.15          | X/E  |
| 11650.55       | V               | 41.75          | 28.64        | 18.87             | 60.62            | 47.51          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode 5825MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5819.40        | H               | 61.88          | 52.33        | 44.67             | 106.55           | 97.00          |                  |                | X/F  |
| #5850.00       | H               | 11.23          | 0.65         | 44.78             | 56.01            | 45.43          | 86.55            | 77.00          | X/E  |
| 11650.32       | H               | 41.77          | 28.64        | 18.87             | 60.64            | 47.51          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode 5755MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | V               | 10.21          | 2.11         | 44.34             | 54.55            | 46.45          | 82.09            | 71.80          | X/E        |
| <b>5756.20</b> | <b>V</b>        | <b>57.63</b>   | <b>47.34</b> | <b>44.46</b>      | <b>102.09</b>    | <b>91.80</b>   |                  |                | <b>X/F</b> |
| 11510.46       | V               | 41.85          | 28.49        | 18.51             | 60.36            | 47.00          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH151 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode 5755MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | H               | 15.30          | 6.26         | 44.34             | 59.64            | 50.60          | 85.07            | 79.11          | X/E        |
| <b>5752.80</b> | <b>H</b>        | <b>60.62</b>   | <b>54.66</b> | <b>44.45</b>      | <b>105.07</b>    | <b>99.11</b>   |                  |                | <b>X/F</b> |
| 11510.54       | H               | 42.05          | 28.71        | 18.51             | 60.56            | 47.22          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH151 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode 5795MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5796.20        | V               | 53.95          | 44.79        | 44.59             | 98.54            | 89.38          |                  |                | X/F  |
| #5850.00       | V               | 8.32           | -0.57        | 44.78             | 44.78            | 44.21          | 78.54            | 69.38          | X/E  |
| 11590.54       | V               | 41.79          | 28.53        | 18.72             | 60.51            | 47.25          | 74.00            | 54.00          | X/H  |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH159 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode 5795MHz                   |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5784.20        | H               | 59.90          | 51.64        | 44.55             | 104.45           | 96.19          |                  |                | X/F  |
| #5850.00       | H               | 9.35           | 0.46         | 44.78             | 54.13            | 45.24          | 84.45            | 76.19          | X/E  |
| 11590.65       | H               | 42.17          | 28.95        | 18.72             | 60.89            | 47.67          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH159 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5745MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | V               | 12.78          | 0.97         | 44.34             | 57.12            | 45.31          | 83.01            | 74.13          | X/E        |
| <b>5751.20</b> | <b>V</b>        | <b>58.57</b>   | <b>49.69</b> | <b>44.44</b>      | <b>103.01</b>    | <b>94.13</b>   |                  |                | <b>X/F</b> |
| 11489.56       | V               | 41.65          | 28.74        | 18.47             | 60.12            | 47.21          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5745MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol. | Reading        |              | Ant./CF      | Act.             |                | Limit            |                | Note       |
|----------------|----------|----------------|--------------|--------------|------------------|----------------|------------------|----------------|------------|
|                |          | Peak<br>(dBuV) | AV<br>(dBuV) |              | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | H        | 15.08          | 2.73         | 44.34        | 59.42            | 47.07          | 87.08            | 78.93          | X/E        |
| <b>5750.60</b> | <b>H</b> | <b>62.64</b>   | <b>54.49</b> | <b>44.44</b> | <b>107.08</b>    | <b>98.93</b>   |                  |                | <b>X/F</b> |
| 11490.41       | H        | 42.11          | 29.03        | 18.47        | 60.58            | 47.50          | 74.00            | 54.00          | X/H        |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH149 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5785MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5790.50        | V               | <b>55.74</b>   | <b>48.01</b> | <b>44.57</b>      | <b>100.31</b>    | <b>92.58</b>   |                  |                | X/F  |
| 11570.55       | V               | 41.57          | 28.45        | 18.67             | 60.24            | 47.12          | 74.00            | 54.00          | X/H  |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5785MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5778.10        | H               | 61.18          | 53.03        | 44.53             | 105.71           | 97.56          |                  |                | X/F  |
| 11570.57       | H               | 42.13          | 28.07        | 18.67             | 60.80            | 46.74          | 74.00            | 54.00          | X/H  |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



**TX CH157 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5825MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5831.30        | V               | 59.19          | 51.04        | 44.71             | 103.90           | 95.75          |                  |                | X/F  |
| #5850.00       | V               | 9.32           | -0.01        | 44.78             | 54.10            | 44.77          | 83.90            | 75.75          | X/E  |
| 11650.64       | V               | 41.53          | 28.16        | 18.87             | 60.40            | 47.03          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode 5825MHz                |                    |              |


| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5819.00        | H               | 61.57          | 53.99        | 44.67             | 106.24           | 98.66          |                  |                | X/F  |
| #5850.00       | H               | 10.21          | 0.69         | 44.78             | 54.99            | 45.47          | 86.24            | 78.66          | X/E  |
| 11650.55       | H               | 42.11          | 28.74        | 18.87             | 60.98            | 47.61          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH165 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N40 Mode 5755MHz                |                    |              |


| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | V               | 10.92          | 1.99         | 44.34             | 55.26            | 46.33          | 78.04            | 70.80          | X/E        |
| <b>5757.60</b> | <b>V</b>        | <b>53.58</b>   | <b>46.34</b> | <b>44.46</b>      | <b>98.04</b>     | <b>90.80</b>   |                  |                | <b>X/F</b> |
| 11511.28       | V               | 41.78          | 28.15        | 18.51             | 60.29            | 46.66          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH151 (Above 1000 MHz, Vertical)**






|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N40 Mode 5755MHz                |                    |              |

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| # 5725.00      | H               | 14.51          | 3.13         | 44.34             | 58.85            | 47.47          | 83.69            | 74.06          | X/E        |
| <b>5741.60</b> | <b>H</b>        | <b>59.29</b>   | <b>49.66</b> | <b>44.40</b>      | <b>103.69</b>    | <b>94.06</b>   |                  |                | <b>X/F</b> |
| 11510.22       | H               | 42.35          | 29.01        | 18.51             | 60.86            | 47.52          | 74.00            | 54.00          | X/H        |

## Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N40 Mode 5795MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| 5782.20        | V               | 56.00          | 46.82        | 44.55             | 100.55           | 91.37          |                  |                | X/F  |
| #5850.00       | V               | 8.36           | -0.27        | 44.78             | 53.14            | 44.51          | 80.55            | 71.37          | X/E  |
| 11591.05       | V               | 42.03          | 28.19        | 18.72             | 60.75            | 46.91          | 74.00            | 54.00          | X/H  |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency◦“F” denotes fundamental frequency; “H” denotes spurious frequency. “E” denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ◦
- (4) Data of measurement within this frequency range shown “ \* ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
“X” - denotes Laid on Table ; “Y” - denotes Vertical Stand ; “Z” - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) “#” The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH159 (Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N40 Mode 5795MHz                |                    |              |



| Freq.    | Ant.Pol. | Reading |        | Ant./CF | Act.     |          | Limit    |          | Note |
|----------|----------|---------|--------|---------|----------|----------|----------|----------|------|
|          |          | Peak    | AV     |         | Peak     | AV       | Peak     | AV       |      |
| (MHz)    | H/V      | (dBuV)  | (dBuV) | CF(dB)  | (dBuV/m) | (dBuV/m) | (dBuV/m) | (dBuV/m) |      |
| 5781.60  | H        | 59.61   | 50.21  | 44.54   | 104.15   | 94.75    |          |          | X/F  |
| #5850.00 | H        | 12.52   | 0.28   | 44.78   | 57.30    | 45.06    | 84.15    | 74.75    | X/E  |
| 11590.55 | H        | 42.01   | 29.36  | 18.72   | 60.73    | 48.08    | 74.00    | 54.00    | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH159 (Above 1000 MHz, Horizontal)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N80 Mode 5775MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note       |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |            |
| #5725          | V               | 12.52          | 5.61         | 44.34             | 56.86            | 49.95          | 76.67            | 70.19          | X/E        |
| <b>5783.00</b> | <b>V</b>        | <b>52.12</b>   | <b>45.64</b> | <b>44.55</b>      | <b>96.67</b>     | <b>90.19</b>   |                  |                | <b>X/F</b> |
| 11550.45       | V               | 40.89          | 27.85        | 18.62             | 59.51            | 46.47          | 74.00            | 54.00          | X/H        |

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH155(Above 1000 MHz, Vertical)**





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N80 Mode 5775MHz                |                    |              |



| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Reading        |              | Ant./CF<br>CF(dB) | Act.             |                | Limit            |                | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
|                |                 | Peak<br>(dBuV) | AV<br>(dBuV) |                   | Peak<br>(dBuV/m) | AV<br>(dBuV/m) | Peak<br>(dBuV/m) | AV<br>(dBuV/m) |      |
| #5725          | H               | 14.26          | 5.95         | 44.34             | 58.60            | 50.29          | 80.79            | 71.91          | X/E  |
| 5749.40        | H               | 56.36          | 47.48        | 44.43             | 100.79           | 91.91          |                  |                | X/F  |
| 11550.56       | H               | 41.78          | 27.91        | 18.62             | 60.40            | 46.53          | 74.00            | 54.00          | X/H  |

**Remark:**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) "#" The radiated frequency is out of the restricted band. Limit line= fundamental - 20dB



**TX CH155 (Above 1000 MHz, Horizontal)**





## 5. BANDWIDTH TEST

### 5.1 Applied procedures / limit

| FCC Part15 (15.247) , Subpart C |           |       |                       |        |
|---------------------------------|-----------|-------|-----------------------|--------|
| Section                         | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2)                    | Bandwidth | N/A   | 5725 - 5825           | PASS   |

#### 5.1.1 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 16, 2013    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.


#### 5.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = Auto

#### 5.1.3 DEVIATION FROM STANDARD

No deviation.

#### 5.1.4 TEST SETUP



#### 5.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





## 5.1.6 TEST RESULTS

|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :      | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode /CH149, CH157, CH165        |                    |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH149        | 5745            | 16.60               | 16.52                        | PASS        |
| CH157        | 5785            | 16.60               | 16.52                        | PASS        |
| CH165        | 5825            | 16.60               | 16.52                        | PASS        |










|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :      | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode /CH149, CH157, CH165      |                    |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH149        | 5745            | 17.76               | 17.64                        | PASS        |
| CH157        | 5785            | 17.80               | 17.64                        | PASS        |
| CH165        | 5825            | 17.80               | 17.64                        | PASS        |









|              |                                       |                           |              |
|--------------|---------------------------------------|---------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :             | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:        | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :            | AC 120V/60Hz |
| Test Mode :  |                                       | TX N40 Mode /CH151, CH159 |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH151        | 5755            | 36.64               | 36.32                        | PASS        |
| CH159        | 5795            | 36.64               | 36.32                        | PASS        |










|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :      | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165   |                    |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH149        | 5745            | 17.80               | 17.68                        | PASS        |
| CH157        | 5785            | 17.84               | 17.68                        | PASS        |
| CH165        | 5825            | 17.84               | 17.68                        | PASS        |









|              |                                       |                              |              |
|--------------|---------------------------------------|------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :                | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:           | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :               | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH151        | 5755            | 36.64               | 36.16                        | PASS        |
| CH159        | 5795            | 36.64               | 36.24                        | PASS        |








|              |                                       |                       |              |
|--------------|---------------------------------------|-----------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name. :         | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:    | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :        | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N80 Mode /CH155 |              |

| Test Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Test Result |
|--------------|-----------------|---------------------|------------------------------|-------------|
| CH155        | 5775            | 76.64               | 76.00                        | PASS        |





## 6. MAXIMUM OUTPUT POWER TEST

### 6.1 Applied procedures / limit

| FCC Part15 (15.247) , Subpart C |                      |                 |                       |        |
|---------------------------------|----------------------|-----------------|-----------------------|--------|
| Section                         | Test Item            | Limit           | Frequency Range (MHz) | Result |
| 15.247(b)(3)                    | Maximum Output Power | 1 watt or 30dBm | 5725 - 5825           | PASS   |

#### 6.1.1 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment     | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-----------------------|--------------|----------|------------|------------------|
| 1    | P-series Power meter  | Agilent      | N1911A   | MY45100473 | Apr. 25, 2014    |
| 2    | Wireband Power sensor | Agilent      | N1921A   | MY51100041 | Apr. 25, 2014    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.


#### 6.1.2 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.3 of FCC KDB 558074 D01 DTS Meas Guidance v03r01(A,N20,N40 mode) and 662911 D01 Multiple Transmitter Output v01r02(N20,N40 mode)

#### 6.1.3 DEVIATION FROM STANDARD

No deviation.

#### 6.1.4 TEST SETUP



#### 6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



#### **6.1.6 TEST RESULTS**

|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode /CH149, CH157, CH165        |                    |              |

| ANT 0        |                 |                            |             |           |
|--------------|-----------------|----------------------------|-------------|-----------|
| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
| CH149        | 5745 MHz        | 21.68                      | 30          | 1         |
| CH157        | 5785 MHz        | 21.96                      | 30          | 1         |
| CH165        | 5825 MHz        | 21.77                      | 30          | 1         |



|              |                                       |                                  |              |
|--------------|---------------------------------------|----------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                     | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:               | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                   | AC 120V/60Hz |
| Test Mode :  |                                       | TX N20 Mode /CH149, CH157, CH165 |              |

**ANT 0**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 17.98                      | 30          | 1         |
| CH157        | 5785 MHz        | 17.95                      | 30          | 1         |
| CH165        | 5825 MHz        | 17.89                      | 30          | 1         |

**ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 17.86                      | 30          | 1         |
| CH157        | 5785 MHz        | 18.81                      | 30          | 1         |
| CH165        | 5825 MHz        | 17.79                      | 30          | 1         |

**ANT 0 + ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 20.93                      | 30          | 1         |
| CH157        | 5785 MHz        | 21.41                      | 30          | 1         |
| CH165        | 5825 MHz        | 20.85                      | 30          | 1         |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain = GANT, that is Directional gain=5.2dBi



|              |                                       |                           |              |
|--------------|---------------------------------------|---------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :              | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:        | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :            | AC 120V/60Hz |
| Test Mode :  |                                       | TX N40 Mode /CH151, CH159 |              |

**ANT 0**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 17.86                      | 30          | 1         |
| CH159        | 5795 MHz        | 17.97                      | 30          | 1         |

**ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 17.60                      | 30          | 1         |
| CH159        | 5795 MHz        | 17.39                      | 30          | 1         |

**ANT 0 + ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 20.74                      | 30          | 1         |
| CH159        | 5795 MHz        | 20.70                      | 30          | 1         |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain =  $G_{ANT}$ , that is Directional gain=5.2dBi.



|              |                                       |                                     |              |
|--------------|---------------------------------------|-------------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                        | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:                  | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                      | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N20 Mode /CH149, CH157, CH165 |              |

**ANT 0**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 17.97                      | 30          | 1         |
| CH157        | 5785 MHz        | 17.85                      | 30          | 1         |
| CH165        | 5825 MHz        | 17.92                      | 30          | 1         |

**ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 17.83                      | 30          | 1         |
| CH157        | 5785 MHz        | 17.69                      | 30          | 1         |
| CH165        | 5825 MHz        | 17.89                      | 30          | 1         |

**ANT 0 + ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH149        | 5745 MHz        | 20.91                      | 30          | 1         |
| CH157        | 5785 MHz        | 20.78                      | 30          | 1         |
| CH165        | 5825 MHz        | 20.92                      | 30          | 1         |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain =  $G_{ANT}$ , that is Directional gain=5.2dBi.



|              |                                       |                              |              |
|--------------|---------------------------------------|------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                 | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:           | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :               | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 |              |

**ANT 0**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 17.98                      | 30          | 1         |
| CH159        | 5795 MHz        | 17.95                      | 30          | 1         |

**ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 17.82                      | 30          | 1         |
| CH159        | 5795 MHz        | 17.46                      | 30          | 1         |

**ANT 0 + ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH151        | 5755 MHz        | 20.91                      | 30          | 1         |
| CH159        | 5795 MHz        | 20.72                      | 30          | 1         |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain =  $G_{ANT}$ , that is Directional gain=5.2dBi.



|              |                                       |                       |              |
|--------------|---------------------------------------|-----------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :          | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:    | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :        | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N80 Mode /CH155 |              |

**ANT 0**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH155        | 5795 MHz        | 17.88                      | 30          | 1         |

**ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH155        | 5795 MHz        | 17.72                      | 30          | 1         |

**ANT 0 + ANT 1**

| Test Channel | Frequency (MHz) | Maximum Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|----------------------------|-------------|-----------|
| CH155        | 5755 MHz        | 20.81                      | 30          | 1         |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, Direction gain =  $G_{ANT}$ , that is Directional gain=5.2dBi.



## 7. ANTENNA CONDUCTED SPURIOUS EMISSION

### 7.1 Applied procedures / limit

20dB in any 100 KHz bandwidth outside the operating frequency band, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(KHz)                       | 300                           |
| 0.490~1.705     | 24000/F(KHz)                      | 30                            |
| 1.705~30.0      | 30                                | 30                            |
| 30~88           | 100                               | 3                             |
| 88~216          | 150                               | 3                             |
| 216~960         | 200                               | 3                             |
| 960~1000        | 500                               | 3                             |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | (dBuV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | Peak                   | Average |
| Above 1000      | 74                     | 54      |

### 7.1.1 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 16, 2013    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

### 7.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time =20 ms.

### 7.1.3 DEVIATION FROM STANDARD

No deviation.



#### **7.1.4 TEST SETUP**





#### **7.1.5 EUT OPERATION CONDITIONS**



The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**7.1.6 TEST RESULTS**



|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode /CH149, CH157, CH165        |                    |              |

| Channel of Worst Data: CH149  |            |  |            |
|---|------------|--|------------|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band   |            | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |            |
| FREQUENCY(MHz)  | POWER(dBm) | FREQUENCY(MHz)   | POWER(dBm) |
| 5725.00   | -37.87     | 5853.60  | -46.90     |
| Result  |            |  |            |
| In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power. |            |  |            |



















|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter   | Model Name :       | WF2190       |
| Temperature: | 25 °C                                   | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                                | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20Mode /CH149, CH157, CH165 / ANT 0 |                    |              |

| Channel of Worst Data: CH149  |            |  |            |
|---|------------|--|------------|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band   |            | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |            |
| FREQUENCY(MHz)  | POWER(dBm) | FREQUENCY(MHz)   | POWER(dBm) |
| 5614.80   | -47.41     | 5863.00  | -47.32     |
| Result  |            |  |            |
| In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power. |            |  |            |











|              |  |                    |              |
|--------------|--|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter    | Model Name :       | WF2190       |
| Temperature: | 25 °C                                    | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                                 | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode /CH149, CH157, CH165 / ANT 1 |                    |              |



**Channel of Worst Data: CH149**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5723.40        | -47.50     | 5863.20        | -48.47     |



**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.











|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode /CH151, CH159 / ANT 0     |                    |              |



**Channel of Worst Data: CH151**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5719.40        | -48.72     | 5885.40        | -47.95     |

**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.









|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode /CH151, CH159 / ANT 1     |                    |              |



**Channel of Worst Data: CH151**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5701.80        | -47.51     | 5864.60        | -48.02     |

**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.









|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter       | Model Name :       | WF2190       |
| Temperature: | 25 °C                                       | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                                    | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165 / ANT 0 |                    |              |



Channel of Worst Data: CH149



The max. radio frequency power in any 100kHz bandwidth outside the frequency band      The max. radio frequency power in any 100 kHz bandwidth within the frequency band.



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5723.20        | -46.62     | 5855.60        | -47.76     |



Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.











|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter       | Model Name :       | WF2190       |
| Temperature: | 25 °C                                       | Relative Humidity: | 58 %         |
| Pressure:    | 1010 hPa                                    | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165 / ANT 1 |                    |              |



**Channel of Worst Data: CH149**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5724.20        | -44.62     | 5850.00        | -46.97     |



**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.











|              |                                       |                                      |              |
|--------------|---------------------------------------|--------------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                         | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:                   | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                       | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 / ANT 0 |              |



**Channel of Worst Data: CH151**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5675.00        | -48.50     | 5876.60        | -48.67     |

**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.









|              |                                       |                                      |              |
|--------------|---------------------------------------|--------------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                         | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:                   | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                       | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 / ANT 1 |              |



**Channel of Worst Data: CH151**



|   |  |
|---|--|
| The max. radio frequency power in any 100kHz bandwidth outside the frequency band | The max. radio frequency power in any 100 kHz bandwidth within the frequency band. |
|---|--|



| FREQUENCY(MHz) | POWER(dBm) | FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|----------------|------------|
| 5715.40        | -47.45     | 5857.40        | -48.61     |

**Result**

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.









|              |                                       |                               |              |
|--------------|---------------------------------------|-------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                  | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:            | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N80 Mode /CH155 / ANT 0 |              |


### Channel of Worst Data: CH155



The max. radio frequency power in any 100kHz bandwidth outside the frequency band

| FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|
| 5863.80        | -48.01     |

### Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.







|              |                                       |                               |              |
|--------------|---------------------------------------|-------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                  | WF2190       |
| Temperature: | 25 °C                                 | Relative Humidity:            | 58 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N80 Mode /CH155 / ANT 1 |              |


### Channel of Worst Data: CH155



The max. radio frequency power in any 100kHz bandwidth outside the frequency band

| FREQUENCY(MHz) | POWER(dBm) |
|----------------|------------|
| 5863.80        | -48.03     |

### Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.







## 8. POWER SPECTRAL DENSITY TEST

### 8.1 Applied procedures / limit

| FCC Part15 (15.247) , Subpart C |                        |                        |                       |        |
|---------------------------------|------------------------|------------------------|-----------------------|--------|
| Section                         | Test Item              | Limit                  | Frequency Range (MHz) | Result |
| 15.247(e)                       | Power Spectral Density | 8 dBm<br>(in any 3KHz) | 5745 - 5825           | PASS   |

#### 8.1.1 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 16, 2013    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.


#### 8.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW=3KHz, VBW=10KHz, Sweep time = auto.
- The power spectral density was performed in accordance with method 10.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r01 (A, N20, N40 mode) and 662911 D01 Multiple Transmitter Output v01r02. (N20,N40 mode)

#### 8.1.3 DEVIATION FROM STANDARD

No deviation.

#### 8.1.4 TEST SETUP



#### 8.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.




## 8.1.6 TEST RESULTS

|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX A Mode /CH149, CH157, CH165        |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -13.74              | 8           |
| CH157        | 5785 MHz        | -13.70              | 8           |
| CH165        | 5825 MHz        | -14.33              | 8           |









|              |  |                    |              |
|--------------|--|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter    | Model Name :       | WF2190       |
| Temperature: | 23 °C                                    | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                                 | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode /CH149, CH157, CH165 / ANT 0 |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -19.24              | 8           |
| CH157        | 5785 MHz        | -18.02              | 8           |
| CH165        | 5825 MHz        | -20.01              | 8           |









|              |  |                    |              |
|--------------|--|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter    | Model Name :       | WF2190       |
| Temperature: | 23 °C                                    | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                                 | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N20 Mode /CH149, CH157, CH165 / ANT 1 |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -18.05              | 8           |
| CH157        | 5785 MHz        | -20.02              | 8           |
| CH165        | 5825 MHz        | -19.33              | 8           |







|              |                                       |  |              |
|--------------|---------------------------------------|--|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                                     | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity:                               | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                                   | AC 120V/60Hz |
| Test Mode :  |                                       | TX N20 Mode /CH149, CH157, CH165 / ANT 0 + ANT 1 |              |


| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -15.59              | 8           |
| CH157        | 5785 MHz        | -15.90              | 8           |
| CH165        | 5825 MHz        | -16.65              | 8           |


Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain = G<sub>ANT</sub>**, that is Directional gain=5.2dBi



|              |                                       |                                   |              |
|--------------|---------------------------------------|-----------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                      | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity:                | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                    | AC 120V/60Hz |
| Test Mode :  |                                       | TX N40 Mode /CH151, CH159 / ANT 0 |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -24.25              | 8           |
| CH159        | 5795 MHz        | -22.62              | 8           |









|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode /CH151, CH159 / ANT 1     |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -24.33              | 8           |
| CH159        | 5795 MHz        | -24.26              | 8           |







|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter   | Model Name :       | WF2190       |
| Temperature: | 23 °C                                   | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                                | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX N40 Mode /CH151, CH159 / ANT 0+ANT 1 |                    |              |


| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -21.28              | 8           |
| CH159        | 5795 MHz        | -20.35              | 8           |


Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain = G<sub>ANT</sub>**, that is Directional gain=5.2dBi.



|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter       | Model Name :       | WF2190       |
| Temperature: | 23 °C                                       | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                                    | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165 / ANT 0 |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -16.29              | 8           |
| CH157        | 5785 MHz        | -16.94              | 8           |
| CH165        | 5825 MHz        | -16.10              | 8           |









|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter       | Model Name :       | WF2190       |
| Temperature: | 23 °C                                       | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                                    | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165 / ANT 1 |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -16.82              | 8           |
| CH157        | 5785 MHz        | -17.96              | 8           |
| CH165        | 5825 MHz        | -15.83              | 8           |







|              |   |                    |              |
|--------------|---|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter               | Model Name :       | WF2190       |
| Temperature: | 23 °C   | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa  | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N20 Mode /CH149, CH157, CH165 / ANT 0 + ANT 1 |                    |              |


| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH149        | 5745 MHz        | -13.54              | 8           |
| CH157        | 5785 MHz        | -14.41              | 8           |
| CH165        | 5825 MHz        | -12.95              | 8           |


Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain =  $G_{ANT}$** , that is Directional gain=5.2dBi.



|              |                                       |                                      |              |
|--------------|---------------------------------------|--------------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                         | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity:                   | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                       | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 / ANT 0 |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -22.01              | 8           |
| CH159        | 5795 MHz        | -21.00              | 8           |









|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N40 Mode /CH151, CH159 / ANT 1  |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -20.86              | 8           |
| CH159        | 5795 MHz        | -21.52              | 8           |





Date: 11.NOV.2013 22:14:57



|              |                                       |  |              |
|--------------|---------------------------------------|--|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                                 | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity:                           | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                               | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N40 Mode /CH151, CH159 / ANT 0 + ANT 1 |              |


| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH151        | 5755 MHz        | -18.39              | 8           |
| CH159        | 5795 MHz        | -18.24              | 8           |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain = G<sub>ANT</sub>**, that is Directional gain=5.2dBi.



|              |                                       |                               |              |
|--------------|---------------------------------------|-------------------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :                  | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity:            | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :                | AC 120V/60Hz |
| Test Mode :  |                                       | TX AC N80 Mode /CH155 / ANT 0 |              |


| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH155        | 5775 MHz        | -23.70              | 8           |





|              |                                       |                    |                               |
|--------------|---------------------------------------|--------------------|-------------------------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190                        |
| Temperature: | 23 °C                                 | Relative Humidity: | 51 %                          |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz                  |
| Test Mode :  |                                       |                    | TX AC N80 Mode /CH155 / ANT 1 |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH155        | 5775 MHz        | -24.79              | 8           |





|              |                                       |                    |              |
|--------------|---------------------------------------|--------------------|--------------|
| EUT:         | AC1200 Wireless Dual Band USB Adapter | Model Name :       | WF2190       |
| Temperature: | 23 °C                                 | Relative Humidity: | 51 %         |
| Pressure:    | 1010 hPa                              | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | TX AC N80 Mode /CH155 / ANT 0 + ANT 1 |                    |              |

| Test Channel | Frequency (MHz) | Power Density (dBm) | LIMIT (dBm) |
|--------------|-----------------|---------------------|-------------|
| CH155        | 5775 MHz        | -21.20              | 8           |

Note: The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers (2T2R), all transmit signals are completely uncorrelated, then, **Direction gain =  $G_{ANT}$** , that is Directional gain=5.2dBi.



**9. EUT TEST PHOTO**

**Conducted Measurement Photos**






**Radiated Measurement Photos**  
**9KHz~30MHz**





**Radiated Measurement Photos**  
**300MHz~1000MHz**





**Radiated Measurement Photos  
Above 1000MHz**

