

RF Exposure Evaluation

LIMIT

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW, **G** = gain of antenna in linear scale;

Pi = 3.1416, **R** = distance between observation point and center of the radiator in cm

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

Type	Antenna	Conducted Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	Antenna 1	21.32	22.00	0.0997	1.0000	Pass
802.11g	Antenna 0	19.81	20.00	0.0629	1.0000	Pass

Type	Antenna	Conducted Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Total Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
802.11n(H20)	Antenna 0	20.03	21.00	0.0792	0.1421	1.0000	Pass
	Antenna 1	19.66	20.00	0.0629			
802.11n(H40)	Antenna 0	18.88	19.00	0.0500	0.1129	1.0000	Pass
	Antenna 1	19.85	20.00	0.0629			

Note:

- 1) The maximum antenna gain is 5dBi
- 2) The exposure evaluation safety distance is 20mm.
- 3) Total Power Density = (Antenna 0 Power Density + Antenna 1 Power Density)/ Limit