

## **FCC EVALUATION REPORT FOR CERTIFICATION**

**FUSIONSOFT Co., Ltd.**  
969-7, Dongcheon-Dong, Buk-Gu, Daegu, Korea  
Attn: Sung-Chae Bae / Vice President

**Date of Issue : May 4, 2006**  
**Test Report No. : GETEC-E3-06-033**  
**Test Site : Gumi College EMC Center**

**FCC ID**

**T76P11N**

**APPLICANT**


**FUSIONSOFT Co., Ltd.**

<b>Rule Part(s)</b>	: FCC Part 15 Subpart B
<b>Equipment Class</b>	: Class B Computing Device Peripheral
<b>EUT Type</b>	: Portable Multimedia Player
<b>Model No.</b>	: P11N, P108, P11N, NAVI-4000


This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

  
\_\_\_\_\_  
Jae-Hoon Jeong, Senior Engineer  
GUMI College EMC center

Reviewed by,

  
\_\_\_\_\_  
Tae-Sig Park, Technical Manager  
GUMI College EMC center

## CONTENTS

1. SCOPE.....	3
2. INTRODUCTION .....	4
3. TEST CONDITIONS & EUT INFORMATION.....	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT USED .....	6
4. DESCRIPTION OF TESTS.....	7
4.1 CONDUCTED EMISSION .....	7
4.2 RADIATED EMISSION .....	8
5. CONDUCTED EMISSION.....	9
5.1 OPERATING ENVIRONMENT .....	9
5.2 TEST SET-UP.....	9
5.3 MEASUREMENT UNCERTAINTY .....	9
5.4 LIMIT .....	10
5.5 TEST EQUIPMENT USED .....	10
5.6 TEST DATA FOR POWER LINE CONDUCTED EMISSION.....	11
6. RADIATED EMISSION .....	14
6.1 OPERATING ENVIRONMENT .....	14
6.2 TEST SET-UP.....	14
6.3 MEASUREMENT UNCERTAINTY .....	14
6.4 LIMIT .....	15
6.5 TEST EQUIPMENT USED .....	15
6.6 TEST DATA FOR RADIATED EMISSION.....	16
9. SAMPLE CALCULATIONS.....	21
9.1 EXAMPLE 1 : .....	21
9.2 EXAMPLE 2 : .....	21
10. RECOMMENDATION & CONCLUSION.....	22
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – PLOTS OF CONDUCTED EMISSIONS	
APPENDIX C – ID SAMPLE LABEL & LOCATION	
APPENDIX D – BLOCK DIAGRAM	
APPENDIX E – TEST SET-UP PHOTOGRAPHS	
APPENDIX F – EXTERNAL PHOTOGRAPHS	
APPENDIX G –INTERNAL PHOTOGRAPHS	
APPENDIX H – USER’S MANUAL	

## 1. Scope

*Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.*

- **FCC ID** T76P11N
- **EUT Type** Portable Multimedia Player
- **Model No.** P11N, P108, P118, NAVI-4000
- **Rule Part(s)** FCC Part 15 Subpart B
- **Equipment Class** Class B Computing Device Peripheral
- **Manufacturer** FUSIONSOFT Co., Ltd.
- **Test Procedure(s)** ANSI C63.4 (2003)
- **Dates of Test** April 25 ~ 26, 2006
- **Place of Test** Gumi College EMC Center
- **Test Report No.** GETEC-E3-06-033


## 2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **FUSIONSOFT Co., Ltd. Portable Multimedia Player (Model No.: P11N)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-Dong, Gumi-City, Gyeongsangbuk-Do, Korea

This test site is one of the highest point of Gumi 1 college at about 200 kilometers away from Seoul city and 40 kilometers away from Daejeon city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufacturers. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on October 19, 1992



**GUMI COLLEGE EMC CENTER**  
 407, Bugok-Dong, Gumi-Si,  
 Gyeongsangbuk-Do 730-711, Korea  
 Tel: +82-54-440-1195  
 Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.

### 3. Test Conditions & EUT Information

#### 3.1 Description of EUT

The Equipment Under Test (EUT) is the FUSIONSOFT Co., Ltd. Portable Multimedia Player (Model No.: P11N)  
**FCC ID : T76P11N**

<b>Test pattern</b>	Download mode Navigation mode Play mode AV-in mode FM radio mode
<b>AC/DC Adapter</b>	: <b>FAP-0520K</b> (FAITH-TECH Co., Ltd ) Input: 100 ~ 250Vac, 50~ 60Hz, 0.5A Output: +5Vdc 2.0A
<b>Cable(s)</b>	1.7m Adapter cable Connected to the EUT 1.3m Download cable Connected to the EUT and Notebook pc 1.5m CVBS input cable Connected to the EUT and DVD player 1.5m CVBS output cable Connected to the EUT and Monitor 1.5m S-Video input cable Connected to the EUT and DVD player 1.5m YCbCr output cable Open 1.3m Earphone cable Connected to the EUT 1.2m GPS cable Connected to the EUT

**3.2 Support Equipment used**

<b>DVD Player</b>	PIONEER DV525 S/N: UEYD0R390LL FCC ID: DoC
<b>Monitor</b>	LG Electronics Inc RZ-13LA60 S/N: Proto type FCC ID: DoC
<b>Notebook pc</b>	COMPAQ PP2060 S/N: AE5P3900T4X20DC1298T FCC ID: DoC
<b>GPS</b>	NAVIUS NSA-U3 S/N: NU6600033 FCC ID: DoC
<b>Printer</b>	Hewlett Packard 970CXI S/N: MY9B01F1FG FCC ID: DoC

*See “Appendix E – Test Setup Photographs” for actual system test set-up*

## 4. Description of tests

### 4.1 Conducted Emission

The Line conducted emission test facility is inside a  $4 \times 8 \times 2.5$  meter shielded enclosure.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table, which is 0.8 meters in height and 0.4 meters away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150kHz to 30MHz with 20msec sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 – 40 centi-meters.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN

## 4.2 Radiated Emission

Preliminary measurements were conducted 3m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000MHz using bicornical log antenna (Schwarzbeck, VULB9160). Above 1GHz, horn antenna (Schwarzbeck, BBHA9120D) was used.

Final measurements were made outdoors at 10m-test range using bicornical antenna (R&S, HK116), log-periodic antenna (R&S, HL223) and horn antenna (Schwarzbeck, BBHA9120D)

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8m high non-metallic 1.0×1.5 meter table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission. Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of Open Site Test Area

## 5. Conducted Emission

### 5.1 Operating environment

Temperature : 21 °C  
 Relative humidity : 43 %

### 5.2 Test set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8m heights above the floor, 0.4m from the reference ground plane (GRP) wall and 0.8m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

### 5.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty ( $\pm$ dB)	
		Power Port	Communication port
Receiver specification	Rectangular	0.50	0.50
LISN coupling specification	Rectangular	1.50	
ISN coupling specification	Rectangular		1.50
Mismatch			
LISN VRC : $\Gamma_l =$ 0.20	U-shaped	0.05	0.05
ISN VRC : $\Gamma_l =$ 0.20		-0.05	-0.05
ATT VRC(IN) : $\Gamma_g =$ 0.03			
Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$			
Mismatch			
Receiver VRC : $\Gamma_l =$ 0.09	U-shaped	0.09	0.09
ATT VRC : $\Gamma_g =$ 0.11		-0.09	-0.09
Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$			
System repeatability	Std Deviation	0.11	0.11
Cable and input attenuator calibration	Normal (k=2)	0.04	0.04
Repeatability of EUT			
Combined standard uncertainty $U_c(y)$	Normal	0.92 -0.92	0.92 -0.92
Extended uncertainty U	Normal (k=2)	1.85 -1.85	1.85 -1.85

**5.4 Limit**

RFI Conducted	FCC Limit(dB) Class B	
Freq. Range	Quasi-Peak	Average
150kHz – 0.5MHz	66 – 56*	56 – 46*
0.5MHz – 5MHz	56	46
5MHz – 30MHz	60	50

\*Limits decreases linearly with the logarithm of frequency.

**5.5 Test equipment used**

Model Number	Manufacturer	Description	Serial Number	Calibrated Date
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 14. 2005
■ - ESH3-Z5	Rohde & Schwarz	Artificial mains network	838979/020	12. 16. 2005
■ - ESH2-Z5	Rohde & Schwarz	Artificial mains network	829991/009	12. 16. 2005

**5.6 Test data for power line conducted emission**

- Test Date : April 26, 2006
- Resolution bandwidth : 9kHz
- Frequency range : 0.15MHz ~ 30MHz

**5.6.1 Operating condition: Download mode**

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.180	0.10	-0.19	H	64.49	44.4	44.31	54.49	40.6	40.51	20.18	13.98
0.230	0.12	-0.21	H	62.45	39.1	39.01	52.45	38.2	38.11	23.44	14.34
0.350	0.13	-0.15	H	58.96	38.4	38.38	48.96	32.8	32.78	20.58	16.18
0.420	0.13	-0.13	H	57.45	37.8	37.80	47.45	33.9	33.90	19.64	13.54
0.550	0.14	-0.20	H	56.00	34.1	34.04	46.00	28.4	28.34	21.96	17.66
0.990	0.15	-0.23	H	56.00	30.6	30.52	46.00	24.1	24.02	25.48	21.98
1.895	0.18	-0.31	N	56.00	35.6	35.47	46.00	27.5	27.37	20.53	18.63
1.995	0.19	-0.32	H	56.00	41.9	41.77	46.00	37.5	37.37	14.23	8.63
5.975	0.31	-0.18	N	60.00	34.4	34.53	50.00	32.5	32.63	25.47	17.37

\*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

**5.6.2 Operating condition: Navigation mode**

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.195	0.12	-0.22	H	63.82	46.9	46.79	53.82	40.7	40.59	17.03	13.23
0.260	0.12	-0.20	H	61.43	40.9	40.83	51.43	34.5	34.43	20.60	17.00
0.325	0.13	-0.16	H	59.58	40.9	40.87	49.58	32.5	32.47	18.71	17.11
0.435	0.14	-0.14	H	57.16	35.1	35.10	47.16	29.2	29.20	22.06	17.96
0.550	0.14	-0.20	H	56.00	31.1	31.04	46.00	19.5	19.44	24.96	26.56
0.915	0.15	-0.23	H	56.00	34.8	34.72	46.00	24.1	24.02	21.28	21.98
1.635	0.18	-0.29	H	56.00	33.5	33.39	46.00	23.4	23.29	22.61	22.71
2.420	0.20	-0.24	H	56.00	34.7	34.66	46.00	22.6	22.56	21.34	23.44
3.730	0.24	-0.14	H	56.00	29.0	29.10	46.00	20.5	20.60	26.90	25.40
29.865	0.88	0.13	H	60.00	47.9	48.90	50.00	41.9	42.90	11.10	7.10

\*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

**5.6.3 Operating condition: AV-in mode**

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.195	0.12	-0.22	H	63.82	42.5	42.39	53.82	37.0	36.89	21.43	16.93
0.395	0.12	-0.12	N	57.96	35.4	35.39	47.96	32.5	32.49	22.56	15.46
0.590	0.12	-0.22	N	56.00	36.4	36.30	46.00	33.3	33.20	19.70	12.80
0.980	0.15	-0.23	H	56.00	38.4	38.32	46.00	37.3	37.22	17.68	8.78
1.505	0.17	-0.28	H	56.00	41.3	41.19	46.00	39.5	39.39	14.81	6.61
2.420	0.20	-0.24	H	56.00	38.1	38.06	46.00	35.0	34.96	17.94	11.04
3.790	0.24	-0.14	H	56.00	38.4	38.50	46.00	34.1	34.20	17.50	11.80
8.380	0.36	0.00	N	60.00	34.7	35.06	50.00	33.0	33.36	24.94	16.64

\*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

**5.6.4 Operating condition: FM radio mode**

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.195	0.12	-0.22	H	63.82	47.1	46.99	53.82	44.0	43.89	16.83	9.93
0.460	0.12	-0.15	N	56.69	34.3	34.27	46.69	32.3	32.27	22.43	14.43
0.785	0.15	-0.23	H	56.00	35.6	35.52	46.00	32.7	32.62	20.48	13.38
1.115	0.14	-0.24	N	56.00	37.5	37.40	46.00	35.8	35.70	18.60	10.30
2.030	0.18	-0.31	N	56.00	40.0	39.87	46.00	36.5	36.37	16.13	9.63
4.455	0.26	-0.15	N	56.00	32.4	32.51	46.00	27.7	27.81	23.49	18.19
6.810	0.33	-0.11	N	60.00	27.0	27.23	50.00	22.1	22.33	32.77	27.67

\*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

**5.6.5 Operating condition: Play mode**

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.200	0.11	-0.23	N	63.61	50.1	49.98	53.61	43.6	43.48	13.63	10.13
0.395	0.13	-0.12	H	57.96	37.2	37.21	47.96	36.7	36.71	20.75	11.25
0.785	0.15	-0.23	H	56.00	36.2	36.12	46.00	33.4	33.32	19.88	12.68
1.115	0.15	-0.24	H	56.00	36.9	36.81	46.00	34.9	34.81	19.19	11.19
2.420	0.20	-0.24	H	56.00	35.8	35.76	46.00	32.1	32.06	20.24	13.94
4.125	0.25	-0.14	H	56.00	36.0	36.11	46.00	31.7	31.81	19.89	14.19
5.960	0.31	-0.18	H	60.00	33.2	33.33	50.00	27.2	27.33	26.67	22.67
10.410	0.41	0.00	H	60.00	30.0	30.41	50.00	27.7	28.11	29.59	21.89

\*Comment : Pol : H (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

## 6. Radiated Emission

### 6.1 Operating environment

Temperature : 20°C  
 Relative humidity : 36 %

### 6.2 Test set-up

A preliminary scan with peak mode was performed in the semi anechoic chamber and found frequency for open area test site.

The formal radiated emission was measured at 10m-distance open area test site.

The EUT was placed on a non-conductive turntable approximately 0.8 meters above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 and 4.0 meters in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

### 6.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95%.

Contribution	Probability Distribution	Uncertainty (dB)			
		Biconical Ant.		Log-periodic Ant.	
		3m	10m	3m	10m
Ambient signal					
Antenna factor calibration	Normal (k=2)	0.50	0.50	0.50	0.50
Receiver specification	Rectangular	0.50	0.50	0.50	0.50
Antenna directivity	Rectangular	0.25	0.00	1.50	0.25
Antenna phase center variation	Rectangular	0.00	0.00	1.00	0.20
Antenna factor frequency interpolation	Rectangular	0.25	0.25	0.25	0.25
Measure distance variation	Rectangular	0.60	0.40	0.60	0.40
Site imperfections	Rectangular	1.46	-2.32	2.26	2.94
Mismatch					
Receiver VRC : $\Gamma_l = 0.09$	U-shaped	0.33	0.33	0.33	0.33
Antenna VRC : $\Gamma_g = 0.43$ (Bi) $0.23$ (Lp)					
Uncertainty limits $20\log(1 \pm \Gamma_l \Gamma_g)$					
System repeatability	Std Deviation	0.18	0.18	0.17	0.17
Cable loss calibration	Normal (k=2)	0.05	0.05	0.05	0.05
Combined standard uncertainty $U_c(y)$	Normal	1.05	1.45	1.78	1.80
		-1.05	-1.45	-1.77	-1.78
Extended uncertainty U	Normal (k=2)	2.11	2.90	3.55	3.59
		-2.11	-2.90	-3.53	-3.57

**6.4 Limit**

Frequency (MHz)	FCC Limit @ 3m. dB $\mu$ V/m	CISPR Limit @ 10m. dB $\mu$ V/m
30 – 88	40.0	30.0
88 – 216	43.5	30.0
216 – 230	46.0	30.0
230 – 960	46.0	37.0
960 – 1000	54.0	37.0
> 1000	54.0	No Specified limit

**6.5 Test equipment used**


<b>Model Number</b>	<b>Manufacturer</b>	<b>Description</b>	<b>Serial Number</b>	<b>Calibrated Date</b>
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 2. 2005
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 14. 2005
■ - HK116	Rohde & Schwarz	Biconical antenna	826861/018	12. 2. 2005
■ - HL223	Rohde & Schwarz	Log-periodic antenna	829228/011	12. 2. 2005
■ - HD100	HD GmbH	Position Controller	100/692/01	NCR
■ - DS415S	HD GmbH	Turntable	415/657/01	NCR
■ - MA240	HD GmbH	Antenna Mast	240/565/01	NCR

## 6.6 Test data for radiated emission

- Test Date : April 25, 2006
- Resolution bandwidth : 120kHz
- Frequency range : 30MHz ~ 1000MHz
- Detector mode : Quasi-peak detector mode

### 6.6.1 Operating condition: Download mode


Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)	Antenna Factor(dB)	Cable Loss(dB)	Test Result (dBuV/m)			Pol. (H/V)	Height (cm)	Angle (deg)
30.78	5.3	13.50	1.63	20.4	30.0	9.6	V	125	188
66.35	4.6	7.86	2.16	14.6	30.0	15.4	V	175	124
100.03	9.1	9.80	2.70	21.6	30.0	8.4	H	228	225
143.76	10.8	11.97	3.30	26.1	30.0	3.9	H	306	216
199.98	8.5	13.84	3.90	26.2	30.0	3.8	V	100	295
299.95	10.9	12.75	5.10	28.8	37.0	8.2	H	385	325
368.64	3.6	14.82	5.79	24.2	37.0	12.8	H	350	340
499.86	2.8	17.27	6.60	26.7	37.0	10.3	H	229	90
601.38	2.1	18.28	7.40	27.8	37.0	9.2	H	390	140
833.05	0.8	22.00	8.70	31.5	37.0	5.5	V	116	20



< Fig 4. Radiated emission result \_ Download mode >

### 6.6.2 Operating condition: Navigation mode


Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)	Antenna Factor(dB)	Cable Loss(dB)	Test Result (dBuV/m)			Pol. (H/V)	Height (cm)	Angle (deg)
66.75	5.3	7.85	2.17	15.3	30.0	14.7	V	188	51
100.03	10.3	9.80	2.70	22.8	30.0	7.2	H	302	120
200.01	8.4	13.84	3.90	26.1	30.0	3.9	H	320	35
248.20	5.4	15.63	4.48	25.5	37.0	11.5	H	225	62
300.02	8.3	12.34	5.10	25.7	37.0	11.3	H	195	185
368.60	3.4	14.82	5.79	24.0	37.0	13.0	H	300	190
448.51	1.5	16.69	6.34	24.5	37.0	12.5	H	250	245
554.20	1.3	18.37	7.03	26.7	37.0	10.3	H	278	85
655.63	0.5	19.71	7.56	27.8	37.0	9.2	V	100	320



< Fig 5. Radiated emission result \_ Navigation mode >


## 6.6.3 Operating condition: Play mode

Frequency (MHz)	Measurement Level				Limit (dBuV/m)	Margin (dBuV/m)	Positioning System		
	Reading Value(dBuV)	Antenna Factor(dB)	Cable Loss(dB)	Test Result (dBuV/m)			Pol. (H/V)	Height (cm)	Angle (deg)
87.85	9.3	8.55	2.56	20.4	40.0	19.6	H	250	270
100.02	24.1	9.80	2.70	36.6	43.5	6.9	H	224	125
151.76	20.3	12.25	3.40	35.9	43.5	7.6	H	190	120
169.30	9.1	12.82	3.55	25.5	43.5	18.0	H	325	155
191.70	14.2	13.55	3.78	31.5	43.5	12.0	H	350	356
199.98	20.1	13.84	3.90	37.8	43.5	5.7	H	315	200
300.02	19.2	12.34	5.10	36.6	46.0	9.4	H	290	19



&lt; Fig 6. Radiated emission result \_ Play mode &gt;

## 6.6.4 Operating condition: AV-in mode



&lt; Fig 7. Radiated emission result \_ AV-in mode &gt;

### 6.6.5 Operating condition: FM Radio mode

Disturbance radiation due to the local oscillator

Ch. No. (CH Freq.)	Harmonics	Measuring Frequency(MHz)	Emission Level(dBuV/m)	Limits (dBuV/m)	Margin (dB)
87.5MHz	1	98.2	-	43.5	<<
	2	196.4	-	43.5	<<
	3	294.6	-	46.0	<<
	4	392.8	-	46.0	<<
	5	491	-	46.0	<<
	6	589.2	-	46.0	<<
	7	687.4	-	46.0	<<
	8	785.6	-	46.0	<<
	9	883.8	-	46.0	<<
99.3MHz	1	110	-	43.5	<<
	2	220	-	46.0	<<
	3	330	-	46.0	<<
	4	440	-	46.0	<<
	5	550	-	46.0	<<
	6	660	-	46.0	<<
	7	770	-	46.0	<<
	8	880	-	46.0	<<
	9	990	-	46.0	<<
103.1MHz	1	113.8	-	43.5	<<
	2	227.6	-	46.0	<<
	3	341.4	-	46.0	<<
	4	455.2	-	46.0	<<
	5	569	-	46.0	<<
	6	682.8	-	46.0	<<
	7	796.6	-	46.0	<<
	9	910.4	-	46.0	<<
	-	100.03	33.7	43.5	9.8
Other Frequency	-	159.74	27.3	43.5	16.2
	-	199.98	27.8	43.5	5.7
	-	368.65	36.9	46.0	9.1
	-	400.03	30.2	46.0	15.8
	-	552.95	33.5	46.0	12.5

“<<” : The margin is more than 30dB

## 9. Sample Calculations

$$dB\mu V = 20 \log_{10}(\mu V/m)$$

$$dB\mu V = dBm + 107$$

$$\mu V = 10^{(dB\mu V/20)}$$

### 9.1 Example 1 :

#### ■ 20.3 MHz

$$\begin{aligned} \text{Class B Limit} &= 250 \mu V &= 48 dB\mu V \\ \text{Reading} &= -67.8 dBm \text{(Calibrated level)} \\ \text{Convert to } dB\mu V &= -67.8 dBm + 107 = 39.2 dB\mu V \\ 10^{(39.2 dB\mu V/20)} &= 91.2 \mu V \\ \text{Margin} &= 39.2 - 48 = -8.8 \\ &= 8.8 \text{ dB below Limit} \end{aligned}$$

### 9.2 Example 2 :

#### ■ 66.7 MHz

$$\begin{aligned} \text{Class B Limit} &= 100 \mu V/m &= 40.0 dB\mu V/m \\ \text{Reading} &= -76.0 dBm \text{(Calibrated level)} \\ \text{Convert to } dB\mu V/m &= -76.0 dBm + 107 = 31.0 dB\mu V/m \\ \text{Antenna Factor + Cable Loss} &= 5.8 \text{ dB} \\ \text{Total} &= 36.8 dB\mu V/m \\ \text{Margin} &= 36.8 - 40.0 = -3.2 \\ &= 3.2 \text{ dB below Limit} \end{aligned}$$

## 10. Recommendation & conclusion

The data collected shows that the **FUSIONSOFT Co., Ltd. Portable Multimedia Player (Model No.: P11N)** was complies with §15.107, §15.109 of the FCC Rules.