
Appendix for the Report

Dosimetric Assessment of the Portable Device 8630 (FCC ID: T7HRTX8630) (IC ID: 4979B-RTX8630)

According to the FCC Requirements

SAR Distribution Plots

March 30, 2011
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
RTX Products Hong Kong Ltd.
11/F, CAC Tower, 165 Hoi Bun Road
Kwun Tong, Kowloon
Hong Kong

The test results only relate to the items tested. This report shall not be reproduced except in full without the written approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, HEAD MEASUREMENTS, ANTENNA 1.....	3
2	SAR DISTRIBUTION PLOTS, HEAD MEASUREMENTS, ANTENNA 2.....	7
3	SAR DISTRIBUTION PLOTS, BODY MEASUREMENTS, ANTENNA 1	11
4	SAR DISTRIBUTION PLOTS, BODY MEASUREMENTS, ANTENNA 2	13
5	SAR Z-AXIS SCANS (VALIDATION)	15
6	SAR Z-AXIS SCANS (MEASUREMENTS).....	16

1 SAR Distribution Plots, Head Measurements, Antenna 1

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yplm_1_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Cheek Left/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.017 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.08 V/m; Power Drift = 0.144 dB

Peak SAR (extrapolated) = 0.033 W/kg

SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.021 mW/g




Fig. 1: SAR distribution for DECT US, antenna 1, channel 2, cheek position, left side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yplm_2_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Tilted Left/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.012 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.78 V/m; Power Drift = -0.173 dB

Peak SAR (extrapolated) = 0.023 W/kg

SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.00553 mW/g

Maximum value of SAR (measured) = 0.014 mW/g




Fig. 2: SAR distribution for DECT US, antenna 1, channel 2, tilted position, left side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yprm_1_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Cheek Right/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.022 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.82 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.035 W/kg

SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.024 mW/g




Fig. 3: SAR distribution for DECT US, antenna 1, channel 2, cheek position, right side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yprm_2_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Tilted Right/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.013 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.20 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.028 W/kg

SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00732 mW/g

Maximum value of SAR (measured) = 0.017 mW/g




Fig. 4: SAR distribution for DECT US, antenna 1, channel 2, tilted position, right side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C)

2 SAR Distribution Plots, Head Measurements, Antenna 2

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yplm_1_ant2.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Cheek Left/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.024 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.06 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.054 W/kg

SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.014 mW/g

Maximum value of SAR (measured) = 0.030 mW/g




Fig. 5: SAR distribution for DECT US, antenna 2, channel 2, cheek position, left side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); **File Name:** [RTX8630_yplm 2_ant2.da4](#)

DUT: RTX; **Type:** 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Tilted Left/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.021 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.74 V/m; Power Drift = -0.192 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.026 mW/g




Fig. 6: SAR distribution for DECT US, antenna 2, channel 2, tilted position, left side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yprm_1_ant2.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Cheek Right/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.042 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.88 V/m; Power Drift = 0.193 dB

Peak SAR (extrapolated) = 0.086 W/kg

SAR(1 g) = 0.041 mW/g; SAR(10 g) = 0.020 mW/g

Maximum value of SAR (measured) = 0.047 mW/g




Fig. 7: SAR distribution for DECT US, antenna 2, channel 2, cheek position, right side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C).

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [RTX8630_yprm_2_ant2.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.77, 7.77, 7.77); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Tilted Right/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.038 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.76 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.074 W/kg

SAR(1 g) = 0.037 mW/g; SAR(10 g) = 0.018 mW/g

Maximum value of SAR (measured) = 0.042 mW/g




Fig. 8: SAR distribution for DECT US, antenna 2, channel 2, tilted position, right side of head (March 29, 2011; Ambient Temperature: 21.2°C; Liquid Temperature: 20.7°C)

3 SAR Distribution Plots, Body Measurements, Antenna 1

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:

[RTX8630_bphm_1_dsp_up_clip_HS_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.89, 7.89, 7.89); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.015 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.13 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.027 W/kg

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00777 mW/g

Maximum value of SAR (measured) = 0.016 mW/g




Fig. 9: SAR distribution for DECT US, antenna 1, channel 2, body worn configuration, display towards the phantom, with headset and 0 mm distance (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature: 20.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:

[RTX8630_bphm_2_dsp_down_clip_HS_ant1.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.89, 7.89, 7.89); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.006 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.94 V/m; Power Drift = 0.182 dB

Peak SAR (extrapolated) = 0.011 W/kg

SAR(1 g) = 0.0063 mW/g; SAR(10 g) = 0.00355 mW/g

Maximum value of SAR (measured) = 0.007 mW/g




Fig. 10: SAR distribution for DECT US, antenna 1, channel 2, body worn configuration, display towards the ground, with headset and 0 mm distance (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature: 20.3° C).

4 SAR Distribution Plots, Body Measurements, Antenna 2

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:

[RTX8630_bphm_1_dsp_up_clip_HS_ant2.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.89, 7.89, 7.89); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.034 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.62 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 0.072 W/kg

SAR(1 g) = 0.034 mW/g; SAR(10 g) = 0.016 mW/g

Maximum value of SAR (measured) = 0.038 mW/g




Fig. 11: SAR distribution for DECT US, antenna 2, channel 2, body worn configuration, display towards the phantom, with headset and 0 mm distance (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature: 20.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:

[RTX8630_bphm_2_dsp_down_clip_HS_ant2.da4](#)

DUT: RTX; Type: 8630;

Program Name: DECT

Communication System: DECT US; Frequency: 1924.99 MHz; Duty Cycle: 1:24

Medium parameters used: $f = 1924.99$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.89, 7.89, 7.89); Calibrated: 16.09.2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 17.09.2010
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.016 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.14 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.028 W/kg

SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00898 mW/g

Maximum value of SAR (measured) = 0.017 mW/g




Fig. 12: SAR distribution for DECT US, antenna 2, channel 2, body worn configuration, display towards the ground, with headset and 0 mm distance (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature: 20.3° C).

5 SAR Z-Axis Scans (Validation)




Fig. 13: SAR versus liquid depth, 1900 MHz, head (March 29, 2011; Ambient Temperature: 21.0° C; Liquid Temperature : 20.6° C).




Fig. 14: SAR versus liquid depth, 1900 MHz, body (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature : 20.3° C).

6 SAR Z-Axis Scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 15: SAR versus liquid depth, head: DECT US, antenna 2, channel 2, cheek position, right side of head (March 29, 2011; Ambient Temperature: 21.2° C; Liquid Temperature : 20.7° C).




Fig. 16: SAR versus liquid depth, body: DECT US, antenna 2, channel 2, headset and 0 mm distance, display towards the phantom (March 28, 2011; Ambient Temperature: 20.7° C; Liquid Temperature: 20.3° C).