

RF-EXPOSURE ASSESSMENT REPORT**FCC 47 CFR Part 2.1091
ISED RSS-102****RF-Exposure evaluation of mobile equipment****Report Reference No.**: G0M-1810-7783-TFC091ME-V02**Testing Laboratory**: Eurofins Product Service GmbHAddress: Storkower Str. 38c
15526 Reichenwalde
Germany**Accreditation**:DAkkS - Registration number : D-PL-12092-01-03 (ISED)
DAkkS - Registration number : D-PL-12092-01-04 (FCC)
FCC Filed Test Laboratory, Reg.-No.: 96970**Applicant's name**: Panasonic Industrial Devices Europe GmbHAddress: Zeppelinstr. 19
21337 Lüneburg
GERMANY**Test specification:**Standard: 47 CFR 2.1091
KDB 447498 D01 v06:2015-10-23
RSS-102, Issue 5:2015-03**Equipment under test (EUT):**

Product description Wi-Fi Dual Band 2.4/5 GHz and Bluetooth Module

Model No. ENWF9201A1EF

Additional Model(s) ENWF9203A1EF

Brand Name(s) PAN9026

Hardware version 05

Firmware / Software version 01

FCC-ID: T7V-9026 IC: 216Q-9026

Test result **Passed**

Test Report No.: G0M-1810-7783-TFC091ME-V02

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2018-09-27

Date (s) of assessment: 2019-05-24

Compiled by: Toralf Jahn

Assessed by (+ signature): Burkhard Pudell
(Responsible for Assessment)



Approved by (+ signature): Christian Weber
(Head of Lab)



Date of issue: 2019-06-28

Total number of pages: 17

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

ADDITIONAL VARIANTS

Additional Variants (not tested and not evaluated variants)		
Not-tested Variant	Description	
1	Product Type Description	Wi-Fi Dual Band 2.4/5 GHz and Bluetooth Module
	Model name	ENWF9208A1EF (multi region)
	Brand name	PAN9026
	Hardware Version	05
	Software Version	01
Comment: Those named additional variants above have not been tested. Those additional variants of the series have been declared by the manufacturer. The test report explicitly states that those variants were neither tested nor assessed nor evaluated.		

Version History

Version	Issue Date	Remarks	Revised by
01	2019-05-24	Initial Release	
02	2019-06-28	Replaced document: G0M-1810-7783-TFC091ME-V01 Replaced by: G0M-1810-7783-TFC091ME-V02 Reason: References updated, Editorial corrections	C. Weber

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	6
1.1	Reference Documents	7
1.2	Standalone Radiation Sources	8
1.3	Multi-transmitter Modes	9
2	RESULT SUMMARY	10
3	RF-EXPOSURE CLASSIFICATIONS	11
4	ASSESSMENT	12
4.1	MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102	12
4.2	Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102	14

1 Equipment (Test item) Description

Description	Wi-Fi Dual Band 2.4/5 GHz and Bluetooth Module
Model	ENWF9201A1EF
Additional Model(s)	ENWF9203A1EF
Brand Name(s)	PAN9026
Serial number	None
Hardware version	05
Software / Firmware version	01
PMN	PAN9026
HVIN	ENWF9203A1EF
FVIN	-/-
HMN	-/-
FCC-ID	T7V-9026
IC	216Q-9026
Equipment type	Radio module

1.1 Reference Documents

Document type	Document No.	Issued by	Date
FCC 15.247 Test Report Bluetooth LE	G0M-1810-7783-TFC247BL-V03	Eurofins Product Service GmbH	2019-06-28
FCC 15.247 Test Report Bluetooth BR+EDR	G0M-1810-7783-TFC247BT-V02	Eurofins Product Service GmbH	2019-05-24
FCC 15.247 Test Report WiFi	G0M-1810-7783-TFC247WF-V01	Eurofins Product Service GmbH	2019-05-24
FCC 15.407 Test Report WiFi	G0M-1810-7783-TFC407WF-V01	Eurofins Product Service GmbH	2019-05-24
IC RSS 247 Test Report WiFi	G0M-1810-7783-TIC247WF-V01	Eurofins Product Service GmbH	2019-05-24

1.2 Standalone Radiation Sources

Mode #	Description	
Bluetooth LE	Frequency range [MHz]	2402 - 2480
	Transmission modes	GFSK
	Maximum conducted power [dBm]	3.1
	Maximum radiated power [dBm]	5.2
	Maximum transmission duty cycle [%]	64
	Antenna gain [dBi]	2.1
	Antenna diameter [cm]	1
	Assessment Frequency [MHz]	2440
Bluetooth BR+EDR	Frequency range [MHz]	2402 - 2480
	Transmission modes	GFSK / $\pi/4$ -DQPSK / 8-DPSK
	Maximum conducted power [dBm]	5.6
	Maximum radiated power [dBm]	7.7
	Maximum transmission duty cycle [%]	74
	Antenna gain [dBi]	2.1
	Antenna diameter [cm]	1
	Assessment Frequency [MHz]	2440
IEEE 802.11 2.4 GHz	Frequency range [MHz]	2412 - 2462
	Transmission modes	BPSK, QPSK, 16-QAM, 32-QAM
	Maximum conducted power [dBm]	22.9
	Maximum radiated power [dBm]	25.0
	Maximum transmission duty cycle [%]	100
	Antenna gain [dBi]	2.1
	Antenna diameter [cm]	1
	Assessment Frequency [MHz]	2437

IEEE 802.11 5 GHz	Frequency range [MHz]	5180 - 5795
	Transmission modes	BPSK, QPSK, 16-QAM, 64-QAM
	Maximum conducted power [dBm]	15.0
	Maximum radiated power [dBm]	16.5
	Maximum transmission duty cycle [%]	100
	Antenna gain [dBi]	1.5
	Antenna diameter [cm]	1
	Assessment Frequency [MHz]	5500

1.3 Multi-transmitter Modes

None

2 Result Summary

FCC 47 CFR Part 2.1091, ISED RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	PASS	
Remarks:			

3 RF-Exposure Classifications

Device Types	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)
Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

4 Assessment

4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

MPE ASSESSMENT ACC. TO 47 CFR 2.1091 / ISED RSS-102		VERDICT: PASS		
Assessment according to reference		Reference Method		
		FCC OET Bulletin 65 / RSS-102		
Device type		mobile		
Exposure category		General public		
ISED Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170	180	-	Instantaneous*
0.1-10	-	1.6 / f	-	6**
1.29-10	193 / $f^{0.5}$	-	-	6**
10-20	61.4	0.163	-10	6
20-48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	$9.40 \times 10^{-4} f^{0.5}$	$3.33 \times 10^{-4} f$	616000 / $f^{1.2}$
ISED Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	83	90	-	Instantaneous*
0.1-10	-	0.73 / f	-	6**
1.1-10	87 / $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	616000 / $f^{1.2}$
* = Based on nerve stimulation				
** = Bases on specific absorption rate				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842 / f	4.89 / f	(900 / f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f / 300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842 / f	2.19 / f	(180 / f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f / 1500	30
1500 - 100000	N/A	N/A	1.0	30

* = Plane wave equivalent power density; f in MHz

Assessment Relations
$\lambda[m] = \frac{c \left[\frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$
$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$
$P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$
$DCC [dB] = 10 \cdot \log_{10} \left(\frac{DC[\%]}{100} \right)$

Assessment procedure
For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.

4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

Assessment result - Bluetooth LE		
Transmission mode		
Operating mode frequency range [MHz]	2402 - 2480	
Assessment frequency (f) [MHz]	2440	
Transmission duty cycle (DC) [%]	64	
Peak conducted power (P _C) [dBm]	3.1	
Peak radiated power (P _R) [dBm e.i.r.p.]	5.2	
Peak Antenna gain (G) [dBi]	2.1	
Maximum Antenna Diameter D [cm]	1	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.123 m	12.30 cm
Antenna far-field distance (R _{FF})	0.002 m	0.16 cm
Power evaluation		
Peak conducted power (P _C)	2.04 mW	3.10 dBm
Peak Antenna Gain (G)	1.62	2.10 dBi
Calculated peak radiated power (P _{R-Calc})	3.31 mW	5.20 dBm
Measured peak radiated power (P _R)	3.31 mW	5.20 dBm
Source average Power		
Maximum transmission duty cycle (DC)	64.0 %	
Duty cycle correction (DCC)	0.64	-1.94 dB
Measured peak radiated power (P _R)	3.31 mW	5.20 dBm
Averaged peak radiated power (P _{RAVG})	2.12 mW	3.26 dBm
Power density		
Compliance power density limit FCC	1.000 mW/cm ²	10.00 W/m ²
Compliance power density limit ISED	0.541 mW/cm ²	5.41 W/m ²
Power density @ Antenna far-field distance	6.373 mW/cm ²	63.734 W/m ²
Power density @ 20cm	0.000 mW/cm ²	0.004 W/m ²
Distance for compliance power density FCC	0.004 m	0.41 cm
Distance for compliance power density ISED	0.006 m	0.56 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the ISED MPE limit!		
Comments:		

Assessment result - Bluetooth BR+EDR		
Transmission mode		
Operating mode frequency range [MHz]	2402 - 2480	
Assessment frequency (f) [MHz]	2440	
Transmission duty cycle (DC) [%]	74	
Peak conducted power (P _C) [dBm]	5.6	
Peak radiated power (P _R) [dBm e.i.r.p.]	7.7	
Peak Antenna gain (G) [dBi]	2.1	
Maximum Antenna Diameter D [cm]	1	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.123 m	12.30 cm
Antenna far-field distance (R _{FF})	0.002 m	0.16 cm
Power evaluation		
Peak conducted power (P _C)	3.63 mW	5.60 dBm
Peak Antenna Gain (G)	1.62	2.10 dBi
Calculated peak radiated power (P _{R-Calc})	5.89 mW	7.70 dBm
Measured peak radiated power (P _R)	5.89 mW	7.70 dBm
Source average Power		
Maximum transmission duty cycle (DC)	74.0 %	
Duty cycle correction (DCC)	0.74	-1.31 dB
Measured peak radiated power (P _R)	5.89 mW	7.70 dBm
Averaged peak radiated power (P _{RAVG})	4.36 mW	6.39 dBm
Power density		
Compliance power density limit FCC	1.000 mW/cm ²	10.00 W/m ²
Compliance power density limit ISED	0.541 mW/cm ²	5.41 W/m ²
Power density @ Antenna far-field distance	13.105 mW/cm ²	131.046 W/m ²
Power density @ 20cm	0.001 mW/cm ²	0.009 W/m ²
Distance for compliance power density FCC	0.006 m	0.59 cm
Distance for compliance power density ISED	0.008 m	0.80 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the ISED MPE limit!		
Comments:		

Assessment result - IEEE 802.11 2.4 GHz		
Transmission mode		
Operating mode frequency range [MHz]	2412 - 2462	
Assessment frequency (f) [MHz]	2437	
Transmission duty cycle (DC) [%]	100	
Peak conducted power (P _C) [dBm]	22.9	
Peak radiated power (P _R) [dBm e.i.r.p.]	25.0	
Peak Antenna gain (G) [dBi]	2.1	
Maximum Antenna Diameter D [cm]	1	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.123 m	12.31 cm
Antenna far-field distance (R _{FF})	0.002 m	0.16 cm
Power evaluation		
Peak conducted power (P _C)	194.98 mW	22.90 dBm
Peak Antenna Gain (G)	1.62	2.10 dBi
Calculated peak radiated power (P _{R-Calc})	316.23 mW	25.00 dBm
Measured peak radiated power (P _R)	316.23 mW	25.00 dBm
Source average Power		
Maximum transmission duty cycle (DC)	100.0 %	
Duty cycle correction (DCC)	1.00	0.00 dB
Measured peak radiated power (P _R)	316.23 mW	25.00 dBm
Averaged peak radiated power (P _{RAVG})	316.23 mW	25.00 dBm
Power density		
Compliance power density limit FCC	1.000 mW/cm ²	10.00 W/m ²
Compliance power density limit ISED	0.540 mW/cm ²	5.40 W/m ²
Power density @ Antenna far-field distance	953.370 mW/cm ²	9533.703 W/m ²
Power density @ 20cm	0.063 mW/cm ²	0.629 W/m ²
Distance for compliance power density FCC	0.050 m	5.02 cm
Distance for compliance power density ISED	0.068 m	6.82 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the ISED MPE limit!		
Comments:		

Assessment result - IEEE 802.11 5 GHz		
Transmission mode		
Operating mode frequency range [MHz]	5180 - 5795	
Assessment frequency (f) [MHz]	5500	
Transmission duty cycle (DC) [%]	100	
Peak conducted power (P _C) [dBm]	15.0	
Peak radiated power (P _R) [dBm e.i.r.p.]	16.5	
Peak Antenna gain (G) [dBi]	1.5	
Maximum Antenna Diameter D [cm]	1	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.055 m	5.45 cm
Antenna far-field distance (R _{FF})	0.004 m	0.37 cm
Power evaluation		
Peak conducted power (P _C)	31.62 mW	15.00 dBm
Peak Antenna Gain (G)	1.41	1.50 dBi
Calculated peak radiated power (P _{R-Calc})	44.67 mW	16.50 dBm
Measured peak radiated power (P _R)	44.67 mW	16.50 dBm
Source average Power		
Maximum transmission duty cycle (DC)	100.0 %	
Duty cycle correction (DCC)	1.00	0.00 dB
Measured peak radiated power (P _R)	44.67 mW	16.50 dBm
Averaged peak radiated power (P _{RAVG})	44.67 mW	16.50 dBm
Power density		
Compliance power density limit FCC	1.000 mW/cm ²	10.00 W/m ²
Compliance power density limit ISED	0.943 mW/cm ²	9.43 W/m ²
Power density @ Antenna far-field distance	26.439 mW/cm ²	264.391 W/m ²
Power density @ 20cm	0.009 mW/cm ²	0.089 W/m ²
Distance for compliance power density FCC	0.019 m	1.89 cm
Distance for compliance power density ISED	0.019 m	1.94 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the ISED MPE limit!		
Comments:		