

Farpointe Data, Inc. RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Mobile-Ready Contactless Smartcard Reader, Model Tested: CSB 3500

REPORT NUMBER

104449578MPK-001A

ISSUE DATE

October 29, 2020

PAGES

9

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 104449578MPK-001A

Project Number: G104449578

Issue Date: October 29, 2020

Product Designation: Mobile-Ready Contactless Smartcard Reader

Model Tested: CSB 3500

FCC ID: T8I-CONEKT5

IC: 6504A-CONEKT5

to

47CFR 2.1091

RSS-102 Issue 5

for

Farpointe Data, Inc.

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Farpointe Data, Inc.
2195 Zanker Road
San Jose, CA 95131 USA

Report prepared by:



Anderson Soungpanya/ Project Engineer

Report reviewed by:



Krishna Vemuri / EMC Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104449578MPK-001A	
Equipment Under Test:	Mobile-Ready Contactless Smartcard Reader
Trade Name:	Farpointe Data, Inc.
Model(s) Tested:	CSB 3500
Applicant:	Farpointe Data, Inc.
Contact:	Kirk Bierach
Address:	Farpointe Data, Inc. 2195 Zanker Road San Jose, CA 95131
Country:	USA
Tel. Number:	(408) 731-8700
Email:	kirk.bierach@farpointedata.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

<i>Farpointe Data, Inc.</i>	<i>1</i>
<i>1.0 RF Exposure Summary</i>	<i>5</i>
<i>2.0 RF Exposure Limits</i>	<i>5</i>
<i>3.0 Test Results (Mobile Configuration)</i>	<i>7</i>
<i>4.0 Document History</i>	<i>9</i>

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Mobile-Ready Contactless Smartcard Reader, Model: CSB 3500 consists of two radios: 13.56 MHz RFID and Bluetooth.

3.3 Maximum RF Power

Mobile-Ready Contactless Smartcard Reader, Model: CSB 3500:

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Note
13.56	70.35	FS measurement was taken from Report # 104449578MPK-003

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2402-2480	1.97	2.1	Conducted power measurements were taken from 104449578MPK-001

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for RFID, Mobile-Ready Contactless Smartcard Reader, Model: CSB 3500:

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Peak FS @20 cm* (dBμV/m)	Peak FS @20 cm (V/m)	RSS Limit (V/m)	FCC Limit (V/m)	Results
13.56	70.35	138.31	8.23	27.46	60.77	Complies

* Distance Correction Factor was used.

3.4.2 RF Exposure calculation for Bluetooth, Mobile-Ready Contactless Smartcard Reader, Model: CSB 3500:

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Results
2402-2480	4.07	2.553	0.000508	1	Complies

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	Results
2402-2480	4.07	2.553	0.00508	5.47	Complies

Note: Antenna gains below 0 are considered as 0dBi.

Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G104449578	AS	KV	October 29, 2020	Original document