



# RADIO TEST REPORT

**Test Report No. : 13004791H-A-R2**

**Applicant** : ASAHI DENSO CO.,LTD.

**Type of Equipment** : Smart key

**Model No.** : CL9-904

**FCC ID** : T8VCL9-904

**Test regulation** : FCC Part 15 Subpart C: 2019

**Test Result** : Complied (Refer to SECTION 3.2)

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
6. The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
7. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the US Government.
8. The information provided from the customer for this report is identified in SECTION 1.
9. This report is a revised version of 13004791H-A-R1. 13004791H-A-R1 is replaced with this report.

**Date of test:** November 18, 2019

**Representative test engineer:**

Akihiko Maeda

Engineer

Consumer Technology Division

**Approved by:**

Shinichi Miyazono

Engineer

Consumer Technology Division



This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
[http://japan.ul.com/resources/emc\\_accredited/](http://japan.ul.com/resources/emc_accredited/)

This report contains data that are not covered by the NVLAP accreditation.

There is no testing item of "Non-accreditation".

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Faxsimile : +81 596 24 8124

Report Cover Page - 13-EM-F0429 Issue # 15.0

## REVISION HISTORY

### Original Test Report No.: 13004791H-A

Revision	Test report No.	Date	Page revised	Contents
- (Original)	13004791H-A	December 13, 2019	-	-
1	13004791H-A-R1	January 22, 2020	P.1	<p>Correction of note 7.</p> <p>From:</p> <p>This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.</p> <p>To:</p> <p>This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the US Government.</p>
1	13004791H-A-R1	January 22, 2020	P.1	<p>Correction of note for the application scope.</p> <p>From:</p> <p>The testing in which “Non-accreditation” is displayed is outside the accreditation scopes in UL Japan.</p> <p>To:</p> <p>This report contains data that are not covered by the NVLAP accreditation.</p>
1	13004791H-A-R1	January 22, 2020	P.9	Addition of the software information in Clause 4.1.
1	13004791H-A-R1	January 22, 2020	P.11	<p>Correction of the Test Volume (1 GHz – 10 GHz) in Test Setup figure.</p> <p>From:</p> <p>Test Volume : 1.0 m</p> <p>To:</p> <p>Test Volume : 2.0 m</p>
2	13004791H-A-R2	January 30, 2020	P.9	Addition of the note *1) and Software information for Normal use mode to Clause 4.1.
2	13004791H-A-R2	January 30, 2020	P.9	Correction of the configuration diagram in Clause 4.2.
2	13004791H-A-R2	January 30, 2020	P.10	Correction of the configuration list and cable list in Clause 4.2.
2	13004791H-A-R2	January 30, 2020	P.14	Correction of the note sentence under the data.

## Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	MCS	Modulation and Coding Scheme
AC	Alternating Current	MRA	Mutual Recognition Arrangement
AFH	Adaptive Frequency Hopping	N/A	Not Applicable
AM	Amplitude Modulation	NIST	National Institute of Standards and Technology
Amp, AMP	Amplifier	NS	No signal detect.
ANSI	American National Standards Institute	NSA	Normalized Site Attenuation
Ant, ANT	Antenna	NVLAP	National Voluntary Laboratory Accreditation Program
AP	Access Point	OBW	Occupied Band Width
ASK	Amplitude Shift Keying	OFDM	Orthogonal Frequency Division Multiplexing
Atten., ATT	Attenuator	P/M	Power meter
AV	Average	PCB	Printed Circuit Board
BPSK	Binary Phase-Shift Keying	PER	Packet Error Rate
BR	Bluetooth Basic Rate	PHY	Physical Layer
BT	Bluetooth	PK	Peak
BT LE	Bluetooth Low Energy	PN	Pseudo random Noise
BW	BandWidth	PRBS	Pseudo-Random Bit Sequence
Cal Int	Calibration Interval	PSD	Power Spectral Density
CCK	Complementary Code Keying	QAM	Quadrature Amplitude Modulation
Ch., CH	Channel	QP	Quasi-Peak
CISPR	Comite International Special des Perturbations Radioelectriques	QPSK	Quadri-Phase Shift Keying
CW	Continuous Wave	RBW	Resolution Band Width
DBPSK	Differential BPSK	RDS	Radio Data System
DC	Direct Current	RE	Radio Equipment
D-factor	Distance factor	RF	Radio Frequency
DFS	Dynamic Frequency Selection	RMS	Root Mean Square
DQPSK	Differential QPSK	RSS	Radio Standards Specifications
DSSS	Direct Sequence Spread Spectrum	Rx	Receiving
EDR	Enhanced Data Rate	SA, S/A	Spectrum Analyzer
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	SG	Signal Generator
EMC	ElectroMagnetic Compatibility	SVSWR	Site-Voltage Standing Wave Ratio
EMI	ElectroMagnetic Interference	TR	Test Receiver
EN	European Norm	Tx	Transmitting
ERP, e.r.p.	Effective Radiated Power	VBW	Video BandWidth
EU	European Union	Vert.	Vertical
EUT	Equipment Under Test	WLAN	Wireless LAN
Fac.	Factor		
FCC	Federal Communications Commission		
FHSS	Frequency Hopping Spread Spectrum		
FM	Frequency Modulation		
Freq.	Frequency		
FSK	Frequency Shift Keying		
GFSK	Gaussian Frequency-Shift Keying		
GNSS	Global Navigation Satellite System		
GPS	Global Positioning System		
Hori.	Horizontal		
ICES	Interference-Causing Equipment Standard		
IEC	International Electrotechnical Commission		
IEEE	Institute of Electrical and Electronics Engineers		
IF	Intermediate Frequency		
ILAC	International Laboratory Accreditation Conference		
ISED	Innovation, Science and Economic Development Canada		
ISO	International Organization for Standardization		
JAB	Japan Accreditation Board		
LAN	Local Area Network		
LIMS	Laboratory Information Management System		

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer information.....</b>	<b>5</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>5</b>
<b>SECTION 3: Test specification, procedures &amp; results.....</b>	<b>6</b>
<b>SECTION 4: Operation of E.U.T. during testing.....</b>	<b>9</b>
<b>SECTION 5: Radiated emission (Electric Field Strength of Fundamental and Spurious Emission).....</b>	<b>11</b>
<b>SECTION 6: Automatically deactivate .....</b>	<b>13</b>
<b>SECTION 7: -20 dB and 99 % Occupied Bandwidth .....</b>	<b>13</b>
<b>APPENDIX 1: Test data .....</b>	<b>14</b>
Automatically deactivate.....	14
Radiated Emission (Electric Field Strength of Fundamental and Spurious Emission).....	15
-20dB and 99% Occupied Bandwidth.....	17
<b>APPENDIX 2: Test instruments .....</b>	<b>18</b>
<b>APPENDIX 3: Photographs of test setup .....</b>	<b>19</b>
Radiated emission .....	19
Worst case position .....	21

## **SECTION 1: Customer information**

Company Name : ASAHI DENSO CO.,LTD.  
Address : 6-2-1 Somejidai, Hamakita-ku, Hamamatsu, Shizuoka 434-0046, Japan  
Telephone Number : +81-53-586-7383  
Facsimile Number : +81-53-584-1589  
Contact Person : Tomohiro Yaguchi

The information provided from the customer is as follows;

- Applicant, Type of Equipment, Model No. FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer information
- SECTION 2: Equipment under test (E.U.T.)
- SECTION 4: Operation of E.U.T. during testing

\* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment : Smart key  
Model No. : CL9-904  
Serial No. : Refer to Section 4, Clause 4.2  
Rating : DC 3.0 V  
Receipt Date of Sample : November 18, 2019  
(Information from test lab.)  
Country of Mass-production : Japan  
Condition of EUT : Production prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Modification of EUT : No Modification by the test lab

### **2.2 Product Description**

Model: CL9-904 (referred to as the EUT in this report) is a Smart key.

### **Radio Specification**

Radio Type : Transceiver  
Frequency of Operation : 433.92 MHz  
Modulation : FSK  
Antenna type : Pattern Antenna  
Clock frequency (Maximum) : 13.56 MHz

Radio Type : Receiver  
Frequency of Operation : 134.2 kHz

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## SECTION 3: Test specification, procedures & results

### 3.1 Test Specification

Test Specification : FCC Part 15 Subpart C  
 FCC Part 15 final revised on July 19, 2019 and effective August 19, 2019 except 15.258

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
 Section 15.231 Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

\* Also the EUT complies with FCC Part 15 Subpart B.

### 3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted emission	FCC: ANSI C63.10:2013 6 Standard test methods	FCC: Section 15.207	N/A	N/A	*1)
	ISED: RSS-Gen 8.8	ISED: RSS-Gen 8.8			
Automatically Deactivate	FCC: ANSI C63.10:2013 6 Standard test methods	FCC: Section 15.231(a)(1)	N/A	Complied a)	Radiated
	ISED: -	ISED: RSS-210 A1.1			
Electric Field Strength of Fundamental Emission	FCC: ANSI C63.10:2013 6 Standard test methods	FCC: Section 15.231(b)	15.32 dB 433.920 MHz Vertical PK with Duty Factor	Complied b)	Radiated
	ISED: RSS-Gen 6.12	ISED: RSS-210 A1.2			
Electric Field Strength of Spurious Emission	FCC: ANSI C63.10:2013 6 Standard test methods	FCC: Section 15.205 Section 15.209 Section 15.231(b)	5.07 dB 867.840 MHz Horizontal PK with Duty Factor	Complied# b)	Radiated
	ISED: RSS-Gen 6.13	ISED: RSS-210 A1.2, 4.4 RSS-Gen 8.9			
-20dB Bandwidth	FCC: ANSI C63.10:2013 6 Standard test methods	FCC: Section 15.231(c)	N/A	Complied c)	Radiated
	ISED: -	ISED: Reference data			

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

\*1) The test is not applicable since the EUT does not have AC Mains.

a) Refer to APPENDIX 1 (data of Automatically deactivate)

b) Refer to APPENDIX 1 (data of Radiated Emission (Electric Field Strength of Fundamental and Spurious Emission))

c) Refer to APPENDIX 1 (data of -20dB and 99% Occupied Bandwidth)

Symbols:

Complied The data of this test item has enough margin, more than the measurement uncertainty.

Complied# The data of this test item meets the limits unless the measurement uncertainty is taken into consideration.

### FCC Part 15.31 (e)

This test was performed with the New Battery (DC 3.0 V) and the constant voltage was supplied to the EUT during the tests. Therefore, the EUT complies with the requirement.

### FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Faxsimile : +81 596 24 8124

### 3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99 % Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: RSS-210 A1.3	N/A	-	Radiated
Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.					

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

There is no applicable rule of uncertainty in this applied standard. Therefore, the following results are derived depending on whether or not laboratory uncertainty is applied.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

#### Radiated emission

Measurement distance	Frequency range	Uncertainty (+/-)
3 m	9 kHz to 30 MHz	3.3 dB
		3.2 dB
3 m	30 MHz to 200 MHz (Horizontal)	4.8 dB
	(Vertical)	5.0 dB
	200 MHz to 1000 MHz (Horizontal)	5.2 dB
	(Vertical)	6.3 dB
10 m	30 MHz to 200 MHz (Horizontal)	4.8 dB
	(Vertical)	4.8 dB
	200 MHz to 1000 MHz (Horizontal)	5.0 dB
	(Vertical)	5.0 dB
3 m	1 GHz to 6 GHz	4.9 dB
	6 GHz to 18 GHz	5.2 dB
1 m	10 GHz to 26.5 GHz	5.5 dB
	26.5 GHz to 40 GHz	5.5 dB
10 m	1 GHz to 18 GHz	5.2 dB

#### Antenna Terminal test

Test Item	Uncertainty (+/-)
Automatically Deactivate	0.10 %
-20dB Emission Bandwidth / 99 % Occupied Bandwidth	0.96 %

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

\*NVLAP Lab. code: 200572-0 / FCC Test Firm Registration Number: 199967 / ISED Lab Company Number: 2973C

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.11 measurement room	6.2 x 4.7 x 3.0	4.8 x 4.6	-	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0 m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

---

**UL Japan, Inc.**  
**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## SECTION 4: Operation of E.U.T. during testing

### 4.1 Operating Mode(s)

Test Item*	Mode
Automatically Deactivate	1) Normal use mode *1)
Electric Field Strength of Fundamental Emission	2) Transmitting mode (Tx)
Electric Field Strength of Spurious Emission	
-20 dB & 99 % Occupied Bandwidth	

\* The system was configured in typical fashion (as a user would normally use it) for testing.  
 \*1) Once UHF transmission from Steering Lock operating.


\*EUT was set by the software as follows;

Software for Transmitting mode : CL9-085\_V0100 Version 1.00  
 (Date: 2019.11.18, Storage location: U1)

Software for Normal use mode: CL9-085\_RFLoop Version 1.00  
 (Date: 2019.11.18, Storage location: U1)

\*This setting of software is the worst case.  
 Any conditions under the normal use do not exceed the condition of setting.  
 In addition, end users cannot change the settings of the output power of the product.

### 4.2 Configuration and peripherals



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

**Description of EUT and Support equipment**

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Smart key	CL9-904	19462671911180001 *1) 19462671911180003 *2)	ASAHI DENSO CO.,LTD.	EUT
B	Switch	CL9-LUB	9Y18	ASAHI DENSO CO.,LTD.	*1)
C	LF Antenna	CZ162A	9522	ASAHI DENSO CO.,LTD.	*1)
D	Steering Lock	CL9	19462661911180001	ASAHI DENSO CO.,LTD.	*1)

**List of cables used**

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	1.0	Unshielded	Unshielded	*1)
2	Signal Cable	0.5	Unshielded	Unshielded	*1)
3	Signal Cable	0.5	Unshielded	Unshielded	*1)

\*1) Used for Normal use mode

\*2) Used for Transmitting mode

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 5: Radiated emission (Electric Field Strength of Fundamental and Spurious Emission)**

### **Test Procedure and conditions**

[For below 30 MHz]

The noise level was checked by moving a search-coil (Loop Antenna) close to the EUT.

[For 30 MHz to 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The measuring antenna height was varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detector function of the test receiver / spectrum analyzer.


### **Test Antennas are used as below:**

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn


	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz
Detector Type	Peak	Peak	Peak	Peak	Peak and Peak with Duty factor	Peak and Peak with Duty factor
IF Bandwidth	200 Hz	200 Hz	9.0 kHz	9.0 kHz	120 kHz	PK: S/A: RBW 1 MHz, VBW: 3 MHz

## [Test Setup]

Below 1 GHz



1 GHz - 10 GHz



- The carrier level (or, noise levels) was (or were) measured at each position of all three axes X, Y and Z, and the position that has the maximum noise was determined.

Noise levels of all the frequencies were measured at the position.

\*The result is rounded off to the second decimal place, so some differences might be observed.

**Measurement range**

: 9 kHz - 4.4 GHz

**Test data**

: APPENDIX

**Test result**

: Pass

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 6: Automatically deactivate**

### **Test Procedure**

The measurement was performed with Electric field strength using a spectrum analyzer.

**Test data** : APPENDIX  
**Test result** : Pass

## **SECTION 7: -20 dB and 99 % Occupied Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
20 dB Bandwidth	150 kHz	1.5 kHz	5.1 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99 % Occupied Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer

Peak hold was applied as Worst-case measurement.


**Test data** : APPENDIX  
**Test result** : Pass

## APPENDIX 1: Test data

### Automatically deactivate

Report No. 13004791H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.3  
Date November 18, 2019  
Temperature / Humidity 22 deg. C / 36 % RH  
Engineer Akihiko Maeda  
Mode Mode 1

Time of Transmitting [sec]	Limit [sec]	Result
0.1686	5.00	Pass



\* The test was performed with Steering Lock operating since the EUT only transmits UHF when LF signal is received from a vehicle.

Please refer to the "Theory of Operation" for details.

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radiated Emission (Electric Field Strength of Fundamental and Spurious Emission)

Report No. 13004791H  
 Test place Ise EMC Lab.  
 Semi Anechoic Chamber No.3  
 Date November 18, 2019  
 Temperature / Humidity 22 deg. C / 36 % RH  
 Engineer Akihiko Maeda  
 Mode Mode 2

### PK

Frequency [MHz]	Detector	Reading [dBuV]		Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]		Limit [dBuV/m]	Margin [dB]		Remark Inside or Outside of Restricted Bands
		Hor	Ver					Hor	Ver		Hor	Ver	
433.920	PK	69.20	70.30	16.24	10.89	31.95	-	64.38	65.48	100.8	36.42	35.32	Carrier
867.840	PK	51.70	48.20	21.80	13.34	31.11	-	55.73	52.23	80.8	25.07	28.57	Outside
1301.760	PK	44.29	43.27	25.40	5.99	34.62	-	41.06	40.04	73.9	32.84	33.86	Inside
1735.680	PK	45.41	43.85	25.04	5.53	33.57	-	42.41	40.85	80.8	38.39	39.95	Outside
2169.600	PK	43.36	42.27	28.06	5.57	32.85	-	44.14	43.05	80.8	36.66	37.75	Outside
2603.520	PK	43.77	43.51	27.70	5.72	32.65	-	44.54	44.28	80.8	36.26	36.52	Outside
3037.440	PK	43.11	44.47	28.70	5.87	32.44	-	45.24	46.60	80.8	35.56	34.20	Outside
3471.360	PK	42.12	40.80	28.70	6.03	32.25	-	44.60	43.28	80.8	36.20	37.52	Outside
3905.280	PK	41.30	40.37	29.73	6.20	32.06	-	45.17	44.24	73.9	28.73	29.66	Inside
4339.200	PK	39.90	41.68	30.28	6.38	31.94	-	44.62	46.40	73.9	29.28	27.50	Inside

### PK with Duty factor

Frequency [MHz]	Detector	Reading [dBuV]		Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]		Limit [dBuV/m]	Margin [dB]		Remark
		Hor	Ver					Hor	Ver		Hor	Ver	
433.920	PK	69.20	70.30	16.24	10.89	31.95	0.0	64.38	65.48	80.8	16.42	15.32	Carrier
867.840	PK	51.70	48.20	21.80	13.34	31.11	0.0	55.73	52.23	60.8	5.07	8.57	Outside
1301.760	PK	44.29	43.27	25.40	5.99	34.62	0.0	41.06	40.04	53.9	12.84	13.86	Inside
1735.680	PK	45.41	43.85	25.04	5.53	33.57	0.0	42.41	40.85	60.8	18.39	19.95	Outside
2169.600	PK	43.36	42.27	28.06	5.57	32.85	0.0	44.14	43.05	60.8	16.66	17.75	Outside
2603.520	PK	43.77	43.51	27.70	5.72	32.65	0.0	44.54	44.28	60.8	16.26	16.52	Outside
3037.440	PK	43.11	44.47	28.70	5.87	32.44	0.0	45.24	46.60	60.8	15.56	14.20	Outside
3471.360	PK	42.12	40.80	28.70	6.03	32.25	0.0	44.60	43.28	60.8	16.20	17.52	Outside
3905.280	PK	41.30	40.37	29.73	6.20	32.06	0.0	45.17	44.24	53.9	8.73	9.66	Inside
4339.200	PK	39.90	41.68	30.28	6.38	31.94	0.0	44.62	46.40	53.9	9.28	7.50	Inside

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Sample calculation:

Result of PK = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1GHz) +Distance factor (above 1 GHz)} - Gain (Amplifier)

Result of PK with Duty factor = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) +Distance factor (above 1 GHz)} - Gain (Amplifier) + Duty factor

For above 1GHz : Distance Factor:  $20 \times \log (4.0 \text{ m}/3.0 \text{ m}) = 2.50 \text{ dB}$

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Since the peak emission result satisfied the average limit, duty factor was omitted.

Although Duty of this product was 100% or less, the result of AV (PK with Duty factor) was calculated by applying Duty 100% as worst.

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radiated Spurious Emission (Plot data, Worst case)

Report No. 13004791H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.3  
Date November 18, 2019  
Temperature / Humidity 22 deg. C / 36 % RH  
Engineer Akihiko Maeda  
Mode Mode 2



\*These plots data contains sufficient number to show the trend of characteristic features for EUT.

## -20dB and 99% Occupied Bandwidth


Report No. 13004791H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.3  
Date November 18, 2019  
Temperature / Humidity 22 deg. C / 36 % RH  
Engineer Akihiko Maeda  
Mode Mode 2

Bandwidth Limit : Fundamental Frequency **433.92** MHz x 0.25% = 1084.80 kHz

\* The above limit was calculated from more stringent nominal frequency.

-20dB Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
39.746	1084.80	Pass

99% Occupied Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
59.7459	1084.80	Pass



## APPENDIX 2: Test instruments

### Test Instruments

Test item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Calibration Due Date	Cal Int
RE	141507	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	258	09/26/2019	09/30/2020	12
RE	178648	EMI measurement program	TSJ	TEPTO-DV	-	-	-	-
RE	177964	Microwave Cable	Junkosha INC.	MMX221	1901S329(1m)/1902S579(5m)	03/05/2019	03/31/2020	12
RE	141297	High Pass Filter(1.1-10GHz)	TOKYO KEIKI	TF219CD1	1001	01/10/2019	01/31/2020	12
RE	141580	MicroWave System Amplifier	AGILENT	83017A	MY39500779	03/05/2019	03/31/2020	12
RE	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/08/2019	02/29/2020	12
RE	141323	Coaxial cable	UL Japan	-	-	07/02/2019	07/31/2020	12
RE	141266	Logperiodic Antenna(200-1000MHz)	Schwarzbeck	VUSLP9111B	9111B-191	08/24/2019	08/31/2020	12
RE	141424	Biconical Antenna	Schwarzbeck	VHA9103+ BBA9106	1915	08/24/2019	08/31/2020	12
RE	142314	Attenuator	Pasternack	PE7390-6	D/C 1504	06/11/2019	06/30/2020	12
RE	142013	AC3_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/08/2019	04/30/2021	24
RE	141901	Spectrum Analyzer	AGILENT	E4440A	MY48250080	10/06/2019	10/31/2020	12
RE	141949	Test Receiver	Rohde & Schwarz	ESCI	100767	08/02/2019	08/31/2020	12
RE	142008	AC3_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	06/26/2018	06/30/2020	24
RE	141554	Thermo-Hygrometer	CUSTOM	CTH-180	1301	01/11/2019	01/31/2020	12
RE	141532	DIGITAL HITESTER	HIOKI	3805	51201197	01/29/2019	01/31/2020	12
RE	142183	Measure	KOMELON	KMC-36	-	-	-	-
RE	142236	Antenna Tilt Jig	Intelligent System Engineering Co., Ltd	Antenna Tilt Jig	T-0001	-	-	-
RE	142645	Loop Antenna	UL Japan	-	-	-	-	-

\*Hyphens for Last Calibration Date, Calibration Due Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

#### Test item:

RE: Radiated emission, 99 % Occupied Bandwidth, -20 dB bandwidth, and Automatically deactivate tests

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124