



Product Service

**Choose certainty.
Add value.**

Report On

RF Exposure Assessment of the
Crane Electronics Ltd
RF-m Torque Transducer

FCC ID:TA6RFMT1
IC:

Document 75928950 Report 05 Issue 1

May 2015



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON

RF Exposure Assessment of the
Crane Electronics Ltd
RF-m Torque Transducer


Document 75928950 Report 05 Issue 1

May 2015

PREPARED FOR

Crane Electronics Ltd
Watling Drive
Sketchley Meadows
Hinckley
LE10 3EY

PREPARED BY



Sarah Jones
Senior Engineer (Projects)

APPROVED BY



Simon Bennett
Authorised Signatory

DATED

3 June 2015



Product Service

CONTENTS

Section	Page No
1 REPORT SUMMARY	3
1.1 Introduction	4
1.2 Regional Requirements	5
1.3 Product Information	6
1.3.1 Technical Description	6
1.3.2 Supported Features	6
1.3.3 Antennas.....	6
1.4 Brief Summary of Results	7
2 TEST DETAILS	9
2.1 Rationale for Assessment of the RF Exposure	10
2.2 Test Result Details.....	11
3 DISCLAIMERS AND COPYRIGHT.....	12
3.1 Disclaimers and Copyright.....	13



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Crane Electronics Ltd
RF-m Torque Transducer



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Crane Electronics Ltd RF-m Torque Transducer to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Crane Electronics Ltd
Manufacturer	Crane Electronics Ltd
Manufacturing Description	Torque Transducer
Model Number(s)	RF-m
Test Specification/Issue/Date	Council Recommendation 1999/519/EC CFR 47 Pt1.1310 Health Canada Safety Code 6 ARPANSA Radiation Protection Series No.3



Product Service

1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
EU	Council Recommendation 1999/519/EC
FCC	CFR 47 Pt1.1310
IC	Health Canada Safety Code 6
AUS	ARPANSA Radiation Protection Series No.3



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment under test was a Crane Electronics Ltd RF-m Torque Transducer. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the RF-m Torque Transducer to demonstrate compliance with the applied test specification(s) the sample assessed was found to comply with the requirements of the applied rules.

1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	SRD
Frequency Band	2400 - 2483.5 MHz

1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain (dBi)
1	SRD	1



Product Service

1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.2	0.2

Table 1 – Compliance Boundary Results



Product Service

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m ²)		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
EU	0.00030	50.0000	0.3073	137.0000	0.0008	0.3630
FCC*	0.00003	5.0000	N/A	N/A	N/A	N/A
IC	0.00030	50.0000	0.3073	137.0000	0.0008	0.3640
AUS	0.00030	50.0000	0.3073	137.0000	0.0008	0.3640

* Requirement and Result in mW/cm²

Table 2 – Occupational Results

The calculations show that the EUT complies with the occupational exposure levels described in the Council Recommendation 1999/519/EC, CFR 47 Pt1.1310, Health Canada Safety Code 6 and ARPANSA Radiation Protection Series No.3 at the point of investigation, 0.2 m.

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m ²)		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
EU	0.00030	10.0000	0.3073	61.0000	0.0008	0.1620
FCC*	0.00000	1.0000	N/A	N/A	N/A	N/A
IC	0.00030	10.0000	0.3073	61.4000	0.0008	0.1630
AUS	0.00030	10.0000	0.3073	61.4000	0.0008	0.1630

* Requirement and Result in mW/cm²

Table 3 – General Population Results

The calculations show that the EUT complies with the occupational exposure levels described in the Council Recommendation 1999/519/EC, CFR 47 Pt1.1310, Health Canada Safety Code 6 and ARPANSA Radiation Protection Series No.3 at the point of investigation, 0.2 m.



Product Service

SECTION 2

TEST DETAILS



Product Service

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The RF-m Torque Transducer operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_o}$$

Where:

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

$\eta_o = 377$



Product Service

2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field	E Field	H Field
1	1	1	SRD	0.000	10	1	2400.5	0.0003	0.3073	0.0008

Table 4 – Occupational Transmitter Summary

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field	E Field	H Field
1	1	1	SRD	0.000	10	1	2400.5	0.0003	0.3073	0.0008

Table 5 – General Population Transmitter Summary



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2015 TÜV SÜD Product Service



Product Service

ANNEX A

REGIONAL REQUIREMENTS



Product Service

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.065 - 1	-	610/f	1.6/f
1 - 10	-	610/f	1.6/f
10 - 400	10	61	0.162
400 - 2000	f/40	3*f^0.5	0.00796*f^0.5
2000 - 300000	50	137	0.363

Table A.1 – Council Recommendation 1999/519/EC Occupational Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.003 - 0.15	-	87	5
0.15 - 1	-	87/f	0.73/f
1 - 10	-	87/f^0.5	0.73/f
10 - 400	2	27	0.071
400 - 2000	f/200	1.375*f^0.5	0.00364*f^0.5
2000 - 300000	10	61	0.162

Table A.2 – Council Recommendation 1999/519/EC General Population Limits

Frequency Range (MHz)	S Field (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	900/f^2	1842/f	4.89/f
30 - 300	1	61.4	0.163
300 - 1500	f/300	-	-
1500 - 100000	5	-	-

Table A.3 – CFR 47 Pt1.1310 Occupational Limits

Frequency Range (MHz)	S Field (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	180/f^2	824/f	2.19/f
30 - 300	0.2	27.5	0.073
300 - 1500	f/1500	-	-
1500 - 100000	1	-	-

Table A.4 – CFR 47 Pt1.1310 General Population Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.003 - 1	-	600	4.9
1 - 10	-	600/f	4.9/f
10 - 30	-	60	4.9/f
30 - 300	10	60	0.163
300 - 1500	f/30	3.54*f^0.5	0.0094*f^0.5
1500 - 150000	50	137	0.364

Table A.5 – Health Canada Safety Code 6 Occupational Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.003 - 1	-	280	2.19
1 - 10	-	280/f	2.19/f
10 - 30	-	28	2.19/f
30 - 300	2	28	0.073
300 - 1500	f/150	1.585*f^0.5	0.0042*f^0.5
1500 - 150000	10	61.4	0.163

Table A.6 – Health Canada Safety Code 6 General Population Limits



Product Service

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.1 - 1	-	614	1.63/f
1 - 10	1000/f ²	614	1.63/f
10 - 400	10	61.4	0.163
400 - 2000	f/40	3.07*f ^{0.5}	0.00814*f ^{0.5}
2000 - 300000	50	137	0.364

Table A.7 – ARPANSA Radiation Protection Series No.3 Occupational Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.1 - 0.15	-	86.8	4.86
0.15 - 1	-	86.8	0.729/f
1 - 10	-	86.8/f ^{0.5}	0.729/f
10 - 400	2	27.4	0.0729
400 - 2000	f/200	1.37*f ^{0.5}	0.00364*f ^{0.5}
2000 - 300000	10	61.4	0.163

Table A.8 – ARPANSA Radiation Protection Series No.3 General Population Limits