

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 1 of 74

Applicant : AiRISTA Flow, Inc.
Address of Applicant : 1966 Greenspring Drive, Suite 125
Timonium, Maryland 21093.

Product Name : Personnel Display Tag
Brand Name : Airista
Model Name : B6
Sample Acquisition Method : Sent by Client
Sample No. : E24120036-01#02
E24120036-01#04

FCC ID : TA7-B6
ISED Number : 26357-B6

Standards : FCC CFR47 Part 15.247, Subpart C
RSS-Gen (Issue 5, Amd.2-Feb 2021)
RSS-247 (Issue 3, August 2023)

Date of Receipt : 2024-12-19
Date of Test : 2024-12-19~ 2025-04-11
Date of Issue : 2025-04-14

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by: Erik Yang
(Erik Yang)

Reviewed by: Jennifer Zhou
(Jennifer Zhou)

Approved by: Echo Mu
(Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE24120036-02DE Date: 2025-04-14 Page 2 of 74

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
3.3	SUPPORT SOFTWARE	9
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement</i>	11
4.1.2	<i>Maximum conducted (average) output power and E.I.R.P</i>	12
4.1.3	<i>6dB Bandwidth and 99% Bandwidth</i>	14
4.1.4	<i>Maximum conducted output power spectral density</i>	27
4.1.5	<i>Conducted Spurious Emission & Authorized-band band-edge</i>	34
4.1.6	<i>Radiated Emission</i>	57
4.1.7	<i>Band Edge (Restricted-band band-edge)</i>	58
4.2	MAINS EMISSIONS	59
4.2.1	<i>Conducted Emission on AC Mains</i>	59
5	APPENDIXES	62
5.1	PHOTOGRAPHS OF THE SAMPLE	62
5.2	SET-UP FOR CONDUCTED EMISSIONS	73
5.3	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	73
5.4	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	74
5.5	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	74

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 3 of 74

1 General Information

1.1 Testing Laboratory

ISED CAB identifier #	CN0081
Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd.
Address	No.1298 Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	AiRISTA Flow, Inc.
Address	1966 Greenspring Drive, Suite 125 Timonium, Maryland 21093.
Contact Person	Patrick Jenkins
Telephone	(443) 212-4251
Email	Patrick.Jenkins@Airista.com
Manufacturer Company Name	AiRISTA Flow, Inc.
Address	1966 Greenspring Drive, Suite 125 Timonium, Maryland 21093.
Factory Company Name	AiRISTA Flow, Inc.
Address	1966 Greenspring Drive, Suite 125 Timonium, Maryland 21093.

1.3 Details of EUT

Product Name	Personnel Display Tag
Brand Name	Airista
Test Model Name	B6
FCC ID	TA7-B6
ISED Number	26357-B6
Mode of Operation	WIFI 802.11b/g/n(HT20/40)
Conducted (average) output power	IEEE 802.11b: 14.99dBm IEEE 802.11g: 14.15dBm IEEE 802.11n(20): 13.29dBm IEEE 802.11n(40):12.47dBm
Frequency Range	2412MHz ~ 2462MHz
Channel Separation	5 MHz
Number of channels	11
Modulation Type	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n(20M/40M): OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	PCB Antenna

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 4 of 74

Antenna Gain	0.50dBi
Extreme Temperature Range	0℃~ +50℃
Test Voltage	DC 3.8V
Hardware Version	1.0.0
Software Version	1.0.0
RF power setting in TEST SW	802.11b: AmebaD_mptool_2V2_Power level setting_90 802.11g: AmebaD_mptool_2V2_Power level setting_84 for low/middle channel AmebaD_mptool_2V2_Power level setting_90 for high channel 802.11n(HT20): AmebaD_mptool_2V2_Power level setting_78 for low channel AmebaD_mptool_2V2_Power level setting_86 for middle/high channel 802.11n(HT40): AmebaD_mptool_2V2_Power level setting_78

Note:

1. The above information was declared by the manufacture.
2. For more details, please refer to the User's manual of the EUT.

Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2.412GHz	5	2.432GHz	9	2.452GHz
2	2.417GHz	6	2.437GHz	10	2.457GHz
3	2.422GHz	7	2.442GHz	11	2.462GHz
4	2.427GHz	8	2.447GHz		

Note:

For 20MHz bandwidth system use Channel 1 to Channel 11

For 40MHz bandwidth system use Channel 3 to Channel 9

1.4 Test Methodology

47 CFR Part 15, Subpart C	Telecommunication-Radio Frequency Devices-Intentional Radiators
KDB Publication 558074 D01 v05r02	15.247 Meas Guidance.
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
RSS-Gen (Issue 5, Amd.2-Feb 2021)	General Requirements for Compliance of Radio Apparatus
RSS-247 (Issue 3, August 2023)	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test.

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 5 of 74

1.5 Test Summary

Test Item	FCC Rules	ISED RULES	Result
Antenna Requirement	FCC Part 15.247(b)(4), Part 15.203	RSS-247 5.4(f) RSS-GEN 6.8	PASS
Maximum conducted (average) output power and E.I.R.P	FCC Part 15.247(b)(3)	RSS-247 5.4(d)	PASS
6dB Bandwidth and 99% Bandwidth	FCC Part 15.247(a)(2)	RSS-247 5.2(a) RSS-Gen 6.7	PASS
Maximum conducted output power spectral density	FCC Part 15.247(e)	RSS-247 5.2(b)	PASS
Conducted Spurious Emission & Authorized-band band-edge	FCC Part 15.247(d)	RSS-247 5.5	PASS
Radiated Emission	FCC Part 15.247(d), 15.205, 15.209	RSS-GEN 8.9	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.247(d), 15.205, 15.209	RSS-GEN 8.10	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	RSS-Gen 8.8	PASS

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 6 of 74

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	15-35
Humidity (%RH)	30-60
Barometric Pressure (mbar)	860-1060

Note: Actual values will be recorded during the test.

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020B	MY59260184	2024-06-26	2025-06-25
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2024-06-04	2025-06-03
Signal Generator	Rohde & Schwarz	SMR27	100184	2024-06-26	2025-06-25
USB Wideband Power Sensor	Keysight	U2021XA	MY57200011	2024-11-09	2025-11-08
USB Wideband Power Sensor	Keysight	U2021XA	MY56090008	2024-11-09	2025-11-08
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2024-06-05	2025-06-04
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2024-06-04	2025-06-03
V-network	SCHWARZBECK	NSLK 8127	8127-902	2024-06-05	2025-06-04
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2024-06-05	2025-06-04
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2023-03-22	2025-03-21
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2025-03-24	2027-03-23
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2023-06-13	2025-06-12
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2023-06-09	2025-06-08
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2023-06-18	2025-06-17
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2024-06-04	2025-06-03
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2023-06-09	2025-06-08
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2023-06-09	2025-06-08
Test Software	BL	BL410_E	Version:2.1.1.436	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 7 of 74

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission		$\pm 1.04\text{dB}$
Radiated Emission	< 1GHz	$\pm 5.00\text{dB}$
	> 1GHz	$\pm 5.46\text{dB}$
Conducted Emission on AC Mains	150kHz-30MHz	$\pm 3.36\text{dB}$
Occupied Channel Bandwidth		$\pm 39.26\text{KHz}$
Maximum Conducted Output Power		$\pm 1.06\text{dB}$
Maximum Conducted Output Power Spectral Density		$\pm 1.12\text{dB}$

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 8 of 74

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software to control EUT work in continuous transmitting mode. Select test channel as below:

For 802.11b/g/n (HT20)

Channel	Frequency
The lowest channel (CH1)	2412MHz
The middle channel (CH6)	2437MHz
The highest channel (CH11)	2462MHz

For 802.11n(HT40)

Channel	Frequency
The lowest channel (CH3)	2422MHz
The middle channel (CH6)	2437MHz
The highest channel (CH9)	2452MHz

Through Pre-scan under all rate at lowest channel, the data rate as below table described is the worst case, so we choose these data rate for test.

Type	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(20M)	MCS0
802.11n(40M)	MCS0

The basic operation modes are:

- A. On
 - 1. WLAN mode
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
- B. Standby
- C. Off

TEST REPORT

3.2 Special Accessories and Auxiliary Equipment


Description	Manufacturer	Model Name	Serial No.
Laptop-1	Lenovo	TP00083A	PF-0PRDGN 17/03
Laptop-2	HP	HP ZHAN 66 Pro G1	5CD7438R1J
Adapter	AOHAI	A8-501000	2017030060611
USB Cable	UGREEN	N/A	1.00m Unshielded
Debugging Box	TI	LAUNCHXL-CC26X2R1	LAUNCHXL-CC26X2R1

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	AmebaD_mptool_2V2

3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

TEST REPORT

Diagram of Measurement Equipment Configuration for Conduction Measurement




Diagram of Measurement Equipment Configuration for Transmitter Measurement





Diagram of Measurement Equipment Configuration for conducted output power setup



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 11 of 74

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard	: FCC Part 15.247(b)(4), Part 15.203 RSS-247 5.4(f), RSS-GEN 6.8
Requirement	: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 0.50dBi. The antenna is an internal antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 12 of 74

4.1.2 Maximum conducted (average) output power and E.I.R.P

RESULT:

PASS

Test standard : FCC Part 15.247(b)(3), RSS-247 5.4(d)
Requirement : ANSI C63.10-2013, Clause 11.9.2.3
KDB 558074 D01 v05r02, Clause 8.3.2
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.4°C
Relative humidity : 46%

Table 1: Maximum conducted (average) output power

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum conducted (average) output power		Limit (W)
			(dBm)	(mW)	
802.11b	100	2412	14.99	31.55	≤1
		2437	14.34	27.16	
		2462	14.46	27.93	
802.11g	100	2412	14.15	26.00	
		2437	14.01	25.18	
		2462	14.06	25.47	
802.11n(HT20)	100	2412	13.01	20.00	
		2437	13.29	21.33	
		2462	12.52	17.86	
802.11n(HT40)	100	2422	12.47	17.66	
		2437	12.19	16.56	
		2452	11.91	15.52	

Notes:

1. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 13 of 74

Table 2: E.I.R.P

Test Mode	Test Channel (MHz)	E.I.R.P		Limit (W)
		(dBm)	(mW)	
802.11b	2412	15.49	35.40	< 4
	2437	14.84	30.48	
	2462	14.96	31.33	
802.11g	2412	14.65	29.17	
	2437	14.51	28.25	
	2462	14.56	28.58	
802.11n(HT20)	2412	13.51	22.44	
	2437	13.79	23.93	
	2462	13.02	20.04	
802.11n(HT40)	2422	12.97	19.82	
	2437	12.69	18.58	
	2452	12.41	17.42	

Note: EIRP = Conducted output power + Antenna Gain(0.50dBi).

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 14 of 74

4.1.3 6dB Bandwidth and 99% Bandwidth

RESULT:

PASS

Test standard

: FCC Part 15.247(a)(2), RSS-247 5.2(a)
RSS-Gen 6.7

Requirement

: ANSI C63.10-2013, Clause 11.8.1
KDB 558074 D01 v05r02, Clause 8.2

Kind of test site

: Shielded room

Test setup

Test Channel

: Low/Middle/High

Operation Mode

: A.1.a

Ambient temperature

: 23.4°C

Relative humidity

: 46%

Table 3: 6dB Bandwidth and 99% Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	6dB Bandwidth Applicable Limit (MHz)
802.11b	2412	10.04	14.698	≥0.5
	2437	10.07	14.700	
	2462	10.04	14.692	
802.11g	2412	16.54	16.930	
	2437	16.57	17.003	
	2462	15.75	16.167	
802.11n(HT20)	2412	17.70	18.058	
	2437	17.71	18.011	
	2462	16.83	17.354	
802.11n(HT40)	2422	36.45	35.850	
	2437	36.46	35.881	
	2452	36.45	35.805	


TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 15 of 74

Figure 1: 6dB Bandwidth, 802.11b, 2412MHz



99% Bandwidth, 802.11b, 2412MHz



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 16 of 74

Figure 2: 6dB Bandwidth, 802.11b, 2437MHz



99% Bandwidth, 802.11b, 2437MHz




TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 17 of 74

Figure 3: 6dB Bandwidth, 802.11b, 2462MHz



99% Bandwidth, 802.11b, 2462MHz



TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 18 of 74

Figure 4: 6dB Bandwidth, 802.11g, 2412MHz



99% Bandwidth, 802.11g, 2412MHz




TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 19 of 74

Figure 5: 6dB Bandwidth, 802.11g, 2437MHz



99% Bandwidth, 802.11g, 2437MHz




TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 20 of 74

Figure 6: 6dB Bandwidth, 802.11g, 2462MHz



99% Bandwidth, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 21 of 74

Figure 7: 6dB Bandwidth, 802.11n(HT20), 2412MHz



99% Bandwidth, 802.11n(HT20), 2412MHz




TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 22 of 74

Figure 8: 6dB Bandwidth, 802.11n(HT20), 2437MHz



99% Bandwidth, 802.11n(HT20), 2437MHz



TEST REPORT

Figure 9: 6dB Bandwidth, 802.11n(HT20), 2462MHz



99% Bandwidth, 802.11n(HT20), 2462MHz




TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 24 of 74

Figure 10: 6dB Bandwidth, 802.11n(HT40), 2422MHz



99% Bandwidth, 802.11n(HT40), 2422MHz




TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 25 of 74

Figure11: 6dB Bandwidth, 802.11n(HT40), 2437MHz



99% Bandwidth, 802.11n(HT40), 2437MHz




TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 26 of 74

Figure12: 6dB Bandwidth, 802.11n(HT40), 2452MHz



99% Bandwidth, 802.11n(HT40), 2452MHz



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 27 of 74

4.1.4 Maximum conducted output power spectral density

RESULT:

PASS

Test standard : FCC Part 15.247(e), RSS-247 5.2(b)

Requirement : ANSI C63.10-2013, Clause 11.10.3
KDB 558074 D01 v05r02, Clause 8.4

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 23.4°C

Relative humidity : 46%

Table 4: Maximum conducted output power spectral density

Test Mode	Test Channel (MHz)	Maximum conducted output power spectral density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-17.23	≤8
	2437	-17.49	
	2462	-17.40	
802.11g	2412	-16.77	
	2437	-17.83	
	2462	-16.64	
802.11n(HT20)	2412	-17.88	
	2437	-16.75	
	2462	-16.76	
802.11n(HT40)	2422	-17.90	
	2437	-17.86	
	2452	-17.85	

TEST REPORT

Report No.: SHE24120036-02DE


Date: 2025-04-14

Page 28 of 74

Figure 13: Power Spectral Density, 802.11b, 2412MHz



Figure 14: Power Spectral Density, 802.11b, 2437MHz




TEST REPORT

Report No.: SHE24120036-02DE Date: 2025-04-14 Page 29 of 74

Figure 15: Power Spectral Density, 802.11b, 2462MHz



Figure 16: Power Spectral Density, 802.11g, 2412MHz



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 30 of 74

Figure 17: Power Spectral Density, 802.11g, 2437MHz





Figure 18: Power Spectral Density, 802.11g, 2462MHz



TEST REPORT

Report No.: SHE24120036-02DE Date: 2025-04-14 Page 31 of 74

Figure 19: Power Spectral Density, 802.11n(HT20), 2412MHz





Figure 20: Power Spectral Density, 802.11n(HT20), 2437MHz



TEST REPORT

Report No.: SHE24120036-02DE Date: 2025-04-14 Page 32 of 74

Figure 21: Power Spectral Density, 802.11n(HT20), 2462MHz





Figure 22: Power Spectral Density, 802.11n(HT40), 2422MHz



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 33 of 74

Figure 23: Power Spectral Density, 802.11n(HT40), 2437MHz





Figure 24: Power Spectral Density, 802.11n(HT40), 2452MHz



TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 34 of 74

4.1.5 Conducted Spurious Emission & Authorized-band band-edge

RESULT:

PASS

Test standard

: FCC Part 15.247(d), 15.209, RSS-247 5.5

Requirement

: ANSI C63.10-2013, Clause 11.11.1(b)
KDB 558074 D01 v05r02, Clause 8.5

Kind of test site

: Shielded room

Test setup

Test Channel

: Low/Middle/High for spurious, Low/High for Band
Edge

Operation Mode

: A.1.a

Ambient temperature

: 23.4°C

Relative humidity

: 46%

For details refer to following test plot.

TEST REPORT

Report No.: SHE24120036-02DE

Date: 2025-04-14

Page 35 of 74

Figure 25: Conducted Spurious Emission & Authorized-band band-edge, 802.11b, 2412MHz Carrier Level



Band Edge



TEST REPORT

Report No.: SHE24120036-02DE Date: 2025-04-14 Page 36 of 74

Conducted spurious emissions 30MHz-25GHz

