



**Compliance Testing, LLC**  
Previously Flom Test Lab  
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268  
fax: (480) 926-3598  
<http://www.ComplianceTesting.com>  
[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## Test Report

Prepared for: **Sensys Networks, Inc.**

**Model: FLEX-RAD-CM**

**Description: FLEXRADIO Cabinet**

**Serial Number: N/A**

**FCC ID: TDB-FLEXRAD**

**To**

**FCC Part 1.1310**

**Date of Issue: July 6, 2017**

**On the behalf of the applicant:**

**Sensys Networks, Inc.  
2560 Ninth St.  
Berkeley, CA 94710**

**Attention of:**

**Sebastian Lodahl, Compliance Manager  
Ph: (510)847-6189  
Email: [slodahl@sensysnetworks.com](mailto:slodahl@sensysnetworks.com)**

**Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1760011**

**Poona Saber  
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

<b>Revision</b>	<b>Date</b>	<b>Revised By</b>	<b>Reason for Revision</b>
1.0	June 27, 2017	Poona Saber	Original Document
2.0	July 5, 2017	Poona Saber	Revised power and antenna gain and hence calculations



### ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

#### **Non-accredited tests contained in this report:**

**N/A**

#### **EUT Description**

**Model:** FLEX-RAD-CM

**Description:** FLEXRADIO Cabinet

**Firmware:** N/A

**Software:** TrafficDOT2

**Serial Number:** N/A

#### **Additional Information:**

The FlexRadio Cabinet is the communications edge gateway for the Sensys Networks VDS240 Wireless Vehicle Detection System. The FlexRadio Cabinet uses its DSSS ISM band radio to communicate to battery operated sensors and then relay the information over RS-422 on Cat5 cables to either an APCC or FlexControl to process the data and provide vehicle detection information to a traffic signal controller or remote traffic management center.

EUT operates in the 2406 – 2480MHz band



### Average Power calculations

Average Power = Peak Power \* duty-cycle%

Tuned Frequency (MHz)	Radiated Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
2440	3.89	100	3.89 mW



## MPE Evaluation

This is a fixed device used in Uncontrolled Exposure environment.

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

## Test Data

Test Frequency, MHz	2440
Power, EIRP, mW (P)	3.89
Antenna gain (dBi)	6
Antenna gain (Numeric)	3.98
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm <sup>2</sup>

Power Density (S) =0.00308
Limit =(from above table) = 1.0

END OF TEST REPORT