



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

Application No. : LF209281(0)

Applicant : U-Kids International (HK) Limited  
Room 901, New East Ocean Centre,  
9 Science Museum Road, TST East,  
Hong Kong

Sample Description : One(1) submitted sample stated to be Radio Control Car "Rally Racer"  
of Model No. 20015

Rating : 1 x 9V size battery  
No. of submitted sample : One (1) piece\*\*\*

Date Received : 2005 June 10

Test Period : 2005 June 10 – 2005 June 15

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15  
Subpart C.

*For and on behalf of*  
CMA Testing and Certification Laboratories

Authorized Signature : \_\_\_\_\_

Page 1 of 11

Danny Chui  
EMC Engineer - EL. Division

FCC ID : TDD20015



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **Table of Contents**

1	General Information .....	3
1.1	General Description.....	3
1.2	Location of the test site.....	4
1.3	List of measuring equipment .....	5
2	Description of the radiated emission test.....	6
2.1	Test Procedure .....	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data .....	7
3	Description of the Line-conducted Test .....	8
3.1	Test Procedure .....	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data.....	8
4	Photograph .....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT .....	9
5	Supplementary document .....	10
5.1	Bandwidth .....	10
5.2	Duty Cycle .....	10
6	Appendices .....	11



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a transmitter for Rally Racer. Operating at 27.145MHz which is controlled by a crystal. The EUT is powered by 1 x 9V battery. There are a forward / backward lever and a wheel on the EUT. When the forward / backward lever is activated, it will transmit a signal for the receiver to go forward / backward. When the wheel is rotated, it will transmit a signal for the receiver to turn left or right.

The brief circuit description is listed as follows :

- XTAL and associated circuit act as oscillator.
- IC TX-1 and associated circuit act as encoder.
- T1 and associated circuit act as amplifier.
- D3 and associated circuit act as voltage regulator.



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **1.3 List of measuring equipment**

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

#### **2.2 Test Result**

All operation modes had been tested.

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

Peak Detector data was measured unless otherwise stated.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector.

\* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **2.3 Radiated Emission Measurement Data**

**Radiated emission**  
**pursuant to**  
**the requirement of FCC Part 15 subpart C**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB $\mu$ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
27.145	V	64.0	9.0	-5.8	67.2	80.0	-12.8
54.286	V	28.9	8.1	-	37.0	40.0	-3.0
81.435	H	16.2	7.2	-	23.4	40.0	-16.6
* 108.572	H	13.7	11.0	-	24.7	43.5	-18.8
* 135.721	H	12.6	12.4	-	25.0	43.5	-18.5
* 162.862	H	16.0	10.4	-	26.4	43.5	-17.1
190.003	H	16.5	9.2	-	25.7	43.5	-17.8
217.156	H	16.2	9.7	-	25.9	46.0	-20.1
* 244.304	H	16.8	9.7	-	26.5	46.0	-19.5
* 271.449	H	13.3	13.9	-	27.2	46.0	-18.8



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **5 Supplementary document**

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

<b>Document</b>	<b>Filename</b>
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

### **5.1 Bandwidth**

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

#### **a. Duty Cycle**

The duty cycle is simply the on-time divided by the period :

$$\text{The duration of one cycle} = 34.90 \text{ ms}$$

$$\begin{aligned}\text{Effective period of the cycle} &= (4 \times 1.68 + 22 \times 0.51) \text{ ms} \\ &= 17.94 \text{ ms}\end{aligned}$$

$$\begin{aligned}\text{Duty Cycle} &= 17.94 / 34.9 \\ &= 0.514\end{aligned}$$

Therefore, the average factor is found by  $20 \log_{10} 0.514 = -5.8 \text{ dB}$



## **TEST REPORT**

Report No. : AF013351-001

Date : 2005 June 23

### **6 Appendices**

A1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	1 page
A4	ID Label/Location	1 page
A5	Bandwidth Plot	1 page
A6	Average Factor	2 pages
A7	Block Diagram	1 page
A8	Schematics	1 page
A9	User Manual	1 page
A10	Operation Description	1 page

\*\*\*\*\* End of Report \*\*\*\*\*