

FCC

EMC

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
X1 MAX FDD-LTE Smartphone

ISSUED TO
TP-LINK Technologies Co., Ltd.

Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology
Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong
Province, P.R. China



Tested by: Xia Long
Xia Long
(Engineer)
Date: May 15, 2017

Approved by: Liao Jianming
Liao Jianming
(Technical Director)
Date: May 15, 2017



Report No.: BL-SZ1730238-401
EUT Name: X1 MAX FDD-LTE Smartphone
Model Name: TP903C
Brand Name: neffos
Test Standard: 47 CFR Part 15 Subpart B
FCC ID: TE7X1MAXV1

Test Conclusion: Pass
Test Date: Apr. 20, 2017 ~ Apr. 26, 2017
Date of Issue: May 15, 2017

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

| <u>Version</u> | <u>Issue Date</u> | <u>Revisions Content</u> |
|----------------|---------------------|--------------------------|
| <u>Rev. 01</u> | <u>May 15, 2017</u> | <u>Initial Issue</u> |

TABLE OF CONTENTS

| | | |
|---------|--|----|
| 1 | GENERAL INFORMATION | 4 |
| 1.1 | Identification of the Testing Laboratory | 4 |
| 1.2 | Identification of the Responsible Testing Location | 4 |
| 1.3 | Laboratory Condition | 4 |
| 1.4 | Announce | 4 |
| 2 | PRODUCT INFORMATION | 5 |
| 2.1 | Applicant Information | 5 |
| 2.2 | Manufacturer Information | 5 |
| 2.3 | Factory Information | 5 |
| 2.4 | General Description for Equipment under Test (EUT) | 5 |
| 2.5 | Ancillary Equipment | 6 |
| 2.6 | Technical Information | 6 |
| 3 | SUMMARY OF TEST RESULTS | 7 |
| 3.1 | Test Standards | 7 |
| 3.2 | Verdict | 7 |
| 3.3 | Test Uncertainty | 7 |
| 4 | GENERAL TEST CONFIGURATIONS | 8 |
| 4.1 | Test Environments | 8 |
| 4.2 | Test Equipment List | 8 |
| 4.3 | Test Enclosure list | 9 |
| 4.4 | Test Configurations | 10 |
| 4.5 | Test Setups | 11 |
| 4.6 | Test Conditions | 13 |
| 5 | TEST ITEMS | 14 |
| 5.1 | Emission Tests | 14 |
| ANNEX A | TEST RESULTS | 16 |

A.1 Radiated Emission 16

A.2 Conducted Emission 22

ANNEX B TEST SETUP PHOTOS 26

ANNEX C EUT EXTERNAL PHOTOS 26

ANNEX D EUT INTERNAL PHOTOS 26

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

| | |
|--------------|---|
| Company Name | Shenzhen BALUN Technology Co., Ltd. |
| Address | Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Phone Number | +86 755 6685 0100 |

1.2 Identification of the Responsible Testing Location

| | |
|---------------------------|---|
| Test Location | Shenzhen BALUN Technology Co., Ltd. |
| Address | Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China |
| Accreditation Certificate | <p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p> |
| Description | All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055 |

1.3 Laboratory Condition

| | |
|---------------------------|-------------------|
| Ambient Temperature | 20°C~25°C |
| Ambient Relative Humidity | 45% - 55% |
| Ambient Pressure | 100 kPa - 102 kPa |

1.4 Announce

- (1) The test report reference to the report template version v6.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

| | |
|-----------|--|
| Applicant | TP-LINK Technologies Co., Ltd. |
| Address | Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China |

2.2 Manufacturer Information

| | |
|--------------|--|
| Manufacturer | TP-LINK Technologies Co., Ltd. |
| Address | Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China |

2.3 Factory Information

| | |
|---------|-----|
| Factory | N/A |
| Address | N/A |

2.4 General Description for Equipment under Test (EUT)

| | |
|---|--|
| EUT Name | X1 MAX FDD-LTE Smartphone |
| Model Name Under Test | TP903C |
| Series Model Name | TP903CXYZZ, TP903C |
| Description of Model name differentiation | The equipment model TP903C and TP903CXYZZ (X=2 or 4 (2 indicates Cloudy Grey, 4 indicates Sunrise Gold); Y= A or 6 (A indicates the memory is 4G RAM + 64G Flash, 6 indicates the memory is 3G RAM + 32G Flash); ZZ indicates different national.) are the EUT model, the electrical parameters and internal structure of circuit are same. Only the model name, colors, memory versions and shipping country are different. |
| Hardware Version | N/A |
| Software Version | N/A |
| Dimensions (Approx.) | N/A |
| Weight (Approx.) | N/A |
| Random-access Memory | 4G RAM + 64G Flash |
| Network and Wireless connectivity | 2G Network GSM GPRS/EDGE 850/1900 MHz 3G Network WCDMA HSDPA/HSUPA Band 2/4/5 4G Network FDD Band 2/4/7 Bluetooth 3.0, Bluetooth 4.0 Low Energy (BLE), WIFI 802.11a, 802.11b, 802.11g, 802.11n(HT20/40) FM, GPS, GLONASS |

2.5 Ancillary Equipment

| | | |
|-----------------------|--|-----------------------------|
| Ancillary Equipment 1 | Battery | |
| | Brand Name | neffos |
| | Model No. | NBL-35A3000 |
| | Serial No. | N/A |
| | Capacitance | 3000 mAh |
| | Rated Voltage | 3.85 V |
| | Limited Voltage | 4.40 V |
| Ancillary Equipment 2 | Adapter | |
| | Brand Name | neffos |
| | Model No. | N090200-2B3 (US Plug) |
| | Serial No. | N/A |
| | Rated Input | 100-240 V~, 0.3 A, 50/60 Hz |
| Rated Output | 5 V=, 3 A or 9 V , 2 A or 12 V , 1.5 A | |
| Ancillary Equipment 3 | USB Cable | |
| | Length (Approx.) | 100 cm |
| Ancillary Equipment 4 | Earphone | |
| | Length (Approx.) | 125 cm |

2.6 Technical Information

N/A

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

| No. | Identity | Document Title |
|-----|---|---|
| 1 | FCC 47 CFR Part 15 Subpart B (10-1-15 Edition) | Unintentional Radiators |
| 2 | ANSI C63.4-2014 | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low- Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |

3.2 Verdict

| No. | Description | FCC Rule | Test Verdict | Result |
|-----|------------------------------|----------|--------------|------------|
| 1 | Radiated Emission | 15.109 | Pass | Annex A .1 |
| 2 | Conducted Emission, AC Ports | 15.107 | Pass | Annex A .2 |

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Measurement | Value |
|------------------------------------|---------|
| Conducted emissions (9 kHz-30 MHz) | 3.23 dB |
| Radiated emissions (30 MHz-1 GHz) | 4.30 dB |
| Radiated emissions (1 GHz-18 GHz) | 4.81 dB |
| Radiated emissions (18 GHz-40 GHz) | 5.71 dB |

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

| Environment Parameter | Selected Values During Tests | | | |
|---|------------------------------|---|-------------------|------------------|
| | Temperature | Voltage | Relative Humidity | Ambient Pressure |
| Normal Temperature, Normal Voltage (NTNV) | 23°C~26°C | AC 120 V/60 Hz from Adapter or DC 3.85 V from Battery | 50%-55% | 100 to 102 kPa |

4.2 Test Equipment List

| Radiated Emission Test For Frequency Below 1 GHz | | | | | | |
|--|-------------------------|-------------------|------------|------------|------------|-------------------------------------|
| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due | Use |
| EMI Receiver | ROHDE&SCHWARZ | ESRP | 101036 | 2016.07.05 | 2017.07.04 | <input checked="" type="checkbox"/> |
| Test Antenna-Bi-Log | SCHWARZBECK | VULB 9163 | 9163-977 | 2016.07.19 | 2018.07.18 | <input checked="" type="checkbox"/> |
| Test Antenna-Horn | SCHWARZBECK | BBHA 9120D | 9120D-1600 | 2016.07.12 | 2018.07.11 | <input type="checkbox"/> |
| Anechoic Chamber | EMC Electronic Co., Ltd | 20.10*11.60*7.35m | N/A | 2016.08.09 | 2018.08.08 | <input checked="" type="checkbox"/> |

| Radiated Emission Test For Frequency Above 1 GHz | | | | | | |
|--|--------------|------------|------------|------------|------------|-------------------------------------|
| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due | Use |
| EMI Receiver | KEYSIGHT | N9038A | MY53220118 | 2016.09.09 | 2017.09.08 | <input checked="" type="checkbox"/> |
| Test Antenna-Bi-Log | SCHWARZBECK | VULB 9163 | 9163-624 | 2015.07.22 | 2017.07.21 | <input type="checkbox"/> |
| Test Antenna-Horn | SCHWARZBECK | BBHA 9120D | 9120D-1148 | 2015.07.22 | 2017.07.21 | <input checked="" type="checkbox"/> |
| Anechoic Chamber | RAINFORD | 9m*6m*6m | N/A | 2017.02.21 | 2019.02.20 | <input checked="" type="checkbox"/> |

| Conducted Emission Test | | | | | | |
|-------------------------|---------------|-----------|------------|------------|------------|-------------------------------------|
| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due | Use |
| EMI Receiver | ROHDE&SCHWARZ | ESRP | 101036 | 2016.07.05 | 2017.07.04 | <input checked="" type="checkbox"/> |
| LISN | SCHWARZBECK | NSLK 8127 | 8127-687 | 2016.07.05 | 2017.07.04 | <input checked="" type="checkbox"/> |
| LISN | SCHWARZBECK | NNLK 8129 | 8129-462 | 2016.09.14 | 2017.09.13 | <input type="checkbox"/> |
| AMN | SCHWARZBECK | NNBM8124 | 8124-509 | 2016.07.05 | 2017.07.04 | <input type="checkbox"/> |
| AMN | SCHWARZBECK | NNBM8124 | 8124-510 | 2016.07.05 | 2017.07.04 | <input type="checkbox"/> |
| ISN | TESEQ | ISN T800 | 34449 | 2016.07.05 | 2017.07.04 | <input type="checkbox"/> |
| Shielded Enclosure | ChangNing | CN-130701 | 130703 | N/A | N/A | <input checked="" type="checkbox"/> |

4.3 Test Enclosure list


| Description | Manufacturer | Model | Serial No. | Length | Description | Use |
|-------------------------------------|--------------|--------------|------------------------|--------|--------------------|-------------------------------------|
| PC | Dell | 015K3N | N/A | N/A | Special Handled | <input checked="" type="checkbox"/> |
| Laptop | Apple | A1465 | N/A | N/A | N/A | <input type="checkbox"/> |
| Printer | HP | DESKJET 1000 | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| Keyboard | Dell | N/A | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| Mouse | Dell | N/A | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| USB disk | Kingston | N/A | N/A | N/A | N/A | <input type="checkbox"/> |
| TF Card | Kingston | N/A | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| VGA Cable | N/A | N/A | N/A | 1.5 m | Shielded with core | <input type="checkbox"/> |
| HDMI Cable | N/A | N/A | N/A | 1.5 m | Shielded with core | <input type="checkbox"/> |
| DVI Cable | N/A | N/A | N/A | 1.5 m | Shielded with core | <input type="checkbox"/> |
| Coaxial video cable | N/A | N/A | N/A | 2.0 m | Shielded with core | <input type="checkbox"/> |
| iPhone | Apple | A1586 | N/A | N/A | N/A | <input type="checkbox"/> |
| Phone | MI | M4 | N/A | N/A | N/A | <input type="checkbox"/> |
| Bluetooth Earphone | SAMSUNG | Gear Circle | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| GPS/GLONASS Vector signal generator | R&S | N5172B EXG | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| WIFI Router | TP-LINK | TL-WDR7500 | N/A | N/A | N/A | <input checked="" type="checkbox"/> |
| Earphone | N/A | OPPO | N/A | 1.1 m | N/A | <input type="checkbox"/> |
| Car Battery | Camel | 55530 | N/A | N/A | 12 V/55 Ah | <input type="checkbox"/> |
| Artificial load | N/A | N/A | N/A | N/A | 2.5 Ω/100 W | <input type="checkbox"/> |
| Artificial load | N/A | N/A | N/A | N/A | 5 Ω/100 W | <input type="checkbox"/> |
| Electronic Load | ITECH | IT8511 | N/A | N/A | N/A | <input type="checkbox"/> |
| USB Cable | N/A | N/A | N/A | 1.5 m | Shielded with core | <input type="checkbox"/> |
| DC Power Supply | ITECH | IT6863A | 60001401068 7210006 | N/A | N/A | <input type="checkbox"/> |
| LCD Monitor | SAMSUNG | UA32C4000P | N/A | N/A | N/A | <input type="checkbox"/> |
| LCD Monitor | Dell | U241HB | N/A | N/A | N/A | <input type="checkbox"/> |
| RJ45 Cable | N/A | N/A | N/A | 1.5 m | Shielded with core | <input type="checkbox"/> |

4.4 Test Configurations

| Test Configurations (TC) No. | Description |
|------------------------------|---|
| Traffic Test Mode | |
| TC01 | <u>The GSM 850 MHz Test Mode</u> GSM 850 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GPS RX |
| TC02 | <u>The EDGE 850 MHz Test Mode</u> EDGE 850 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GLONASS RX |
| TC03 | <u>The GSM 1900 Test Mode</u> GSM 1900 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GPS RX |
| TC04 | <u>The EDGE 1900 MHz Test Mode</u> EDGE 1900 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GLONASS RX |
| TC05 | <u>The WCDMA Band 2 Test Mode</u> WCDMA Band 2 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GPS RX |
| TC06 | <u>The WCDMA Band 4 test mode</u> WCDMA Band 4 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GLONASS RX |
| TC07 | <u>The WCDMA Band 5 test mode</u> WCDMA Band 5 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GPS RX |
| TC08 | <u>The FDD LTE Band 2 test mode</u> LTE Band 2 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GLONASS RX |
| TC09 | <u>The FDD LTE Band 4 test mode</u> LTE Band 4 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GPS RX |
| TC10 | <u>The FDD LTE Band 7 test mode</u> LTE Band 7 Link + Adapter + USB Cable + Battery+ TF Card + Earphone + BT Link + WIFI Link + GLONASS RX |
| TC11 | <u>The Idle Test Mode</u> GSM 850(Idle) + Battery + TF Card + Adapter + USB Cable + FM RX |
| Amusement Test Mode | |
| TC12 | <u>The USB Test Mode</u> EUT + Battery + TF Card + Earphone + USB Cable + PC + Printer + Keyboard + Mouse |
| TC13 | <u>The Camera Test Mode</u> EUT + Battery + TF Card + Adapter + USB Cable + Earphone |
| TC14 | <u>The Video Play Test Mode</u> EUT + Battery + TF Card + Adapter + USB Cable + Earphone |


4.5 Test Setups

Test Setup 1




(For Radiated Emission Test (30 MHz-1 GHz))

Test Setup 2



(For Radiated Emission Test (above 1 GHz))

Test Setup 3



(For Conducted Emission, AC Ports Test)

4.6 Test Conditions

| Test Case | Test Conditions | |
|------------------------------|--------------------|---------------------------|
| Radiated Emission | Test Env. | NTNV |
| | Test Setup | Test Setup 1&2 |
| | Test Configuration | TC01~TC14 ^{Note} |
| Conducted Emission, AC Ports | Test Env. | NTNV |
| | Test Setup | Test Setup 3 |
| | Test Configuration | TC01~TC14 ^{Note} |

Note: Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report. The GSM 850 MHz Test Mode is the worst mode in this report.

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

| Frequency range (MHz) | Class B (at 3 m) | | Class A (at 10 m) | |
|--------------------------|---------------------------------------|---|---------------------------------------|---|
| | Field Strength ($\mu\text{V/m}$) | Field Strength (dB $\mu\text{V/m}$) | Field Strength ($\mu\text{V/m}$) | Field Strength (dB $\mu\text{V/m}$) |
| 30 - 88 | 100 | 40 | 90 | 39 |
| 88 - 216 | 150 | 43.5 | 150 | 43.5 |
| 216 - 960 | 200 | 46 | 210 | 46.4 |
| Above 960 | 500 | 54 | 300 | 49.5 |

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log$ [Field Strength ($\mu\text{V/m}$)].
- 2) In the emission tables above, the tighter limit applies at the band edges.

5.1.1.2 Test Setup

Refer to 4.5 section (test setup 1 to test setup 2) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.1.1.4 Test Result

Please refer to ANNEX A.1.

5.1.2 Conducted Emission

5.1.2.1 Test Limit

| Frequency range (MHz) | Class A | |
|-----------------------|-------------------------|----------------------|
| | Quasi-peak (dB μ V) | Average (dB μ V) |
| 0.15 - 0.50 | 79 | 66 |
| 0.50 - 30 | 73 | 60 |

| Frequency range (MHz) | Class B | |
|-----------------------|-------------------------|----------------------|
| | Quasi-peak (dB μ V) | Average (dB μ V) |
| 0.15 - 0.50 | 66 to 56 | 56 to 46 |
| 0.50 - 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.5 section test (test setup 3) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.1.2.4 Test Result

Please refer to ANNEX A.2.

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: This frequency which remake N/A should be ignored because they are MS and SS carrier frequency, Bluetooth or WIFI carrier frequency.

Test Data and Plots


The GSM 850 MHz Test Mode

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|----------|---------|
| 1 | 31.234 | 26.60 | -16.86 | 30.0 | 3.40 | Peak | 278.00 | 103.00 | Vertical | N/A |
| 1* | 31.234 | 22.14 | -16.86 | 30.0 | 7.86 | QP | 278.00 | 103.00 | Vertical | Pass |
| 2 | 59.335 | 23.09 | -14.90 | 30.0 | 6.91 | Peak | 104.00 | 300 | Vertical | Pass |
| 3 | 184.676 | 16.67 | -16.57 | 33.5 | 16.83 | Peak | 333.00 | 100 | Vertical | Pass |
| 4 | 212.072 | 19.52 | -15.10 | 33.5 | 13.98 | Peak | 39.00 | 100 | Vertical | Pass |
| 5 | 293.047 | 22.05 | -12.41 | 36.0 | 13.95 | Peak | 18.00 | 100 | Vertical | Pass |
| 6 | 331.110 | 20.89 | -11.32 | 36.0 | 15.11 | Peak | 230.00 | 100 | Vertical | Pass |

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|------------|---------|
| 1 | 65.396 | 12.24 | -15.84 | 30.0 | 17.76 | Peak | 0.00 | 400 | Horizontal | Pass |
| 2 | 203.587 | 16.03 | -14.94 | 33.5 | 17.47 | Peak | 49.00 | 400 | Horizontal | Pass |
| 3 | 279.955 | 21.62 | -12.84 | 36.0 | 14.38 | Peak | 239.00 | 300 | Horizontal | Pass |
| 4 | 339.110 | 20.65 | -10.87 | 36.0 | 15.35 | Peak | 48.00 | 300 | Horizontal | Pass |
| 5 | 452.087 | 19.36 | -8.85 | 36.0 | 16.64 | Peak | 229.00 | 300 | Horizontal | Pass |
| 6 | 778.168 | 22.68 | -2.70 | 36.0 | 13.32 | Peak | 107.00 | 400 | Horizontal | Pass |

A.1.3 Test Antenna Vertical, 1 GHz – 6 GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|----------|---------|
| 1 | 1236.500 | 41.41 | -6.39 | 74.0 | 32.59 | Peak | 291.80 | 100 | Vertical | Pass |
| 2 | 1673.000 | 45.34 | -6.04 | 74.0 | 28.66 | Peak | 176.10 | 100 | Vertical | N/A |
| 3 | 2423.000 | 91.04 | -2.24 | 74.0 | -17.04 | Peak | 320.60 | 100 | Vertical | N/A |
| 4 | 2465.500 | 90.78 | -2.83 | 74.0 | -16.78 | Peak | 23.10 | 100 | Vertical | N/A |
| 5 | 3346.500 | 43.36 | 5.55 | 74.0 | 30.64 | Peak | 293.70 | 100 | Vertical | Pass |
| 6 | 5529.750 | 48.12 | 10.52 | 74.0 | 25.88 | Peak | 209.80 | 100 | Vertical | Pass |

A.1.4 Test Antenna Horizontal, 1 GHz – 6 GHz




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|------------|---------|
| 1 | 1252.000 | 41.84 | -6.95 | 74.0 | 32.16 | Peak | 312.20 | 100 | Horizontal | Pass |
| 2 | 1673.000 | 45.80 | -6.04 | 74.0 | 28.20 | Peak | 181.20 | 100 | Horizontal | N/A |
| 3 | 2418.500 | 75.88 | -1.83 | 74.0 | -1.88 | Peak | 268.20 | 100 | Horizontal | N/A |
| 4 | 2461.000 | 73.41 | -2.79 | 74.0 | 0.59 | Peak | 274.00 | 100 | Horizontal | N/A |
| 5 | 3598.500 | 42.94 | 5.93 | 74.0 | 31.06 | Peak | 312.90 | 100 | Horizontal | Pass |
| 6 | 5529.750 | 46.29 | 10.52 | 74.0 | 27.71 | Peak | 123.80 | 100 | Horizontal | Pass |

Test Data and Plots


The USB Test Mode

A.1.5 Test Antenna Vertical, 30 MHz – 1 GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|----------|---------|
| 1 | 83.579 | 20.72 | -18.74 | 30.0 | 9.28 | Peak | 3.00 | 200 | Vertical | Pass |
| 2 | 139.098 | 26.37 | -18.82 | 33.5 | 7.13 | Peak | 83.00 | 100 | Vertical | Pass |
| 3 | 178.130 | 26.66 | -17.11 | 33.5 | 6.84 | Peak | 213.00 | 100 | Vertical | Pass |
| 4 | 268.573 | 36.00 | -13.09 | 36.0 | 0.00 | Peak | 153.00 | 141.00 | Vertical | N/A |
| 4* | 268.573 | 30.35 | -13.09 | 36.0 | 5.65 | QP | 153.00 | 141.00 | Vertical | Pass |
| 5 | 357.293 | 28.21 | -10.57 | 36.0 | 7.79 | Peak | 111.00 | 100 | Vertical | Pass |
| 6 | 660.585 | 23.15 | -4.58 | 36.0 | 12.85 | Peak | 35.00 | 100 | Vertical | Pass |

A.1.6 Test Antenna Horizontal, 30 MHz – 1 GHz



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (o) | Height (cm) | ANT | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|-----------|-------------|------------|---------|
| 1 | 142.007 | 25.48 | -18.91 | 33.5 | 8.02 | Peak | 205.00 | 400 | Horizontal | Pass |
| 2 | 269.773 | 32.80 | -13.20 | 36.0 | 3.20 | Peak | 328.00 | 300 | Horizontal | Pass |
| 3 | 360.508 | 35.69 | -10.55 | 36.0 | 0.31 | Peak | 270.00 | 255.00 | Horizontal | N/A |
| 3* | 360.508 | 29.48 | -10.55 | 36.0 | 6.52 | QP | 270.00 | 255.00 | Horizontal | Pass |
| 4 | 449.178 | 22.25 | -8.93 | 36.0 | 13.75 | Peak | 130.00 | 300 | Horizontal | Pass |
| 5 | 666.888 | 31.76 | -4.52 | 36.0 | 4.24 | Peak | 311.00 | 100 | Horizontal | Pass |
| 6 | 959.755 | 29.80 | -0.58 | 36.0 | 6.20 | Peak | 205.00 | 100 | Horizontal | Pass |


A.2 Conducted Emission

Test Data and Plots

The GSM 850 MHz Test Mode


Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

A.2.1 L Phase



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|--------|---------|
| 1 | 0.162 | 37.9 | 9.85 | 65.4 | 27.50 | Peak | L Line | Pass |
| 1** | 0.162 | 25.6 | 9.85 | 55.4 | 29.80 | AV | L Line | Pass |
| 2 | 0.620 | 45.2 | 11.05 | 56.0 | 10.80 | Peak | L Line | Pass |
| 2** | 0.620 | 32.9 | 11.05 | 46.0 | 13.10 | AV | L Line | Pass |
| 3 | 1.444 | 36.7 | 10.02 | 56.0 | 19.30 | Peak | L Line | Pass |
| 3** | 1.444 | 25.5 | 10.02 | 46.0 | 20.50 | AV | L Line | Pass |
| 4 | 2.842 | 39.2 | 10.69 | 56.0 | 16.80 | Peak | L Line | Pass |
| 4** | 2.842 | 26.8 | 10.69 | 46.0 | 19.20 | AV | L Line | Pass |
| 5 | 5.410 | 35.2 | 10.24 | 60.0 | 24.80 | Peak | L Line | Pass |
| 5** | 5.410 | 22.5 | 10.24 | 50.0 | 27.50 | AV | L Line | Pass |
| 6 | 21.660 | 35.8 | 11.00 | 60.0 | 24.20 | Peak | L Line | Pass |
| 6** | 21.660 | 31.8 | 11.00 | 50.0 | 18.20 | AV | L Line | Pass |

A.2.2 N Phase




| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|--------|---------|
| 1 | 0.182 | 42.6 | 10.46 | 64.4 | 21.80 | Peak | N Line | Pass |
| 1** | 0.182 | 26.7 | 10.46 | 54.4 | 27.70 | AV | N Line | Pass |
| 2 | 0.616 | 47.4 | 11.40 | 56.0 | 8.60 | Peak | N Line | Pass |
| 2** | 0.616 | 35.8 | 11.40 | 46.0 | 10.20 | AV | N Line | Pass |
| 3 | 1.444 | 39.5 | 10.02 | 56.0 | 16.50 | Peak | N Line | Pass |
| 3** | 1.444 | 25.4 | 10.02 | 46.0 | 20.60 | AV | N Line | Pass |
| 4 | 4.204 | 43.0 | 10.59 | 56.0 | 13.00 | Peak | N Line | Pass |
| 4** | 4.204 | 29.2 | 10.59 | 46.0 | 16.80 | AV | N Line | Pass |
| 5 | 6.914 | 40.0 | 9.99 | 60.0 | 20.00 | Peak | N Line | Pass |
| 5** | 6.914 | 25.8 | 9.99 | 50.0 | 24.20 | AV | N Line | Pass |
| 6 | 12.316 | 40.5 | 10.74 | 60.0 | 19.50 | Peak | N Line | Pass |
| 6** | 12.316 | 28.6 | 10.74 | 50.0 | 21.40 | AV | N Line | Pass |

Test Data and Plots

The USB Test Mode


A.2.3 L Phase



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|--------|---------|
| 1 | 0.194 | 43.9 | 9.43 | 63.9 | 20.00 | Peak | L Line | Pass |
| 1** | 0.194 | 39.2 | 9.43 | 53.9 | 14.70 | AV | L Line | Pass |
| 2 | 0.324 | 33.3 | 11.21 | 59.6 | 26.30 | Peak | L Line | Pass |
| 2** | 0.324 | 24.4 | 11.21 | 49.6 | 25.20 | AV | L Line | Pass |
| 3 | 0.698 | 32.9 | 9.53 | 56.0 | 23.10 | Peak | L Line | Pass |
| 3** | 0.698 | 28.5 | 9.53 | 46.0 | 17.50 | AV | L Line | Pass |
| 4 | 1.256 | 32.2 | 10.26 | 56.0 | 23.80 | Peak | L Line | Pass |
| 4** | 1.256 | 27.8 | 10.26 | 46.0 | 18.20 | AV | L Line | Pass |
| 5 | 4.142 | 37.7 | 10.18 | 56.0 | 18.30 | Peak | L Line | Pass |
| 5** | 4.142 | 26.3 | 10.18 | 46.0 | 19.70 | AV | L Line | Pass |
| 6 | 9.852 | 49.6 | 10.30 | 60.0 | 10.40 | Peak | L Line | Pass |
| 6** | 9.852 | 34.8 | 10.30 | 50.0 | 15.20 | AV | L Line | Pass |

A.2.4 N Phase

CE Test case_FCC_CE_FCC PART 15_Class B



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|--------|---------|
| 1 | 0.194 | 45.8 | 9.43 | 63.9 | 18.10 | Peak | N Line | Pass |
| 1** | 0.194 | 39.5 | 9.43 | 53.9 | 14.40 | AV | N Line | Pass |
| 2 | 0.322 | 31.6 | 10.67 | 59.7 | 28.10 | Peak | N Line | Pass |
| 2** | 0.322 | 20.3 | 10.67 | 49.7 | 29.40 | AV | N Line | Pass |
| 3 | 0.700 | 29.5 | 9.66 | 56.0 | 26.50 | Peak | N Line | Pass |
| 3** | 0.700 | 25.1 | 9.66 | 46.0 | 20.90 | AV | N Line | Pass |
| 4 | 1.770 | 28.7 | 10.17 | 56.0 | 27.30 | Peak | N Line | Pass |
| 4** | 1.770 | 24.2 | 10.17 | 46.0 | 21.80 | AV | N Line | Pass |
| 5 | 4.138 | 37.9 | 10.02 | 56.0 | 18.10 | Peak | N Line | Pass |
| 5** | 4.138 | 24.6 | 10.02 | 46.0 | 21.40 | AV | N Line | Pass |
| 6 | 9.998 | 49.2 | 10.32 | 60.0 | 10.80 | Peak | N Line | Pass |
| 6** | 9.998 | 36.6 | 10.32 | 50.0 | 13.40 | AV | N Line | Pass |

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1730238-AE.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1730238-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1730238-AI.PDF".

--END OF REPORT--