



Electromagnetic Compatibility Test Report

Test Report No: EGT 230505

Issued on: May 23, 2005

Product Name

**iMedia (FCC ID: TEA-IMC-001),
iMedia RF Controller (FCC ID: TEA-IRF-001)**

**Tested According to
47 CFR, Part 15, Subparts B & C**

**Tests Performed for
SkipJam Corp.**

Tel. 914-933 0590
168 Irving Ave #500G
Port Chester, NY, USA , 10573

QualiTech EMC Laboratory

30 Hasivim St,
Petah-Tikva, 49130, Israel
Tel: 972-3-926 8443
Fax: 972-3-928 7490



1633.01

The information contained herein is the property of QualiTech, EMC Lab and is supplied without liability for errors or omissions.

*The copyright for this document vests in QualiTech, EMC Lab.
All rights reserved.*

This Test Report may not be reproduced, by any method, without the written permission of the QualiTech, EMC Lab.

If and when such permission is granted, the report must be reproduced only in the full format.

Test personnel



Tests Performed By: -----

Rami Nataf

Ilya Arbitman



Report Prepared By: -----

Bina Talkar



Report Reviewed By: -----

Y. Zucker
QA and Lab. Manager
QualiTech EMC Laboratory



1633.01

Test Facility description

The tests were performed at the QualiTech EMC Laboratory.

Address: 30, Hasivim St., Petah Tikva, Israel.

Tel: 972-3-926-8443

Semi Anechoic Chamber:

Measurement distance	3m
Chamber dimensions	9.5m x 6.5m x 5.2m
Antenna height	1 - 4m
Shielding Effectiveness	Magnetic field ≥ 80 dB at 15 kHz ≥ 90 dB at 100 kHz Electric field > 120 dB from 1MHz to 1GHz > 110 dB from 1GHz to 10GHz
Absorbing material	Ferrite tiles on the walls and ceiling Frankonia hybrid absorbing material in selected positions on the walls
Normalized Site Attenuation measured at 5 positions	± 3.49 dB, 30MHz to 1GHz
Transmission Loss measured at 5 positions, at 1.5m height	± 3 dB, 1GHz to 18GHz

Test Report details:

Test commencement date: 01.05.2005

Test completion date: 04.05.2005

Customer's Representative: Erez Segev

Issued on: **23.05.2005**

Assessment information:

This report contained an assessment of the EUT against Electromagnetic Compatibility based upon tests carried out on the samples submitted. The results contained in this report relate only to the items tested. Manufactured products will not necessarily give identical results due to production and measurement tolerances. QualiTech, EMC Lab does not assume responsibility for any conclusion and generalization drawn from the test results with regards to other specimens or samples of type of the equipment represented by test item.

The EUT was set up and exercised using the configuration, modes of operation and arrangements defined in this report only.

Modifications:

Modifications made to the EUT

The following changes were made in order to achieve compliance with the limits requirements.

Galvanic connection was improved by the following means:

1. Adding copper tape between:
 - Rear panel and LAN connector,
 - RF Antenna connector and rear panel.
 - Front Panel and connectors.
2. EMI Fingers were added between front panel and cover.
3. Conductive foam SiL-CON 022, 1.5 mm thick linear MT x 560 mm was inserted between rear panel and connectors.
4. Two capacitors (820pF and 22nF) were added on the power connector.

Modifications made to the Test Standard

No modifications were made to the Test Standard.

Summary of Compliance Status

Test Spec. Clause	Test Case	Remarks	Notes
§15.203	Antenna Connector requirement	Pass	<i>iMedia RF Controller</i>
§15.247 (a) (1)	Carrier Frequency Separation	Pass	<i>iMedia</i>
§15.247 (a) (1)(ii)	Number of Hopping Channels	Pass	<i>iMedia</i>
§15.247 (a) (1)(ii)	Time Occupancy (Dwell Time)	Pass	<i>iMedia</i>
§15.247 (a) (1) (ii)	Spectrum Bandwidth of a FHSS system/20dB BW	Pass	<i>iMedia</i>
§15.247 (b) (1)	Maximum Output Power	Pass	<i>iMedia</i>
§15.247 (c)	Band-Edge compliance of RF Conducted Emission (Transmitter)	Pass	<i>iMedia</i>
§15.205	Band-Edge compliance of Radiated Emission, Restricted Bands	Pass	<i>iMedia + iMedia RF Controller</i>
§15.247 (c)	Spurious Emission Conducted (Transmitter)	Pass	<i>iMedia</i>
§15.247 (c)	Spurious Emission Radiated (Transmitter)	Pass	<i>iMedia + iMedia RF Controller</i>
§15.109	Radiated Emission (receiver)	Pass	<i>iMedia + iMedia RF Controller</i>
§15.107/207	Conducted Emission (receiver)	Pass	<i>iMedia</i>

Note: Both iMedia and iMedia RF Controller (handset) employ the same transceiver device,



1633.01

Table of Content

1. GENERAL DESCRIPTION	7
1.1. Description of the EUT system/test Item: 7	
<i>Product name: iMedia + iMedia RF Controller (handset).....</i>	<i>7</i>
1.2. EUT Configuration	8
2. METHOD OF MEASUREMENTS	8
3. REPORT OF MEASUREMENTS AND EXAMINATIONS	9
3.1. Antenna Connector Requirements	9
3.2. Carrier Frequency Separation	9
3.3. Number of Hopping Channels,	10
3.4. Time of Occupancy (Dwell Time),	10
3.5. Spectrum Bandwidth of FHSS/ 20dB Bandwidth	11
3.6. Maximum Output Power	12
3.7. Band-edge compliance of RF Conducted Emission	13
3.8. Band-edge compliance of Radiated Emission, restricted Bands	14
3.9. Spurious Emission- Conducted (Transmitter)	15
3.10. Spurious Emission- Radiated (Transmitter)	16
3.11. Radiated Emission- (Receiver)	19
3.12. Conducted Emission- (Receiver)	20
4. APPENDIX	22

1. General Description

1.1. Description of the EUT system/test Item:

Product name: *iMedia + iMedia RF Controller (handset)*

S/N: # 0001

FCC ID: TEA-IMC-001 & TEA-IRF-001

Description: Video and Audio distribution

Maximum rated Power: 25dBm

H/W status: Prototype

S/W status: Prototype

Antenna: integral for controller 2dBi Gain, and an external antenna for i media 2.2dBi Gain.


Power-Supply: This product is intended to be supplied by a Listed Direct Plug-In Power Unit marked "Class 2" and rated 12V dc, 2.5Amp to 3.0Amps

Temp. Range: -30°C to +50°C

CVM 2.4 GHz – RADIO PART RF SPEC (on both, *iMedia + iMedia RF Controller*)r :

- Receive Sensitivity DCT (2G4) Minimum: -89dBm, Typically: -92dBm to -94dBm, Maximum: -96dBm@BER = 0.001
- Receive IIP3 DCT (2G4) -21dBm to -19dBm,
- Transmit Power (NTP) DCT (2G4) Minimum: 20dBm, Typically: 22dBm to 24dBm, Maximum: 25dBm, Approx. 200mW
- Signaling Bit-rate DCT (2G4) 576Kbit/sec
- Modulation DCT (2G4) GFSK Bandwidth 20dB <0,864MHz
- Channels DCT (2G4) 95 Channel spacing: 0.864MHz
- RX/TX slots DCT (2G4)
- Antenna Diversity DCT (2G4) Control signals are available from the module

1.2. EUT Configuration



The SkipJam iMedia operates as a network hub for Audio & Video devices with remote control capabilities. The iMedia converts analog input signals to digital form suitable for transmission over a network. These signals can then be sent over the network and recorded to a network hard drive, or transmitted to another iMedia which can convert the signals back to analog form for display on a TV at the destination. The remote control system includes a 2.4GHz RF link to a mobile handset which includes a data display.

2. Method of Measurements

Conducted measurements:

The RF output of the transmitter under test was directly connected to the input of the Spectrum analyzer through a specialized antenna connector provided by the manufacturer, and a 10dB attenuator. The measurements readings were corrected by the set-up loss.

Radiated Emission measurements:

Measurements were performed at a 3-meter measurement distance in the semi-anechoic chamber in order to evaluate the radiated electromagnetic interference characteristics of the EUT. The EUT was placed on a non-metallic table, 0.8m above the turntable, was configured, arranged and operated in a manner consistent with typical application and load conditions. The test program of exercising the equipment ensured that various parts of the EUT were exercised to permit detection of all EUT disturbances. An appropriate antenna depending upon the frequency range, per ANSI C63.4-2003 clause 4.1.5 was used. While the turntable was being rotated, the height of the antenna was varied from 1 to 4m for the frequency range of 30MHz to 1GHz. The highest radiated emission was detected by manipulating the system cables to the worst-case position. This process was repeated for both antenna polarizations. The amplitudes of worst-case emission were measured with the detector modes and resolution bandwidths over various frequency ranges according to the requirements of C63.4-2003 clause 4.2.

3. Report of Measurements and examinations

3.1. Antenna Connector Requirements

Reference document:	47 CFR §15.203	
Test Requirements:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with provisions of this section.	
Test Result:	The iMedia employs an RP-SMA (Antenna Factor) connector, which meets the requirements for a unique antenna coupler. The iMedia RF Controller employs an internal PCB antenna without any connector.	Pass

3.2. Carrier Frequency Separation

Reference document:	47 CFR §15.247 (a) (1) & DA 00-705		
Test Requirements:	Hopping channels carrier frequencies separated by a minimum of 25kHz or 20dB Bandwidth of the hopping channel, whichever is greater.		
Date of Test:	26.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 100kHz, VBW: 100kHz		
Hopping function:	Enabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	Carrier separation: 850kHz – 860kHz	See Plot 1 – Plot 4	

3.3. Number of Hopping Channels,

Reference document:	47 CFR §15.247 (a) (1)(ii) & DA 00-705		
Test Requirements:	Hopping system shall use at least 15 non-overlapping channels.		
Date of Test:	26.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 300kHz, VBW: 1MHz		
Hopping function:	Enabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	95 hopping channels	See Plot 5 – Plot 7	

3.4. Time of Occupancy (Dwell Time),

Reference document:	47 CFR §15.247 (a) (1) (ii) & DA 00-705		
Test Requirements:	The average time of occupancy on any channel shall not be greater than 0.4seconds within a period of 30 second period.		
Date of Test:	25/26.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 1MHz, VBW: 3MHz, Span:0 centered on hopping channel		
Hopping function:	Disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 8 – Plot 13	

Test results:

Channel	Frequency [GHz]	Duty Cycle	Dwell time [msec]	Limit [Sec]	Reference
00	2.401	0.08625	27.24	0.4	Plot 8 – Plot 9
48	2.443	0.09188	29.01	0.4	Plot 10 – Plot 11
94	2.482	0.090277	28.51	0.4	Plot 12 – Plot 13

Dwell-Time =(Duty-Cycle / # of hopping frequencies)*30seconds

3.5. Spectrum Bandwidth of FHSS/ 20dB Bandwidth

Reference document:	47 CFR §15.247 (a) (1)(ii) & DA 00-705		
Test Requirements:	Maximum 20dB BW of the hopping channels shall be 1MHz.		
Date of Test:	25.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 10kHz, VBW: 100kHz, Span: 2MHz		
Hopping function:	Disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 14 – Plot 16	

Test results:

Channel	Frequency [GHz]	20dB BW [kHz]	Standard [MHz]	Measured Channel Separation [kHz]	Reference	Result
00	2.401	670	<1MHz	850÷860 >20dB BW	Plot 14	Pass
48	2.443	660	<1MHz	850÷860 >20dB BW	Plot 15	Pass
94	2.482	670	<1MHz	850÷860 >20dB BW	Plot 16	Pass

3.6. Maximum Output Power

Reference document:	47 CFR §15.247 (b) (1) & DA 00-705		
Test Requirements:	The maximum peak output power shall not exceed 1Watt (30dBm)		
Date of Test:	25.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 1MHz, VBW: 3MHz, Span: 3.5MHz		
Hopping function:	Disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 17 – Plot 19	

Test results:

Channel	Frequency [GHz]	External cable Loss [dB]	Max. Peak Output power* [dBm]	Max. Peak Output power* mW	Reference
00	2.401	0.45	22.31	170.21	Plot 17
48	2.443	0.45	22.46	176.19	Plot 18
94	2.482	0.45	22.44	175.38	Plot 19

*Corrected for external attenuations

3.7. Band-edge compliance of RF Conducted Emission

Reference document:	47 CFR §15.247 (c) & DA 00-705		
Test Requirements and limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 5.205(c).		
Date of Test:	25.04.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 100kHz, VBW: 100kHz, Span: 10MHz		
Hopping function:	Disabled/disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 20 – Plot 23	

Test results of *iMedia*:

Activity	Delta value [dB]	Reference
Hopping off, lowest frequency	-57.42	Plot 20
Hopping on, lowest frequency	-54.66	Plot 21
Hopping off, highest frequency	-57.71	Plot 22
Hopping on, highest frequency	-58.73	Plot 23

3.8. Band-edge compliance of Radiated Emission, restricted Bands

Reference document:	47 CFR §15.205 & DA 00-705		
Test Requirements:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 5.205(c).		
Limit:	54dBμV/m	Pass	
Date of Test:	11.05.2005		
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Radiated		
S.A. Settings:	RBW: 1MHz, VBW: 3MHz,		
Hopping function:	Disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 24 – 31	

Test results:

iMedia

Channel	Max. Measured (Average detector) in restricted band at 3m [dBμV/m]	Dwell time correction factor [dB]	Calculated Value [dBμV/m]	Limit [dBμV/m]	Reference	Result
00	39.56	-11.30	28.26	54	Plot 24-25	Pass
94	40.31	-10.90	29.41	54	Plot 26-27	Pass

iMedia RF Controller

Channel	Max. Measured (Average detector) in restricted band at 3m [dBμV/m]	Dwell time correction factor [dB]	Calculated Value [dBμV/m]	Limit [dBμV/m]	Reference	Result
00	36.37	-11.30	25.07	54	Plot 28-29	Pass
94	37.23	-10.90	26.33	54	Plot 30-31	Pass

3.9. Spurious Emission- Conducted (Transmitter)

Reference document:	47 CFR §15.247 (c) & DA 00-705		
Test Requirements:	In any 100 kHz bandwidth outside the frequency band at least 20 dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))		
Date of Test:	01.05.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted		
S.A. Settings:	RBW: 100kHz, VBW: 100kHz,		
Hopping function:	Disabled		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 32 – Plot 34	

Test results:

Frequency [GHz]	Spurious Frequency [GHz]	Limit: Max. Allowed emission power	Delta spurious emission below frequency of operation [dBc]	Result	Reference
2.401	1.24	-20dBc	-49.48	Pass	Plot 32
	3.63		-51.23	Pass	
2.443	1.24		-49.17	Pass	Plot 33
	3.63		-53.79	Pass	
2.482	1.4		-45.37	Pass	Plot 34

3.10. Spurious Emission- Radiated (Transmitter)

Reference document:	47 CFR §15.247 (c) & DA 00-705		
Test Requirements:	In any 100 kHz bandwidth outside the frequency band at least 20 dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))		
Date of Test:	01.05.2005	Pass	
Test setup:	Setup 1		
Operating conditions:	Under normal test conditions		
Method of testing:	Radiated		
S.A. Settings:	F <1GHz: RBW: 120kHz, VBW: 1MHz F >1GHz: RBW: 1MHz, VBW: 3MHz		
Hopping function:	Disabled (lowest, middle, and highest)		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 35 – Plot 95	

Test results of iMedia:

Lowest channel, 2.401					
Frequency [MHz]	Detector	Spurious level [dB μ V/m]	Limit [dB μ V/m]	Result	Reference
95.99	QP	38.2	43.5	Pass	Plot 35 –Plot 44
100.00	QP	36.5	43.5	Pass	
48.00	QP	30.5	40	Pass	
323.96	QP	42.3	46	Pass	
351.00	QP	42	46	Pass	
497.04	QP	41.2	46	Pass	
695.9	QP	37.9	46	Pass	
994.17	QP	42	54	Pass	
971.93	QP	29.8	54	Pass	
1255	AV	36.6	54	Pass	
2510	AV	39.2	54	Pass	
3565	AV	42.5	54	Pass	

Middle channel, 2.443					
Frequency [MHz]	Detector	Spurious level [dB μ V/m]	Limit [dB μ V/m]	Result	Reference
95.99	QP	34.5	43.5	Pass	Plot 45 –Plot 54
107.9	QP	35.2	43.5	Pass	
48.00	QP	30.5	40	Pass	
323.96	QP	40.7	46	Pass	
350.99	QP	41.7	46	Pass	
994.17	QP	39.5	54	Pass	
971.93	QP	42.2	54	Pass	
1255	AV	38.7	54	Pass	
2510	AV	42.3	54	Pass	
3654	AV	44.7	54	Pass	

Highest channel, 2.482					
Frequency [MHz]	Detector	Spurious level [dB μ V/m]	Limit [dB μ V/m]	Result	Reference
95.99	QP	38	43.5	Pass	Plot 55–Plot 64
107.99	QP	35.8	43.5	Pass	
48.00	QP	29.7	40	Pass	
323.96	QP	39.8	46	Pass	
350.99	QP	34.7	46	Pass	
994.17	QP	37.3	54	Pass	
971.93	QP	42.9	54	Pass	
1255	AV	37.5	54	Pass	
2510	AV	41.9	54	Pass	
3654	AV	43.8	54	Pass	

Test results of iMedia RF Controller:

Lowest channel, 2.401					
Frequency [MHz]	Detector	Spurious level [dBμV/m]	Limit [dBμV/m]	Result	Reference
1221	AV	31.73	54	Pass	Plot 65 –Plot 75
3546	AV	40.29	54	Pass	
4802	AV	46.29	54	Pass	
7094	AV	45.97	54	Pass	

Middle channel, 2.443					
Frequency [MHz]	Detector	Spurious level [dBμV/m]	Limit [dBμV/m]	Result	Reference
1221	AV	30.45	54	Pass	Plot 76 –Plot 85
3634	AV	37.57	54	Pass	
4885	AV	48.75	54	Pass	
7281	AV	45.37	54	Pass	
9770	AV	38.56	54	Pass	

Highest channel, 2.482					
Frequency [MHz]	Detector	Spurious level [dBμV/m]	Limit [dBμV/m]	Result	Reference
1221	AV	30.76	54	Pass	Plot 86 –Plot 95
3676	AV	34.34	54	Pass	
4964	AV	43.29	54	Pass	
7346	AV	48.94	54	Pass	
9928	AV	40.10	54	Pass	

3.11. Radiated Emission- (Receiver)

Reference document:	47 CFR §15.109		
Test Requirements:	Emission Level shall not exceed §15.109 limits		
Date of Test:	04/15.05.2005	Pass	
Test setup:	Setup 2		
Operating conditions:	Under normal test conditions		
Method of testing:	Radiated		
S.A. Settings:	F <1GHz: RBW: 120kHz, VBW: 1MHz F >1GHz: RBW: 1MHz, VBW: 3MHz		
Mode of operation:	Receive		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 96- Plot 116	

Test results of *iMedia*:

Frequency [MHz]	Detector	Emission level [dBμV/m]	Limit [dBμV/m]	Result	Reference
47.991000	QP	35.4	40	Pass	Plot 96 –Plot 106
198.830800	QP	33.9	43.5	Pass	
107.982800	QP	32.7	43.5	Pass	
491.8	QP	41.5	46	Pass	
647.97	QP	38.3	46	Pass	
972.00	QP	31.7	54	Pass	

Test results *iMedia RF Controller*:

Frequency [MHz]	Detector	Emission level [dBμV/m]	Limit [dBμV/m]	Result	Reference
All readings were at least 20 db below the limit.					Plot 107–Plot 116

3.12. Conducted Emission- (Receiver)

Reference document:	47 CFR §15.107/207		
Test Requirements:	Emission Level shall not exceed §15.107/207 limits		
Date of Test:	26.01.2005	Pass	
Test setup:	Setup 3		
Operating conditions:	Under normal test conditions		
Method of testing:	Radiated		
S.A. Settings:	RBW: 9kHz, VBW: 30 kHz,		
Mode of operation:	Receive		
Environment conditions:	Ambient Temperature: 21°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 117 – Plot 118	

Test results of I media:

“Phase” Lead

Frequency [MHz]	Measured Result [dBμV]		Class B Limit [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.175841	58.9	26.3	64.68	54.68	-5.78	-28.38	Pass
0.20851	55.4	23.9	63.26	53.26	-7.86	-29.36	Pass
0.239335	49.8	18	62.12	52.12	-12.32	-34.12	Pass
0.444184	36.8	34.6	56.98	46.98	-20.18	-12.38	Pass
0.885753	34.4	32.5	56.00	46.00	-21.60	-13.50	Pass
6.087554	34.5	29.2	60.00	50.00	-25.50	-20.80	Pass

“Neutral” Lead

Frequency [MHz]	Measured Result [dBμV]		Class B Limit [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.188981	52.1	44.3	64.08	54.08	-11.98	-9.78	Pass
0.252617	42.8	38.4	61.67	51.67	-18.87	-13.27	Pass
0.377182	35.1	34.4	58.34	48.34	-23.24	-13.94	Pass
0.444184	34.9	34.2	56.98	46.98	-22.08	-12.78	Pass
0.885753	36.4	34.9	56.00	46.00	-19.60	-11.10	Pass
6.087554	32.8	24.2	60.00	50.00	-27.20	-25.80	Pass

4. Appendix


Appendix A: List of Measuring Equipment used:

Equipment	Manufacturer/ Model	Serial Number	Due date
CISPR16 EMI Receiver	HP8546A	3710A00392	30-06-05
Spectrum Analyzer 9kHz ÷ 22 GHz	HP 8593EM	3536A00131	30-06-05
Spectrum Analyzer 100 Hz ÷ 26.5 GHz	Agilent E7405A	US41160436	30-06-05
LNA Amplifier 1 GHz ÷ 18 GHz	AMP – 5D-010180-30-10P-GW	618653	01-01-06
Dual Ridged Guide Ant.1-18 GHz	EMCO 3115	9602-4677	01-01-06
Antenna 18 GHz ÷ 26.5 GHz	Alpha Industry 861A/599	505	01-01-06
Turn table	HD100	100/693	-
Antenna Mast	HD 100	100/693	-
Biconical 20 –200 MHz	Schwarzbeck VHBB9124	9124/0255	16-05-06
Log-Periodic 200 – 1000 MHz	Schwarzbeck VUSLP9111	VUSLP9111184	16-05-06
Pre-Amplifier	MiTeq, AMF-5F-18002650-30-10P	945372	01-01-06
LISN	Fischer 50/250-25-2	-	30-06-05
Transient Limiter	HP11947A	-	30-06-05
Notch Filter	Micro-Tronics BRM50702-05	0001	01-01-2006

Appendix B: Plots


Plot 1

Agilent 15:12:18 26 Apr 2005




Plot 2

Agilent 15:13:11 26 Apr 2005




Plot 3

Agilent 15:14:03 26 Apr 2005




Plot 4

Agilent 15:14:39 26 Apr 2005




Plot 5

Agilent 14:51:16 26 Apr 2005




Plot 6

Agilent 15:53:27 1 May 2005




Plot 7

Agilent 18:22:54 1 May 2005




Plot 8

Agilent 12:45:32 26 Apr 2005




Plot 9

Agilent 12:47:21 26 Apr 2005




Plot 10

Agilent 12:41:02 26 Apr 2005




Plot 11

Agilent 12:42:42 26 Apr 2005




Plot 12

Agilent 18:18:36 25 Apr 2005




Plot 13

Agilent 13:56:06 26 Apr 2005




Plot 14

Agilent 14:44:55 25 Apr 2005




Plot 15

Agilent 14:42:28 25 Apr 2005




Plot 16

Agilent 14:37:51 25 Apr 2005




Plot 17

✱ Agilent 14:57:31 25 Apr 2005




Plot 18

✱ Agilent 15:00:56 25 Apr 2005




Plot 19

✱ Agilent 15:04:26 25 Apr 2005




Plot 20

✱ Agilent 16:54:01 25 Apr 2005




Plot 21

Agilent 17:23:30 25 Apr 2005




Plot 22

Agilent 17:33:07 25 Apr 2005




Plot 23

Agilent 17:40:10 25 Apr 2005




Plot 24


Agilent 15:13:57 11 May 2005




Plot 25




Plot 26




Plot 27




Plot 28




Plot 29




Plot 30



Plot 31




Plot 32




Plot 33

Agilent 19:18:34 1 May 2005




Plot 34

Agilent 19:08:42 1 May 2005




iMedia


**Lowest
Plot 35
Horizontal Polarization**




**Plot 36
Vertical Polarization**




Plot 37 Horizontal Polarization




Plot 38 Vertical Polarization




Plot 39 Horizontal Polarization




Plot 40 Vertical Polarization



Plot 41 Horizontal Polarization




Plot 42 Vertical Polarization




Plot 43 Horizontal Polarization

Agilent 17:19:17 2 May 2005




Plot 44 Vertical Polarization


Agilent 17:08:42 2 May 2005




**Middle
Plot 45
Horizontal Polarization**




**Plot 46
Vertical Polarization**




Plot 47 Horizontal Polarization




Plot 48 Vertical Polarization




Plot 49 Horizontal Polarization




Plot 50 Vertical Polarization



Plot 51 Horizontal Polarization




Plot 52 Vertical Polarization




Plot 53 Horizontal Polarization

✱ Agilent 17:29:48 2 May 2005




Plot 54 Vertical Polarization


✱ Agilent 17:27:35 2 May 2005




**Highest
Plot 55
Horizontal Polarization**




**Plot 56
Vertical polarization**




Plot 57
Horizontal Polarization




Plot 58
Vertical polarization




Plot 59 Horizontal Polarization




Plot 60 Vertical polarization



Plot 61 Horizontal Polarization




Plot 62 Vertical polarization




Plot 63 Horizontal Polarization

✱ Agilent 17:40:46 2 May 2005




Plot 64 Vertical polarization

✱ Agilent 17:31:46 2 May 2005




iMedia RF Controller


Lowest Plot 65 Horizontal Polarization




Plot 67 Vertical Polarization




Plot 68 Horizontal Polarization




Plot 69 Vertical Polarization




Plot 70 Horizontal Polarization




Plot 71 Vertical Polarization



Plot 72
Horizontal Polarization




Plot 73
Vertical Polarization




Plot 74 Horizontal Polarization

✱ Agilent 06:51:05 11 May 2005




Plot 75 Vertical Polarization


✱ Agilent 08:50:22 15 May 2005




**Middle
Plot 76
Horizontal Polarization**




**Plot 77
Vertical Polarization**




Plot 78 Horizontal Polarization




Plot 79 Vertical Polarization




Plot 80
Horizontal Polarization




Plot 81
Vertical Polarization




Plot 82 Horizontal Polarization



Plot 83 Vertical Polarization




Plot 84
Horizontal Polarization




Plot 85
Vertical Polarization


**Highest
Plot 86
Horizontal Polarization**




**Plot 87
Vertical polarization**




Plot 88 Horizontal Polarization




Plot 89 Vertical polarization




Plot 90 Horizontal Polarization




Plot 91 Vertical polarization



Plot 92 Horizontal Polarization




Plot 93 Vertical polarization




Plot 94 Horizontal Polarization

Agilent 06:45:57 11 May 2005




Plot 95 Vertical polarization


Agilent 09:00:22 15 May 2005




Plot 96
Horizontal Polarization




Plot 97
Vertical Polarization




Plot 98 Horizontal Polarization




Plot 99 Vertical Polarization




Plot 100 Horizontal Polarization




Plot 102 Vertical Polarization



Plot 103 Horizontal Polarization




Plot 104 Vertical Polarization




Plot 105 Horizontal Polarization

Agilent 18:26:09 4 May 2005




Plot 106 Vertical Polarization


Agilent 18:30:57 4 May 2005




Plot 107
Horizontal Polarization




Plot 108
Vertical Polarization



Plot 109 Horizontal Polarization




Plot 110 Vertical Polarization




Plot 111 Horizontal Polarization

Agilent 09:16:49 15 May 2005




Plot 112 Vertical Polarization

Agilent 09:15:32 15 May 2005




Plot 113 Horizontal Polarization

Agilent 09:21:35 15 May 2005




Plot 114 Vertical Polarization

Agilent 09:22:07 15 May 2005




Plot 115 Horizontal Polarization

Agilent 09:07:15 15 May 2005




Plot 116 Vertical Polarization


Agilent 08:58:10 15 May 2005



Plot 117
"Phase" Lead




Plot 118
"Neutral" Lead




Appendix C: Test setups


Setup 1



Setup 2



Setup 3



End of the Test Report