



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: TEB-HUNTGS10122  
IC: 5931A-HUNTGS10122**

**FCC Rule Part: 15.247  
IC Radio Standards Specification: RSS-210**

**ACS Project Number: 11-0031**

Manufacturer: Hunt Technologies, Inc.  
Model: 10122

## **RF Exposure**

**General Information:**

Applicant: Hunt Technologies, Inc.  
 ACS Project: 11-0031  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information 900MHz:**

Antenna Type: Patch  
 Antenna Gain: 2.15dBi  
 Maximum Transmitter Conducted Power: 26.97dBm  
 Maximum System EIRP: 29.12dBm, 816.6 mW  
 Exposure Conditions: Greater than 20 centimeters

**Technical Information 2400MHz ZigBee:**

Antenna Type: PCB inverted-F  
 Antenna Gain: 5.15dBi  
 Maximum Transmitter Conducted Power: 21.06dBm  
 Maximum System EIRP: 26.21 dBm, 417.8 mW  
 Exposure Conditions: Greater than 20 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
904	26.97	0.60	497.74	2.15	1.641	20	0.162
2405	21.06	1.00	127.64	5.15	3.273	20	0.083

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.