



FCC LISTED,  
REGISTRATION  
NUMBER: 905266

IC LISTED,  
REGISTRATION  
NUMBER: IC 4621

CENTRO DE  
TECNOLOGÍA DE LAS  
COMUNICACIONES, S.A.  
Parque Tecnológico de Andalucía,  
c/Sévero Ochoa nº 2  
29590 Campanillas/ Málaga/ España  
Tel. 952 61 91 00 - Fax 952 61 91 13  
MÁLAGA, C.I.F. A29 507 456  
Registro Mercantil Tomo 1169 Libro 82  
Folio 133 Hoja MA3729

## TEST REPORT



Report No.: 22542RET.101

TEST NAME: FCC PART 15.247 TESTING FOR BLUETOOTH RADIO DEVICE

Product	:	BLUETOOTH STEREO HEADSET
Trade Mark	:	SIEMENS
Model/type Ref.	:	HHB-750
Manufacturer	:	PHILIPS PERSONNAL CONNECTIVITY
Requested by	:	PHILIPS PERSONNAL CONNECTIVITY
Other identification of the product	:	FCC ID: TF6-HHB750 IC: 135I-HHB750 Prototype
Standard(s)	:	USA FCC Part 15.247, 15.205, 15.209, 15.109 CANADA RSS-210

This test report includes 2 annexes and therefore the total number of pages is 60.

**IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (CETECOM).**

Date: 2005-07-26	Test operator A. Llamas 	Revised by: Date: 28.07.05 J. C. Soler Consultant  DE LAZ DE TECNOLOGÍA DE LAS COMUNICACIONES Approved by: Date: 28. July 2005 A. Rojas Technical Director 	Page: 1 of 8
------------------	---	--	--------------

**INDEX**

1. COMPETENCE AND GUARANTEES .....	3
2. GENERAL CONDITIONS .....	3
3. CHARACTERISTICS OF THE TEST .....	3
3.1 TEST REQUESTED.....	3
3.2 REQUIREMENTS AND METHOD .....	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT.....	4
4.1 APPLICANT.....	4
4.2 REPRESENTATIVE.....	4
4.3 TEST SAMPLES SUPPLIER.....	4
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED .....	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS .....	5
5.1 USAGE OF SAMPLES .....	5
5.2 PERIOD OF TESTING .....	6
5.3 ENVIROMENTAL CONDITIONS.....	6
6. TEST RESULTS .....	7
7. REMARKS AND COMMENTS.....	7
8. SUMMARY.....	8

**ANNEXES**

ANNEX A. TEST RESULTS

ANNEX B. PHOTOGRAPHS

Report No.: 22542RET.101		Page: 2 of 8
Date: 2005-07-26		

## 1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621.

In order to assure the traceability to other national and international laboratories, CETECOM has a calibration and maintenance programme for its measuring equipment.

CETECOM guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at CETECOM at the time of execution of the test.

CETECOM is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

## 2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of CETECOM.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of CETECOM and the Accreditation Bodies.

## 3. CHARACTERISTICS OF THE TEST

### 3.1 TEST REQUESTED

Measurements for frequency hopping spread spectrum equipment (Bluetooth) operating in the 2400 MHz -2483.5 MHz band and using, according to FCC Part 15.247.

### 3.2 REQUIREMENTS AND METHOD

The test has been carried out according to FCC parts 15.33, 15.35, 15.109, 15.205, 15.209, 15.247 and the document DA 00-705:"Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems".

The testing was performed according to the procedure in ANSI C63.4. Radiated testing was performed in Cetecom's semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002.

Report No.: 22542RET.101		Page: 3 of 8
Date: 2005-07-26		

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Antenna mast EM 1072 NMT.
4. Rotating table EM 1084-4. ON.
5. Multi device controller ETS 2090.
6. Bilog antenna CHASE CBL6111.
7. Antenna tripod EMCO 11968C.
8. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
9. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
10. RF pre-amplifier Miteq JS4-12002600-30-5A.
11. Semianechoic Absorber Lined Chamber IR 11. BS.
12. RF pre-amplifier Miteq AFS5-04001300-15-10P-6.
13. RF pre-amplifier Schaffner CPA 9231.
14. Spectrum analyzer R&S ESIB 26.
15. Spectrum analyzer R&S FSM.
16. DC power supply R&S NGPE 40/40.

#### **4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT**

Identification data in this section has been supplied by the client.

##### **4.1 APPLICANT**

**Name or Company:** PHILIPS PERSONNAL CONNECTIVITY

**V.A.T.:** -----

**Address:** Route d'Angers

**City:** Le Mans, Cedex 9

**Postal code:** 72081

**Country:** FRANCE

**Telephone:** +33243411730

**Fax:** +33243411745

##### **4.2 REPRESENTATIVE**

**Name:** Mr. Daniel Chaillou

##### **4.3 TEST SAMPLES SUPPLIER**

**Name or Company:** Same as indicated in point 4.1.

Report No.: 22542RET.101		Page: 4 of 8
Date: 2005-07-26		

Samples undergoing test have been selected by: **the client.**

#### 4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

## Product: BLUETOOTH STEREO HEADSET

**Trade mark: SIEMENS** **Model: HHB-750**

**Manufacturer:** : PHILIPS PERSONNAL CONNECTIVITY

**Country of manufacture:** ROMANIA

**Manufacture site:** Data not available

**Description:** The Bluetooth Stereo Headset is a convenient (wearing comfort, stability) wireless Stereo Headset.

The headset consists of a small main body incorporating the Bluetooth hardware, a display and control elements and a separate short corded stereo-headset with ear-buds and microphone.

The LC-display is for showing Caller ID and MP3/AAC titles and other file information. The box offers buttons to control for call functionality. It also includes remote control functions for music to start and stop playback and skip to the next/previous title.

The Stereo Headset speakers offer a frequency range which is suitable for listening to music with a MP3/AAC-Player. The earpieces can be placed at the main body, specially formed molds and magnets will keep the earpieces in position.

The Headset is powered by a single exchangeable AAA alkaline battery. A separate battery lid is necessary for exchanging the battery.

## 5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

## 5.1 USAGE OF SAMPLES

**Sample M/01 is formed by the following elements:**

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22542/03	Bluetooth Headset with integral antenna	HHB-750	Prototype	05/07/2005

**Sample M/02 is formed by the following elements:**

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
22542/02	Bluetooth Headset with connector	HHB-750	Prototype	05/07/2005

Report No.: 22542RET.101		Page: 5 of 8
Date: 2005-07-26		

1. Sample M/01 has undergone following test(s).  
Radiated measurements indicated in annex A.
  
2. Sample M/02 has undergone following test(s).  
All tests indicated in annex A, except radiated measurements.

## 5.2 PERIOD OF TESTING

The performed test started on 2005-07-05 and finished on 2005-07-06.

The tests as detailed in this report have been performed at CETECOM.

## 5.3 ENVIRONMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 24 °C Max. = 24 °C
Relative humidity	Min. = 48 % Max. = 48 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 22 °C Max. = 22 °C
Relative humidity	Min. = 51 % Max. = 51 %
Air pressure	Min. = 1019 mbar Max. = 1019 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

Report No.: 22542RET.101		Page: 6 of 8
Date: 2005-07-26		

In the chamber for conducted measurements the following limits were no exceeded during the test:

Temperature	Min. = 22 °C Max. = 22 °C
Relative humidity	Min. = 45 % Max. = 45 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

## 6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

**P** Pass  
**F** Fail  
**NA** not applicable  
**NM** not measured

FCC PART 15 PARAGRAPH	VERDICT			
	NA	P	F	NM
15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation	P			
15.247 Subclause (a) (1) (iii). Number of hopping channels	P			
15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)	P			
15.247 Subclause (b). Maximum peak output power and antenna gain	P			
15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)	P			
15.247 Subclause (d). Emission limitations conducted (Transmitter)	P			
15.247 Subclause (d). Emission limitations radiated (Transmitter)	P			
15.109. Receiver spurious radiation	P			

## 7. REMARKS AND COMMENTS

None.

Report No.: 22542RET.101		Page: 7 of 8
Date: 2005-07-26		

## 8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 “TEST REQUESTED”.

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 “IDENTIFICATION OF ITEM/ITEMS TESTED” of this document, as presented for test on the date(s) declared in section 5, “USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS”.

Report No.: 22542RET.101		Page: 8 of 8
Date: 2005-07-26		

**ANNEX A**  
**TEST RESULTS**

**Report No: 22542RET.101**

Report No: 22542RET.101		Page: 1 of 45
Date: 2005-07-26 FET45_00.DOC		Annex A

## INDEX

	Page
TEST CONDITIONS .....	3
Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation....	4
Section 15.247 Subclause (a) (1) (iii). Number of hopping channels .....	9
Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time) .....	11
Section 15.247 Subclause (b). Maximum peak output power and antenna gain.....	14
Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter) .....	21
Section 15.247 Subclause (d). Emission limitations conducted (Transmitter).....	25
Section 15.247 Subclause (d). Emission limitations radiated (Transmitter) .....	28
Section 15.109. Receiver spurious radiation .....	38

Report No: 22542RET.101		Page: 2 of 45
Date: 2005-07-26		Annex A

## TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 1.4 \text{ Vdc}$$

Type of power supply = Single exchangeable AAA alkaline battery.

Type of antenna = Integral antenna

Maximum Declared Gain for antenna = 0 dBi

Operating Temperature Range (°C):

$$T_n = 0 \text{ to } +35$$

## TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

The test set-up was made in accordance to the general provisions of ANSI C63.4.

## CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyser via the antenna connector (sma type) provided with the test sample. No coaxial low-loss connecting cable was necessary for such connection so no cable attenuation correction was made.

## RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Report No: 22542RET.101		Page: 3 of 45
Date: 2005-07-26		Annex A

**Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation****SPECIFICATION**

Frequency hopping system shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

**RESULTS**


20 dB Bandwidth (see next 3 plots).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	829.66	829.66	829.66
Measurement uncertainty (kHz)	$\pm 11$		

Report No: 22542RET.101		Page: 4 of 45
Date: 2005-07-26		Annex A

20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.



Report No:  
22542RET.101


Page: 5 of 45

Date: 2005-07-26

Annex A

20 dB BANDWIDTH.

Middle Channel: 2441 MHz.



Report No:  
22542RET.101


Page: 6 of 45

Date: 2005-07-26

Annex A

20 dB BANDWIDTH.

Highest Channel: 2480 MHz.




Report No:  
22542RET.101

Page: 7 of 45

Date: 2005-07-26

Annex A

Carrier frequency separation (see next plot).



The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Report No: 22542RET.101		Page: 8 of 45
Date: 2005-07-26		Annex A


### Section 15.247 Subclause (a) (1) (iii). Number of hopping channels

#### SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels.


#### RESULTS

The number of hopping channels is 79 (see next two plots).



Number of hopping frequencies: 39

Report No: 22542RET.101		Page: 9 of 45
Date: 2005-07-26 FET45_00.DOC		Annex A



Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

Report No: 22542RET.101		Page: 10 of 45
Date: 2005-07-26		Annex A

### Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)

#### SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed =  $0.4 \times 79 = 31.6$  seconds.


#### RESULTS

##### 1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of  $625\mu\text{s}$  with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/2 = 800$  hops per second with 79 channels. So you have each channel  $800/79 = 10.13$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $10.13 \times 31.6 = 320.11$  times of appearance.

Each Tx-time per appearance is  $426.85 \mu\text{s}$  (see next plot).

So we have  $320.11 \times 426.85 \mu\text{s} = 136.64 \text{ ms}$  per 31.6 seconds.



Verdict: PASS


Report No: 22542RET.101		Page: 11 of 45
Date: 2005-07-26		Annex A

## 2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet need 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/4 = 400$  hops per second with 79 channels. So you have each channel  $400/79 = 5.1$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $5.1 \times 31.6 = 161.16$  times of appearance.

Each Tx-time per appearance is 1.67 ms (see next plot).

So we have  $161.16 \times 1.67 \text{ ms} = 269.14 \text{ ms}$  per 31.6 seconds.



Verdict: PASS


Report No: 22542RET.101		Page: 12 of 45
Date: 2005-07-26		Annex A

### 3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet need 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/6 = 266.67$  hops per second with 79 channels. So you have each channel  $266.67/79 = 3.37$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $3.37 \times 31.6 = 106.49$  times of appearance.

Each Tx-time per appearance is 2.93 ms (see next plot).

So we have  $106.49 \times 2.93$  ms = 312.02 ms per 31.6 seconds.



Verdict: PASS

Report No: 22542RET.101		Page: 13 of 45
Date: 2005-07-26 FET45_00.DOC		Annex A

**Section 15.247 Subclause (b). Maximum peak output power and antenna gain****SPECIFICATION**

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm).

**RESULTS**

MAXIMUM PEAK OUTPUT POWER (CONDUCTED). See next plots.

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	2.73	2.51	2.50
Measurement uncertainty (dB)	±1.5		

The maximum declared antenna gain for this device is 0 dBi, therefore the maximum theoretical peak radiated power (EIRP) in the three measurement channels for this device is 2.73 dBm or 1.87 mW.

The actual peak radiated power (EIRP) was measured for the lowest, middle and highest frequency (see next plots):

MAXIMUM PEAK OUTPUT POWER (RADIATED).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Correction Factor (dB)	34.96	35.10	35.24
Maximum EIRP peak power (dBm)	0.76	0.91	1.04
Measurement uncertainty (dB)	+1.98 / -1.75		

Declared peak gain: 0 dBi


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

Report No: 22542RET.101		Page: 14 of 45
Date: 2005-07-26		Annex A

## PEAK OUTPUT POWER (CONDUCTED).

Lowest Channel: 2402 MHz.

Report No:  
22542RET.101


Page: 15 of 45

Date: 2005-07-26

Annex A

## PEAK OUTPUT POWER (CONDUCTED).


Middle Channel: 2441 MHz.



Report No: 22542RET.101		Page: 16 of 45
Date: 2005-07-26		Annex A

## PEAK OUTPUT POWER (CONDUCTED).


Highest Channel: 2480 MHz.



Report No: 22542RET.101		Page: 17 of 45
Date: 2005-07-26		Annex A

**PEAK OUTPUT POWER (RADIATED).**


Lowest Channel: 2402 MHz.



Report No: 22542RET.101		Page: 18 of 45
Date: 2005-07-26		Annex A

**PEAK OUTPUT POWER (RADIATED).**


Middle Channel: 2441 MHz.



Report No: 22542RET.101		Page: 19 of 45
Date: 2005-07-26		Annex A

## PEAK OUTPUT POWER (RADIATED).

Highest Channel: 2480 MHz.



Report No: 22542RET.101		Page: 20 of 45
Date: 2005-07-26		Annex A


### Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)

#### SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

#### RESULTS:


1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.



Verdict: PASS

Report No: 22542RET.101		Page: 21 of 45
Date: 2005-07-26		Annex A


2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.



Verdict: PASS

Report No: 22542RET.101		Page: 22 of 45
Date: 2005-07-26		Annex A


3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

Report No: 22542RET.101		Page: 23 of 45
Date: 2005-07-26		Annex A

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

Report No: 22542RET.101		Page: 24 of 45
Date: 2005-07-26		Annex A


## Section 15.247 Subclause (d). Emission limitations conducted (Transmitter)

## **SPECIFICATION**

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

## RESULTS:

1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).




Date: 6.JUL.2005 10:19:45

Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22542RET.101		Page: 25 of 45
Date: 2005-07-26		Annex A

2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22542RET.101		Page: 26 of 45
Date: 2005-07-26		Annex A

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 22542RET.101		Page: 27 of 45
Date: 2005-07-26		Annex A

**Section 15.247 Subclause (d). Emission limitations radiated (Transmitter)****SPECIFICATION**

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

**RESULTS:**

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Report No: 22542RET.101		Page: 28 of 45
Date: 2005-07-26		Annex A

Note: The spurious emissions below 1 GHz do not depend on the operating channel selected in the EUT.

**Frequency range 30 MHz-1000 MHz. Spurious levels (radiated) closest to limit.**

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Uncertainty (dB)
179.679359	H	Quasi-peak	25.71	$\pm 3.8$ dB
181.623246	H	Quasi-peak	19.99	$\pm 3.8$ dB
399.338677	H	Quasi-peak	25.91	$\pm 3.8$ dB
403.226453	H	Quasi-peak	25.95	$\pm 3.8$ dB
560.681363	H	Quasi-peak	27.95	$\pm 3.8$ dB
576.232465	H	Quasi-peak	28.56	$\pm 3.8$ dB
607.3346693	H	Quasi-peak	29.53	$\pm 3.8$ dB
617.0541082	H	Quasi-peak	28.78	$\pm 3.8$ dB
624.3296593	H	Quasi-peak	28.61	$\pm 3.8$ dB

**Frequency range 1 GHz-25 GHz.**

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4804.0930	H	Peak	47.12	$\pm 4.0$
4804.0930	H	Average	43.89	$\pm 4.0$

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Report No: 22542RET.101		Page: 29 of 45
Date: 2005-07-26		Annex A

**2. CHANNEL: MIDDLE (2441 MHz).**

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4881.9670	H	Peak	45.60	$\pm$ 4.0
4881.9670	H	Average	41.11	$\pm$ 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

**3. CHANNEL: HIGHEST (2480 MHz).**


Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4959.9310	H	Peak	48.83	$\pm$ 4.0
4959.9310	H	Average	46.41	$\pm$ 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS

Report No: 22542RET.101		Page: 30 of 45
Date: 2005-07-26		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels).

Report No: 22542RET.101		Page: 31 of 45
Date: 2005-07-26		Annex A


FREQUENCY RANGE 1 GHz to 2.9 GHz.

**CHANNEL: Lowest (2402 MHz).**




Note: The peak above the limit is the carrier frequency.

**CHANNEL: Middle (2441 MHz).**



Note: The peak above the limit is the carrier frequency.

Report No: 22542RET.101		Page: 32 of 45
Date: 2005-07-26		Annex A


**CHANNEL: Highest (2480 MHz).**

Note: The peak above the limit is the carrier frequency.


Report No: 22542RET.101		Page: 33 of 45
Date: 2005-07-26		Annex A

FREQUENCY RANGE 2.9 GHz to 12.75 GHz.


**CHANNEL: Lowest (2402 MHz).**



**CHANNEL: Middle (2441 MHz).**



Report No: 22542RET.101		Page: 34 of 45
Date: 2005-07-26		Annex A

**CHANNEL: Highest (2480 MHz).**

Report No:  
22542RET.101


Date: 2005-07-26

FET45\_00.DOC

Page: 35 of 45

Annex A


FREQUENCY RANGE 12.75 GHz to 18 GHz.



(This plot is valid for all three channels).

Report No: 22542RET.101		Page: 36 of 45
Date: 2005-07-26		Annex A

FREQUENCY RANGE 18 GHz to 25 GHz.



(This plot is valid for all three channels).

Report No: 22542RET.101		Page: 37 of 45
Date: 2005-07-26		Annex A

**Section 15.109. Receiver spurious radiation****SPECIFICATION**

The field strength shall not exceed the following values:

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

**RESULTS:**

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Report No: 22542RET.101		Page: 38 of 45
Date: 2005-07-26		Annex A

Note: The spurious emissions below 1 GHz do not depend on the receiving channel selected in the EUT.

**Frequency range 30 MHz-1000 MHz.**

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Uncertainty (dB)
339.078156	H	Quasi-peak	26.84	$\pm 3.8$ dB
319.639278	H	Quasi-peak	27.14	$\pm 3.8$ dB
368.236473	H	Quasi-peak	28.19	$\pm 3.8$ dB
383.787575	H	Quasi-peak	25.28	$\pm 3.8$ dB

**Frequency range 1 GHz-25 GHz.**

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
1602.3230	H	Peak	39.33	$\pm 4.0$
1602.3230	H	Average	35.65	$\pm 4.0$

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
1628.5720	H	Peak	37.50	$\pm 4.0$
1628.5720	H	Average	33.57	$\pm 4.0$

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Report No: 22542RET.101		Page: 39 of 45
Date: 2005-07-26		Annex A

## 3. CHANNEL: HIGHEST (2480 MHz).


Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
1654.3740	H	Peak	38.37	$\pm$ 4.0
1654.3740	H	Average	35.14	$\pm$ 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS.

Report No: 22542RET.101		Page: 40 of 45
Date: 2005-07-26		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.



(This plot is valid for all three channels)

Report No:  
22542RET.101


Page: 41 of 45

Date: 2005-07-26


Annex A

FREQUENCY RANGE 1 GHz-12.75 GHz.


**CHANNEL: Lowest (2402 MHz).**



**CHANNEL: Middle (2441 MHz).**




Report No: 22542RET.101		Page: 42 of 45
Date: 2005-07-26		Annex A

**CHANNEL: Highest (2480 MHz).**

Report No: 22542RET.101		Page: 43 of 45
Date: 2005-07-26		Annex A


FREQUENCY RANGE 12.75 GHz-18 GHz.



(This plot is valid for all three channels).

Report No: 22542RET.101		Page: 44 of 45
Date: 2005-07-26		Annex A

FREQUENCY RANGE 18 GHz-25 GHz.



(This plot is valid for all three channels)

Report No: 22542RET.101		Page: 45 of 45
Date: 2005-07-26		Annex A

## **ANNEX B**

### **PHOTOGRAPHS**

**(Number of photographs: 6)**

**Report No.: 22542RET.101**


Report No.: 22542RET.101		Page: 1 of 7
Date: 2005-07-26		Annex B

1. Equipment (external view)



Report No.: 22542RET.101		Page: 2 of 7
Date: 2005-07-26		Annex B


## 2. Equipment for conducted measurements.



Report No.:		Page: 3 of 7
22542RET.101		


 Date: 2005-07-26 |  | Annex B |

3. General test set-up for radiated measurements.




Report No.: 22542RET.101		Page: 4 of 7
Date: 2005-07-26		Annex B

## 4. Test set-up for radiated measurements below 1 GHz.



Report No.: 22542RET.101		Page: 5 of 7
Date: 2005-07-26		Annex B

## 5. Test set-up for radiated measurements above 1 GHz.



Report No.: 22542RET.101		Page: 6 of 7
Date: 2005-07-26		Annex B

6. Test set-up for RF conducted measurements.



Report No.:  
22542RET.101

Date: 2005-07-26

Page: 7 of 7

Annex B