

ODYSSEY 2.4G DIODE LASER

POWER INPUT: 100-240V ~ 50-60HZ 1.5A
WORKING BEAM WAVELENGTH: 810±10 NM
810 NM POWER OUTPUT: 5 WATTS
AIMING BEAM WAVELENGTH: 650±30 NM
650 NM POWER OUTPUT: 3 MILLIWATTS
WIRELESS FREQUENCY: 2.4 GHz
FUSE: T2A / 250V
MODEL: 595126
MANUF DATE: MMM YYYY
SERIAL: XXXXXX

MANUFACTURED FOR:
IVOCLAR VIVADENT, INC.
175 PINEVIEW DR.
AMHERST, NY 14228
ASSEMBLED IN USA

COMPLIES WITH:
MANUFACTURED FOR:
IVOCLAR VIVADENT, INC.
175 PINEVIEW DR.
AMHERST, NY 14228
ASSEMBLED IN USA



FCCID: TFIODYSSSEY24G
IC: 5810A-ODYSSEY 2.4G



COMPLIES WITH:
21 CFR 1040.10 & 1040.11 EXCEPT FOR DEVIATIONS
PURSUANT TO LASER NOTICE 50,
DATED JULY 26, 2001
ALSO COMPLIES WITH
IEC 60601-1:1998+A1; IEC 60601-2-22:1995;
IEC 60825-1:1993+A1+A2
*This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.*
PATENTS PENDING