

# FCC Test Report

## FCC ID: TFJNPOSJUNIOR

**Product:** Mobile POS Tablet

**Trade Mark:** UIC

**Model Number:** nPOS Junior

**Family Model:** N/A

**Report No.:** S20102601202006

**Prepared for**

Uniform Industrial Corp.  
2901 Bayview Dr. Fremont, CA 94538

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel.: +86-755-6115 6588  
Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name**.....: Uniform Industrial Corp.

Address .....: 2901 Bayview Dr.Fremont, CA 94538

**Manufacturer's Name**.....: Uniform Industrial Corp.

Address .....: 1F.,No1,Ln.15,Ziqiang St.,TuchengDist.,New Taipei City  
236,R.O.C.

### Product description

Product name .....: Mobile POS Tablet

Model and/or type reference : nPOS Junior

Family Model .....: N/A

FCC Part15B

**Standards**.....: ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** .....:

Date (s) of performance of tests.....: 15 Dec. 2020 ~ 08 Jan. 2021

Date of Issue .....: 12 Jan. 2021

Test Result .....: **Pass**

Testing Engineer : 

(Allen Liu)

Technical Manager : 

(Jason Chen)

Authorized Signatory : 

(Alex Li)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
3.2.2 TEST PROCEDURE	15
3.2.3 TEST SETUP	16
3.2.4 TEST RESULTS	17
3.2.5 TEST RESULTS(1000~26500MHz)	19

## 1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

IC-Registration The Certificate Registration Number is 9270A.

CAB identifier:CN0074

FCC- Accredited Test Firm Registration Number: 463705.

Designation Number: CN1184

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	±2.80dB	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz~1000MHz	±2.64dB	
		1GHz~6GHz	±2.40dB	
		6GHz~26.5GHz	±2.52dB	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mobile POS Tablet				
Trade Mark	UIC				
Model Name	nPOS Junior				
Family Model	N/A				
Model Difference	N/A				
Product Description	<p>The EUT is a Mobile POS Tablet.</p> <table border="1"><tr><td>Connecting I/O port:</td><td>Micro USB, Earphone</td></tr><tr><td>Operation Frequency:</td><td>1.3GHz</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Connecting I/O port:	Micro USB, Earphone	Operation Frequency:	1.3GHz
Connecting I/O port:	Micro USB, Earphone				
Operation Frequency:	1.3GHz				
Power Source	DC 3.8V/7000mAh from battery or DC 5V from Adapter.				
Adapter	Model: PA1024-050HUB400 Input: 100-240V~50-60Hz 0.6A Output: 5V ---4.0A 20W Max				
HW Version	TVE1048D_V01				
SW Version	Windows 10 19H2 64-bit Pro version				

### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM
Mode 5	GPS

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM
Mode 5	GPS


For Radiated Test	
Final Test Mode	Description
Mode 1	USB Data Transmission
Mode 2	TF card Playing
Mode 3	REC
Mode 4	FM
Mode 5	GPS

Note: Final Test Mode: Through Pre-scan, find the mode 1 is the worst case.


Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP

CE



RE



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	PA1024-050HUB400	N/A	Peripherals
AE-2	Load	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	Power Cable	NO	NO	1.2m	
C-2	Power Cable	NO	NO	1.0m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

## Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2020.05.11	2021.05.10	1 year
2	Test Receiver	R&S	ESPI	101318	2020.05.11	2021.05.10	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2020.04.11	2021.04.10	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2020.05.11	2021.05.10	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2020.05.11	2021.05.10	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2020.04.11	2021.04.10	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2020.05.11	2021.05.10	1 year
8	Amplifier	EMC	EMC051835SE	980246	2020.07.13	2021.07.12	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2020.05.11	2021.05.10	1 year
10	Power Meter	DARE	RPR3006W	15I00041S NO84	2020.07.13	2021.07.12	1 year
11	Power Sensor	R&S	URV4-Z4	0395.1619.05	2020.05.11	2021.05.10	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2020.07.13	2021.07.12	1 year
13	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
14	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2020.04.11	2021.04.10	1 year

## AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2020.05.11	2021.05.10	1 year
2	LISN	R&S	ENV216	101313	2020.04.11	2021.04.10	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2020.05.11	2021.05.10	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2021.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**  
**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.


## 3.1.5 TEST RESULTS

EUT:	Mobile POS Tablet	Model Name. :	nPOS Junior
Temperature:	25 °C	Relative Humidity:	62%
Pressure:	1010hPa	Test Date:	2021-01-05
Test Mode:	Mode 1	Phase :	L
Test Voltage:	DC 5V from PC AC 120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1539	48.28	9.56	57.84	65.78	-7.94	QP
0.1539	39.02	9.56	48.58	55.78	-7.20	AVG
0.1900	43.57	9.55	53.12	64.03	-10.91	QP
0.1900	34.04	9.55	43.59	54.03	-10.44	AVG
0.2429	39.23	9.55	48.78	61.99	-13.21	QP
0.2429	29.10	9.55	38.65	51.99	-13.34	AVG
0.4858	30.53	9.55	40.08	56.24	-16.16	QP
0.4858	21.70	9.55	31.25	46.24	-14.99	AVG
7.0297	23.38	9.65	33.03	60.00	-26.97	QP
7.0297	14.00	9.65	23.65	50.00	-26.35	AVG
13.0739	31.38	9.74	41.12	60.00	-18.88	QP
13.0739	21.71	9.74	31.45	50.00	-18.55	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Mobile POS Tablet	Model Name.:	nPOS Junior
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2021-01-05
Test Mode:	Mode 1	Phase :	N
Test Voltage:	DC 5V from PC AC 120V/60Hz		

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.1554	49.42	9.55	58.97	65.70	-6.73	QP
0.1554	39.44	9.55	48.99	55.70	-6.71	AVG
0.1980	43.50	9.54	53.04	63.69	-10.65	QP
0.1980	34.02	9.54	43.56	53.69	-10.13	AVG
0.2740	37.48	9.53	47.01	60.99	-13.98	QP
0.2740	28.72	9.53	38.25	50.99	-12.74	AVG
0.3659	32.89	9.54	42.43	58.59	-16.16	QP
0.3659	23.00	9.54	32.54	48.59	-16.05	AVG
2.6099	19.37	9.58	28.95	56.00	-27.05	AVG
2.6099	9.75	9.58	19.33	46.00	-26.67	QP
13.7939	29.35	9.74	39.09	60.00	-20.91	QP
13.7939	19.41	9.74	29.15	50.00	-20.85	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the

worst case is recorded in the report  
During the radiated emission test, according to ANSI C63.4-2014(4.2), the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



## 3.2.4 TEST RESULTS


## TEST RESULTS (30~1000 MHz)

EUT:	Mobile POS Tablet	Model Name:	nPOS Junior
Temperature:	25 °C	Relative Humidity:	55%
Pressure:	1010 hPa	Test Date :	2021-01-05
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from PC AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	55.8046	21.86	6.53	28.39	40.00	-11.61	QP
H	63.5356	22.15	6.20	28.35	40.00	-11.65	QP
H	77.5926	21.03	7.67	28.70	40.00	-11.30	QP
H	98.8324	19.61	10.78	30.39	43.50	-13.11	QP
H	210.0482	22.04	9.93	31.97	43.50	-11.53	QP
H	420.5803	16.57	18.27	34.84	46.00	-11.16	QP

## Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	Mobile POS Tablet	Model Name :	nPOS Junior
Temperature:	25 °C	Relative Humidity:	55%
Pressure:	1010 hPa	Test Date :	2021-01-05
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from PC AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.9791	16.09	17.55	33.64	40.00	-6.36	QP
V	44.4307	19.04	11.68	30.72	40.00	-9.28	QP
V	56.9911	24.74	6.37	31.11	40.00	-8.89	QP
V	66.0340	26.97	6.10	33.07	40.00	-6.93	QP
V	78.6888	21.29	7.87	29.16	40.00	-10.84	QP
V	106.0126	18.96	11.11	30.07	43.50	-13.43	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



## 3.2.5 TEST RESULTS(1000~18000MHz)

EUT:	Mobile POS Tablet	Model Name :	nPOS Junior
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2021-01-05
Test Mode :	Mode 1		
Test Power :	DC 5V from PC AC 120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Reading	Correct	Result	Limit	Over Limit	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	1297.5	40.85	2.16	43.01	74	-30.99	peak
V	1297.5	32.86	2.16	35.02	54	-18.98	AVG
V	1807.5	38.91	3.91	42.82	74	-31.18	peak
V	1807.5	27.34	3.91	31.25	54	-22.75	AVG
V	2105	38.87	6.29	45.16	74	-28.84	peak
V	2105	27.16	6.29	33.45	54	-20.55	AVG
V	2955	39.87	6.24	46.11	74	-27.89	peak
V	2955	29.08	6.24	35.32	54	-18.68	AVG
V	4315	37.65	11.95	49.6	74	-24.4	peak
V	4315	27.27	11.95	39.22	54	-14.78	AVG
V	4825	35.47	13.63	49.1	74	-24.9	peak
V	4825	24.82	13.63	38.45	54	-15.55	AVG
H	1212.5	40.25	2.08	42.33	74	-31.67	peak
H	1212.5	31.27	2.08	33.35	54	-20.65	AVG
H	1510	39.78	2.45	42.23	74	-31.77	peak
H	1510	29.2	2.45	31.65	54	-22.35	AVG
H	2105	38.6	6.29	44.89	74	-29.11	peak
H	2105	28.83	6.29	35.12	54	-18.88	AVG
H	2955	38.73	6.24	44.97	74	-29.03	peak
H	2955	25.92	6.24	32.16	54	-21.84	AVG
H	3847.5	36.42	10.36	46.78	74	-27.22	peak
H	3847.5	23.05	10.36	33.41	54	-20.59	AVG
H	4230	36.96	11.52	48.48	74	-25.52	peak
H	4230	25.02	11.52	36.54	54	-17.46	AVG

## Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Only the worst results data points are reported in the report.

END OF REPORT