

Nemko Korea Co., Ltd.

300-2, Osan-Ri, Mohyun-Myeon, Cheoin-Gu, Yongin-City, Gyeonggi-Do, Korea

TEL: + 82 31 322 2333 FAX: + 82 31 322 2332

FCC PART 15 Class II Permissive Change

Applicant :

D&T Inc.

Daedeok Valley, 59-9, Jang Dong, Yuseong Gu,
Daejeon, 305-343 Korea

Attn : Mr. W. W. Lee

Dates of Issue : November 18, 2008

Test Report No. : NK08E829

Test Site : Nemko Korea Co., Ltd.

EMC site, Korea

FCC ID

THCFS-P6501C

Brand Name

TANDBERG

Contact Person

D&T Inc.

**Daedeok Valley, 59-9, Jang Dong, Yuseong Gu,
Daejeon, 305-343 Korea**

Mr. W. W. Lee

Telephone No. : + 82 42 360 0820

Applied Standard: Part 15 & 2
Classification : FCC Class B Device
EUT Type: 65" LCD Monitor

The device bearing the brand name and FCC ID specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Tested By : C. S. Choi
Engineer



Reviewed By : D.H. Ryu
Manager & Chief Engineer

D&T Inc.

FCC ID : THCFS-P6501C

Page 1 of 58

TABLE OF CONTENTS

SCOPE	3
INTRODUCTION (Site Description)	4
TEST CONDITIONS & EUT INFORMATION	5
SUMMARY OF TEST RESULTS	9
RECOMMANDATION / CONCLUSION	9
SAMPLE CALCULATION	9
DESCRIPTION OF TESTS (Conducted Emissions)	10
DESCRIPTION OF TESTS (Radiated Emissions)	11
TEST DATA (Conducted Emissions)	12
TEST DATA (Radiated Emissions)	13
PLOT OF EMISSIONS (Conducted Emissions Diagram)	16
ACCURACY OF MEASUREMENT	20
LIST OF TEST EQUIPMENT	21
APPENDIX A - SAMPLE LABEL	22
APPENDIX B - PHOTOGRAPHS OF TEST SET-UP	23
APPENDIX C - EUT PHOTOGRAPHS	25
APPENDIX D – MODIFICATION LIST	52
APPENDIX E - BLOCK DIAGRAM	56
APPENDIX F - USER'S MANUAL	57
APPENDIX G - SCHEMATIC DIAGRAM	58

SCOPE

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15.

Responsible Party :

D&T Inc.

Contact Person :

Mr. W. W. Lee

Tel No.: + 82 42 360 0820

Manufacturer :

D&T Inc.

Daedeok Valley, 59-9, Jang Dong, Yuseong Gu,
Daejeon, 305-343 Korea

Factory :

D&T Inc.

Daedeok Valley, 59-9, Jang Dong, Yuseong Gu,
Daejeon, 305-343 Korea

- FCC ID: THCFCS-P6501C
- Model: FS-P6501C
- EUT Type: 65" LCD Monitor
- Electric Rating: a.c. 100-240 V, 50-60 Hz, 5 A MAX.
- Test Voltage: a.c. 120 V, 60 Hz
- Port/Connector: HDMI, RGB, RS-232C
- Classification: FCC Class B
- Applied Standard: FCC Part 15 & Part 2
- Test Procedure(s): ANSI C63.4 (2003)
- Dates of Test: October 29, 2008 to November 14, 2008
- Place of Tests: Nemko Korea Co., Ltd. EMC Site
- Test Report No.: NK08E829

INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) was used in determining radiated and conducted emissions emanating from **D&T Inc.**


FCC ID : **THCFS-P6501C, 65" LCD Monitor.**

These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory.**

The site address is 300-2, Osan-Ri, Mohyun-Myeon, Cheoin-Gu, Yongin-City, Gyeonggi-Do, KOREA. The area of Nemko Korea Corporation Ltd. EMC Test Site is located in a mountain area at 80 kilometers (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 kilometers (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on 2003.



Nemko Korea Co., Ltd.
OPEN AREA TEST SITE
300-2, Osan-Ri, Mohyun-Myeon,
Cheoin-Gu, Yongin-City, Gyeonggi-Do,
KOREA, 449-852
Tel)+ 82 31 322 2333
Fax)+ 82 31 322 2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.

The map also shows Nemko Korea Corporation Ltd. EMC Lab and Incheon Airport.

TEST CONDITIONS & EUT INFORMATION

Operating During Test

The EUT was connected to the PC and it displayed continuously an "H" pattern on the screen. The EUT was set to 1920 x 1080 video resolution, with 60 Hz vertical refresh rate.

Support Equipment

65" LCD Monitor (EUT)	D&T Inc. FCC ID : THCFCS-P6501C 2.0 m shielded HDMI cable 1.8 m shielded Analogue cable	S/N: N/A
PC	Dell ASIA PACIFIC SDN Model : DHM(Dimension 4550) 1.6 m unshielded AC power cable	FCC DOC S/N: N/A
Keyboard	Samsung Electro-Mechanics Model : SEM-DT35 1.5 m shielded Din cable	FCC DOC S/N: 3V006171
PS/2 Mouse	KYE SYSTEMS Model : SCROLL MOUSE P801 1.9 m unshielded Din cable	FCC ID : FSUGMZFT S/N: 1181250
Serial Mouse	ALL SPIRIT CO., LTD. Model : WS-V1-400 1.6 m unshielded serial cable	FCC DOC S/N: B050402
Printer	HEWLETT PACKARD COMPANY. Model : C6429A 1.8 m shielded parallel cable 1.8 m unshielded AC power cable	FCC DOC S/N: N/A

EUT Information

Clock	27.00 MHz (Y1), 28.322 MHz(Y2)
Chipset(s)	U4(SII8185), U9(PW338C), U10(SII9185),
	U14/U15(K4H561638H-UCCC), U12(M29W800DT),
	U27(AD9984A), U29(ATmega88V)
LCD Panel Type	A-si TFT Active matrix
Screen size	163.9 cm (Diagonal)
Maximum Resolution	1920 x 1080 @ 60 Hz
Pixel pitch	0.744 (H) mm x 0.744 (V) mm
Display colors	16.7 M (RGB 8-bit data)
Contrast Ratio(Typ.)	2000:1
Viewing Angle(Typ.)	88/88/88/88
Response Time(Typ.)	6 ms
Luminance(Typ.)	450 cd/m ²
Synchronization	Horizontal Frequency : 25 ~ 90 kHz
	Vertical Frequency : 24 ~ 120 Hz
Power Consumption	Maximum : 500 W
Port(s)	HDMI, RGB, RS-232C
Size and weight	1532 x 170 x 1235.5 / 130.5 kg

Description of Test Modes

The EUT was pre-tested under the following resolutions mode:

1. 800 X 600 (60 Hz / 37 kHz) : Clock 35.5 MHz
2. 1280 X 720 (60 Hz / 45 kHz) : Clock 74.25 MHz
3. 1366 X 768 (60 Hz / 48.3 kHz) : Clock 87.75 MHz
4. 1680 X 1050 (60 Hz / 64.7 kHz) : Clock 119.125 MHz
5. 1920 X 1080 (60 Hz / 76.5 kHz) : Clock 148.5 MHz

The worst emission level was found when the EUT was tested under 1920 x 1080 resolution, therefore, the test data of this mode was recorded in the report.

Description of the Changes according to FCC part 2.1043


Please see appendix D of the test report. (page 52 ~ 55)

EUT System

Equipment	Model	Manufacturer	Serial Number
LCD Panel	LK645D3LZ6L	SHARP	87-010
LB506 Main Board	0300400302AA	D&T Inc.	N/A
AC Divide Board	0300990311AA	D&T Inc.	N/A
IO Board	0300990410AA	D&T Inc.	N/A
Inverter Board	IM3852-1	D&T Inc.	N/A
	IM3852-2	D&T Inc.	N/A
Status Indicator Board	0300990414AA	D&T Inc.	N/A
Inverter Divide Board	0300990112AA	D&T Inc.	N/A
Before	SMPS Board ¹⁾ (Right)	0627D04349(R1) Transformer : PSP8004FL ²⁾	Li Shin International Enterprise Corp.
	SMPS Board ¹⁾ (Left)	0627D04349(R1) Transformer : PSP8004FL ²⁾	Li Shin International Enterprise Corp.
After	SMPS Board ¹⁾ (Right)	0627D04349 Transformer : 5124-0611-0 ²⁾	Li Shin International Enterprise Corp.
	SMPS Board ¹⁾ (Left)	0627D04349(R1) Transformer : PSP8004FL ²⁾	Li Shin International Enterprise Corp.

1) Now the manufacture (D&T Inc.) will use 2 kinds of SMPS Board (0627D04349, 0627D04349(R1)). Because the 0627D04349 will be EOL (End Of Line) a few months later, and they will use new one 0627D04349(R1). But the inventory of old one is too many, so they will install the old one for first MP product.

2) The type PSP8004FL is similar to type 5124-0611-0, except for the size of core and outer insulation tapes on the windings (see appendix C)

Setup Drawing

SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

Name of Test	Paragraph No.	Result	Remark
Conducted Emission	15.107(a)	Complies	
Radiated Emission	15.109(g)	Complies	Below 1 GHz
Radiated Emission	15.109(a)	Complies	Above 1 GHz

RECOMMENDATION/CONCLUSION

The data collected shows that the **D&T Inc.**

FCC ID : **THCFS-P6501C, 65" LCD Monitor.**

The highest emission observed was at **0.27 MHz** for conducted emissions with a A.V margin of **3.9 dB**, at **80.42 MHz** for radiated emissions with a margin of **3.2 dB**.

SAMPLE CALCULATION

$$\text{dB } \mu\text{V} = 20 \log_{10} (\mu\text{V}/\text{m})$$

$$\mu\text{V} = 10^{(\text{dB } \mu\text{V}/20)}$$

EX. 1.

@57.7 MHz

Class B limit = 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$

Reading = 19.1 dB μV (calibrated level)

Antenna factor + Cable Loss = 10.12 dB

Total = 29.22 dB $\mu\text{V}/\text{m}$

Margin = 40.0 - 29.22 = 10.78

10.78 dB below the limit

DESCRIPTION OF TESTS

Conducted Emissions

The Line conducted emission test facility is located inside a 4 X 7 X 2.5 m shielded enclosure.

It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6.

A 1 m X 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 0.5 m away from the side of wall of the shielded room

Rohde & Schwarz (ESH2-Z5) and Kyoritsu (KNW-407) of the 50 ohm / 50 uH Line Impedance Stabilization Network(LISN) are bonded to the shielded room.

The EUT is powered from the Rohde & Schwarz LISN and the support equipment is powered from the Kyoritsu LISN. Power to the LISN s are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1/2".

If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs,

All interconnecting cables more than 1 m were shortened by non inductive bundling (serpentine fashion) to a 1 m length.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 20 ms sweep time.

The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30).

The detector function were set to CISPR quasi-peak mode & average mode.

The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; which ever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

DESCRIPTION OF TESTS

Radiated Emissions

Preliminary measurement were made indoors at 3 meter using broad band antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The Technology configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was note for each frequency found. The spectrum was scanned from 30 to 1000 MHz using Biconical log Antenna(ARA, LPB-2520/A). Above 1 GHz, Double Ridged Broadband Horn Antenna (SCHWARTZBECK, BBHA9120D) was used.

Final Measurements were made outdoors at 3 m or 10 m test range using Trilog-Broadband Antenna (Shwarzbeck, VULB9168) or Double Ridged Broadband Horn Antenna (SCHWARTZBECK, BBHA9120D). The test equipment was placed on a wooden table.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was reexamined and investigated using EMI test receiver. (ESCS30)

The detector function were set to CISPR quasi-peak and peak mode and the bandwidth of the receiver were set to 120 kHz and 1 MHz depending on the frequency or type of signal. The half wave dipole antenna was tuned to the frequency found during preliminary radiated measurements.

The EUT support equipment and interconnecting cables were re configured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non- metallic 1.0 X 1.5 meter table.

The EUT, support equipment and interconnecting cables were re-arranged and manipulated to maximize each EME emission.

The turn table containing the Technology was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by : switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; which ever determined the worst case emission.

Each EME reported was calibrated using the R/S signal generator.




Fig. 3. Dimensions of Outdoor Test Site

TEST DATA

Conducted Emissions

FCC ID : THCFCS-P6501C

► Analogue mode

Frequency (MHz)	Level(dB μ N)		Line	Limit(dB μ N)		Margin(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.27	50.5	47.2	L	61.1	51.1	10.6	3.9
1.19	37.5	27.5	L	56.0	46.0	18.5	18.5
1.37	38.0	28.2	L	56.0	46.0	18.0	17.8
7.63	41.1	33.0	L	60.0	50.0	18.9	17.0
19.44	46.4	32.6	L	60.0	50.0	13.6	17.4
29.91	42.4	31.1	N	60.0	50.0	17.6	18.9

Table 1. Line Conducted Emissions Tabulated Data

► HDMI mode

Frequency (MHz)	Level(dB μ N)		Line	Limit(dB μ N)		Margin(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.27	50.6	47.2	N	61.1	51.1	10.5	3.9
1.18	36.9	29.8	L	56.0	46.0	19.1	16.2
1.38	38.0	28.0	N	56.0	46.0	18.0	18.0
7.63	40.5	32.1	N	60.0	50.0	19.5	17.9
19.44	46.4	32.8	N	60.0	50.0	13.6	17.2
29.92	42.0	31.0	L	60.0	50.0	18.0	19.0

Table 2. Line Conducted Emissions Tabulated Data

NOTES:

1. Measurements using CISPR quasi-peak mode & average mode.
2. All modes of operation were investigated and the worst -case emission are reported. See attached Plots.
3. LINE : L =Line , N = Neutral
4. The limit for Class B device is on the FCC Part section 15.107(a).



Tested by : C. S. Choi

D&T Inc.

Page 12 of 58

FCC ID : THCFCS-P6501C

TEST DATA

Radiated Emissions

FCC ID : THCF5-P6501C

► 30 MHz ~ 1 GHz (Analogue mode)

Frequency (MHz)	Reading (dB μ N/m)	Pol* (H/V)	AF+CL+Amp (dB)**	Result (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
79.23	43.3	V	-16.7	26.6	30.0	3.4
80.40	42.9	V	-16.4	26.5	30.0	3.5
81.26	42.4	V	-16.2	26.2	30.0	3.8
192.39	33.5	H	-11.5	22.0	30.0	8.0
797.75	28.9	H	0.5	29.4	37.0	7.6
900.80	22.1	H	2.7	24.8	37.0	12.2

Table 3. Radiated Measurements at 10 meters (1920 x 1200, 60 Hz)

► 30 MHz ~ 1 GHz (HDMI mode)

Frequency (MHz)	Reading (dB μ N/m)	Pol* (H/V)	AF+CL+Amp (dB)**	Result (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
79.23	43.4	V	-16.7	26.7	30.0	3.3
80.42	43.2	V	-16.4	26.8	30.0	3.2
81.28	42.7	V	-16.2	26.5	30.0	3.5
192.41	33.6	H	-11.5	22.1	30.0	7.9
797.76	28.7	H	0.5	29.2	37.0	7.8
900.81	22.3	H	2.7	25.0	37.0	12.0

Table 4. Radiated Measurements at 10 meters (1920 x 1200, 60 Hz)

► 1 GHz ~ 2 GHz (Analogue mode)

Frequency (MHz)	Reading (dB μ N)		Pol* (H/V)	AF+CL+Amp (dB)**	Limit (dB μ N/m)		Final Result (dB μ N/m)	
	Peak	Average			Peak	Average	Peak	Average
1063.36	54.8	38.8	H	-6.5	74.0	54.0	48.3	32.3
1151.09	59.0	47.6	H	-6.3	74.0	54.0	52.7	41.3
1296.14	54.6	54.0	H	-5.8	74.0	54.0	48.8	48.2
1543.93	53.6	38.4	H	-5.2	74.0	54.0	48.4	33.2
1781.57	53.7	41.9	V	-4.6	74.0	54.0	49.1	37.3
1863.53	59.6	45.4	H	-4.1	74.0	54.0	55.5	41.3

NOTES : Measurements using peak mode & average mode.

Table 5. Radiated Measurements at 3 meters (1920 x 1200, 60 Hz)

►1 GHz ~ 2 GHz (HDMI mode)

Frequency (MHz)	Reading (dB μ N)		Pol* (H/V)	AF+CL+Amp (dB)**	Limit (dB μ N/m)		Final Result(dB μ N/m)	
	Peak	Average			Peak	Average	Peak	Average
1151.51	57.2	48.4	H	-6.3	74.0	54.0	50.9	42.1
1296.07	56.1	54.0	H	-5.8	74.0	54.0	50.3	48.2
1336.65	55.0	49.2	H	-5.7	74.0	54.0	49.3	43.5
1634.07	57.2	53.2	V	-5.1	74.0	54.0	52.1	48.1
1782.79	57.4	53.7	V	-4.6	74.0	54.0	52.8	49.1
1863.48	53.3	45.7	V	-4.1	74.0	54.0	49.2	41.6

NOTES : Measurements using peak mode & average mode.

Table 6. Radiated Measurements at 3 meters (1920 x 1200, 60 Hz)




Fig. 4. Limits at 10 meters

NOTES:

- 1. The worst-case emission was reported.**
- 2. Below 1 GHz, the radiated limits are shown on Figure 4.**




Fig. 5. Limits at 3 meters

NOTES:

- 1. The worst-case emission was reported.**
- 2. Above 1 GHz, the radiated limits are shown on Figure 5.**

NOTES:


1. *Pol. H=Horizontal V=Vertical
2. **AF+CL+Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Measurements using CISPR quasi-peak mode below 1 GHz.
4. The limit for Class B device is on the FCC Part section 15.109(g) & (a).
5. All modes of operations were invested and the worst -case emission was reported.
6. Above 1 GHz, peak detector function mode is used using a resolution bandwidth of 1 MHz and a video bandwidth of 1 MHz, average detector function mode is used using a resolution bandwidth of 1 MHz and a video bandwidth of 30 Hz.
Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.



Tested by : **C. S. Choi**


PLOTS OF EMISSIONS

- ***Conducted Emission at the Mains port (Analogue mode, Line)***




PLOTS OF EMISSIONS

- ***Conducted Emission at the Mains port (Analogue mode, Neutral)***




PLOTS OF EMISSIONS

- **Conducted Emission at the Mains port (HDMI mode, Line)**



PLOTS OF EMISSIONS

- **Conducted Emission at the Mains port (HDMI mode, Neutral)**



ACCURACY OF MEASUREMENT

The Measurement Uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 with the confidence level of 95 %

1. Radiation Uncertainty Calculation

<i>Contribution</i>	<i>Probability Distribution</i>	<i>Uncertainty(+/-dB)</i>
Antenna Factor	Normal ($k = 2$)	± 0.5
Cable Loss	Normal ($k = 2$)	± 0.04
Receiver Specification	Rectangular	± 2.0
Antenna directivity		
Antenna Factor variation with Height		
Antenna Phase Center Variation	Rectangular	± 1.0
Antenna Factor Frequency Interpolation		
Measurement Distance Variation		
Site Imperfections	Rectangular	± 2.0
Mismatch: Receiver VRC $r_i=0.3$		
Antenna VRC $r_R=0.1(B_i)0.4(L_p)$	U-Shaped	$+ 0.25 / - 0.26$
Uncertainty Limits $20\log(1+/-r_i r_R)$		
System Repeatability	Std.deviation	± 0.05
Repeatability of EUT	-	-
Combined Standard Uncertainty	Normal	± 1.77
Expendited Uncertainty U	Normal ($k = 2$)	± 3.5

2. Conducted Uncertainty Calculation

<i>Contribution</i>	<i>Probability Distribution</i>	<i>Uncertainty(+/-dB)</i>
Receiver Specification	Normal ($k = 2$)	± 2.0
LISN coupling spec.	Normal ($k = 2$)	± 0.4
Cable and input attenuator cal.	Rectangular	± 0.4
Mismatch: Receiver VRC $r_i=0.3$		
LISN vrc $r_g=0.1$	U-Shaped	± 0.26
Uncertainty Limits $20\log(1+/-r_i r_R)$		
System Repeatability	Std.deviation	± 0.68
Repeatability of EUT	-	-
Combined Standard Uncertainty	Normal	± 1.18
Expendited Uncertainty U	Normal ($k = 2$)	± 2.4

LIST OF TEST EQUIPMENT

No.	Instrument	Manufacturer	Model	Serial No.	Calibration Date	Calibration Interval
1	*Test Receiver	R & S	ESCS 30	833364/020	Apr. 01 2008	1year
2	*Test Receiver	R & S	ESCS 30	100302	Dec. 03 2007	1year
3	*Amplifier	HP	8447F	2805A03427	Jul. 21 2008	1year
4	Amplifier	HP	8447F	2805A03351	Oct. 23 2008	1year
5	*Amplifier	HP	8447F	2805A03406	Apr. 17 2008	1year
6	*Pre Amplifier	HP	8449B	3008A00107	Feb. 27 2008	1year
7	Spectrum Analyzer	Advantest	R3265A	45060401	Dec. 04 2007	1year
8	*Spectrum Analyzer	R & S	FSP40	100361	Sep. 04,2008	1year
9	*Spectrum Analyzer	Agilent	E4440A	MY44022567	Dec. 04, 2007	1year
10	Spectrum Analyzer	HP	8566B	2607A03469	Feb. 27 2008	1year
11	Loop Antenna	EMCO	EMCO/6502	8911-2436	Dec. 13 2007	1year
12	Biconical Log Antenna	ARA	LPB-2520/A	1180	Apr. 21 2008	1year
13	*Biconical Log Antenna	ARA	LPB-2520/A	1209	Dec. 31 2007	1year
14	*Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-257	Apr. 21 2008	1year
15	*Double Ridged Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-474	June. 13 2008	1year
16	Signal Generater	R & S	SMP02	833286/003	Jul. 21 2008	1year
17	*LISN	R & S	ESH2-Z5	100227	Sep. 02 2008	1year
18	*LISN	Kyoritsu	KNW-407	8-1034-10	Feb. 27 2008	1year
19	*Position Controller	DAEIL EMC	N/A	N/A	N/A	N/A
20	*Turn Table	DAEIL EMC	N/A	N/A	N/A	N/A
21	*Antenna Mast	DAEIL EMC	N/A	N/A	N/A	N/A
22	*Anechoic Chamber	EM Eng.	N/A	N/A	N/A	N/A
23	*Shielded Room	EM Eng.	N/A	N/A	N/A	N/A
24	*Position Controller	Seo-Young EMC	N/A	N/A	N/A	N/A
25	*Turn Table	Seo-Young EMC	N/A	N/A	N/A	N/A
26	*Antenna Mast	Seo-Young EMC	N/A	N/A	N/A	N/A
27	*Anechoic Chamber	Seo-Young EMC	N/A	N/A	N/A	N/A
28	*Shielded Room	Seo-Young EMC	N/A	N/A	N/A	N/A

**) Test equipment used during the test*


APPENDIX A – SAMPLE LABEL

Labelling Requirements

The sample label shown shall be *permanently affixed* at a conspicuous location on the device and be readily visible to the user at the time of purchase.



● FCC ID Location of EUT



APPENDIX B – PHOTOGRAPHS OF TEST SET-UP

The **Conducted Test Picture** and **Radiated Test Picture** and show the worst-case configuration and cable placement.

- **Conducted Test Picture(Front)**




- **Conducted Test Picture(Rear)**



● Radiated Test Picture(Front)





● Radiated Test Picture(Rear)






APPENDIX D – MODIFICATION LIST


1. On the LCD Panel Module Assembly.

Before	After
	
1) Removed all kind of EMI tape and gasket on the LCD Panel	

2. On the LVDS Cable.



Before	After
	
	
1) One more ferrite core(ZCAT1518-0730A, TDK) installed on the DC power wire with one time turning.	
2) Both DC power wire(Black and white) must be twisted each other	
3) EMI Tape removed on this cable	

3. On the SMPS cable

Before	After
	

1) Four Ferrite core(PC2910, SCC) installed on this cable.

4. SMPS Cable Arrangement


Before	After
	

1) both SMPS cable must be arranged in this way with insulation sheet to prevent touching SMPS circuit.


5. On the speaker Assembly

Before	After
	
1) EMI Tape removed at left and right speaker	
2) Rubber damper installed to prevent the vibration from speaker	



6. Signal cable arrangement



Before	After
	
1) one ferrite core(ZCAT1730-0730A,TDK) installed on the RS232C wire	
2) One ferrite core(ZCAT2035-0930A,TDK) installed on both inductor cable with 1 time turning.	
3) EMI Tape removed on this wire	

7. Crossover filter board

Before	After
	
1) Crossover filter board installed on the main chassis : Originally this board was installed in the speaker cabinet before, but now it will be moved on the main chassis	

8. Main chassis

Before	After
	
1) Main chassis cut off for the heat ventilation. 2) EMI Form gasket installed on this point to make contact with rear cover.	

9. Add the SMPS Boards

10. Status indicator board


2kind of Status indicator board will be modified

- 1) one more LED will be added for each indication logo
- 2) PCB Coating color will be changed from green to black

APPENDIX E – BLOCK DIAGRAM

APPENDIX F – USER'S MANUAL

APPENDIX G – SCHEMATIC DIAGRAM
