

Test Report

Report Number:

F182314E3

Equipment under Test (EUT):

dosing module

Applicant:

Mettler-Toledo GmbH

Manufacturer:

Mettler-Toledo GmbH



Deutsche
Akkreditierungsstelle
D-PL-17186-01-01
D-PL-17186-01-02
D-PL-17186-01-03

References

- [1] **ANSI C63.10: 2013** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- [2] **FCC CFR 47 Part 15** Radio Frequency Devices
- [3] **RSS-210 Issue 9 (August 2016)** Licence-Exempt Radio Apparatus: Category I Equipment
- [4] **RSS-Gen Issue 5 (March 2019) Amendment 1** General Requirements for Compliance of Radio Apparatus

Test result

The requirements of the tests performed as shown in the overview (chapter 4 of this test report) were fulfilled by the equipment under test.

The complete test results are presented in the following.

Tested and written by:	Thomas KÜHN		24.04.2019
	Name	Signature	Date
Authorized reviewer:	Bernd STEINER		24.04.2019
	Name	Signature	Date

This test report is only valid in its original form.

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

This test report is valid in hardcopy form as well as in electronic form.

Contents:	Page
1 Identification	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Test Laboratory	4
1.4 EUT (Equipment under Test).....	5
1.5 Technical data of equipment.....	5
1.6 Ancillary Equipment.....	6
1.7 Dates.....	6
2 Operational states and test setup.....	6
3 Additional information.....	6
4 Overview	7
5 Results	8
5.1 Conducted emissions on power supply lines (150 kHz to 30 MHz)	8
5.1.1 Method of measurement	8
5.1.2 Test results (conducted emissions on power supply lines).....	9
5.2 Radiated emissions	10
5.2.1 Method of measurement (radiated emissions)	10
5.2.2 Results preliminary measurement 9 kHz to 1 GHz.....	17
5.2.3 Result final measurement from 9 kHz to 30 MHz	20
5.2.4 Result final measurement from 30 MHz to 1 GHz	21
5.3 99 % bandwidth	23
5.3.1 Method of measurement	23
5.3.2 Test results	24
6 Test equipment.....	25
7 Report history	26
8 List of annexes	26

1 Identification

1.1 Applicant

Name:	Mettler-Toledo GmbH
Address:	Im Langacher 44, 8606 Greifensee
Country:	Switzerland
Name for contact purposes:	Mr. David KRESS
Phone:	+41 44 944 23 84
eMail address:	David.Kress@mt.com
Applicant represented during the test by the following person:	---

1.2 Manufacturer

Name:	Mettler-Toledo GmbH
Address:	Im Langacher 44, 8606 Greifensee
Country:	Switzerland
Name for contact purposes:	Mr. David KRESS
Phone:	+41 44 944 23 84
eMail address:	David.Kress@mt.com
Manufacturer represented during the test by the following person:	---

1.3 Test Laboratory

The tests were carried out at:

PHOENIX TESTLAB GmbH
Königswinkel 10
32825 Blomberg
Germany

Accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS) in compliance with DIN EN ISO/IEC 17025 under Reg. No. D-PL-17186-01-02 and D-PL-17186-01-05, FCC Test Firm Designation Number DE0004, FCC Test Firm Registration Number 469623, CAB Identifier DE0003 and ISED# 3469A.

1.4 EUT (Equipment under Test)

Test object: *	RFID Reader/Writer
Model name / HVIN: *	dosing module
Serial number: *	00000 2239
FCC ID: *	THVQ3MODULE
IC: *	22032-Q3MODULE
PCB identifier: *	30240559 / E, 30327921 / D, 30465127 / B
PMN: *	dosing module
Software version / FVIN: *	30323760 1.0.0.1, 30323761 0.9.1.205
Highest internal frequency: *	48 MHz

*: Declared by the applicant

Note: PHOENIX TESTLAB GmbH does not take samples. The sample used for tests is provided exclusively by the customer.

1.5 Technical data of equipment

Operating frequency: *	125 kHz
Power supply: *	Externally 12 V _{DC} by dedicated power supply FSP060-DIBAN2
Supply voltage: *	U _{nom} = 12.0 V _{DC} U _{min} = 10.8 V _{DC} U _{max} = 13.2 V _{DC}
Type of modulation: *	ASK
Antenna connector: *	None (soldered to PCB)
Number of channels: *	1
Antenna type: *	Wired coil antenna with ferrite core Antenna area 0.00216 m ²
Data rate: *	5.2 kbit/s
Temperature range: *	5 °C to +40 °C

*: Declared by the applicant

Ports / Connectors			
Identification	Connector		Length during test
	EUT	Ancillary	
EUT connector	SMD Single Row spring connector 6P	SMD Single Row spring connector 6P	0 cm
-	-	-	-
-	-	-	-
-	-	-	-

1.6 Ancillary Equipment

- Test Adapter for operation in measurement chamber (provided by the applicant),
- Dedicated AC/DC adapter Type FSP060-DIBAN2 (provided by the applicant)
- Dosing Head containing RFID Transponder (provided by the applicant),
- Siemens Fujitsu Laptop PC type Lifebook E series Model E780 (provided by the laboratory).

1.7 Dates

Date of receipt of test sample:	13.03.2019
Start of test:	20.03.2019
End of test:	01.04.2019


2 Operational states and test setup

The EUT is a tagging system, which is part of a liquid weighting system. As declared by the applicant, it will be connected to a pump module, which is regarded as host and not part of this test report. The EUT will always be used with a dedicated AC/DC adaptor type FSP060-DIBAN2.

During all measurements the EUT was mounted on a test adapter and equipped with a dosing head with integrated TAG. The test adapter was supplied by the dedicated AC/DC adaptor type FSP060-DIBAN2.

All measurements were carried out with an unmodified sample operating in a test mode. The test mode was entered with the help of a test-software running on a laptop PC, which is connected to the Test Adapter via the RS 232 interface. With this test mode the TAG data were cyclic read and the TAG was written.

Physical boundaries of the Equipment Under Test



3 Additional information

None.

4 Overview

Application	Frequency range [MHz]	FCC 47 CFR Part 15 section [2]	RSS-Gen [4] and RSS 210 [3]	Status	Refer page
Conducted emissions on supply line	0.15 – 30	15.207	8.8 [4]	Passed	8 et seq.
Radiated emissions	0.009 – 1.000	15.205 15.209	4.1 and 4.4 [3] 8.9 and 8.10 [4]	Passed	10 et seq.
99 % bandwidth	0.125	-	6.7 [4]	-	23 et seq.
Antenna requirement	-	15.203	6.8 [4]	Passed *	-

*: Integrated antenna only, requirement fulfilled.

5 Results


5.1 Conducted emissions on power supply lines (150 kHz to 30 MHz)

5.1.1 Method of measurement

This test will be carried out in a shielded chamber. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm above the ground plane. Floor-standing devices will be placed directly on the ground plane. The setup of the Equipment under test will be in accordance to [1].

The frequency range 150 kHz to 30 MHz will be measured with an EMI Receiver set to MAX Hold mode with peak and average detector and a resolution bandwidth of 9 kHz. A scan will be carried out on the phase (or plus pole in case of DC powered devices) of the AC mains network. If levels detected 10 dB below the appropriable limit, this emission will be measured with the average and quasi-peak detector on all lines.

Frequency range	Resolution bandwidth
150 kHz to 30 MHz	9 kHz



5.1.2 Test results (conducted emissions on power supply lines)

Ambient temperature	20 °C	Relative humidity	32 %
---------------------	-------	-------------------	------


Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m.

Cable guide: The cable of the EUT was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The test was carried out in TAG reading and writing mode of the EUT (refer also clause 2 of this test report). All results are shown in the following.

Supply voltage: During this test the EUT was powered with 12 V_{AC} by the test adapter, which was itself supplied by an AC/DC adaptor type FSP60-DIBAN2 (connected to an AC mains network with 120 V_{AC} / 60 Hz).

The curves in the diagram only represent for each frequency point the maximum measured value of all preliminary measurements which were made for each power supply line. The top measured curve represents the peak measurement and the bottom measured curve the average measurement. The quasi-peak measured points are marked by ◆ the average measured points are marked with ▼.



Data record name: 182314_AC

Remark: The limits of FCC 15.207 are identical to [3]

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Transducer (dB)
0.451500	43.3	---	56.9	13.6	5000	9.000	N	GND	9.9
0.453300	43.2	---	56.8	13.6	5000	9.000	N	GND	9.9
0.453300	---	35.2	46.8	11.6	5000	9.000	N	GND	9.9
0.767400	32.9	---	56.0	23.1	5000	9.000	N	GND	9.9
1.441500	29.7	---	56.0	26.3	5000	9.000	L1	GND	9.9
16.122300	27.5	---	60.0	32.5	5000	9.000	L1	FLO	10.8
Measurement uncertainty			±2.8 dB						

Test: Passed

Test equipment used (see clause 6):

6 - 14

5.2 Radiated emissions

5.2.1 Method of measurement (radiated emissions)

The radiated emission measurement is subdivided into six stages.

- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 9 kHz to 1 GHz.
- A final measurement carried out on an outdoor test site without reflecting ground plane and a fixed antenna height in the frequency range 9 kHz to 30 MHz.
- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 30 MHz to 1 GHz.
- A final measurement carried out on an open area test site with reflecting ground plane and various antenna heights in the frequency range 30 MHz to 1 GHz.
- A preliminary measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 5 GHz.
- A final measurement carried out in a fully anechoic chamber with a fixed antenna height in the frequency range 1 GHz to 5 GHz.


Preliminary measurement (9 kHz to 30 MHz):

In the first stage a preliminary measurement will be performed in a shielded room with a measuring distance of 3 meters. Table-top devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to [1].

The frequency range 9 kHz to 30 MHz will be monitored with a spectrum analyser while the system and its cables will be manipulated to find out the configuration with the maximum emission levels if applicable. The EMI Receiver will be set to MAX Hold mode. The EUT and the measuring antenna will be rotated around their vertical axis to found the maximum emissions.

The resolution bandwidth of the spectrum analyser will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	10 kHz



Preliminary measurement procedure:

Prescans were performed in the frequency range 9 kHz to 150 kHz and 150 kHz to 30 MHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
- 2) Manipulate the system cables within the range to produce the maximum level of emission.
- 3) Rotate the EUT by 360 ° to maximize the detected signals.
- 4) Make a hardcopy of the spectrum.
- 5) Measure the frequencies of highest detected emission with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 6) Repeat steps 1) to 5) with the other orthogonal axes of the EUT (because of EUT is a module and might be used in a handheld equipment application).
- 7) Rotate the measuring antenna and repeat steps 1) to 5).


Final measurement (9 kHz to 30 MHz):

In the second stage a final measurement will be performed on an open area test site with no conducting ground plane in a measuring distances of 3 m, 10 m and 30 m. In the case where larger measuring distances are required the results will be extrapolated based on the values measured on the closer distances according to Section 15.31 (f) (2) [2]. The final measurement will be performed with a EMI Receiver set to Quasi Peak detector except for the frequency bands 9 kHz to 90 kHz and 110 kHz to 490 kHz where an average detector will be used according Section 15.209 (d) [2].

On the frequencies, which were detected during the preliminary measurements, the final measurement will be performed while rotating the EUT and the measuring antenna in the range of 0 ° to 360 ° around their vertical axis until the maximum value is found.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	9 kHz



Final measurement procedure:

The following procedure will be used:

- 1) Monitor the frequency range with the measuring antenna at vertical orientation parallel to the EUT at an azimuth of 0 °.
- 2) Rotate the EUT by 360 ° to maximize the detected signals and note the azimuth and orientation.
- 3) Rotate the measuring antenna to find the maximum and note the value.
- 4) Rotate the measuring antenna and repeat steps 1) to 3) until the maximum value is found.
- 5) Repeat steps 1) to 4) with the other orthogonal axes of the EUT (if the EUT is a module and might be used in a handheld equipment application).


Preliminary measurement (30 MHz to 1 GHz)

In the first stage a preliminary measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to [1].

The frequency range 30 MHz to 1 GHz will be measured with an EMI Receiver set to MAX Hold mode and a resolution bandwidth of 120 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	100 kHz



Procedure preliminary measurement:

Prescans were performed in the frequency range 30 MHz to 1 GHz.

The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Manipulate the system cables within the range to produce the maximum level of emission.
3. Rotate the EUT by 360 ° to maximize the detected signals.
4. Make a hardcopy of the spectrum.
5. Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
6. Repeat 1) to 4) with the other orthogonal axes of the EUT if handheld equipment.
7. Repeat 1) to 5) with the vertical polarisation of the measuring antenna.

Final measurement (30 MHz to 1 GHz)

A final measurement on an open area test site will be performed on selected frequencies found in the preliminary measurement. During this test the EUT will be rotated in the range of 0 ° to 360 °, the measuring antenna will be set to horizontal and vertical polarisation and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	120 kHz



Procedure final measurement:

The following procedure will be used:

- 1) Measure on the selected frequencies at an antenna height of 1 m and a EUT azimuth of 23 °.
- 2) Move the antenna from 1 m to 4 m and note the maximum value at each frequency.
- 3) Rotate the EUT by 45 ° and repeat 2) until an azimuth of 337 ° is reached.
- 4) Repeat 1) to 3) for the other orthogonal antenna polarization.
- 5) Move the antenna and the turntable to the position where the maximum value is detected.
- 6) Measure while moving the antenna slowly +/- 1 m.
- 7) Set the antenna to the position where the maximum value is found.
- 8) Measure while moving the turntable +/- 45 °.
- 9) Set the turntable to the azimuth where the maximum value is found.
- 10) Measure with Final detector (QP and AV) and note the value.
- 11) Repeat 5) to 10) for each frequency.
- 12) Repeat 1) to 11) for each orthogonal axes of the EUT if handheld equipment.

Preliminary and final measurement (1 GHz to 110 GHz)


This measurement will be performed in a fully anechoic chamber. Table top devices will set up on a non-conducting turn device on the height of 1.5 m. The set-up of the Equipment under test will be in accordance to [1].

Preliminary measurement (1 GHz to 40 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The spectrum analyser set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °. This measurement is repeated after raising the EUT in 30 ° steps according 6.6.5.4 in [1].

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 26.5 GHz	1 MHz
26.5 GHz to 40 GHz	1 MHz
40 GHz to 60 GHz	1 MHz
50 GHz to 75 GHz	1 MHz
75 GHz to 110 GHz	1 MHz



Procedure preliminary measurement:

Prescans were performed in the frequency range 1 to 40 GHz.

The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Rotate the EUT by 360° to maximize the detected signals.
3. Repeat 1) to 2) with the vertical polarisation of the measuring antenna.
4. Make a hardcopy of the spectrum.
5. Repeat 1) to 4) with the EUT raised by an angle of 30° (60°, 90°, 120° and 150°) according to 6.6.5.4 in [1].
6. Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
7. The measurement antenna polarisation, with the according EUT position (Turntable and Turn device) which produces the highest emission for each frequency will be used for the final measurement. The six closest values to the applicable limit will be used for the final measurement.

Final measurement (1 GHz to 110 GHz)

The frequency range will be divided into different sub ranges depending of the frequency range of the used antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1 MHz. The measurement will be performed by rotating the turntable through 0 to 360° in the worst-case EUT orientation which was obtained during the preliminary measurements.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
1 GHz to 4 GHz	1 MHz
4 GHz to 12 GHz	1 MHz
12 GHz to 18 GHz	1 MHz
18 GHz to 26.5 GHz	1 MHz
26.5 GHz to 40 GHz	1 MHz
40 GHz to 60 GHz	1 MHz
50 GHz to 75 GHz	1 MHz
75 GHz to 110 GHz	1 MHz



Procedure of measurement:

The measurements were performed in the frequency range 1 GHz to 110 GHz.

The following procedure will be used:


- 1) Set the turntable and the turn device to obtain the worst-case emission for the first frequency identified in the preliminary measurements.
- 2) Set the measurement antenna polarisation to the orientation with the highest emission for the first frequency identified in the preliminary measurements.
- 3) Set the spectrum analyser to EMI mode with peak and average detector activated.
- 4) Rotate the turntable from 0° to 360° to find the EUT angle that produces the highest emissions.
- 5) Note the highest displayed peak and average values
- 6) Repeat the steps 1) to 5) for each frequency detected during the preliminary measurements.

5.2.2 Results preliminary measurement 9 kHz to 1 GHz


Ambient temperature	20 °C	Relative humidity	35 %
---------------------	-------	-------------------	------

- Position of EUT: The EUT was set-up on a non-conducting table.
- Cable guide: The cable of the EUT was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.
- Test record: The test was carried out in TAG reading and writing mode of the EUT (refer also clause 2 of this test report). All results are shown in the following.
- Power supply: During this test the EUT was powered with 12 V_{AC} by the test adapter, which was itself supplied by an AC/DC adaptor type FSP60-DIBAN2 (connected to an AC mains network with 120 V_{AC} / 60 Hz).
- Frequency range: According to [2] from 9 kHz to 1 GHz.


182314_201.png: Spurious emissions from 9 kHz to 150 kHz



182314_202.png: Spurious emissions from 150 kHz to 1 MHz



182314_203.png: Spurious emissions from 1 MHz to 30 MHz




The following emission was found according to [2] and [3].


- 119.504 kHz, 125.232 kHz and 131.445 kHz.

This frequency has to be measured on the outdoor test site. The result is presented in the following.

182314_204.png: Spurious emissions from 30 MHz to 230 MHz



182314_205.png: Spurious emissions from 230 MHz to 1 GHz



The following frequency was found outside the restricted bands during the preliminary radiated

- 30.224 MHz.

The following frequencies were found inside the restricted bands during the preliminary radiated emission test:

- 112.395 MHz and 988.476 MHz.

These frequencies have to be measured on the open area test site. The results were presented in the following.

Test equipment used (see clause 6):

6 - 14

5.2.3 Result final measurement from 9 kHz to 30 MHz

Ambient temperature	20 °C	Relative humidity	45 %
---------------------	-------	-------------------	------

Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m and 10 m.

Cable guide: The cable of the EUT was fixed on the non-conducting support. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The test was carried out in TAG reading and writing mode of the EUT (refer also clause 2 of this test report). All results are shown in the following.

Power supply: During this test the EUT was powered with 12 V_{AC} by the test adapter, which was itself supplied by an AC/DC adaptor type FSP60-DIBAN2 (connected to an AC mains network with 120 V_{AC} / 60 Hz).

Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{antenna factor [dB/m]} + \text{Distance correction dB}$$

Results with measuring distance of 3 m							
Frequency (kHz)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Distance correction ²⁾ (dB)	Readings (dB μ V)	Detector	Antenna factor ¹⁾ (dB/m)
119.504	-46.5 @ 300 m	26.1	72.6	-80.0	13.2	AV	20.3
125.232	-36.5 @ 300 m	25.6	62.1	-80.0	23.2	AV	20.3
131.445	-49.3 @ 300 m	25.2	74.4	-80.0	10.4	AV	20.3
Results with measuring distance of 10 m							
Frequency (kHz)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Distance correction ²⁾ (dB)	Readings (dB μ V)	Detector	Antenna factor ¹⁾ (dB/m)
The emissions is below the noise floor of the measuring system							
Measurement uncertainty: ± 4.7 dB							

¹⁾: Cable loss included

²⁾: Correction Factor according to [2] and [3] extrapolated with a factor of 40 dB/decade according to [2]

Test: Passed

Test equipment used (see clause 6):

11, 14, 15

5.2.4 Result final measurement from 30 MHz to 1 GHz

Ambient temperature	20 °C	Relative humidity	44 %
---------------------	-------	-------------------	------

- Position of EUT: The EUT was setup on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Test record: The test was carried out in TAG reading and writing mode of the EUT (refer also clause 2 of this test report). All results are shown in the following.
- Power supply: During this test the EUT was powered with 12 V_{AC} by the test adapter, which was itself supplied by an AC/DC adaptor type FSP60-DIBAN2 (connected to an AC mains network with 120 V_{AC} / 60 Hz).


Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{correction factor (cable loss [dB] + antenna factor [dB/m] + 6 dB)}$$

The measured points and the limit line in the following diagrams refer to the standard measurement of the emitted interference in compliance with the above-mentioned standard. The measured points marked with an are the
 ◆ measured results of the standard final measurement on the open area test site.

The results of the standard subsequent measurement on the open area test site are indicated in the table below. The limits as well as the measured results (levels) refer to the above mentioned standard while taking account of the specified requirements for a 3 m measuring distance.

The measurement time with the quasi-peak measuring detector is 5 seconds.



Result measured with the quasi-peak detector:

Spurious emissions inside restricted bands									
Frequency (MHz)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
112.395	25.2	43.5	18.3	1000	120	154.0	Vertical	14.0	20.5
988.476	31.0	54.0	23.0	1000	120	209.0	Vertical	59.0	31.8
Spurious emissions outside restricted bands									
Frequency (MHz)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol.	Azimuth (deg)	Corr. (dB)
30.224	26.9	40.0	13.1	1000	120	103.0	Vertical	168.0	26.8
Measurement uncertainty				±4.7 dB					


Test: Passed

Test equipment used (see clause 6):

2, 16 - 21

5.3 99 % bandwidth

5.3.1 Method of measurement



The following procedure will be used for the occupied bandwidth measurement according to [4]:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).


5.3.2 Test results

Ambient temperature:	20 °C	Relative humidity:	31 %
----------------------	-------	--------------------	------

Test record: The test was carried out in TAG reading and writing mode of the EUT (refer also clause 2 of this test report). All results are shown in the following.

Power supply: During this test the EUT was powered with 12 V_{AC} by the test adapter, which was itself supplied by an AC/DC adaptor type FSP60-DIBAN2 (connected to an AC mains network with 120 V_{AC} / 60 Hz).

182314_207.jpeg: 99 % bandwidth:



Frequency	F _L	F _U	BW (F _U - F _L)
125.210 kHz	114.4659 kHz	134.2525 kHz	19.787 kHz
Measurement uncertainty		< 1*10 ⁻⁷	

Test equipment used (see clause 6):

22, 23

6 Test equipment

No.	Test equipment	Type	Manufacturer	Serial No.	PM. No.	Cal. Date	Cal Due
1	LISN	NSLK8128	Schwarzbeck	8128161	480138	13.03.2018	03.2020
2	Software	EMC32	Rohde & Schwarz	100061	481022	Calibration not necessary	
3	Shielded chamber M4	B83117-S1-X158	Siemens	190075	480088	Calibration not necessary	
4	EMI Receiver / Spectrum Analyser	ESIB 26	Rohde & Schwarz	100292	481182	28.02.2018	02.2020
5	Transient Filter Limiter	CFL 9206A	Teseq GmbH	38268	481982	14.03.2018	03.2020
6	Antenna mast	AS615P	Deisel	615/310	480187	Calibration not necessary	
7	Turntable	DS420 HE	Deisel	420/620/00	480315	Calibration not necessary	
8	Multiple Control Unit	MCU	Maturo GmbH	MCU/043/971107	480832	Calibration not necessary	
9	Antenna (Bilog)	CBL6112B	Schaffner EMV GmbH (-Chase)	2688	480328	19.06.2017	06.2020
10	RF-cable No.36	Sucoflex 106B	Suhner	0587/6B / Kabel 36	480865	Calibration not necessary	
11	EMI Receiver / Spectrum Analyser	ESW44	Rohde & Schwarz	101635	482467	22.06.2017	06.2019
12	Fully anechoic chamber M20	B83117-E2439-T232	Albatross Projects	103	480303	Calibration not necessary	
13	Antenna support	AS620P	Deisel	620/375	480325	Calibration not necessary	
14	Loop antenna	HFH2-Z2	Rohde & Schwarz	100417	481912	10.01.2019	01.2020
15	Outdoor test site	-	PHOENIX TESTLAB GmbH	-	480293	Calibration not necessary	
16	Open area test site M6	Freifeld M6	Phoenix Contact	-	480085	Calibration not necessary	
17	Antenna mast	MA240-0	Inn-Co GmbH	MA240-0/030/6600603	480086	Calibration not necessary	
18	Turntable	DS412	Deisel	412/316	480087	Calibration not necessary	
19	Controller	HD100	Deisel	100/349	480139	Calibration not necessary	
20	Antenna (Bilog)	CBL6111D	Schaffner Elektrotest GmbH / Teseq GmbH	25761	480894	19.10.2017	10.2020
21	EMI Receiver / Spectrum Analyser	ESR7	Rohde & Schwarz	101939	482558	19.09.2017	09.2019
22	Signal & Spectrum Analyzer	FSW43	Rohde & Schwarz	100586 & 100926	481720	30.5.2018	05.2019
23	Loop antenna	Æ11 cm	PHOENIX TESTLAB	-	410084	Calibration not necessary	

7 Report history

Report Number	Date	Comment
F182314E3	24.04.2019	Document created
-	-	-
-	-	-
-	-	-

8 List of annexes

Annex A	Test set-up photographs	6 pages
Annex B	External photographs	10 pages
Annex C	Internal photographs	8 pages