

Component Map



M.2 Slot Pin Assignment

M.2 B+M Key Slot pin assignment			
Top side		Bottom side	
1	NC	2	VDD_3V3
3	GND	4	VDD_3V3
5	NC	6	NC
7	NC	8	WLAN_DISABLE
9	NC	10	NC
11	GND	12	
Mechanical key B			
21	NC	20	NC
23	NC	22	NC
25	NC	24	NC
27	GND	26	NC
29	PCIE0_RX1_N	28	NC
31	PCIE0_RX1_P	30	NC
33	GND	32	NC
35	PCIE0_TX1_N	34	NC
37	PCIE0_TX1_P	36	NC
39	GND	38	NC
41	PCIE0_RX0_N	40	NC
43	PCIE0_RX0_P	42	NC
45	GND	44	NC
47	PCIE0_TX0_N	46	NC
49	PCIE0_TX0_P	48	NC
51	GND	50	RERST_3V3
53	REFCLK_N	52	CLKREQ_3V3
55	REFCLKP	54	WAKE_3V3
57	GND	56	NC
		58	NC
Mechanical key M			
67	NC	68	NC
69	NC	70	VDD_3V3
71	GND	72	VDD_3V3
73	GND	74	VDD_3V3
75	NC		

Power Requirements

DC Power	3.3V
Power Consumption	8W

WiFi 7 (802.11be) 2x2 Dual Band Dual Concurrent Wireless Module

FCC Statement

§ 15.19 This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation of the device.

§ 15.21 Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

§ 15.105 This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.— Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Notice to Users in Canada for IC compliance: This equipment complies with the Class B limits for radio noise emissions from digital apparatus as established by the Radio Interference Regulations of Industrial Canada.

FCC Radiation Exposure Statement

The modular can be installed or integrated in mobile or fix devices only. This modular cannot be installed in any portable device, for example, USB dongle like transmitters is forbidden. This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

If simultaneous with other transmitters is required, re-evaluation of RF Exposure is required according to KDB 996369. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

If the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: " Contains Transmitter Module FCC ID: TK4WLE7002E25 Or Contains FCC ID: TK4WLE7002E25 "

When the module is installed inside another Host, the user manual of host must contain below warning statements:

1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 - (1) This device may not cause harmful interference, and
 - (2) This device must accept any interference received, including interference that may cause undesired operation.
2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

The devices must be installed and used in strict accordance with the manufacturer's instructions as described in the user documentation that comes with the product.

The host product manufacturer is responsible for compliance to any other FCC rules that apply to the host not covered by the modular transmitter grant of certification. The final host product still requires Part 15 Subpart B compliance testing with the modular transmitter installed.

The end user manual shall include all required regulatory information/warning as shown in this manual, include:
This product must be installed and operated with a minimum distance of 20 cm between the radiator and user body.

Antenna Type and Gain

The following antennas have been certified for use with this module. Antenna Specification list below:

Antenna No	Antenna Type	Frequency Band (GHz)	Max Antenna Gain (dBi)
1	Omni	2412 ~ 2462	4
		5150 ~ 5850	6
2	Omni	2412 ~ 2462	2.83
		5150 ~ 5850	3.98
3	Omni	2412 ~ 2462	2.22
		5150 ~ 5850	4.29
4	Omni	2412 ~ 2462	1.27
		5150 ~ 5850	3.68
5	Omni	5150 ~ 5850	3.51
6	Omni	5150 ~ 5850	3.49

IC Statement

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

IC RF Exposure statement

This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

L'appareil est conforme aux limites d'exposition au rayonnement IC spécifiées pour les environnements non contrôlés. Lors de l'installation et de l'utilisation de cet appareil, la distance entre le radiateur et le corps doit être d'au moins 20 cm.

LE-LAN devices are restricted to indoor operation only in the band 5150-5250 MHz.
Les appareils LE-LAN sont limités à fonctionner à l'intérieur uniquement dans la bande 5150-5250 MHz.