



RF Exposure Evaluation Declaration

FCC ID: TK4WLM200NX

APPLICANT: Compex Systems Pte Ltd


Application Type: Certification

Product: WIRELESS-N NETWORK MINI PCI ADAPTER

Model No.: WLM200NX

Brand Name: COMPEX

FCC Classification: Unlicensed National Information Infrastructure (UNII)
Digital Transmission System (DTS)

Reviewed By : 
Manager : _____
(Robin Wu)

Approved By : 
CEO : _____
(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1611RSU02702	Rev. 01	Initial report	11-14-2016	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	WIRELESS-N NETWORK MINI PCI ADAPTER
Model No.	WLM200NX
Brand Name	COMPEX
WLAN Specification	
Frequency Range	<u>2.4GHz:</u> 802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz <u>5GHz:</u> 802.11a/n-HT20: 5180 ~ 5240MHz, 5745 ~ 5825MHz 802.11n-HT40: 5190 ~ 5230MHz, 5755 ~ 5795MHz
Type of Modulation	802.11b: DSSS 802.11g/a/n: OFDM

1.2. Antenna Description

Antenna Type	Frequency Band (GHz)	Manufacturer	Tx Paths	Max Peak Gain (dBi)	Directional Gain (dBi)	
					For Power	For PSD
Dipole Antenna	2.4	Compex Systems Pte Ltd	2	2	2	5.01
	5		2	2	2	5.01
PCB Antenna	2.4	Taoglas Antenna Solutions	2	3	3	6.01
	5		2	5	5	8.01

Note:

The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

For CDD transmissions, directional gain is calculated as follows, $N_{ANT} = 2$, $N_{SS} = 1$.

- If all antennas have the same gain, G_{ANT} , Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.
 - For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log (N_{ANT} / N_{SS})$ dB = 3.01;
 - For power measurements on IEEE 802.11 devices,
Array Gain = 0 dB for $N_{ANT} \leq 4$;
- If antenna gains are not equal, the user may use either of the following methods to calculate directional gain, provided that each transmit antenna is driven by only one spatial stream:
 - Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

$$\bullet \text{ DirectionalGain} = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

$g_{j,k} = 10^{G_k/20}$ if the kth antenna is being fed by spatial stream j, or zero if it is not;

G_k is the gain in dBi of the kth antenna.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	WIRELESS-N NETWORK MINI PCI ADAPTER
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to Clause 1.2 of antenna description.

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	23.69	0.0928	1
802.11a/n	5745 ~ 5825	22.59	0.1142	1
802.11a/n	5180 ~ 5240	22.51	0.1121	1

CONCLUSION:

The Max Power Density at R (20 cm) = 0.1142mW/cm² < 1mW/cm².

So the EUT complies with the requirement.

_____ The End _____