

FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

| Mode | Frequency Range (MHz) | Maximum Antenna Gain | | ★Tune-up Output Power | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) | MPE ratio |
|------------|-----------------------|----------------------|-----------|-----------------------|--------|--------------------------|-------------------------------------|---------------------------------|-----------|
| | | (dBi) | (numeric) | (dBm) | (mW) | | | | |
| 2.4G Wi-Fi | 2412-2462 | 4.5 | 2.82 | 21.0 | 125.89 | 20 | 0.0706 | 1.0 | 0.0706 |
| 5G Wi-Fi | 5150-5250 | 7.0 | 5.01 | 20.0 | 100 | 20 | 0.0997 | 1.0 | 0.0998 |
| | 5250-5350 | 7.0 | 5.01 | 20.0 | 100 | 20 | 0.0997 | 1.0 | 0.0998 |
| | 5470-5725 | 7.0 | 5.01 | 21.0 | 125.89 | 20 | 0.1255 | 1.0 | 0.1256 |
| | 5725-5850 | 7.0 | 5.01 | 20.0 | 100 | 20 | 0.0997 | 1.0 | 0.0998 |

The 2.4G Wi-Fi & 5G Wi-Fi can be transmitting simultaneously, So

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0706 + 0.1256 = 0.1962 \leq 1.0$$

Note:

1. For the above tune up power were declared by the manufacturer.

Result: The device meet FCC MPE at 20 cm distance.